CONTENTS

VEHICLE MAKE	PAGE #
ALFA ROMEO	17
AUDI	20
BMW	24
CHEVROLET	38
CHRYSLER / DODGE	44
CITROEN	46
DAEWOO	53
DAIHATSU	54
DAIMLER	56
EUNOS	57
FERRARI	57
FIAT	58
FORD	61
FORD - TICKFORD / FPV	65
FORD - TRUCKS	74
GMC	79
HILLMAN	83
HOLDEN	86
HOLDEN - HSV	88
HOLDEN - COMMERCIAL / 4WD	100
HONDA	102
HUMBER	108
HUMMER	108
HYUNDAI	109
HYUNDAI - 4WD / SUV	111
ISUZU	112
JAGUAR	113
JEEP / CHRYSLER	114
KIA	115
KIA - 4WD / SUV	116
LADA	116
LANCIA	116
LANDROVER / RANGE ROVER	117
LEXUS	119
LEYLAND	120
LOTUS	121

VEHICLE MAKE	PAGE #
MASERATI	121
MAZDA	122
MAZDA - 4WD / SUV / VAN	126
MERCEDES BENZ	127
MERCEDES BENZ - 4WD / SUV	131
MG	140
MINI - COOPER	140
MITSUBISHI	142
MITSUBISHI - 4WD / SUV / VAN	147
MORRIS - AUSTIN	150
NISSAN	151
NISSAN - 4WD / SUV / VAN	157
OPEL	160
PEUGEOT	161
PONTIAC	163
PORSCHE	164
PROTON	166
RANGEROVER	166
RENAULT	167
ROLLS ROYCE	169
ROVER	169
SAAB	170
SEAT	171
SSANYONG	171
SKODA	171
SUBARU	172
SUBARU WRX UPGRADE	177
SUZUKI	178
TOYOTA	180
TOYOTA - 4WD / SUV / VAN	187
TRIUMPH	193
VOLKSWAGEN	194
VOLKSWAGEN COMMERCIAL	198
VOLVO	201
WEIGHTS & DIMENSIONS CHART	225

www.dba.com.au

GENERAL DISCLAIMER
Important Disclaimer: Certain information in this Catalogue has been compiled from data published by original equipment manufacturers. Disc Brakes Australia Pty Ltd is unable to warrant the accuracy of third party data, and does not accept responsibility for loss or damage of any kind caused as a result of such data being inaccurate. We also encourage you to contact DBA if you have any concerns about the information provided. We will make every effort to correct any errors once they are brought to our attention.

TRADEMARKS
DBA, 4000 series, 5000 series Kangaroo Paw, TSP, Thermal Stability Profiling, DBA XS, ALUMALITE logos are either registered or trademarks of Disc Brakes Australia Pty Ltd.

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd. Trademarks include Part Number identification issued by DISC BRAKES AUSTRALIA PTY LTD.

COPYRIGHT © DISC BRAKES AUSTRALIA
This work is copyright. You may display this material in unaltered form only (retaining this notice) for your use within your organisation. All other rights are reserved. Requests and inquiries concerning reproduction and rights should be addressed to DBA - PO Box 6666, Silverwater DC, NSW, 1811, Australia; or by e-mail info@dba.com.au

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

ALFA ROMEO

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ALFA GIULIA														
1300 1300 Ti Giulia Super Giulia GT Junior Giulia 1600 GT Coupe	1968 - 72 1968 - 71 1971 - 72 1968 - 73 1972 - 74	F	**353**	PART NOT AVAILABLE REFERENCE ONLY				Solid	267	70	10.9	**10**	82	4
Giulia (Dunlop Brakes)	1964 - 69	F	**360**	PART NOT AVAILABLE REFERENCE ONLY				Solid	286	55.5	10	**9**	87	4
1300 Berlina (Ti & Super) GT, GTA Junior Coupe Spider Junior	1966 - 73	R	**354**	PART NOT AVAILABLE REFERENCE ONLY				Solid	267	64	9.4	**7.5**	70	4
1600 Berlina (Ti & Super) GTV Spider Roadster	1966 - 72 1966 - 68	R	**354**	PART NOT AVAILABLE REFERENCE ONLY				Solid	267	64	9.4	**7.5**	70	4
GIULIETTA														
1800	1980 - 83	F	**367**	✓				Solid	250	54.5	12.6	**10.7**	72	4
2000	1984 - 86	F	**366**	PART NOT AVAILABLE REFERENCE ONLY				Solid	261	51.5	12.7	**10**	72	4
1800 2000	1980 - 86	R	**365**	PART NOT AVAILABLE REFERENCE ONLY				Solid	250	21	10	**8**	62	6
									8mm Stud Hole					
GTV														
2 Door Coupe 2.0 Litre	6/98 - on	F	**763**	PART NOT AVAILABLE REFERENCE ONLY				Vented	284	40	22	**20.2**	59	5
		R	**779**	✓				Solid	240	40	11	**9.2**	59	5
V6 2 Door Coupe 3.0 Litre	6/98 - on	F	**769**	✓		✓		Vented	305	45	28	**26**	59	5
(Brembo Calipers)		R	**779**	✓				Solid	240	40	11	**9.2**	59	5
ALFA 1750														
Berlina, GTV Coupe Spider Roadster	1968 - 72	F	**357**	PART NOT AVAILABLE REFERENCE ONLY				Solid	272	68	12.5	**11.5**	82	4
Berlina, GTV Coupe Spider Roadster	1968 - 72	R	**354**	PART NOT AVAILABLE REFERENCE ONLY				Solid	267	64	9.4	**7.5**	70	4
ALFA 2000														
Berlina, GTV Coupe Spider Roadster	1972 - 76	F	**358**	PART NOT AVAILABLE REFERENCE ONLY				Solid	272	68	12.6	**10.7**	82	4
Berlina, GTV Coupe Spider Roadster	1972 - 76	R	**354**	PART NOT AVAILABLE REFERENCE ONLY				Solid	267	64	9.4	**7.5**	70	4

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

ALFA ROMEO

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ALFA 33														
All Models	1983 - 85	F	**368**	✓				Solid	239	45	11	**9**	58	4
1.5	1986 - 88	F	**658**	PART NOT AVAILABLE REFERENCE ONLY				Solid	239	45	12.7	**9**	58	4
1.7 Sprint, Ti, iE	1987 - 92	F	**369**	PART NOT AVAILABLE REFERENCE ONLY				Vented	239	46	22	**20.2**	58	4
ALFA 75														
2.0 TS, 2.5 V6, 3.0 V6	1986 - 92	F	**668**	PART NOT AVAILABLE REFERENCE ONLY				Vented	268	51.5	22	**20**	72	5
		R	**667**	PART NOT AVAILABLE REFERENCE ONLY				Solid	250	21	9.9	**8**	62	6
ALFA 90														
2.5 V6 Sedan	1985 - 88	F	**668**	PART NOT AVAILABLE REFERENCE ONLY				Vented	268	51.5	22	**20**	72	5
ALFA 147 GTA														
V6 DOHC 2D Hatchback	7/2003 - on	F	**769**	✓		✓		Vented	305	45	28	**26**	59	5
ALFA 155														
2.0i Turbo 16V Q4 2.5 V6 2.5 Turbodiesel	1992 - 97	F	**665**	✓		✓		Vented	284	44	22	**20.2**	59	4
		R	**666**	✓				Solid	251	50.5	10	**9**	59	4
ALFA 156														
1.8L	1997 - on	F	**763**	PART NOT AVAILABLE REFERENCE ONLY				Vented	284	40	22	**20.2**	59	5
2.0i 16V Twin Spark 2.5i V6 24V	1997 - on	F	**356**	✓		✓		Vented	284	44	22	**20.2**	59	5
Turbodiesel 2.4 JTD		R	**359**	✓				Solid	251	50.5	10	**9**	59	5
ALFA 164														
2.0i Turbo 2.0i V6 Turbo 3.0i V6 Quadrifoglio V6	1987 - 9/92	F	**356**	✓		✓		Vented	284	44	22	**20.2**	59	5
Turbodiesel 2.5		R	**359**	✓				Solid	251	50.5	10	**9**	59	5
ALFETTA														
1.8 Sedan, 2.0 Sedan GT 1.8 Coupe, GTV 2000	1974 - 80	F	**361**	PART NOT AVAILABLE REFERENCE ONLY				Solid	261	51	11	**9**	72	4
2.0 Sedan	1980 - 85	F	**366**	PART NOT AVAILABLE REFERENCE ONLY				Solid	261	51.5	12.7	**10**	72	4
1.8 Sedan, 2.0 Sedan GT 1.8 Coup e, GTV 2000	1974 - 80	R	**362**	✓				Solid	250	21	10	**8**	62	6
									10mm Stud Hole					
1.8 Sedan, 2.0 Sedan, GTV 2500	1979 - 85	R	**365**	PART NOT AVAILABLE REFERENCE ONLY				Solid	250	21	10	**8**	62	6
									8mm Stud Hole					

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

ALFA ROMEO

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ALFASUD														
1200, 1500, L, Ti, Sprint	1971 - 83	F	**363**	✓				Solid	258	10.5	10	**8.8**	98	4
Ti, Sprint	1983 - 85	F	**669**	PART NOT AVAILABLE REFERENCE ONLY				Solid	258	16	10	**8**	62	6
1200, 1500, L, Ti, Sprint	1971 - 83	R	**364**	✓				Solid	233	70	9	**7.8**	HUB	4
MONTREAL														
2.6L V8 DOHC	1970 - 77	F	**2360**	✓		✓		Vented	272	58	22	**20**	82.1	4

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

AUDI

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
AUDI 80 INCLUDING FOX														
1.5 Litre S, LS Fox	1972 - 7/76	F	**242**	✓				Solid	239	39	10	**8**	65	4
1.5, 1.6 Litre Fox	9/76 - 79	F	**240**	✓				Solid	239	35.2	12	**10**	65	4
1.8 Litre CC 1.9E, 1.9S	1986 - 87 1988 - 92	F	**241**	✓				Vented	256	47	22	**20**	68	4
2.2 Coupe	1982 - 84	F	**444**	✓				Vented	239	38.5	20	**18**	65	4
1.8 Litre CC 1.9E, 1.9S + V6	1986 - on	R	**445**	✓				Solid	245	59	10	**8.6**	68	4
AUDI 90														
2.3 Litre except 20v	1989 - 92	F	**241**	✓				Vented	256	47	22	**20**	68	4
2.3 Litre 20V (125kW)	1989 - 92	F	**2241**					Vented	276	51.2	25	**23**	68	4
all rears		R	**445**	✓				Solid	245	59	10	**8.6**	68	4
AUDI 100														
S, LS, GL Automatic	1968 - 74	F	**248**	✓				Solid	291	41.5	10.5	**9.5**	108	4
S, LS, GL Automatic	1971 - 74	F	**249**	PART NOT AVAILABLE REFERENCE ONLY				Solid	291	37.5	10.5	**9**	108	4
All Models	1974 - 77	F	**440**	✓				Solid	257	40.5	13	**11**	68	4
All Models	1974 - 77	F	**441**	✓				Vented	257	39.9	20	**19**	68	4
5+5 GLE, 5E	1978 - 83	F	**247**	✓				Solid	257	46	13	**11**	68	4
2.1, 2.2, 2.3 CD	1983 - 91	F	**241**	✓				Vented	256	47	22	**20**	68	4
		R	**445**	✓				Solid	245	59	10	**8.6**	68	4
2.0 4CYL (74KW) 2.4 DIESEL 2.0E 4CYL (85KW) 2.3E 5CYL 2.0E 16V	12/90 - 94 1992 - 94	F	**805**	✓				Solid	288	46.2	15	**13**	68	5
2.6E V6 2.8E V6	05/92 - 94 12/90 - 94	F	**807**	✓				Vented	288	46.2	25	**23**	68	5
All Models inc. Avant & Quattro rear	1990 - 94	R	**810**	✓				Solid	245	63.9	10	**8**	68	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

AUDI

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
QUATTRO 80														
1.8, 1.9, 2.0 (Except 20V)	1986 - 89	F	**241**	✓				Vented	256	47	22	**20**	68	4
1.9, 2.0 16V	1986 - 89	R	**244**	✓				Solid	245	39	10	**8**	68	4
2.3, 20V	1989 - 92	R	**445**	PART NOT AVAILABLE REFERENCE ONLY				Solid	245	59	10	**8.6**	68	4
QUATTRO 90														
All models (Except 2.3L 20V)	1989 - 91	F	**241**	✓				Vented	256	47	22	**20**	68	4
2.3 Litre 20V (125 kw)	1988 - 92	F	**2241**	PART NOT AVAILABLE REFERENCE ONLY				Vented	276	51.2	25	**23**	68	4
ALL MODELS	1989 - 91	R	**244**	✓				Solid	245	39	10	**8**	68	4
QUATTRO 100														
2.2. Station Wagon CD 2.3 (14", 15" Wheels)	1982 - 88 1988 - 91	F	**241**	✓				Vented	256	47	22	**20**	68	4
2.2, 2.3 (14" Wheels)	1982 - 91	R	**445**	PART NOT AVAILABLE REFERENCE ONLY				Solid	245	59	10	**8.6**	68	4
A3														
1.6 (AEH Engine)	1997 - 4/03	F	**800**	✓				Vented	256	36.7	22	**19**	65	5
1.8 (AGN Engine)	1997 - 4/03	F	**801**	✓				Vented	280	36.7	22	**19**	65	5
1.8 Turbo (AGU Engine)	1997 - 4/03	F	**802**	✓				Vented	288	34	25	**23**	65	5
all models A3 Rear	1997 - 4/03	R	**803**	✓				Solid	232	39.5	9	**7**	65	5
A4 & A4 QUATTRO														
1.6	11/94 - 9/97	F	**804**	✓				Solid	280	46.2	13	**11**	68	5
1.8 20 Valve (ADR engine) up to Ch: 8DV-054-061	11/94 - 9/97	F	**805**	✓				Solid	288	46.2	15	**13**	68	5
1.8 20 Valve (ADR engine) from Ch: 8DV-054-062 1.6 with 280, 1.9 TDI	9/97 - 11/04 9/97 - 10/04	F	**806**	✓				Vented	280	46.2	22	**20**	68	5
1.8 Turbo (AEB engine) 1.6 (288) 1.9 TDI	11/94 - 7/02 12/00 - 10/04 1995 - 10/04	F	**807**	✓				Vented	288	46.2	25	**23**	68	5
1.9 Tdi	11/94 - 9/97	F	**804**	✓				Solid	280	46.2	13	**11**	68	5
V6 2.6 & 2.8 (ABC engine) V6 2.4 30V Quattro	11/94 -10/04 1997 - 11/00	F	**807**	✓				Vented	288	46.2	25	**23**	68	5
A4 Rear QUATTRO Hub	11/94 - 11/00	R	**808**	✓				Solid	245	83.6	10	**8**	HUB	5
A4 Rear (except Quattro)	11/94 - 11/00	R	**809**	PART NOT AVAILABLE REFERENCE ONLY				Solid	245	48	10	**8**	68	5
1.8i 20V Turbo	8/02 - 10/04	F	**2800**	✓		✓		Vented	312	46.2	25	**23**	68	5
		R	**2801**	✓				Solid	245	39.8	10	**8**	68	5
Please check Rotor Dimensions	8/02 - on	R	**2802**	✓				Solid	255	40	12	**10**	68	5

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

AUDI - A6 / A8

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
A6 & A6 QUATTRO														
1.8 20 Valve (ABK Engine) 2.0 16 Valve (ABK Engine) 2.0 E (ABK Engine) Turbodiesel 1.9 TDI Turbodiesel 2.5 TDI (85 kW)	10/95 - 3/97 1995 - 3/97 6/94 - 3/97	F	**805**	✓				Solid	288	46.2	15	**13**	68	5
V6 2.6 & 2.8 (ABC Engine) Turbodiesel 2.5 TDI (103 kW) All A6 15" Wheels inc. Quattro	6/94 - 3/97 1995 - 3/97 3/97 - 4/04	F	**807**	✓				Vented	288	46.2	25	**23**	68	5
1.8i 20V inc. Turbo, 2.4i V6 30V 2.8i V6 30V, 1.9 Tdi, 2.5 V6 Tdi 2.0i 20V All with 16" Wheels inc. Quattro	3/97 - 4/04 01 - 4/04	F	**2800**	✓		✓		Vented	312	46.2	25	**23**	68	5
2.7i V6 30V Turbo 3.0i V6 30V 4.2i V8 40V Quattro	1999 - 4/04 2001 - 4/04 1999 - 4/04	F	**4575**			✓	✓	Vented	320	46.2	30	**28**	68	5
All above A6 / Avant (rear) All above A6 Quattro (rear)	6/94 - 4/04 6/94 - 3/97	R	**810**	✓				Solid	245	63.9	10	**8**	68	5
All A6 Quattro (rear) with 15" Wheels	3/97 - 4/04	R	**2803**	✓				Solid	245	53.8	10	**8**	68	5
All A6 Quattro with 16" Wheels (rear)	03/97 - 04/04	R	**2805**	✓				Solid	255	47.8	10	**8**	68	5
A8														
4.2L DOHC V8 quattro	2002 - on	F	**4242**			✓	✓	Vented	321	59.4	30	**28**	68	5

dba™ DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

AUDI - S3 / S4 / S6

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ALLROAD														
2.7i V6 30V Turbo 4.2i V8 40V Turbodiesel 1.9 TDI	2000 - on 2002 - on 2000 - on	F	**4575**			✓	✓	Vented	320	46.2	30	**28**	68	5
Solid rear disc models	2000 - on	R	**2805**	✓				Solid	255	47.8	10	**8**	68	5
RS4														
2.7i V6 Biturbo	2001 - 2006	F	**52804**				✓	Vented	360	46.7	32	**30.4**	68	10
S3 & TT														
1.8i TT Coupe + Roadster	1998 - 2002 1999 - on	F	**838**	✓		✓		Vented	312	34.2	25	**23**	65	5
Front Wheel Drive	2000 - 02	R	**803**	✓				Solid	232	39.5	9	**7**	65	5
Quattro 1KE solid rear disc	2000 - 02	R	**352**	✓				Solid	239	34	9	**7**	65	5
Quattro 1KF vented rear disc	2000 - 02	R	**800**	✓				Vented	256	36.5	22	**20**	65	5
S4														
2.7 Twin Turbo	1999 - 04	F	**4575**			✓	✓	Vented	320	45.5	30	**28**	68	5
(DBA 4000 series)		R	**4569**			✓		Vented	256	48	22	**20**	68	5
V8 4.2L Quattro	2004 - on	F	**42575**			✓		Vented	344.5	46.7	30	**28**	68	5
		R	**42576**			✓		Vented	300	36.5	22	**20**	68	5
S6														
4.2L V8	2002 - on	F	**4240**			✓	✓	Vented	321	52	30	**28**	68	5
(DBA 4000 series)		R	**4241**			✓		Vented	269	54	22	**20**	68	5
Q7														
4.2 FSI Quattro 3.0 TDI Quattro	03/06 - on	F	**42246**			4x4		Vented	350	69	34	**32**	85	5
all models rear		R	**42245**			4x4		Vented	330	74	28	**26**	85	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor and also available as a plain standard finish rotor

DBA™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
130i														
E87	2005 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
1502														
All	1975 - 77	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
1600														
Touring	1971 - 73	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
1600-2														
All	1966 - 71	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
1602														
Touring	1971 - 73	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
1800														
Touring	1971 - 73	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
1802														
Saloon/Touring	1971 - 75	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
2000														
Touring	1969 - 75	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
2002														
(- Ti/Rii/Turbo)	1968 - 75	F	**370**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	58.5	10	**8.4**	63	4
2500														
CS/Automatic	1969 - 77	F	**371**	✓				Solid	272	59.8	12.7	**11.4**	74	5
		R	**374**	✓				Solid	272	61.5	9.5	**7.9**	75	5
2800														
Automatic	1969 - 77	F	**373**	✓				Solid	272	59.8	12.7	**11.4**	74	5
		R	**374**	✓				Solid	272	61.5	9.5	**7.9**	75	5
CS/Automatic	1970 - 72	F	**371**	✓				Solid	272	59.8	12.7	**11.4**	74	5
3000														
Bavaria/Automatic	1971 - 77	F	**371**	✓				Solid	272	59.8	12.7	**11.4**	74	5
		R	**374**	✓				Solid	272	61.5	9.5	**7.9**	75	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 3 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
315														
(E21)	1981 - 83	F	**376**	✓				Solid	255	75.1	12.5	**11.1**	63	4
316														
(E21)	1975 - 82	F	**376**	✓				Solid	255	75.1	12.5	**11.1**	63	4
316i														
(E30)	1982 - 87	F	**678**	✓				Solid	260	35.1	12.7	**11.1**	66	4
(E30) including ABS	1982 - 93	F	**679**	✓				Vented	260	35.1	22	**20.4**	66	4
Touring		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E36) including ABS	1990 - 2000	F	**978**	✓				Solid	286	51.7	12	**10.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
318i, 318d														
(E21)	1975 - 82	F	**376**	✓				Solid	255	75.1	12.5	**11.1**	63	4
(E30)	1982 - 91	F	**678**	✓				Solid	260	35.1	12.7	**11.1**	66	4
(E30) including ABS	1982 - 93	F	**679**	✓				Vented	260	35.1	22	**20.4**	66	4
Touring / Cabriolet		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E36) including ABS	12/90 - 98	F	**978**	✓				Solid	286	51.7	12	**10.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
(E46) Saloon	4/98 - on	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
E90 With option code: S100A	2004 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
E91	2005 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
318iS														
(E30)	1989 - 91	F	**679**	✓				Vented	260	35.1	22.5	**20.4**	66	4
		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E36) Saloon/Coupe	1992 - 98	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
318TDS														
(E36) Saloon/Compact	1994 - on	F	**978**	✓				Solid	286	51.7	12	**10.4**	79	5
(E36) Touring	1994 - on	F	**978**	✓				Solid	286	51.7	12	**10.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
318Ti														
(E36) Compact	1995 - 4/98	F	**978**	✓	✓			Solid	286	51.7	12	**10.4**	79	5
		R	**981**	✓				Solid	272	78	10	**8.4**	75	5

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 3 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
320 / 320-6														
(E21)	1975 - 79	F	**394**	PART NOT AVAILABLE REFERENCE ONLY				Solid	255	75.1	12.5	**11.1**	63	4
320D														
(E46) Saloon	4/98 - on	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**980**	✓				Vented	276	60	19	**17.4**	75	5
E90	2004 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	TBA					Vented	300		20			
E91	2004 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
E90, E91	2004 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
With option code: S102A		R	**2859**	✓		✓		Vented	336	67.2	22	**20.4**	75	5
320i : iS														
(E21)	1975 - 78	F	**378**	PART NOT AVAILABLE REFERENCE ONLY				Vented	255	75.1	22	**20.4**	63	4
(E21) USA	9/77 - 83	F	**376**	✓				Solid	255	75.1	12.5	**11.1**	63	4
(E30)	1982 - 91	F	**679**	✓				Vented	260	35.1	22	**20.4**	66	4
incl. Touring / Cabriolet		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E36)	12/90 - 98	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
(E46) Saloon	4/98 - on	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**980**	✓				Vented	278	60	19	**17.4**	75	5
E90	2004 - on	F	TBA					Vented	292		22			
		R	TBA					Solid	296		10			
E90 With option code: S100A	2004 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	TBA					Vented	300		20			
E91	2004 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
320Si														
E90	2005 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

BMW - 3 SERIES

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
323i														
E90, E92	2004 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
	2006 - on	R	TBA	✓				Vented	300		20			
E91	2005 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
323id														
(E21)	1978 - 82	F	**378**	PART NOT AVAILABLE REFERENCE ONLY				Vented	255	75.1	22	**20.4**	63	4
		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E30)	1981 - 86	F	**679**	✓				Vented	260	35.1	22	**20.4**	66	4
		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E36)	1995 - 99	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**980**	✓				Vented	276	60.1	19	**17.4**	75	5
(E46) Saloon (E46) Coupe	4/98 - on 1999- on	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**980**	✓				Vented	276	60	19	**17.4**	75	5
324d : td														
(E30)	1987 - 91	F	**679**	✓				Vented	260	35.1	22	**20.4**	66	4
		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E36) Touring	1988 - 93	F	**679**	✓				Vented	260	35.1	22	**20.4**	66	4
		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

BMW - 3 SERIES

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
325i : 325ix : 325ci														
(E30)	1989 - 91	F	**679**	✓				Vented	260	35.1	22	**20.4**	66	4
		R	**671**	✓				Solid	258	60.1	10	**8.4**	62	4
(E36)	12/90 - 99	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
(E46) Saloon/Touring	2000 - on	F	**966**	✓				Vented	300	52	22	**20**	79	5
		R	**967**	✓				Vented	294	59.5	19	**17.4**	75	5
E90 E92 With option code: S212A	2004 - on 2005 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	TBA					Vented	300		20			
E91	2004 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
E90, E91	2004 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
With option code: S100A		R	**2859**	✓		✓		Vented	336	67.2	22	**20.4**	75	5
E92	2005 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
		R	TBA					Vented	300		20			
325D														
E90, E91	2006 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
		R	**2859**	✓		✓		Vented	336	67.2	22	**20.4**	75	5
325Xi														
E90	2006 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
E90 With S100A option	2006 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
		R	**2859**	✓		✓		Vented	336	67.2	22	**20.4**	75	5
E91 U.S. Model	2006 - on	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
E91 Euro Model	2005 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
		R	**2859**	✓		✓		Vented	336	67.2	22	**20.4**	75	5
E92 Euro Model	2005 - on	F	**2860**	✓				Vented	330	73.2	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 3 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
325td : tds														
(E36), (E36) Touring	9/91 - 1999	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
328i : 328ci														
(E36) Coupe	11/94 - 99	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**980**	✓				Vented	276	60.1	19	**17.4**	75	5
(E36) Saloon/Cabriolet	11/94 - 99	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**983**	✓				Solid	280	60.1	10	**8.4**	75	5
(E36) Saloon Cabriolet (German Application)	11/94 - on	R	**980**	✓				Vented	276	60.1	19	**17.4**	75	5
(E36) Touring	11/94 - 99	F	**979**	✓				Vented	286	51.6	22	**20.4**	79	5
		R	**980**	✓				Vented	276	60.1	19	**17.4**	75	5
(E46)	4/98 - on	F	**966**	✓				Vented	300	52	22	**20**	79	5
		R	**967**	✓				Vented	294	59.5	19	**17.4**	75	5
E90 E92	2006 - ON 2005 - ON	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	TBA					Vented	300		20			
E91 U.S. Model	2004 - ON	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
328Xi														
E90, E91, E92 All U.S. Models	2005 - ON	F	**2862**	✓				Vented	300	73.7	24	**22.4**	79	5
		R	**2861**	✓				Vented	300	66	20	**18.4**	75	5
330														
(E46)	7/00 - 05	F	**2855**	✓				Vented	324	52	25	**23.4**	79	5
		R	**2856**	✓				Vented	320	60.8	22	**20.4**	75	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 3 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
330D : 330I : 330XD : 330XI														
With option code;	12/06 - on	F	**2858**	✓		✓	✓	Vented	348	73.2	30	**28.4**	79	5
S100A /S102A		R	**2859**	✓		✓		Vented	336	67.2	22	**20.4**	75	5
E90 Saloon														
E91 Touring														
E92 Coupe														
330CD : 330CI : 330I : 330D : 330XD : 330XI														
(E46)	7/00 - 05	F	**2855**	✓				Vented	324	52	25	**23.4**	79	5
		R	**2856**	✓		✓		Vented	320	60.8	22	**20.4**	75	5
335d : 335i														
E90 Saloon	2006 - on	F	**2858**	✓		✓	✓	Vented	348	73.2	30	**28.4**	79	5
E91 Touring		R	**2859**	✓		✓		Vented	336	67.2	22	**20.4**	75	5
E92 Coupe														

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

BMW - 5 SERIES

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
518														
(E12)	1974 - 2/76	F	**373**	✓				Solid	272	59.8	12.7	**11.4**	74	5
(E12)	3/76 - 81	F	**377**	✓				Solid	280	78.1	12.7	**11.1**	74	5
(E12) vented discs	8/76 - 81	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
518i														
(E28)	1981 - 88	F	**672**	✓				Solid	284	76.1	12	**10.4**	79	5
(E30) Touring	1981 - 88	F	**675**	✓				Vented	284	76.1	22	**20.4**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
518i														
(E34) including ABS	1989 - 1996	F	**975**	✓				Solid	302	76.1	12	**10.4**	79	5
incl. Touring		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
520-6														
(E12)	1977 - 81	F	**377**	✓				Solid	280	78.1	12.7	**11.4**	74	5
(E12) vented discs	1977 - 81	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
520i														
(E12)	1972 - 2/76	F	**373**	✓				Solid	272	59.8	12.7	**11.4**	74	5
(E12)	3/76 - 79	F	**377**	✓				Solid	280	78.1	12.7	**11.1**	74	5
(E12) vented discs	1976 - 79	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
520i														
(E28)	1980 - 8/84	F	**672**	✓				Solid	284	76.1	12	**10.4**	79	5
(E28) + ABS	1980 - 87	F	**675**	✓				Vented	284	76.1	22	**20.4**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
(E34) Sedans	1987 - 95	F	**975**	✓				Solid	302	76.1	12	**10.4**	79	5
(E34) Wagons + Touring 24V	1989 - 95	F	**974**	✓				Vented	302	76.1	22	**20.4**	79	5
(E34) All Models (Rear)		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
(E39)	1996 - 03	F	**986**	✓				Vented	296	76	22	**20.4**	79	5
		R	**987**	✓				Solid	298	61	10	**8.4**	75	5
523i														
(E39)	1995 - 2000	F	**986**	✓				Vented	296	76	22	**20.4**	79	5
Saloon solid rear disc		R	**987**	✓				Solid	298	61	10	**8.4**	75	5
Saloon vented rear + all TOURING models		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 5 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
524d														
(E28)	1986 - 87	F	**675**	✓				Vented	284	76.1	22	**20.4**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
524td														
(E28)	10/82 -8/84	F	**672**	✓				Solid	284	76.1	12	**10.4**	79	5
(E28) + ABS	10/82 -1987	F	**675**	✓				Vented	284	76.1	22	**20.4**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
(E34)	1987 - 92	F	**975**	PART NOT AVAILABLE REFERENCE ONLY				Solid	302	76.1	12	**10.4**	79	5
		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
525														
(E12) solid front disc	1973 - 2/76	F	**373**	✓				Solid	272	59.8	12.7	**11.4**	74	5
(E12) solid front disc	2/76 - 81	F	**377**	✓				Solid	280	78.1	12.7	**11.1**	74	5
(E12) vented front disc	1976 - 81	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
rear suits all models above	1973 - 81	R	**374**	✓				Solid	280	61.1	9.5	**7.9**	75	5
525e/i														
(E28)	1981 - 87	F	**675**	✓				Vented	284	76.1	22	**20.4**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
525i														
(E34)	1987 - 90	F	**974**	✓				Vented	302	76.1	22	**20.4**	79	5
		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
525i 24V														
(E34)	8/90 - 96	F	**974**	✓				Vented	302	76.4	22	**20.4**	79	5
incl. Touring		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
525td : tds														
(E34)	1990 - 95	F	**975**	✓				Solid	302	76.1	12	**10.4**	79	5
		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
(E34) Touring	7/91 - 96	F	**974**	✓				Vented	302	76.1	22	**20.4**	79	5
		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
(E39)	1996 - 2000	F	**986**	✓				Vented	296	76	22	**20.4**	79	5
		R	**987**	✓				Solid	298	61	10	**8.4**	75	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 5 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
528														
(E12)	1975 - 1/76	F	**373**	✓				Solid	272	59.8	12.7	**11.4**	74	5
(E12)	2/76 - 7/76	F	**377**	✓				Solid	280	78.1	12.7	**11.1**	74	5
(E12)	8/76 - 77	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
(E12) (Rear)	1975 - 77	R	**374**	✓				Solid	272	61.5	9.5	**7.9**	75	5
528i														
(E12)	1977 - 6/81	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
		R	**374**	✓				Solid	272	61.5	9.5	**7.9**	75	5
(E28)	1981 - 5/84	F	**675**	✓				Vented	284	76.1	22	**20.4**	79	5
(E28)	6/84 - 87	F	**970**	✓				Vented	282	76.1	25	**23**	79	5
	1981 - 87	R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
528i 24V														
(E39) 2.8	1996 - 2000	F	**986**	✓				Vented	296	76	22	**20.4**	79	5
		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5
530i														
(E34)	1988 - 96	F	**974**	✓				Vented	302	76.1	22	**20.4**	79	5
		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
(E39)	1999 - 03	F	**2854**	✓				Vented	324	73.5	30	**28.4**	79	5
		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5
(E60)	2001 - on	F	**2868**					Vented	324	77.5	30	**28.4**	79	5
		R	**2869**					Vented	320	63	20	**18.4**	75	5
535i														
(E28)	1985 - 87	F	**970**	✓				Vented	282	76.1	25	**23**	78	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
(E34)	1988 - 95	F	**974**	✓				Vented	302	76.1	22	**20.4**	79	5
		R	**976**	✓				Solid	300	61.1	10	**8.4**	75	5
(E39)	1995 - 9/97	F	**986**	✓				Vented	296	76	22	**20.4**	79	5
		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5
(E39)	9/97 - 3/00	F	**988**	✓				Vented	324	77.1	30	**28.4**	79	5
		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5
(E39) V8	3/2000 - on	F	**2854**	✓				Vented	324	73.5	30	**28.4**	79	5
		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 5 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
540 / 540i														
(E34) Saloon	10/92 - 95	F	**971**	✓				Vented	302	76.1	28	**26.4**	79	5
(E34) Touring	10/92 - 97	F	**971**	✓				Vented	302	76.1	28	**26.4**	79	5
		R	**969**	PART NOT AVAILABLE REFERENCE ONLY				Vented	300	61.1	20	**18.4**	75	5
(E39) 4.4 V8	1995 - 3/00	F	**988**	✓				Vented	324	77.1	30	**28.4**	79	5
		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5
(E39) V8	3/2000 - 03	F	**2854**	✓				Vented	324	73.5	30	**28.4**	79	5
		R	**989**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	61	20	**18.4**	75	5

BMW - 6 SERIES

628														
(E24) CSi	1979 - 4/82	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
(E24) CSi	5/82 - 87	F	**970**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	76.1	25	**23**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5
630														
(E24) CSi	1976 - 79	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
		R	**673**	PART NOT AVAILABLE REFERENCE ONLY				Vented	272	68.5	19	**17**	75	5
633														
(E24) CSi	1976 - 4/82	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
		R	**673**	PART NOT AVAILABLE REFERENCE ONLY				Vented	272	68.5	19	**17**	75	5
635														
(E24) CSi	1978 - 4/82	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
		R	**673**	PART NOT AVAILABLE REFERENCE ONLY				Vented	272	68.5	19	**17**	75	5
(E24) CSi	5/82 - 89	F	**970**	✓				Vented	282	76.1	25	**23**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 7 SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
728i : 728iA														
(E23)	1977 - 8/82	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
		R	**676**	✓				Solid	280	68.1	10	**8.4**	75	5
(E23)	9/82 - 86	F	**677**	✓				Vented	280	78.1	25	**23.4**	74	5
		R	**674**	✓				Solid	284	68.1	10	**8.4**	75	5
(E38)	1995 - 10/01	F	**990**	✓				Vented	316	77	28	**26**	79	5
		R	**991**	✓				Solid	324	61	12	**10**	75	5
730 : 730i : 730iL														
(E23)	1977 - 79	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
		R	**676**	✓				Solid	280	68.1	10	**8.4**	75	5
(E32) 6 cyl & V8	11/87 - 6/94	F	**974**	✓				Vented	302	76.1	22	**20.4**	79	5
	1987 - 1993	R	**972**	PART NOT AVAILABLE REFERENCE ONLY				Solid	300	68.5	12	**10.4**	75	5
	1993 - 1994	R	**977**	PART NOT AVAILABLE REFERENCE ONLY				Solid	300	68.1	10	**8.4**	75	5
(E38)	1994 - 2000	F	**990**	✓				Vented	316	77	28	**26**	79	5
		R	**991**	✓				Solid	324	61	12	**10**	75	5
732i : 733i														
(E23)	1977 - 86	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
(E23)	1979 - 8/81	R	**676**	✓				Solid	280	61.1	10	**8.4**	75	5
(E23)	9/81 - 86	R	**674**	✓				Solid	284	68.1	10	**8.4**	75	5
735i : iL														
(E23)	1979 - 8/81	F	**379**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	78.1	22	**20.4**	74	5
		R	**676**	✓				Solid	280	68.1	10	**8.4**	75	5
(E23)	9/81 - 86	F	**677**	✓				Vented	280	78.1	25	**23.4**	74	5
		R	**674**	✓				Solid	284	68.1	10	**8.4**	75	5
(E32)	1986 - 1992	F	**971**	✓				Vented	302	76.1	28	**26.4**	79	5
		R	**972**	PART NOT AVAILABLE REFERENCE ONLY				Solid	300	68.1	12	**10.4**	75	5
(E38)	1994 - 2000	F	**990**	✓				Vented	316	77	28	**26**	79	5
		R	**991**	✓				Solid	324	61	12	**10**	75	5
740i : iL														
(E32)	1992 - 6/94	F	**971**	✓				Vented	302	76.1	28	**26.4**	79	5
(E32)		R	**2852**	✓				Vented	300	68.5	20	**18.4**	75	5
(E38)	1995 - 01	F	**988**	✓				Vented	324	77.1	30	**28.4**	79	5
		R	**991**	✓				Solid	324	61	12	**10**	75	5

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - 7 / 8 / M SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
745i														
(E23)	1980 - 86	F	**677**	✓				Vented	280	78.1	25	**23.4**	74	5
(E23)	1980 - 8/81	R	**676**	✓				Solid	280	68.1	10	**8.4**	75	5
(E23)	9/81 - 86	R	**674**	✓				Solid	284	68.1	10	**8.4**	75	5
750i : iL														
(E32) (E32) + floating caliper	87 - 89 90 - 6/94	F	**971**	✓				Vented	302	76.1	28	**26.4**	79	5
(E32)	87 - 6/94	R	**2852**	✓				Vented	300	68.5	20	**18.4**	75	5
(E38) 750i V12 5.4L 240kW	6/94 - 10/01	F	**2670**	✓				Vented	334	77	32	**30**	79	5
		R	**2671**	✓				Vented	328	61	20	**18.4**	75	5
840i, 840 Ci														
E31	12/92 - 5/99	F	**988**	✓				Vented	324	77.1	30	**28.4**	79	5
		R	**991**	✓				Solid	324	61	12	**10**	75	5
850 Ci														
E31 (M70)	7/89 - 10/94	F	**988**	✓				Vented	324	77.1	30	**28.4**	79	5
		R	**991**	✓				Solid	324	61	12	**10**	75	5
M3														
(E36) 3.0i 24V (E36) 3.2i 24V	1992 - 1995 1995 - 2001	F	**984**	✓		✓		Vented	315	52.5	28	**26.4**	79	5
		R	**985A**	✓				LH Vented	312	61	19.9	**18.4**	79	5
		R	**985B**	✓				RH Vented	312	61	19.9	**18.4**	79	5
(E46)	2001 - on	F	**42850**			✓		Vented	325	52.5	28	**26.4**	79	5
		F	**52880**				✓	Vented	325	52.5	28	**26.4**	79	5
		R	**42851**			✓		Vented	327	61	20	**18.4**	75	5
M5														
(E34) 3.5i 24V	1988 -1996	F	**968**	PART NOT AVAILABLE REFERENCE ONLY				Vented	315	76	28	**26.4**	79	5
		R	**969**	PART NOT AVAILABLE REFERENCE ONLY				Vented	300	61.1	20	**18.4**	75	5
M535i														
(E28)	1985 - 87	F	**970**	✓				Vented	282	76.1	25	**23**	79	5
		R	**670**	PART NOT AVAILABLE REFERENCE ONLY				Solid	284	61.1	10	**8.4**	75	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

BMW - Z / X SERIES

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Z3														
1.8i Roadster 1.9i 16V Roadster 2.0i 24V Roadster	1996 - 03 1996 - 99 1999 - 00	F	**978**	✓				Solid	286	51.7	12	**10.4**	79	5
2.0i, 2.2i, 2.8 Coupe/Roadster	1999 - 03	F	**979**	✓		✓		Vented	286	51.6	22	**20.4**	79	5
3.0i - Except M-Series	1999 - on	F	**966**	✓		✓		Vented	300	52	22	**20**	79	5
All models except M Series	1996 - 03	R	**982**	✓				Solid	272	83.4	10	**8.4**	75	5
M-Series	1997 - 03	F	**984**	✓		✓		Vented	315	52.5	28	**26.4**	79	5
		R	**985A**	✓				LH Vented	312	61	19.9	**18.4**	79	5
		R	**985B**	✓				RH Vented	312	61	19.9	**18.4**	79	5
Z4														
2.5i 24V	2003 - on	F	**979**	✓		✓		Vented	286	51.6	22	**20.4**	79	5
3.0i 24V	2003 - on	F	**966**	✓		✓		Vented	300	52	22	**20**	79	5
X5 (4 WD)														
(E53) 3.0Litre & 4.4i	2001 - on	F	**813**					Vented	332	62	30	**28.4**	75	5
		R	**814**					Solid	324	80	12	**10.4**	75	5
(E53) 4.6iS 4 Door Wagon	2001 - 03	F	**823**					Vented	356	62	36	**34.4**	75	5
4.8iS	2003 - 06	R	**824**					Vented	324	80	20	**18.4**	75	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CHEVROLET

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ASTRO VAN														
2WD & 4WD	2003 - 2005	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
CAMARO														
All models	1998 - 2002	F	**2996**	✓		✓		Vented	303	52.5	32	**30.7**	71	5
		R	**2997**	✓		✓		Vented	305	62	26	**24.7**	71	5
V6	2010 - on	F	**2602**					Vented	321	51.3	30	**27**	67.4	5
		R	**2603**					Vented	315	48	23	**21**	67.4	5
V8	2010 - on	F	**2604**	✓		✓	✓	Vented	355	50	32	**30**	67.4	5
		R	**2605**	✓		✓		Vented	365	47.7	28	**26**	67.4	5
COBALT														
SS 2.0L Coupe	2005 - on	F	**2052**	✓		✓		Vented	296	43	26	**23**	66	5
		R	**2053**	✓		✓		Solid	270	45	14	**12**	66	5
CORVETTE														
C4 - 12 inch	1988 - 96	F	**999**	✓				Vented	304.8	56	20.5	**19**	71	5
(curved vane left & right handed)		R	**997**	✓				Vented	304.8	50.4	20.5	**19**	71	5
C4 - 13 inch	1988 - 96	F	**996**	✓		✓		Vented	330	56	28	**26.5**	71	5
(curved vane REAR left & right handed)		R	**997**	✓				Vented	304.8	50.4	20.5	**19**	71	5
C5	1997 - 03	F	**067**	✓		✓	✓	Vented	325	46	32	**30.3**	71	5
(DBA067 interchangeable with DBA2994)		R	**2995**	✓		✓		Vented	305	49	26	**24**	70.5	5
C6	2005 - on	F	**2994**	✓		✓	✓	Vented	325	45	32	**30**	70.5	5
		R	**2995**	✓		✓		Vented	305	49	26	**24**	70.5	5
C6 Z-51	2005 - on	F	**2990**	✓		✓	✓	Vented	340	45	32	**30**	70.5	5
(performance package)		R	**2991**	✓		✓		Vented	330	49	26	**24**	70.5	5
C6 Z06	2005 - on	F	**2992**	✓		✓	✓	Vented	355	45.5	32	**30**	70.7	5
		R	**2993**	✓		✓		Vented	340	49.7	26	**24**	70.7	5
IMPALA														
All Models	2005 - 08	F	**2606**	✓		✓		Vented	303	52	30	**28**	70.7	5
		R	**2607**	✓		✓		Solid	278	51	11	**9**	70.7	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CHEVROLET TRUCKS/SUV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
AVALANCHE 1500														
w/o Ltd. Slip Axel 18.5mm min. thick. rear	2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
w/ Ltd. Slip Axel 28.5mm min. thick rear disc	2002 - 2006	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
w/18.5mm min. thick rear disc	2000 - 2002	F	**2000**	4x4		4x4		Vented	305	61	30	**27.2**	76	6
AVALANCHE 2500														
exc. factory 2" body lift	2002	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
exc. factory 2" body lift	2003 - 2006	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
BLAZER														
ALL	1992 - 1994	F	**773**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
EXPRESS 1500 VAN														
1/2 Ton	2003 - 2006	F	**2000**					Vented	305	61	29	**27.2**	79	6
EXPRESS 2500 VAN														
3/4 Ton - 7300lb GVW 6 lug	2003 - 2006	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
3/4 Ton - 8500-8600 GVW pass./panel (8 lug)	2003 - 2006	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CHEVROLET

SILVERADO 1500 1/2 TON 2WD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
1/2 Ton - ex. std. cab & std.	1988 - 1991	F	**773**	4x4		4x4		Vented	295	63.5	32.5	**30.8**	79	6
1/2 Ton	1992 - 1999	F	**773**	4x4		4x4		Vented	295	63.5	32.5	**30.8**	79	6
3/4 Ton - 7200 lb. GVW, 6 lug	1988 - 1998	F	**773**	4x4		4x4		Vented	295	63.5	32.5	**30.8**	79	6
w/ rear disc, exc. HD	1999 - 2000	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
4 dr. HD - 4.63" rear disc hub hole	2000 - 2001	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr	2001 - 2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
4 dr HD - crew cab (8 lug front)	2001	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. - ext. cab- Quadrasteer	2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
4 dr. HD - crew cab	2002	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. - reg. & ext. cab- 2 wh. steer	2003	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab - Quadrasteer w/ 18.5mm min, thick rear discs	2003	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. ext. cab quadrasteer w/ 28.5mm min, thick rear discs	2003	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. reg. & ext. cab 2 wh. steer	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab hybrid and quadrasteer models	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
2 dr. HD - ext. cab w/ 4.63" read disc hub hole	2004	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
2 dr. HD - ext. cab w/ 4.84" rear disc hub hole	2004	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab w/ rear disc, 2 wh. steer & quadrasteer	2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab w/ rear disc & 2 wh. Steer (8 lug front)	2006	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8

DBA™ DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

CHEVROLET

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SILVERADO 1500 1/2 TON 4WD														
w/ rear disc	1999 - 2000	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
2 dr. - reg. cab	2001	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab	2001	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
4 dr. HD	2001	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr.	2002	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
2 dr. ext. cab quadrasteer	2002	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
4 dr. HD crew cab	2002	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. ext. cab - SS	2003	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
4 dr. HD - crew cab - 2 wh. steer	2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
4 dr. Hd - crew cab Quadrasteer	2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
2 dr. - reg. & ext. cab 2 wh. steer	2004	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
2 dr. - reg. & ext. cab Quadrasteer	2004	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab - SS	2004	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
2 Dr. HD - ext. cab w/ 4.63" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. HD - ext. cab w/ 4.84" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. - crew cab - std. duty	2004	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
2 dr. - ext. cab - SS	2005	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6

DBA™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CHEVROLET

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SILVERADO 1500 1/2 TON 4WD continued														
4 dr. HD - crew cab w/ rear disc & 2 wh. steer	2005	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab, w/ rear disc & quadrateer	2005	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab w/ rear disc & 2 wh. steer (8 lug front)	2006	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
SILVERADO 2500 3/4 TON 2WD														
exc. 6.0L, w/ 5-speed 4.63" rear disc hub hole	1999 - 2000	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
6.0L w/ 5-speed 4.84 rear disc hub hole	1999 - 2000	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8
exc. HD - w/ A/T 4.63" rear disc hub hole	2001 - 2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
exc. HD - w/ M/T 4.84" rear disc hub hole	2001 - 2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8
exc. HD - w/ A/T 4.63" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
exc. HD - w/ M/T 4.84" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8
HD - 2 wh. steer	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
exc. HD	2005	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
exc. HD	2006	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
SILVERADO 2500 3/4 TON 4WD														
exc. 6.0L, w/ 5 speed 4.63" rear disc hub hole	1999 - 2000	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
6.0L w/ 5-speed 4.84" rear disc hub hole	1999 - 2000	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CHEVROLET

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SILVERADO 2500 3/4 TON 4WD continued														
exc. HD w/ A/T 4.63" rear disc hub hole exc. HD w/ A/T 4.63" rear disc hub hole	2001 - 2003 2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
exc. HD w/ M/T 4.84" rear disc hub hole exc. HD w/ M/T 4.84" rear disc hub hole	2001 - 2003 2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**					Vented	330	91.5	29	**27**	122	
HD - 2 wh. steer exc. HD exc. HD	2004 2005 2006	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
SUBURBAN 1500 1/2 TON 2WD														
w/28.5mm min. thick rear disc	2000 - 2002	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
all models	2003 - on	R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
SUBURBAN 1500 1/2 TON 4WD														
6 lug	1992 - 1999	F	**773**	4×4		4×4		Vented	295	63.5	32.5	**30.8**	79	6
w/28.5mm min. thick rear disc all models	2000 - 2002 2003 - on	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
w/18.5mm min. thick rear disc	2000 - 2002	F	**2000**	4×4		4×4		Vented	305	61	30	**27.2**	76	6
SUBURBAN 2500 3/4 TON 2WD & 4WD														
2 wh. steer - 4.63"	2000 - 2005	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
2 wh. steer - 4.84" Quadrasteer all models	2000 - 2005 2000 - 2005 2006 - on	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
TAHOE														
all models	2000 - 2006	F	**2000**	4×4		4×4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4×4		4×4		Vented	330	97	30	**28.5**	76	6
all models	2008 - on	F	**2010**	4×4		4×4		Vented	330	55.7	30	**28**	78.6	6
		R	**2011**	4×4		4×4		Vented	345	85.3	20	**18.5**	78.6	6

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CHRYSLER / DODGE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
300C + DODGE CHARGER														
3.5L V6 2WD & 4WD	2005 - on	F	**2438**	✓		✓		Vented	345	55.1	28	**26.5**	72.6	5
5.7L Hemi V8 2WD & 4WD		R	**2439**	✓		✓		Vented	320	67.3	22	**20.5**	72.6	5
5.7L V8 SRT8 2WD & 4WD	2005 - on	F	**2444**	✓		✓		Vented	360	58.5	32	**30**	72.5	5
		R	**2445**	✓		✓		Vented	350	68.5	28	**26**	72.6	5

IMPORTANT INFORMATION

The wheel stud P.C.D. of ALL the above Chrysler 300C + Dodge Charger discs are definitely 115 mm.
Correct P.C.D. wheels must be fitted.
DO NOT install any replacement wheels which have a wheel stud PCD of 114.3 mm = 4.5 inch,
because this will cause distortion of the BEARING HUB mounting face when the wheel nuts are tightened.
A new HUB will need to be installed to rectify the problem, if a wrong wheel is fitted.
Please advise your customers, failure to follow the above information will void any warranty.

CENTURA														
KB 4 Cyl GF16	1975 - 77	F	**206**	PART NOT AVAILABLE REFERENCE ONLY				Solid	249	35.6	12.9	**11.5**	69	4
CROSSFIRE														
all models - exc. SRT-6	2004 - 2006	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**267**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	56	9	**7.3**	67	5
DURANGO														
2WD & 4WD	1998 - 02	F	**2440**	✓		✓		Vented	287	64	24	**22.6**	73.5	6
All Models	2005 - on	F	**2442**	✓		✓		Vented	336	67.6	28	**26.4**	78.6	5
		R	**2443**	✓		✓		Vented	354	72.1	22	**20.4**	78.6	5
NEON														
Neon All Models	1996 - 99	F	**175**	✓				Vented	257	38	20	**18.4**	61	5
SE, LX Sedan		R	**166**	✓		✓		Solid	270	53	9	**7.25**	58	5
Neon All Models	2000 - on	F	**165**	✓				Vented	257	38	22	**20.4**	61	5
		R	**166**	✓		✓		Solid	270	53	9	**7.25**	57	5
PT CRUISER														
2.4L DOHC	2000 - on	F	**167**	✓		✓		Vented	280	39.5	23	**21.4**	61	5
		R	**166**	✓		✓		Solid	270	53	9	**7.25**	61	5
2.4 DOHC TURBO GT 2.4L DOHC TURBO	2003 2004 - on	F	**2446**	✓				Vented	280	39.9	28	**26.4**	61	5
		R	**2447**	✓				Solid	270	53.2	11.9	**7.25**	57.5	5
LIMITED	2004 - on	F	**2446**	✓				Vented	280	39.9	28	**26.4**	61	5
2.4L DOHC TURBO		R	**166**	✓		✓		Solid	270	53	9	**7.25**	61	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CHRYSLER / DODGE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
VALIANT														
VC, VE, VF	9/68 - 70	F	**201**	PART NOT AVAILABLE REFERENCE ONLY				Solid	279.4	61	12.7	**11.2**	79	5
VG (early) P.C.D. 101mm Rare Model	1970	F	**204**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	62	24	**22.3**	78	5
VG, VH, CH, VJ, VK, CJ, CK, CL (Girlock Calipers) P.C.D. 114mm	1970 - 73	F	**202**	✓				Vented	283	63	24	**22.3**	78	5
CL, CM	1976 - 81	F	**203**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	56.5	25.4	**24.4**	78	5
VIPER														
All models Front disc in 5000 series only	1992 - 2002	F	**52430**				✓	Vented	330	62.7	32	**30.1**	73.5	6
		R	**2431**	✓		✓		Vented	330	43.7	22.6	**20.4**	73.5	6
VIPER SRT10	2003 - 2005	F	**42448**			✓	✓	Vented	355	59.6	32	**30**	73.5	6
		R	**42449**			✓		Vented	355	52.2	32	**30**	73.5	6
VOYAGER														
GS (SE, LE & LTD)	1997 - 2000	F	**177**	✓				Vented	282	38	24	**22.4**	73.4	5
RG (SE, LX & LTD)	2001 - 09/07	F	**776**	✓				Vented	302	39	28	**26.5**	73.4	5
Front & All wheel drive		R	**777**	✓				Solid	290	56	12.5	**11.25**	72	5
Voyager III series 2.4, 3.3, 3.3 AWD, 3.8	02/00 - on	F	**776**	✓				Vented	282	38	24	**22.4**	73.4	5
2.5 CRD	08/05 - on													
2.8 CRD	06/04 - on													

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CITROEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
AMI SUPER														
1.0	1973 - 76	F	**054**	✓				Solid	269	29.5	9	**7**	87	6
AX														
GTI	1991 - 96	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
BERLINGO														
1.4i	10/02 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4i (vented disc)	1996 - 9/02	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.6i 16V	10/02 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.6i 16V	2001 - 9/02	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.8i	1997 - 01	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.9L Diesel	10/02 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.9L Diesel	1996 - 9/02	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0 HDi Turbodiesel	10/02 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
2.0 HDi Turbodiesel	2000 - 9/02	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
BERLINGO ENTREPRISE														
1.4i	10/02 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4i (vented disc)	1996 - 9/02	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.9 Diesel	10/02 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.9 Diesel	1996 - 9/02	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0 HDi Turbodiesel	10/02 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
2.0 HDi Turbodiesel	2000 - 9/02	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
BX														
19 16V	1987 - 94	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CITROEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
C2														
1.6i 16V	2003 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.6i 16V VTS (90kW)	2004 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
C3														
1.4 16V HDi Turbodiesel	2002 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.6i 16V	2002 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
C4														
1.4i 16V (Non ESP)	10/04 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4i 16V (with ESP)	10/04 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
1.6 16V HDi Turbodiesel (Non ESP) (66kW)	10/04 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.6 16V HDi Turbodiesel (with ESP) (66kW)	10/04 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
1.6 16V HDi Turbodiesel (80kW)	10/04 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
1.6i 16V (Non ESP)	10/04 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.6i 16V (with ESP)	10/04 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
C5														
1.6 16V HDi Turbodiesel	2004 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
1.8i 16V	2001 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
2.0 HDi Turbodiesel (80kW)	2001 - 4/09	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0 HPi 16V	2001 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0i 16V	2001 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
C5 BREAK														
1.6 16V HDi Turbodiesel	2004 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
1.8i 16V	2001 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0 HDi Turbodiesel (80kW)	2001 - 4/09	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0 HPi 16V	2001 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0i 16V	2001 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4

DBA DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

CITROEN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CX														
2000	1974 - 9/77	F	056	PART NOT AVAILABLE REFERENCE ONLY				Vented	260	54	20	18	58	5
		R	057	✓				Solid	233	58	9	7	58	5
2200	1974 - 9/77	F	056	PART NOT AVAILABLE REFERENCE ONLY				Vented	260	54	20	18	58	5
		R	057	✓				Solid	233	58	9	7	58	5
2400	10/77 - 85	F	056	PART NOT AVAILABLE REFERENCE ONLY				Vented	260	54	20	18	58	5
		R	059	✓				Vented	247	35	20.5	18.6	66	4
2500 i E	10/77 - 85	F	056	PART NOT AVAILABLE REFERENCE ONLY				Vented	260	54	20	18	58	5
		R	059	✓				Vented	247	35	20.5	18.6	66	4
D SERIES														
D SERIES	1966 - 76	F	050	PART NOT AVAILABLE REFERENCE ONLY				Solid	300	54	12	10.8	99.5	6
GS														
1015	1970 - 72	F	051	✓				Solid	270	32	7	6.3	90.5	5
1200	2/71 - 78	F	054	✓				Solid	269	29.5	9	7	87	6
		R	053	PART NOT AVAILABLE REFERENCE ONLY				Solid	178	15	7	6.3	45	4
1220 GXS Pallas	2/71 - 78	F	054	✓				Solid	269	29.5	9	7	87	6
		R	053	PART NOT AVAILABLE REFERENCE ONLY				Solid	178	15	7	6.3	45	4
SAXO														
1.6i	1996 - 04	F	273	✓				Vented	247	35	20.5	18.6	66	4
1.6i 16V VTS	1996 - 04	F	273	✓				Vented	247	35	20.5	18.6	66	4
		R	276	✓				Solid	246.5	25	8	6	71	4
XANTIA														
1.6i	1993 - 97	F	274	✓				Vented	266	27.5	20.5	18.6	66	4
1.8i	1993 - 02	F	274	✓				Vented	266	27.5	20.5	18.6	66	4
1.8i 16V	1993 - 02	F	274	✓				Vented	266	27.5	20.5	18.6	66	4
1.9 Diesel	1993 - 96	F	274	✓				Vented	266	27.5	20.5	18.6	66	4
1.9 Turbo Diesel (55/66kW) Automatic	1993 - 02	F	274	✓				Vented	266	27.5	20.5	18.6	66	4
2.0 HDi Turbo Diesel (66kW)	1993 - 02	F	274	✓				Vented	266	27.5	20.5	18.6	66	44
2.0i	1993 - 02	F	274	✓				Vented	266	27.5	20.5	18.6	66	4
2.0i 16v	1993 - 02	F	275	✓				Vented	283	27.5	22	20	66	4
2.0i Automatic	1998 - 02	F	275	✓				Vented	283	27.5	22	20	66	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CITROEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
XANTIA BREAK														
1.8i	1995 - 02	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
1.9 Turbodiesel	1993 - 02	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0 HDi Turbo Diesel (66kW)	1993 - 02	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0i 16v	1995 - 02	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
XSARA														
1.4 HDi Turbodiesel	1999 - 8/00	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4i	9/00 - 2004	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4i (with ABS)	1997 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.5 Diesel (with ABS)	1997 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.6i	1997 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.6i 16V	9/00 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.8i	1997 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.8i 16V	1997 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.9 Diesel	9/00 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.9 Diesel	1997 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.9 Turbodiesel	1997 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
2.0 HDi Turbodiesel	1999 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0 HDi Turbodiesel (66kW)	9/00 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
2.0 HDi Turbodiesel (80kW) (upto Ch. 09064)	01 - on	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0 HDi Turbodiesel (80kW) (from Ch. 09065)	01 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0i 16V	1997 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0i 16V (upto Ch. 09064)	9/00 - on	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0i 16V (from Ch. 09065)	9/00 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
All Models	1997 - 04	R	**276**	✓				Solid	246.5	25	8	**6**	71	4

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CITROEN

XSARA BREAK

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
1.4 HDi Turbodiesel	2003 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4i	9/00 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4i (Non ABS)	1998 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.4i (with ABS)	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.5 Diesel (Non ABS)	1998 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.5 Diesel (with ABS)	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.6i (Non ABS)	1998 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.6i (with ABS)	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.6i 16V	9/00 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.8i 8/16V	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.9 Diesel	9/00 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.9 Diesel (Non ABS)	1998 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.9 Diesel (with ABS)	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.9 Turbodiesel	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0 HDi Turbodiesel	1999 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0 HDi Turbodiesel (66kW)	9/00 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
2.0 HDi Turbodiesel (80kW) (upto Ch. 09064)	01 - on	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0 HDi Turbodiesel (80kW) (from Ch. 09065)	01 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0i 16V	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0i 16V (upto Ch. 09064)	9/00 - on	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0i 16V (from Ch. 09065)	9/00 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
All Models	1998 - on	R	**276**	✓				Solid	246.5	25	8	**6**	71	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

CITROEN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

XSARA COUPE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
1.4i (with ABS)	1998 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.4i	9/00 - 04	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.4 HDi Turbodiesel	2003 - 04	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.6i	1998 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.6i 16V	9/00 - 04	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.8i 16V VTS	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.9 Turbodiesel	1998 - 8/00	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
2.0 HDi Turbodiesel	1999 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0 HDi Turbodiesel (66kW)	9/00 - 04	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
2.0 HDi Turbodiesel (80kW) (upto Ch. 09064)	9/00 - on	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0 HDi Turbodiesel (80kW) (from Ch. 09065)	9/00 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0i 16V VTS (120kW) 9/00 - on (upto Ch. 09064)		F	**275**	✓				Vented	283	27.5	22	**20**	66	4
2.0i 16V VTS (120kW) (from Ch. 09065)	9/00 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
2.0i 16V VTS (98kW)	1998 - 8/00	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
All Models	1998 - 04	R	**276**	✓				Solid	246.5	25	8	**6**	71	4

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CITROEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
XSARA PICASSO														
1.6i (Bosch System)	2000 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.6i (Lucas System)	2000 - on	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.8i 16V (Bosch System)	2000 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
1.8i 16V (Lucas System)	2000 - on	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
2.0 HDi Turbodiesel (Bosch System)	2000 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
2.0 HDi Turbodiesel (Lucas System)	2000 - on	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
ZX														
1.6, 1.8, 1.9, 2.0	1991 - 98	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.9 Break Diesel	1994 - 98	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
1.9 Turbodiesel	1992 - 98	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
		R	**276**	✓				Solid	246.5	25	8	**6**	71	4
2.0i 16V	1992 - 98	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

DAEWOO

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
1.5 i 3D & 5D Hatchback 1.5 i 4D Sedan (Racer)	9/94 - on	F	**890**	✓				Solid	236	41	12	**9.7**	60	4
CIELO / ESPERO / LANOS														
Cielo	2/95 - on	F	**890**	✓				Solid	236	41	12	**9.7**	60	4
Cielo (All 13" Wheels) Espero CD 4D Sedan Lanos SOHC SE 1.4L , 1.5L	2/95 - on 6/97 - on	F	**896**	✓				Vented	236	41	20	**17**	60	4
Cielo (All 14" Wheels) Espero CD 4D Sedan Lanos DOHC SX 1.5L, 1.6L	2/95 - on 6/97 - on	F	**891**	✓				Vented	256	41	24	**22**	60	4
KALOS														
TK Sedan & Hatch 1.6L DOHC	2003 - 2005	F	**2032**	✓				Vented	236	41	20	**18**	59	4
LEGANZA														
Leganza SX (15" Wheels)	8/97 - on	F	**892**	✓				Vented	256	47	24	**22**	60	5
2.0 Litre, 2.2 Litre		R	**893**	✓				Solid	258	64.5	10	**8**	57	5
MATIZ														
Matiz	1999 - on	F	**897**	✓				Solid	236	35	12.7	**9.7**	86	4
NUBIRA														
Nubira	6/97 - on	F	**894**	✓				Vented	256	47	24	**22**	60	4
SX, SE, CDX		R	**895**	✓				Solid	258	64.5	10	**8**	57	4
TACUMA														
Tacuma U100 2.2L T/Cam	8/2000 - on	F	**726**	✓				Vented	256	47	24	**22**	60	4
MUSSO 4X4 (Also listed under Ssanyong)														
2.9L & 3.2L	1996 - on	F	**554**	✓				Vented	278	40	24	**22**	88	6
		R	**555**	✓				Solid	300	67	10.5	**8.5**	105	6

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

DAIHATSU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
APPLAUSE														
A101	6/89 - on	F	**295**	✓				Vented	234	47	18	**17**	56	4
A101	6/89 - 94	R	**494**	✓				Solid	236	40	10	**9**	56	4
5 Door 1.6 Litre	1998 - on	F	**295**	✓				Vented	234	47	18	**17**	56	4
ALTIS														
SXV20	7/97 - 2002	F	**733**	✓				Vented	255	49	28	**26**	62	5
MCV20	7/97 - 2002	F	**735**	✓				Vented	276	49.5	28	**26**	62	5
Rear disc fits all sedans and wagons		R	**736**	✓				Solid	269	65	10	**9**	62	5
CHARADE														
G10, G20	1980 - 1/83	F	**290**	✓				Solid	207	39	10	**9**	47	4
G11	1983 - 12/86	F	**294**	✓				Solid	208	29	11	**10**	47	4
G100, G102	1987 - 1/89	F	**295**	✓				Vented	234	47	18	**17**	56	4
G100, G102	1987 - 1/89	F	**291**	✓				6mm Flange	234	47	11	**10**	56	4
G100, G102 CX, TS Van G202	1989 - 1/93 1989 - 1/93 1993 - on	F	**296**	✓				7mm Flange	234	47	11	**10**	56	4
G100, G200, G203 SG	1989 - 94	F	**295**	✓				Vented	234	47	18	**17**	56	4
CENTRO														
MS, MX	1994 - 98	F	**297**	PART NOT AVAILABLE REFERENCE ONLY				Solid	211	35	10	**9**	70	4
Centro MS, MX	3/95 - 2002	F	**293**	✓				Solid	210	35	10	**9**	70	4
COPEN														
4cyl Turbo	5/2002 - on	F	**2498**	✓				Vented	246	42	17	**16**	55	4
DELTA														
V57, V67, V107	4/87 - on	F	**299**	✓				Vented	285	61	24	**23**	94	6
FEROZA														
4WD F300, F310	10/88 - on	F	**292**	4×4				Solid	277	30	12.5	**11.5**	96	5
4WD F300, F310	10/88 - on	F	**491**	4×4				Vented	277	33	18	**17**	96	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

DAIHATSU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HANDYVAN														
L80	8/85 - 2/90	F	**293**	✓				Solid	212	35	10	**9**	70	4
L55, L60 without booster	6/83 - 85	F	**490**	PART NOT AVAILABLE REFERENCE ONLY				Solid	236	33	10	**9**	70	4
L55, L60 with booster	6/83 - 85	F	**493**	✓				Solid	179	33	10	**9**	70	4
HI-JET														
S75	10/83 - 5/86	F	**293**	✓				Solid	212	35	10	**9**	70	4
S76	2/84 - 5/86	F	**492**	✓				Solid	211	23	10	**9**	79	4
MIRA														
L200, L201 (solid disc)	3/90 - 8/92	F	**297**	PART NOT AVAILABLE REFERENCE ONLY				Solid	211	35	10	**9**	70	4
L200, L201 (vented disc)	8/90 - on	F	**298**	PART NOT AVAILABLE REFERENCE ONLY				Vented	211	41	16	**15**	70	4
MOVE														
L601	5/97 - on	F	**495**	✓				Vented	234	41	16	**15**	55	4
PYZAR														
Pyzar	1997 - on	F	**497**	✓				Vented	250	47	18	**17**	56	4
ROCKY 4WD														
Non Turbo, F20, F50, F60 F70, F75, F80, F85	10/81 - 3/84 1984 - 4/93	F	**292**	4×4				Solid	277	30	12.5	**11.5**	96	5
F7#, F8# Turbo F73, F78	4/84 - 4/93 5/93 - on	F	**491**	4×4				Vented	277	33	18	**17**	96	5
SIRION														
M100 , NM101, 1.3Lt	6/98 - on	F	**495**	✓				Vented	234	41	16	**15**	55	4
TERIOS														
J100, J102 (DX, SX, AERO)	3/97 - on	F	**496**	✓				Solid	273	37.5	16	**15**	66.5	5
YRV														
YRV (M200) 4 Door Wagon	7/2001 - on	F	**498**	✓				Vented	246	41	16	**15**	55	4

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

DAIMLER

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
2.5 Litre Saloon V8	1959 - 67	F	**072**	✓				Solid	280	51.5	9.75	**8.5**	82.5	5
		R	**073**	✓				Solid	287	53	9.5	**8**	82.5	5
Limousine	1969 - 79	R	**075**	✓				Solid	262	25.5	12.5	**11.4**	70	4
Sovereign Series 1	1967 - 73	F	**074**	PART NOT AVAILABLE REFERENCE ONLY				Solid	283	60	12.5	**11.4**	82	5
Sovereign Series 2, 3	1974 - 82	F	**076**	✓				Vented	285	60.5	24	**22.9**	82	5
Sovereign Series 1, 2, 3	1968 - 82	R	**075**	✓				Solid	262	22.5	12.5	**11.4**	70	4
Double Six Series 1	1972 - 73	F	**074**	PART NOT AVAILABLE REFERENCE ONLY				Solid	283	60	12.5	**11.4**	82	5
Double Six Series 2, 3	1973 - 82	F	**076**	✓				Vented	285	60.5	24	**22.9**	82	5
Double Six Series 1, 2, 3	1972 - 82	R	**075**	✓				Solid	262	25.5	12.5	**11.4**	70	4
Double Six	1982 - 86	F	**076**	✓				Vented	285	60.5	24	**22.9**	82	5
		R	**075**	✓				Solid	262	25.5	12.5	**11.4**	70	4
Sedan 6 XJ Series	11/86 - 90	F	**077**	PART NOT AVAILABLE REFERENCE ONLY				Vented	295	67	22.3	**21**	80	5
		R	**078**					Solid	278	68	10	**8.8**	74	5
Sedan 6 XJ Series with Dana Rear Axle P.C.D of Large Holes 120.5 mm	11/86 - 90	R	**075B**	✓				Solid	262	25.5	12.5	**11.4**	70	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

EUNOS

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
30X	1992 - 01/98	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
		R	**534**	✓		✓		Solid	250.5	34.5	9	**8**	55	4
500	1992 - on	F	**950**	✓				Vented	258	49	24	**22**	72	5
		R	**951**	✓				Solid	261	40	9.5	**8**	72	5
800 - 2.5 litre	Up to 5/96	F	**868**	✓				Vented	274	50.8	28	**26**	72	5
		R	**867**	✓				Solid	286	57	9.5	**7.5**	72	5
	6/96 - on	F	**868**	✓				Vented	274	50.8	28	**26**	72	5
		R	**869**	✓				Solid	286	57	9.5	**7.5**	72	5
800M - 2.3 litre	Up to 5/96	F	**866**	PART NOT AVAILABLE REFERENCE ONLY				Vented	296	51	28	**26**	72	5
		R	**867**	✓				Solid	286	57	9.5	**7.5**	72	5
	6/96 - on	F	**866**	PART NOT AVAILABLE REFERENCE ONLY				Vented	296	51	28	**26**	72	5
		R	**869**	✓				Solid	286	57	9.5	**7.5**	72	5

FERRARI

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Dino 208 GT4	1973 - 5/86	F	**070**	PART NOT AVAILABLE REFERENCE ONLY				Vented	272	78	22	**20**	58	5
308 GT4 / GTB / GTS	1973 - 5/86	R	**071**	✓				Vented	277	73	20	**18**	67	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FIAT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
124, 125, 127, 128														
All Models	1966 - 85	F/R	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
130														
All Models	1976 - on	F	**162**	PART NOT AVAILABLE REFERENCE ONLY				Vented	275	72	18.5	**17**	59	5
131														
All Models	1974 - 85	F/R	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
132														
All Models	1972 - 76	F/R	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
GLS, 2000 GLS	1979 - 82	F	**161**	✓				Solid	251.5	51.2	11	**9.5**	62	4
850														
Coupe, Spider, Sport, Special, Super	1968 - 72	F/R	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
X 1/9														
All Models	1972 - 88	F/R	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
ARGENTA														
All Models	1981 - 86	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Vented	257	51.5	12	**10.8**	62	4
BRAVO														
2.0i 20V HGT	1995 - on	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
COUPE														
2.0i 16V Turbo	1994 - on	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
2.0i 20V Turbo (FA/175)	1996 - 00	F	**2160**	✓		✓		Vented	305	45	28	**26**	59	4
CROMA														
2.0i Turbo, 2.5i V6	1993 - 96	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
MAREA														
2.0i 20V (155/150)	1996 - 03	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
2.4 Turbodiesel (125)	1996 - 99	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
2.4 JTD Turbodiesel (130)	1999 - 00	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

dba™
DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FIAT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MAREA WEEKEND														
2.0i 20V (155/150)	1996 - 03	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
2.4 Turbodiesel (125)	1996 - 99	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
2.4 JTD Turbodiesel (130)	1999 - 00	F	**665**	✓		✓		Vented	284	44	22	**20.4**	59	4
PANDA														
All Models (except Selecta)	1980 - 04	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
REGATA														
70, 75, 85, 100, Diesel 1.7	1983 - 90	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
Diesel 1.9	1983 - 90	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
Turbodiesel 1.9	1986 - 90	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
REGATA WEEKEND														
70	1983 - 90	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
100	1984 - 90	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
Diesel 1.7	1983 - 90	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
Diesel 1.9	1984 - 90	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
Turbodiesel 1.9	1986 - 90	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
RITMO														
1.1, 1.3, 1.5	1978 - 88	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
1.6	1986 - 88	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
105 TC	1981 - 4/83	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
105 TC	5/83 - 85	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
Diesel	1978 - 88	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
Turbodiesel	1986 - 88	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
SPORT SPIDER (124)														
2.0i	1982 - 84	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
2.0i	1984 - 86	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
		R	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
UNO														
0.9, 1.0, 1.1, 1.3, 1.4, 1.5 Diesel 1.3	1983 - 95	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
FIORINO														
(127)	1978 - 87	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FIAT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MARENGO														
(Regata)	1983 - 90	F	**164**	✓				Solid	257	51.5	12	**10.8**	62	4
PANDA CITIVAN														
All Models	1992 - 04	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
PANDA VAN														
All Models	1986 - 04	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4
UNO VAN														
1.0	1990 - 95	F	**160**	PART NOT AVAILABLE REFERENCE ONLY				Solid	227	46	10.8	**9.7**	62	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
AMERICAN IMPORTED (EARLY)														
Fairlane Imported	1974 - 79	F	**123**	PART NOT AVAILABLE REFERENCE ONLY				Vented	300	81	30	**28.5**	HUB	5
LTD Imported	1977 - 79													
Ranchero														
Thunderbird														
Torino														
CAPRI														
GT1600, Deluxe, XL	1969 - 73	F	**113**	✓				Solid	245	27	12.7	**11.4**	68	4
GT3000	1970 - 73													
SA, SC, SE Convertible (Non Turbo)	1989 - 94	F	**930**	✓				Vented	238	31	18	**16**	75	4
SA, SC, SE Convertible (Turbo)	1989 - 94	F	**101**	✓				Vented	260	32	18	**16**	75	4
SA, SC, SE Convertible Hub Seal Dia. = 54mm	1989 - 94	R	**931**	✓				Solid	222	35	10	**8**	HUB	4
CORTINA														
220, 240, 440, MKI, MKII	10/62 - 71	F	**112**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	27	9.5	**8.6**	68	4
English Import DB625 Pads	1975 - 78	F	**118**	PART NOT AVAILABLE REFERENCE ONLY				Solid	247	26.5	12.5	**11.4**	68	4
TC, TD DB625 Pads	1971 - 5/77	F	**115**	PART NOT AVAILABLE REFERENCE ONLY				Solid	246	62	12.5	**11.5**	69	4
TE, TF DB1024 Pads	6/77 - 8/82	F	**116**	✓				Vented	237	63.5	22.4	**20**	78	4
CORSAIR														
UA	1989 - 92	F	**617**	✓				Vented	257	49	22	**20**	68	4
		R	**614**	✓				Solid	257	45	10	**8**	68	4
COUGAR														
COUGAR 3 Door Hatch	1999 - on	F	**508**	✓				Vented	278	47.5	24	**22.2**	64	4
2.5 Litre V6		R	**509**	✓				Vented	253	43.5	20	**18**	64	4
CROWN VICTORIA														
All models (incl Police)	1998 - 2001	F	**2148**	✓		✓		Vented	316	66	28	**27.75**	71.7	5
All models (incl Police)	2003 - 2009	F	**2146**	✓		✓		Vented	305.5	45	28	**26.35**	71.8	5
		R	**2149**	✓		✓		Vented	295	58.5	19	**18**	70.7	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ESCORT														
Sedan, P/Van (Mk 1) DB538 Pads	1970 - 75	F	**117**	PART NOT AVAILABLE REFERENCE ONLY				Solid	219	23	9.5	**8.5**	63	4
Sedan, P/Van (Mk 2) DB625 Pads	1975 - 81	F	**118**	PART NOT AVAILABLE REFERENCE ONLY				Solid	247	26.5	12.5	**11.4**	68	4
RS2000	5/79 - 81	F	**118**	PART NOT AVAILABLE REFERENCE ONLY				Solid	247	26.5	12.5	**11.4**	68	4
DOHC - 1.8L	1991 - 1996	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
w/ front caliper casting #22-14		R	**534**	✓		✓		Solid	250.5	34.5	9	**8**	55	4
SOHC - 1.9L w/ front caliper casting #22-13	1991 - 1996	F	**532**	✓				Vented	235	45.5	22	**20**	55	4
all models - Front	1997 - 2003	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
w/rear disc brakes		R	**534**	✓		✓		Solid	250	34.5	9	**8**	55	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD - FALCON (EARLY)

FALCON / FALCON UTE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
XP 5 Stud	3/65 - 66	F	**114A**	PART NOT AVAILABLE REFERENCE ONLY				Solid	274	50	12.7	**11.5**	79	5
XP 4 Stud	3/65 - 66	F	**114B**	PART NOT AVAILABLE REFERENCE ONLY				Solid	274	50	12.7	**11.5**	79	4
XR, XT 6 Cyl.	1966 - 6/69	F	**104**	PART NOT AVAILABLE REFERENCE ONLY				Solid	273	50	12.7	**11.5**	79.5	5
XR, XT 8 Cyl.	1966 - 6/69	F	**105**	✓				Solid	280	50	16	**14.6**	79.5	5
XW, XY, XA, XB	7/69 - 10/75	F	**106**	✓				Hat Only	287	58.5	24	**22.2**	83	5
XW, XY, XA, XB Special Note *	7/69 - 10/75	F	**106H**	✓		✓		With Studs	287	75	24	**22.2**	HUB	5
XB, XC (Rear) (9" DIFF)	11/73 - 79	R	**103**	✓				Vented	287	58.5	24	**22.2**	83	5
XB, XC, XD, XE, XF Incl. Ute XF Ute, XG Longreach Complete with Studs & Cups	10/75 - 88 1988 - 95	F	**107**	✓	✓	✓		Vented	287	75	24	**22.2**	HUB	5
XD (Rear) Flange Thickness 0.350 inch	1979 - 81	R	**108**	✓				Vented	287	70	24.6	**22.2**	70.5	5
XE, XF (Rear) Flange Thickness 0.250 inch	1982 - 88	R	**109**	✓				Vented	287	71	24	**22.2**	70.5	5
EA, EB, ED (Not ABS) XR6, XR8 Supplied with Grease Cap	1988 - 94	F	**110B**	✓		✓		Vented	287	70	24	**22.2**	HUB	5
EA, EA Series II (Rear)	1988 -12/89	R	**111A**	✓		✓		Solid	287	62	15	**14**	70.5	5
EA Series II, EB, ED XR6, XR8 (Rear) XG Longreach, XH	1990 - 94 1992 - on	R	**111B**	✓		✓		Solid	287	61	13	**12**	70.5	5
EB, ED with ABS XR6, XR8 Includes Sensor Ring	7/91 - 94	F	**130**	✓				Vented	287	115	24	**22.2**	HUB	5
EF, EL with ABS XR6, XR8 Includes Sensor Ring XH incl. Panel Van with ABS	Until 1/11/96 only 4/96 - 11/96	F	**132**	✓				Vented	287	115	25	**21***	HUB	5
EF, EL (Not ABS) XH incl. Panel Van non ABS	Until 1/11/96 4/96 - 11/96	F	**131**	✓				Vented	287	115	25	**21***	HUB	5
EL with ABS XR6, XR8 Includes Sensor Ring XH incl. Panel Van with ABS	1/11/96 11/96 - on	F	**134**	✓		✓		Vented	287	115	24	**21**	HUB	5
EL (not ABS) XH incl. Panel Van non ABS	1/11/96 11/96 - on	F	**135**	✓		✓		Vented	287	115	24	**21**	HUB	5
EF, EL XR6, XR8 (Rear)	1994 - on	R	**133**	✓		✓		Solid	299	56.5	10.5	**8.5**	70.5	5

***THE MINIMUM THICKNESS OF THE DBA 131 & 132 HAS BEEN REVISED TO FORDS CURRENT SPECIFICATIONS AND NOW COVERS ALL YEAR MODELS OF THE EF, EL, XH FALCONS. AS A RESULT THE DBA 134 & 135 WILL BE DISCONTINUED ONCE STOCK IS EXHAUSTED. THE MANUFACTURED THICKNESS OF THE DBA 131 & 132 HAS REMAINED AT 25MM AS THE CALIPER HAS NOT BEEN REVISED OVER ANY OF THESE MODELS.**

SPECIAL NOTE: * DBA 106H is a direct replacement for a DBA 106 + Hub
Please check bearings as they differ on the various models (Bearings not supplied)

* Check dimensions

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD - (FALCON)

FALCON / FALCON UTE (CONTINUED)

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
AU + UTE	1998 - 3/00	F	**500**	✓		✓		Vented	287	70	24	**21**	71.8	5
		R	**501**	✓		✓		Solid	287	51.5	10.5	**8.5**	70.5	5
AU II, AU III + UTE	3/2000 - on	F	**502**	✓		✓		Vented	287	65	28	**25.6**	71.8	5
(non Brembo upgrade)		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
BA incl RTV, BF Mark I & II XR6 4.0L DOHC	2002 - 2005	F	**504**	✓	✓	✓		Vented	298	65	28	**26**	71.5	5
BA XR6T 4.0L Turbo BA XR8 5.4L V8 4V	2002 - 2005 2003 - 2005	R	**505**	✓	✓	✓		Solid	303	51	16	**14.5**	70.5	5
BF Mark I XR6T 4.0L Turbo	2005 - 2006	F	**42107**			✓		Vented	322	68	28	**26**	71	5
XR8 5.4L V8		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FG SERIES XT, XR6, G6, G6E	2008 - on	F	**504**	✓	✓	✓		Vented	298	65	28	**26**	70.5	5
		R	**505**	✓	✓	✓		Solid	303	51	16	**14.5**	70.5	5
BF Mark II, FG SERIES XR6-Turbo, XR8, G6E-Turbo	2006 - on	F	**42107**			✓		Vented	322	68	28	**26**	71	5
		R	**4505**			✓		Solid	303	51	16	**14.5**	70.5	5

FORD PREMIUM UPGRADE - BA SERIES

BA XR6, XR6T, XR8	2002 - 2005	F	**42104**			✓	✓	Vented	325	45.3	32	**30**	71.5	5
(Black Ford 2 Piston front caliper)		R	**505**	✓	✓	✓		Solid	303	51	16	**14.5**	70.5	5

SPECIAL NOTE: BF FPV Premium Brake Kit = Brembo 6 Front and 4 Piston Rear Calipers. Standard on SUPER PURSUIT, optional on PURSUIT & F6 TORNADO.

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD - TICKFORD / FPV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
TICKFORD / FPV - F6 UTE														
FG - Performance Brakes Brembo 4 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FG - Premium Brakes Brembo 6 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
TICKFORD / FPV - F6X														
FG - Premium Brakes Brembo 6 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
TICKFORD / FPV - F6 TORNADO														
BF - Performance Brakes Brembo 4 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
BF - Premium Brakes Brembo 6 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
TICKFORD / FPV - F6 TYPHOON														
BA - Performance Brakes Blue FPV 2 Piston Calipers	2003 - 05	F	**42104**			✓	✓	Vented	325	45.3	32	**30**	71.5	5
		R	**505**	✓		✓		Vented	303	51	16	**14.5**	70.5	5
BF - Performance Brakes Brembo 4 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
BF - Premium Brakes Brembo 6 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5
TICKFORD / FPV - GS SEDAN & UTE														
FG - Standard Brakes 2 Piston Front Calipers	2009 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FG - Performance Brakes Brembo 4 Piston Calipers	2009 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD - TICKFORD / FPV

TICKFORD / FPV - GT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
EL Limited Edition	1997 - 98	F	**136**	✓				Vented	329	41	28	**26.4**	HUB	5
		R	**133**	✓				Solid	299	56.5	10.5	**8.5**	70.5	5
BA - Performance Brakes Blue FPV 2 Piston Calipers	2003 - 05	F	**42104**			✓	✓	Vented	325	45.3	32	**30**	71.5	5
		R	**505**	✓		✓		Vented	303	51	16	**14.5**	70.5	5
BA - Premium Brakes Brembo 4 Piston Calipers	2003 - 05	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5
BF - Performance Brakes Brembo 4 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
BF - Premium Brakes Brembo 6 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5
FG - Performance Brakes Brembo 4 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FG - Premium Brakes Brembo 6 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5

TICKFORD / FPV - GT-P

BA - Premium Brakes Brembo 4 Piston Calipers	2003 - 05	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5
BF - Premium Brakes Brembo 6 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5
FG - Premium Brakes Brembo 6 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD - TICKFORD / FPV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
TICKFORD / FPV - GT E														
FG - Premium Brakes Brembo 6 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5
TICKFORD / FPV - PURSUIT UTE														
AU III Series Performance Brakes Grey 2 Piston Front Calipers	2000 - 03	F	**506**	✓		✓	✓	Vented	329	48.3	28	**25**	71.8	5
		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
AU III Series Premium Brakes 4 Piston Front Calipers	2000 - 03	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
BA Performance Brakes Blue FPV 2 Piston Calipers	2003 - 05	F	**42104**			✓	✓	Vented	325	45.3	32	**30**	71.5	5
		R	**505**	✓		✓		Solid	303	51	16	**14.5**	70.5	5
BA - Premium Brakes 4 Piston Front Calipers	2003 - 05	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
BF - Performance Brakes Brembo 4 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
BF - Premium Brakes Brembo 6 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FG - Performance Brakes Brembo 4 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FG - Premium Brakes Brembo 6 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5

DISC BRAKES AUSTRALIA ™

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD - TICKFORD / FPV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
TICKFORD / FPV - PURSUIT 250														
AU III Series Performance Brakes Grey 2 Piston Front Caliper	2000 - 03	F	**506**	✓		✓	✓	Vented	329	48.3	28	**25**	71.8	5
		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
AU III Series Premium Brakes 4 Piston Front Calipers	2000 - 03	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
TICKFORD / FPV - SUPER PURSUIT UTE														
BF - Premium Brakes Brembo 6 Piston Calipers	2005 - 07	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FG - Premium Brakes Brembo 6 Piston Calipers	2008 - on	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**42108**			✓		Vented	328	59	26	**24**	71	5
TICKFORD / FPV - TE50														
AU III Series Performance Brakes Grey 2 Piston Front Caliper	2000 - 03	F	**506**	✓		✓	✓	Vented	329	48.3	28	**25**	71.8	5
		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
AU III Series Premium Brakes 4 Piston Front Calipers	2000 - 03	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5
TICKFORD / FPV - TS50														
AU III Series Performance Brakes Grey 2 Piston Front Caliper	2000 - 03	F	**506**	✓		✓	✓	Vented	329	48.3	28	**25**	71.8	5
		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
AU III Series Premium Brakes 4 Piston Front Calipers	2000 - 03	F	**42102**			✓	✓	Vented	355	50.5	32	**30**	71.8	5
		R	**507A**	✓		✓		Vented	330	51	28	**26**	70.5	5
		R	**507B**	✓		✓		Vented	330	51	28	**26**	70.5	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD

FAIRLANE / FAIRMONT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ZA, ZB 6 Cyl.	1966 - 6/69	F	**104**	PART NOT AVAILABLE REFERENCE ONLY				Solid	272	50	12.5	**11.5**	79.5	5
ZA, ZB 8 Cyl.	1966 - 6/69	F	**105**	✓				Solid	279	50	16	**14.6**	79.5	5
ZC, ZD, ZF, ZG Complete with Studs	7/69 - 10/75	F	**106H**	✓				Special Note *	287	75	24	**22.2**	HUB	5
ZG, ZH (Rear)	11/73 - 79	R	**103**	✓				Vented	287	58.5	24	**22.2**	83	5
ZG, ZH, ZJ, ZK, ZL Complete with Studs & Cups	10/75 - 88	F	**107**	✓	✓	✓		Vented	287	75	24	**22.2**	HUB	5
ZJ (Rear) Flange Thickness 0.350 inch	1979 - 81	R	**108**	✓				Vented	286	71.5	24	**22.2**	70.5	5
ZK, ZL (Rear) Flange Thickness 0.250 inch	1981 - 88	R	**109**	✓				Vented	286	71.5	24	**22.2**	70.5	5
NA, NA Series II, NC (Not ABS) Supplied with Grease Cap	1988 - 6/91	F	**110B**	✓		✓		Vented	287	70	24	**22.2**	HUB	5
NA, NA Series II (Rear)	1988 - 1/90	R	**111A**	✓		✓		Solid	287	62	15	**14**	70.5	5
NA Series II, NC (Rear)	1990 on	R	**111B**	✓		✓		Solid	287	61	13	**12**	70.5	5
NC with ABS Includes Sensor Ring	7/91 on	F	**130**	✓		✓		Vented	287	115	24	**22.2**	HUB	5
NF, NL with ABS Includes Sensor Ring only	Until 1/11/96	F	**132**	✓		✓		Vented	287	115	25	**22**	HUB	5
NL with ABS Includes Sensor Ring	1/11/96 - on	F	**134**	✓		✓		Vented	287	115	24	**21**	HUB	5
NF, NL (Rear)	2/95 - on	R	**133**	✓		✓		Solid	299	56.5	10.5	**8.5**	71	5
AU	1998 - on	F	**500**	✓		✓		Vented	287	70	24	**21**	71.8	5
		R	**501**	✓		✓		Solid	287	51.5	10.5	**8.5**	70.5	5
AU II, AU III - all models	2000 - on	F	**502**	✓		✓		Vented	287	65	28	**25.6**	71.8	5
(non Brembo upgrade)		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
BA, BF 4.0L DOHC	2002 - on	F	**504**	✓	✓	✓		Vented	298	65	28	**26**	71.5	5
BA, BF 5.4L SOHC V8		R	**505**	✓	✓	✓		Solid	303	51	16	**14.5**	70.5	5
BF 5.4L SOHC V8	2005 - on	F	**42107**			✓		Vented	322	68	28	**26**	71	5
(optional brake upgrade)		R	**42108**			✓		Vented	328	59	26	**24**	71	5

SPECIAL NOTE: * DBA 106H is a direct replacement for a DBA 106 + Hub
Please check bearings as they differ on the various models (Bearings not supplied)

* Check dimensions

DBA™ DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LTD														
54J (Rear)	6/73 - 79	R	**103**	✓				Vented	287	58.5	24	**22.2**	83	5
FC, FD, FE Complete with Studs & Cups	1979 - 88	F	**107**	✓	✓	✓		Vented	287	75	24	**22.2**	HUB	5
FC (Rear) Flange Thickness 0.350 inch	1979 - 81	R	**108**	✓				Vented	287	71.5	24	**22.2**	70.5	5
FD, FE (Rear) Flange Thickness 0.250 inch	1982 - 88	R	**109**	✓				Vented	287	71.5	24	**22.2**	70.5	5
DA, DA Series II, DC (Not ABS) Supplied with Grease Cap	1988 - 7/91	F	**110B**	✓		✓		Vented	287	70	24	**22.2**	HUB	5
DA, DA Series II (Rear)	1988 - 1/90	R	**111A**	✓		✓		Solid	287	62	15	**14**	70.5	5
DA Series II, DC (Rear)	1990 - 2/95	R	**111B**	✓		✓		Solid	287	61	13	**12**	70.5	5
DC with ABS Includes Sensor Ring	7/91 - 2/95	F	**130**	✓		✓		Vented	287	115	24	**22.2**	HUB	5
DF, DL with ABS Includes Sensor Ring only	Until 1/11/96	F	**132**	✓		✓		Vented	287	115	25	**22**	HUB	5
DL with ABS Includes Sensor Ring	1/11/96 - on	F	**134**	✓		✓		Vented	287	115	24	**21**	HUB	5
DF, DL (Rear)	2/95 - on	R	**133**	✓		✓		Solid	299	56.5	10.5	**8.5**	71	5
AU	1998 - 3/00	F	**500**	✓		✓		Vented	287	70	24	**21**	71.8	5
		R	**501**	✓		✓		Solid	287	51.5	10.5	**8.5**	70.5	5
AU II, AU III - all models	3/2000 - on	F	**502**	✓		✓		Vented	287	65	28	**25.6**	71.8	5
(non Brembo upgrade)		R	**503**	✓		✓		Solid	287	51	16	**14.5**	70.5	5
BA, BF 4.0L DOHC	2002 - on	F	**504**	✓	✓	✓		Vented	298	65	28	**26**	71.5	5
BA, BF 5.4L SOHC V8		R	**505**	✓	✓	✓		Solid	303	51	16	**14.5**	70.5	5
BF 5.4L SOHC V8	2005 - on	F	**42107**			✓		Vented	322	68	28	**26**	71	5
(optional brake upgrade)		R	**42108**			✓		Vented	328	59	26	**24**	71	5
FESTIVA														
WA	10/91 - 94	F	**635**	✓				Solid	219	37	13	**11**	75	4
WB Manual WF 3 & 5 Door	1994 - 97 11/97 - 2000	F	**530**	✓				Vented	235	45.5	18	**16**	55	4
WB Automatic WF 5 Door	1994 - 97 11/97 - 2000	F	**532**	✓		✓		Vented	235	45.5	22	**20**	55	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
FIESTA														
Fiesta	1996 - on	F	**854**	✓				Vented	239.5	43	20	**18**	63.5	4
1.6L 16V LX, Zetec, Ghia	11/03 - on	F	**2100**	✓				Vented	258	43.5	22	**20**	63.5	4
FOCUS														
1.8L, 2.0 all models	2002 - 2005	F	**2100**	✓		✓		Vented	258	43.5	22	**20**	63.5	4
		R	**2109**	✓				Solid	253	33	10	**8.9**	63.5	4
2.0L 127kW ST170	2003 - 2006	F	**2101**	✓				Vented	300	43.5	24	**22**	63.5	4
		R	**2103**	✓				Solid	280	25	10	**8.9**	63.5	4
2.0L DOHC	2005 - on	F	**2118**	✓				Vented	278	48.5	25	**23**	64	5
		R	**2119**	✓				Solid	265	41	11	**9**	64	5
XR5 Turbo 2.5L 5cyl Turbo	04/06 - on	F	**2120**	✓		✓		Vented	320	48.6	25	**23**	64	5
		R	**2121**	✓		✓		Solid	280	41	11	**9**	64	5

FORMULA FORD (SPECIAL APPLICATION)

Formula Ford Disc Flat design	PCD=148.5	F/R	**4993**	✓		✓		Solid	248	7	7		126	6
Formula Ford Disc Hat- design	PCD=95	F/R	**4994**	✓		✓		Solid	248	41	7		76	4
Formula Ford Disc Flat- slotted - AP calipers	PCD=148.5	F/R	**42999**	✓		✓		Solid	254	9.65	9.65		126	6

FORMULA 3

Formula 3 disc Flat- - slotted disc only	PCD=176mm	F/R	**5003.1**				✓	Vented	277.8	16.5	15.9		156	8

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
KA														
TB KA 1.3L Hatchback	1999 - on	F	**529**	✓				Solid	240	43	12	**10**	63.5	4
KA 1.3L Series II	2000 - on	F	**168**	✓				Vented	240	43	20	**18**	63.5	4
LASER / METEOR														
KA, KB GA, GB	1981-85 1982-85	F	**100**	✓				Solid	228	31	11	**10**	75	4
KC, KE (Non-Turbo) GC	1985-90 1985-87	F	**930**	✓				Vented	238	31	18	**16**	75	4
KE Turbo 2WD, 4WD	1987-90	F	**101**	PART NOT AVAILABLE REFERENCE ONLY				Vented	260	32	18	**16**	75	4
KC, KE Except 4WD Hub Seal Dia. = 54mm	1985-90	R	**931**	PART NOT AVAILABLE REFERENCE ONLY				Solid	222	35	10	**8**	HUB	4
KC, KE Except 4WD Hub Seal Dia. = 65mm	1985-90	R	**933**	✓				Solid	221	35	10	**8**	HUB	4
KE TX3 Turbo 4WD	1987-90	R	**932**	✓				Solid	247	30	10	**8**	75	4
KF, KH - 1600 EFi Manual Transmission	4/90-94 Check Dimensions	F	**530**	✓				Vented	235	45.5	18	**16**	55	4
KF, KH 1600 Automatic KH 1800 SOHC, DOHC	4/90 - 94 10/91-94	F	**532**	✓		✓		Vented Check Dimensions	235	45.5	22	**20**	55	4
KF, KH, TX3 1.8 DOHC KJ, KL 1.6, 1.8	11/89-94 1994 - 2000	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
KF, KH, 1.8L SOHC	4/90 - 94	R	**531**	✓		✓		Solid	231	35	9	**8**	55	4
KF, KH, KL TX3 2WD	10/91 - 2000	R	**534**	✓		✓		Solid	250.5	34.5	9	**8**	55	4
KF, KH, KL TX3 4WD Turbo	4/90 - 2000	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
KF, KH, KJ, KL, 1.8L DOHC	4/90 - 2000	R	**534**	✓		✓		Solid	250.5	34.5	9	**8**	55	4
KN, KQ 1.6L (LXi)	1999 - 2002	F	**532**	✓		✓		Vented	235	45.5	22	**20**	55	4
KN, KQ 1.8L (GLXi, SR)	1999 - 2002	F	**576**	✓				Vented	258	47	24	**22**	55	4
		R	**539**	✓				Solid	261	40	10	**8**	55	4
KQ 2.0L SR2	2000 - 2002	F	**577**	✓				Vented	258	48.5	24	**22**	72	5
		R	**951**	✓				Solid	261	40	9.5	**8**	72	5
MONDEO														
HA , HC, HD & HE 2.0L D.O.H.C	7/95 - on	F	**850**	✓				Vented	260	47	24	**22.2**	63.5	4
		R	**851**	✓				Vented	253	44	20	**18**	63.5	4

DBA™ DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MUSTANG														
All Complete with Studs	1968 - 73	F	**106H**	✓		✓		Vented	287	75	24	**22.2**	HUB	5
Cobra standard models only without upgraded discs	1994 - 04	F	**855**	✓				Vented	276	46.6	26	**24.8**	71	5
		R	**856**	✓				Solid	267	50	14	**12.8**	71	5
Cobra Bullitt & MACH 1 suits vehicles fitted with upgraded OE rotors	1994 - 04	F	**069**	✓		✓	✓	Vented	330	43.5	28	**26.4**	71	5
		R	**102A**	✓				RH Vented	296	51	18	**16.8**	71	5
			102B	✓				LH Vented	296	51	18	**16.8**	71	5
V6	2005 - 06	F	**2115**	✓		✓		Vented	293	48.5	30	**28.4**	71	5
		R	**2114**	✓		✓		Vented	300	35	19	**17.4**	71	5
GT (V8)	2005 - 06	F	**2113**	✓		✓	✓	Vented	316	48.5	30	**28.4**	71	5
		R	**2114**	✓		✓		Vented	300	35	19	**17.4**	71	5
Shelby Cobra GT500	2007 - on	F	**2124**	✓		✓	✓	Vented	355	47	32	**30**	71	5
		R	**2114**	✓		✓		Vented	300	35	19	**17.4**	71	5
PROBE														
w/ rear disc	1993 - 97	F	**950**	✓				Vented	258	49	24	**22**	72	5
		R	**951**	✓				Solid	261	40	9.5	**8**	72	5
w/ rear drum	1993 - 97	F	**950**	✓				Vented	258	49	24	**22**	72	5
TAURUS														
Ghia 4 dr sedan	2/96 - 99	F	**852**	✓				Vented	276	46.5	26	**24.75**	71	5
		R	**853**	✓				Solid	257	39.5	14	**12.75**	64.5	5
TELSTAR														
AR	5/83-9/85	F	**119**	✓				Solid	250	35	14	**12.5**	75	4
AS	9/85-9/87	F	**334**	✓				Vented	250	36	20	**18.5**	75	4
AR, AS	5/83-9/87	R	**945**	PART NOT AVAILABLE REFERENCE ONLY				Solid	254	50.2	10.2	**9**	HUB	4
AT	10/87-89	F	**633**	✓				Vented	264	47	24	**22**	64	5
AV TX-5	1990-1/92	R	**634**	PART NOT AVAILABLE REFERENCE ONLY				Solid	258	50	10	**8**	HUB	5
AX, AY	1992 - on	F	**950**	✓				Vented	258	49	24	**22**	72	5
		R	**951**	✓				Solid	261	40	9.5	**8**	72	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

FORD - TRUCKS

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
F100 / BRONCO														
F100, 2WD Complete with Studs & Cups	1973 - 5/87	F	**120**	✓				Vented	297	82	30	**28.5**	HUB	5
F100 4WD Bronco	1979 - 5/87 1981 - 87	F	**121**	✓				Vented	298	69	30	**28.5**	98.5	5
F150														
F150	5/87 - 90	F	**120**	✓				Vented	297	82	30	**28.5**	HUB	5
F150 4WD 5 Litre EFi V8	5/87 - 90	F	**121**	✓				Vented	297	70	30	**28.5**	98.5	5
F150 4WD 5 Litre V8 Including EFi	5/87 - 92	F	**937**	✓				Vented	298	75.5	30	**28.5**	HUB	5
F150 2WD	1986 - 94	F	**995**	PART NOT AVAILABLE REFERENCE ONLY				Vented	319	94	32	**30**	HUB	8
F150 5.4L 5 Lug exc. Lightning	1999 - 05	F	**2150**	✓				Vented	308	104	26	**24.5**	HUB	5
		R	**863**	PART NOT AVAILABLE REFERENCE ONLY				Solid	334	57	14	**12**	87	5
F150 SVT 5.4L 5 Lug Lightning & Nascar	1999 - 05	F	**2151**	✓				Vented	308	103	30	27.7	HUB	5
5.4L Supercharged V8		R	**863**	PART NOT AVAILABLE REFERENCE ONLY				Solid	334	57	14	**12**	87	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

FORD - TRUCKS

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
F250														
F250 Single Piston, 2WD	1973 - 79	F	**124**	✓				Vented	320	95	30	**28.5**	HUB	8
F250 Double Piston, 2WD	1976 - 79	F	**122**	PART NOT AVAILABLE REFERENCE ONLY				Vented	320	94	32	**30**	HUB	8
F250 2WD 128A = 1/2" Dia. Studs 128B = 9/16" Dia Studs	2/83 - 85	F	**128A** **128B**					Vented	320	95	32	**30**	HUB	8
F250 Double Piston, 2WD	1986 - 93	F	**995**	PART NOT AVAILABLE REFERENCE ONLY				Vented	319	94	32	**30**	HUB	8
2WD, 4WD XL, XLT 5.4L, 7.3L Turbo Diesel	07/01 - 04	F	**795**	✓				Vented	330	144	38	**36**	HUB	8
2WD, 4WD XL, XLT 4 Wheel ABS models	07/01 - 04	F	**798**	4×4		4×4		Vented	331	99.5	38	**36**	128.7	8
2WD/4WD XL, XLT 4.2L Turbo Diesel	07/01 - 04	F	**797**	✓				Vented	330	143	38	**36**	HUB	8
all models (Rear)	07/01 - 04	R	**796**	4×4		4×4		Vented	326	98.5	30	**28**	126.5	8
2WD	2005 - on	F	**2797**	✓				Vented	347	116	38	**36.4**	HUB	8
4WD	2005 - on	F	**2798**	4×4		4×4		Vented	347	100	38	**36.4**	129	8
Single Rear Wheel - all models	2005 - on	R	**2799**	4×4		4×4		Vented	340	126	34	**32.4**	127	8
F350														
F350 2WD * Rare Model *	1974 - 75	F	**938**	PART NOT AVAILABLE REFERENCE ONLY				Rotor Only	320	98	26	**24**	91	8
F350 2WD Single Rear Wheel	1976 - 79	F	**125**	✓				Vented	320	94	32	**30**	HUB	8
F350 2WD Dual Rear Wheel	1981 - 85	F	**129**	PART NOT AVAILABLE REFERENCE ONLY				Rotor Only	318	93	32	**30**	91	8
F350 2WD Single Rear Wheel	1986 - 94	F	**995**	PART NOT AVAILABLE REFERENCE ONLY				Vented	319	94	32	**30**	HUB	8
All models single rear wheel 5.4L, 7.3L Turbo Diesel	07/01 - 04	F	**795**	✓				Vented	330	144	38	**36**	HUB	8
Single Rear Wheel - all models		R	**796**	4×4		4×4		Vented	326	98.5	30	**28**	126.5	8
Super Cab 4 Wheel ABS	07/01 - 04	F	**798**	4×4		4×4		Vented	331	99.5	38	**36**	128.7	8
2WD Super/Crew Cab 4WD Super Cab	07/01 - 04	F	Not Available											
Dual Rear Wheel		R	**799**	4×4		4×4		Vented	326	113	30	**28**	119.5	8
2WD	2005 - on	F	**2797**	✓				Vented	347	116	38	**36.4**	HUB	8
4WD	2005 - on	F	**2798**	4×4		4×4		Vented	347	100	38	**36.4**	129	8
Single Rear Wheel - all models	2005 - on	R	**2799**	4×4		4×4		Vented	340	126	34	**32.4**	127	8

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

FORD - TRUCKS

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
COURIER / RAIDER														
All Models	1981 - 84	F	**941**	PART NOT AVAILABLE REFERENCE ONLY				Solid	255	36	20	**19**	80	4
1.8, 2.0, 2.2, 2.6 2WD	1985 - 95	F	**631**	✓				Vented	256	20	20	**18**	86	6
PD 2.6L 2WD	4/96 - on	F	**958**	✓				Vented	255.5	24	24	**22**	86	6
2.6L 4WD incl. Raider	5/87 - 98	F	**965**	✓				Vented	272	25	22	**20**	93	6
2.6L 4WD incl. South Africa	11/98 - on	F	**964**	✓				Vented	275	24	24	**22**	93	6
Courier 4WD	1996 - 1998	F	**959**	✓				Vented	274	28	28	**26**	93	6
Ranger / Courier 2.5L, 2.6L	2003 - on	F	**2952**	4x4		4x4		Vented	288.5	70.5	28	**26**	98	6
ECONOVAN / SPECTRON (UTES & VANS)														
1400/1600/2200	5/81 - 3/84	F	**939**	✓				Vented	275	33	20	**19**	85	4
1400, 1800, 2000, 2200 SWB models only Spectron SGMD 1800	4/84 - 96	F	**632A** **632B**					RH Vented LH Vented ID Groove	231.5	58.5	18	**16**	HUB	4
1800/2000/2200 Spectron 2000 (STD & LWB)	3/84 - 92	F	**631**	✓				Vented	256	20	20	**18**	86	6
2000 Pickup, Crew Cab Ute	4/84 - 88	F	**934**	✓				Vented	268	20	20	**18**	86	6
2000 Pickup, Crew Cab Ute	7/87 - 7/88	F	**631**	✓				Vented	256	21	20	**18**	86	6
2000 4WD Wagon	3/86 - 88	F	**943**	PART NOT AVAILABLE REFERENCE ONLY				Vented	256	25	24	**22**	93	6
Spectron SGMB 1600	2/83 - 4/84	F	**939**	✓				Vented	275	33	20	**19**	85	4
Maxi 4.4m Van 2.0, 2.2 Litre	12/94 - 1/97	F	**857**	✓				Vented	256	25	24	**22**	86	6
Maxi 4.7m Van 2.0, 2.2 Cabchassis Glass Van 1.8 Litre	12/94 - 1/97	F	**934**	✓				Vented	268	20	20	**18**	86	6
JG 4.0m Van S.W.B.	2/97 - on	F F	**859A** **859B**	PART NOT AVAILABLE REFERENCE ONLY				RH Vented LH Vented	256 256	72 72	18 18	**16** **16**	HUB HUB	4 4
JG 4.4m Van 2.0 Litre	6/97 - on	F	**958**	✓				Vented	256	24	24	**22**	86	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

FORD - TRUCKS

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

ESCAPE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
XLS 2.0L, XLS, XLT 3.0L	2000 - 05	F	**957**	4x4		4x4		Vented	278	47	24	**22**	72	5
2.3L 4 cyl, 3.0L V6	2006 - on	F	**2560**	4x4		4x4		Vented	302.7	47.2	26	**24**	72	5
		R	**2561**	4x4		4x4		Solid	302	56.1	12	**11**	72	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

EXPLORER / EXPEDITION

UN, UP, US,	11/96 - 4/01	F	**860**	✓				Vented	286	66	26	**24.5**	72	5
XLT 4.0 Litre		R	**861**	PART NOT AVAILABLE REFERENCE ONLY				Solid	285	58.5	12	**11**	71	5
Expedition XLT 4.6 Litre V8	5/01 - 05	F	**862**	PART NOT AVAILABLE REFERENCE ONLY PART NOT AVAILABLE REFERENCE ONLY				Vented	308	103	30	**27.7**	HUB	5
SOHC 2WD		R	**863**	✓				Solid	334	57	14	**12**	87	5
UT V8 4.6 Litre 4WD	5/01 - 05	F	**864**	✓				Vented	305	56.5	26	**24.5**	82	5
XLT 4 Door Wagon		R	**865**	✓				Solid	301	58.5	12	**11**	82	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

FORD - TRUCKS

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MAVERICK														
GY, KY	1988 - 93	F	**329**	✓		✓		Vented	294	30	20	**18**	104	6
Optional* Disc Rear End		R	**622**	✓		✓		Vented	315	80	18	**16**	111	6
TERRITORY														
TX, TS, GHIA - RWD + AWD	6/2004 - on	F	**2107**	✓		✓		Vented	322	68	28	**26**	71	5
except TURBO front disc		R	**2108**	✓		✓		Vented	328	59	26	**24**	71	5
TRANSIT														
125 Series V21, V22, V24, V33	1973 - 86 Single Rear Wheel	F	**127**	✓				Solid	270	71.5	14.3	**13.2**	78	5
175 Series, V21, V22, V24, V33, V51, V54	1973 - 86 Dual Rear Wheels	F	**126**	✓				Vented	270	71.5	24	**22.6**	78	5
VE High Roof 2.5 L Diesel	1991 - 2000	F	**827**	✓				Solid	254	32	14.7	**12.9**	78	5
VE 15" Wheel	1/94 - 2000	F	**828**	✓				Vented	270	43	24	**22.15**	78	5
VG 2.5Lt 14" Wheel	1/96 - 2000	F	**829**	✓				Vented	254	43	24	**22.15**	78	5
VH , VJ	2001 - 06	F	**871**	✓				Vented	294	43	24	**22.15**	82	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

GMC

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Ambulance		F	**848**	✓				Vented	317	80	32.5	**31**	HUB	8

SIERRA 1500 1/2 TON FULL SIZE PICKUP 2WD

w/ rear disc, exc. HD	1999 - 2000	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr	2001 - 2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
4 dr HD - crew cab (8 lug front)	2001	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. - ext. cab- Quadrasteer	2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
4 dr. HD - crew cab	2002	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. - reg. & ext. cab- 2 wh. steer	2003	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab - Quadrasteer w/ 18.5mm min, thick rear discs	2003	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. ext. cab quadrasteer w/ 28.5mm min, thick rear discs	2003	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. reg. & ext. cab 2 wh. steer	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab hybrid and quadrasteer models	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
2 dr. HD - ext. cab w/ 4.63" read disc hub hole	2004	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
2 dr. HD - ext. cab w/ 4.84" rear disc hub hole	2004	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab w/ rear disc, 2 wh. steer & quadrasteer	2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab w/ rear disc & 2 wh. Steer (8 lug front)	2006	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8

SIERRA 1500 1/2 TON FULL SIZE PICKUP 4WD

w/ rear disc	1999 - 2000	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - reg. cab	2001	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab	2001	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
2 dr.	2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

GMC

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SIERRA 1500 1/2 TON FULL SIZE PICKUP 4WD CONTINUED

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
2 dr. ext. cab quadrasteer	2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
4 dr. HD crew cab	2002	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. ext. cab	2003	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
4 dr. HD - crew cab - 2 wh. steer	2003	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
4 dr. Hd - crew cab Quadrasteer	2003	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
2 dr. - reg. & ext. cab 2 wh. steer	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - reg. & ext. cab Quadrasteer	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
2 dr. - ext. cab	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
2 Dr. HD - ext. cab w/ 4.63" rear disc hub hole	2004	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 dr. HD - ext. cab w/ 4.84" rear disc hub hole	2004	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. - crew cab - std. duty	2004	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
4 dr. HD - crew cab w/ rear disc & 2 wh. steer	2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab, w/ rear disc & quadrateer	2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
4 dr. HD - crew cab w/ rear disc & 2 wh. steer (8 lug front)	2006	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8

SIERRA 2500 3/4 TON FULL SIZE PICKUP 2WD

exc. 6.0L, w/ 5-speed 4.63" rear disc hub hole	1999 - 2000	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
6.0L w/ 5-speed 4.84" rear disc hub hole	1999 - 2000	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4x4		4x4		Vented	330	91.5	29	**27**	122	8

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

GMC

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SIERRA 2500 3/4 TON FULL SIZE PICKUP 2WD CONTINUED

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
exc. HD - w/ A/T 4.63" rear disc hub hole	2001 - 2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
exc. HD - w/ M/T 4.84" rear disc hub hole	2001 - 2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8
exc. HD - w/ A/T 4.63" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
exc. HD - w/ M/T 4.84" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
HD - 2 wh. steer	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
exc. HD	2005	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
exc. HD	2006	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8

SIERRA 2500 3/4 TON FULL SIZE PICKUP 4WD

exc. 6.0L, w/ 5 speed 4.63" rear disc hub hole	1999 - 2000	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
6.0L w/ 5-speed 4.84" rear disc hub hole	1999 - 2000	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8
exc. HD w/ A/T 4.63" rear disc hub hole	2001 - 2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
exc. HD w/ M/T 4.84" rear disc hub hole	2001 - 2003	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8
exc. HD w/ A/T 4.63" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4×4		4×4		Vented	330	85.6	29	**26.5**	118.2	8
exc. HD w/ M/T 4.84" rear disc hub hole	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2051**	4×4		4×4		Vented	330	91.5	29	**27**	122	8
HD - 2 wh. steer	2004	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8
exc. HD	2005 - 2006	F	**2048**	4×4		4×4		Vented	325	89.5	38	**36.5**	118.2	8

DBA™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

GMC

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SUBURBAN 1500 1/2 TON 4WD														
6 lug	1992 - 1999	F	**773**	4x4		4x4		Vented	295	63.5	32.5	**30.8**	79	6
w/28.5mm min. thick rear disc	2000 - 2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
all models	2003 - on	R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
w/28.5mm min. thick rear disc	2000 - 2002	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
all models	2003 - on													
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
w/18.5mm min. thick rear disc	2000 - 2002	F	**2000**	4x4		4x4		Vented	305	61	30	**27.2**	76	6
SUBURBAN 2500 3/4 TON 2WD														
2 wh. steer - 4.63”	2000 - 2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 wh. steer - 4.84”	2000 - 2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
Quadrasteer	2000 - 2005													
all models	2006 - on													
SUBURBAN 2500 3/4 TON 4WD														
2 wh. steer - 4.63”	2000 - 2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
2 wh. steer - 4.84”	2000 - 2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
Quadrasteer	2000 - 2005													
all models	2006 - on													
YUKON 2WD EXCEPT YUKON XL														
ALL	1992 - 1994	F	**773**	4x4		4x4		Vented	295	63.5	32.5	**30.8**	79	6
w/ rear disc	2000 - 2005	F	**2000**	4x4		4x4		Vented	305	61	30	**27.2**	76	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
ALL	2006	F	**2000**	4x4		4x4		Vented	305	61	30	**27.2**	76	6
YUKON 4WD EXCEPT YUKON XL														
w/ rear drum	1995 - 1999	F	**773**	4x4		4x4		Vented	295	63.5	32.5	**30.8**	79	6
w/ rear disc	2000 - 2005	F	**2000**	4x4		4x4		Vented	305	61	30	**27.2**	76	6
ALL	2006	F	**2000**	4x4		4x4		Vented	305	61	30	**27.2**	76	6

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

GMC

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
YUKON XL 1/2 TON 2WD & 4WD														
ALL	2000 - 2005	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
		R	**2001**	4x4		4x4		Vented	330	97	30	**28.5**	76	6
ALL	2006	F	**2000**	4x4		4x4		Vented	305	61	29	**27.2**	79	6
YUKON XL 3/4 TON 2WD & 4WD														
w/ 4.63" rear disc hub hole 2 wh. steer	2000 - 2005	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
		R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
w/ 4.84" rear disc hub hole 2 wh. steer		F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8

HILLMAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Hunter, Arrow, Hustler (DB835 Pads)	1967 - 74	F	**085**	✓				Solid	244	23.5	8.8	**7.9**	66	4

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ADVENTRA														
all models - AWD / 4WD	2004 - on	F	**2050**	✓		✓		Vented	302	45	28	**25**	71.5	5
(rear suits all models 2WD+4WD)		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
APOLLO														
JK, JL SL, SLX, SLE Exec	1989 - 92	F	**730**	✓				Vented	255	47.5	22	**21**	54	5
JK, JL SL, SLX, SLE Exec	1989 - 92	R	**741**	✓				Solid	269	65	10	**9**	54	5
JM 4 Cyl	3/93 - 97	F	**733**	✓				Vented	255	49	28	**26**	62	5
JM V6	3/93 - 97	F	**735**	✓				Vented	275	49.5	28	**26**	62	5
JM Sedan	3/93 - 97	R	**736**	✓				Solid	269	65	10	**9**	62	5
JM Wagon	3/93 - 97	R	**734**	✓				Solid	288	65	10	**9**	62	5
ASTRA														
LB, LC	1984 - 7/87	F	**303**	✓				Solid	240	35.5	12	**11**	76	4
LD DB1117 Pads	7/87 - 89	F	**602**	✓				Vented	240	45.5	18	**16**	60	4
TR City 1.6 Litre	8/96 - 98	F	**021**	✓				Vented	235	41.25	20	**17**	60	4
TR 1.8 & 2.0	8/96 - 98	F	**023**	✓				Vented	256	41.1	24	**21**	60	4
		R	**819**	✓				Solid	260	69	10	**8**	57	4
TS (City) 5 stud wheels	9/1998 - 05	F	**815**	✓				Vented	280	42	25	**22**	70	5
TS Series II		R	**816**	✓				Solid	264	42	10	**8**	65	5
TS (City) 4 stud wheels	9/1998 - 05	F	**817**	✓				Vented	256	41	24	**21**	60	4
TS Series II		R	**818**	✓				Solid	240	42	10	**8**	57	4
TS SRI Turbo	2002 - 04	F	**2815**	✓		✓		Vented	308	42.3	25.1	**22**	70	5
		R	**816**	✓				Solid	264	42	10	**8**	65	5
AH - CD, CDX, CDXi	2005 - 06	F	**815**	✓				Vented	280	42	25	**22**	70	5
Coupe, Hatch, Wagon		R	**816**	✓				Solid	264	42	10	**8**	65	5
AH07 - SRi, Twin Top, CDTi	2007 - on	F	**2815**	✓		✓		Vented	308	42.3	25.1	**22**	70	5
2.2L Petrol, 1.9L Diesel		R	**816**	✓				Solid	264	42	10	**8**	65	5
AH07 - SRi Turbo	2007 - on	F	**2815**	✓		✓		Vented	308	42.3	25.1	**22**	70	5
2.0L Turbo		R	**2035**	✓		✓		Solid	278	42.2	10	**8**	65	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
BARINA														
MB, ML	2/85 - 88	F	**012**	✓				Solid	215	33.5	10	**8**	86	4
MF, MH	1989 - 94	F	**022**	✓				Vented	231	50	17	**15**	64	4
SB City 1.2L & 1.4L	1994 - 2000	F	**820**	✓				Solid	236	41	12	**9.7**	60	4
SB Joy, Swing 1.4L	1994 - 2000	F	**821**	✓				Vented	236	41	20	**17**	60	4
SB GSi 1.6L	1994 - 2000	F	**822**	✓				Vented	256	41	20	**17**	60	4
XC 2D+4D Hatchback	4/2001 - 06	F	**847**	✓				Vented	260	41.2	24	**21**	60	4
		R	**849**	✓				Solid	240	41	10	**8**	57	4
TK Sedan & Hatch 1.6L DOHC	2006 - ON	F	**2032**	✓				Vented	236	41	20	**18**	59	4
CALIBRA														
YE YE V6 2 Door Coupe Some models have DBA 038 on Front	9/91 - on 7/95 - on	F	**023**	✓				Vented	256	41.1	24	**21**	60	4
		R	**024**	✓				Solid	270	77	10	**8**	57	4
C20 ELT Turbo, C25 XE, V6 From Chassis : T9000001 From Chassis : T1000001	1992 - 97	F	**825**	✓				Vented	288	42	25	**22**	70	5
YE 2 Door Coupe 4 Wheel Drive	6/94 - on	F	**038**	PART NOT AVAILABLE REFERENCE ONLY				Vented	284	41	23.7	**21**	70	5
		R	**039**	PART NOT AVAILABLE REFERENCE ONLY				Solid	270	77	10	**8**	65	5
CAMIRA														
JB 1600cc	1982 - 84	F	**011**	✓				Solid	236	41.25	12.7	**10.7***	60	4
JD 1800cc, JE 2000cc	1984 - 8/89	F	**021***	✓				Vented	236	41.25	20	**17**	60	4
CAPTIVA														
All Models	2006 - on	F	**2040**	✓				Vented	296	52	29	**27.4**	70.7	5

dba™ DISC BRAKES AUSTRALIA

* SPECIAL NOTE: GENERAL MOTORS HOLDEN AUTOMOTIVE REVISED SPECIFICATIONS

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

HOLDEN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

COMMODORE INCL. UTE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
VC, VH 4 Cyl Complete with Studs and Cups	1980 - 83	F	**013**	✓				Solid	256	78	15.6	**14.3**	HUB	5
VB, VC, VH, VK, 6, 8 Cyl VL 6 Cyl VN, VG, V6 incl. UTE VP V6 (Up to & Incl. Chassis No.L569902)	1978 - 86 1986 - 88 1988 - 92	F	**015**	✓		✓		Vented Complete with Studs and Cups	270	82	22	**20***	HUB	5
VL 6 Cyl Turbo VL V8, Calais VN V6 with FE2 Suspension VN, VG V8 incl. UTE VP V8 (Up to & Incl. Chassis No. L570556) VQ Statesman without ABS	1986 - 88 1986 - 88 1988 - 9/91 1988 - 92 3/90 - 10/92	F	**017**	✓		✓		Vented Complete with Studs and Cups	290	82	22	**20***	HUB	5
VP 6 Cyl incl. UTE (Chassis No. 569903 on) (Limited Run) Non ABS	1992 Ends 10/92	F	**025**	✓				Vented Complete with Studs and Cups	272	82	23	**20***	HUB	5
VP V8 incl. UTE (Chassis No. 570557 on) VP V6 Series II VQ Statesman	1992 - 93 11/92 - 93	F	**027**	✓				Vented Suitable for ABS No Sensor Ring Supplied	290	82	23	**20***	HUB	5
VR, VS incl. ABS incl. UTE	7/93 - on	F	**035**	✓		✓		Vented	289	83	23	**20***	70	5
VB, VC, VH, VK, VL VN, VP, VR, VS incl. UTE Except IRS 6, 8 Cyl VQ Statesman without IRS	1978 - 97 1990 - 93	R	**016**	✓		✓		Solid	279	83	10.5	**8.5**	70	5
VP, IRS VQ Statesman IRS	1992 - 7/93	R	**026**	✓				Solid	279	67	10.5	**8.5***	70	5
VR, VS IRS	7/93 - 97	R	**036**	✓		✓		Solid	279	86	10.7	**8.5***	70	5
VR, VS IRS 10 Hole Stud Pattern	7/93 - 97	R	**036B**	✓				Solid	279	86	10.7	**8.5***	70	10
VS 10 Hole Stud Pattern VS UTE	2/95 - 97 2/95 - 00	R	**037**	✓		✓		Solid	279	83	10.7	**8.5***	70	10
VT, VX, VY, VZ, V6 & V8 + VT, VX, VU, VZ UTE WH, WK, WL Statesman	9/97 - 05 2001 - 07	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
VZ SSZ Commodore incl. Ute	2005 - 06	F	**2020™**	✓	✓	✓	✓	Vented	320	83	32	**30**	71.6	5
		R	**2021™**	✓	✓	✓		Vented	286	80	18	**16**	70	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
COMMODORE INCL. UTE – CONTINUED														
VZ SSZ 1 Tonner	2005 - 06	F	**2020™**	✓	✓	✓	✓	Vented	320	83	32	**30**	71.6	5
		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
VE / VEII **V6** Omega, Berlina SV6	08/06 - on	F	**2026™**	✓	✓	✓		Vented	298	52.2	30	**28**	67.5	5
Calais, Calais V, WM Statesman		R	**2027™**	✓	✓	✓		Vented	302	56	22	**20**	67.4	5
VE / VEII **V8** Berlina, SS inc. V	08/06 - on	F	**2028™**	✓	✓	✓		Vented	321	52.2	30	**28**	67.5	5
Calais inc. V, WM Statesman		R	**2029™**	✓	✓	✓		Vented	324	56.1	22	**20**	67.4	5
COMMODORE UPGRADE OPTIONS														
VR, VS	7/93 - 97	F	**040B**	✓	✓	✓		Vented	296	83	28	**25**	70	5
VT - VZ	9/97 - 05	F	**046B**	✓		✓	✓	Vented	328	83	28	**25**	71.5	5
CREWMAN (UTE)														
VY, VZ - Crewman, S, SS - 2WD	2002 - on	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
Cross 6 / 8 - AWD / 4WD	2004 - on	F	**2050**	✓		✓		Vented	302	45	28	**25**	71.5	5
VZ SSZ	2005 - on	F	**2020™**	✓	✓	✓	✓	Vented	320	83	32	**30**	71.6	5
(Rear all models 2WD+4WD)	2004 - on	R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
EPICA														
All Models	2006 - on	F	**2038**					Vented	278	47	24	**22**	60	4
		R	**2039**					Solid	276	58.5	12	**10**	60	4
GEMINI														
TC, TD, TE, TX, TF, TG	1975 - 5/85	F	**006**	✓				Solid	240	47	10	**8.6**	68	4
RB FWD	5/85 - 87	F	**007**	✓				Solid	227	42	11	**9.6**	57	4
HOLDEN														
HD, HR	1965 - 67	F	**001**	✓				Solid	253	50	9.7	**9**	72	5
HK, HT	1968 - 70	F	**002**	✓				Solid	270	55	12.7	**11.7**	72	5
HT - V8 HG Check Spacer in Caliper	1969 - 71	F	**003**	✓				Solid	270	56.5	15.9	**14.7**	72	5
HQ - HJ HX - HZ WB Utility, Panel Van	1971 - 76 1976 - 80 1980 - 85	F	**014**	✓	✓	✓		Vented With Studs & Cups	276	72	25.4	**24.5**	HUB	5
HQ - HJ HX - HZ WB Utility, Panel Van	1971 - 76 1976 - 80 1980 - 85	R	**018**	✓				Solid	292	90	15.9	**14.7**	72	5

TM = Trademark

DBA is protecting its intellectual property rights and has begun Trademark Registration of its product part numbers

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - HSV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV ASTRA VXR														
2L Turbo	2005 - on	F	**2034**	✓		✓		Vented	321	44	28	**26**	70	5
		R	**2035**	✓		✓		Solid	278	42.2	10	**8**	65	5
HSV AWD														
Coupe 4 Avalanche Wagon	05/04 - on	F	**42022**			✓		Vented	336	45.2	32	**30**	71.5	5
Avalanche XUV Dual Cab Ute All VY series II on	05/04 - on	R	**4049**			✓		Vented	315	71	18	**16**	70	5
HSV - CLUBSPORT														
VN	1988 - 91	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**020**	✓		✓		Vented	278	83.6	20	**19**	70	5
VP inc. Clubsport 5000i	1991 - 93	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**045**	✓		✓		Vented	280	67	20	**19**	70	5
VR (Sedan & Wagon)	1993 - 95	F	**046**	✓		✓	✓	Vented	328	82	28	**25**	70	5
		R	**047**	✓		✓		Vented	280	86	20	**19**	70	5
VS	1995 - 97	F	**046**	✓		✓	✓	Vented	328	82	28	**25**	70	5
		R	**047**	✓		✓		Vented	280	86	20	**19**	70	5
VT	9/97 - 10/02	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
Standard Brakes		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
VT	9/97 - 10/02	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VX	9/97 - 10/02	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
Standard Brakes		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
VX	9/97 - 10/02	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY	10/02 - 8/04	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY Premium Brakes	10/02 - 8/04	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY II	10/02 - 8/04	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY II Premium Brakes	10/02 - 8/04	F	**5055**				✓	Vented	343	82.5	32	**30**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - HSV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - CLUBSPORT														
VZ	8/04 - 1/05	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
VZ (Not Suitable for use with OE hat/bell)	8/04 - 1/05	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VZ II	1/05 - 8/06	F	**52018**				✓	Vented	350	83	32	**30**	71.6	5
Performance Brakes -		R	**42019**			✓		Vented	332	75.2	24	**22**	70.1	5
AP 4 Piston Calipers														
VZ II (Not Suitable for use with OE hat/bell)	1/05 - 8/06	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
HSV - CLUBSPORT R8 inc. TOURER														
VX	9/97 - 10/02	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
VX Premium Brakes	9/97 - 10/02	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY Premium Brakes	10/02 - 8/04	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY II Premium Brakes	10/02 - 8/04	F	**5055**				✓	Vented	343	82.5	32	**30**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VZ Premium Brakes	8/04 - 1/05	F	**5055**				✓	Vented	343	82.5	32	**30**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VZ (Not Suitable for use with OE hat/bell)	8/04 - 1/05	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VZ II	1/05 - 8/06	F	**52018**				✓	Vented	350	83	32	**30**	71.6	5
Performance Brakes -		R	**42019**			✓		Vented	332	75.2	24	**22**	70.1	5
AP 4 Piston Calipers														
VZ II (Not Suitable for use with OE hat/bell)	1/05 - 8/06	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VE (LS2 V8), VE (LS3 V8)	2006 - 09	F	**42030**			✓	✓	Vented	365	54	32	**30**	67.4	5
inc. Clubsport R8 Tourer		R	**42031**			✓		Vented	350	61.5	26	**24**	67.4	5
VE2 (LS3 V8)	9/09 - on	F	**42030**			✓	✓	Vented	365	54	32	**30**	67.4	5
inc. Clubsport R8 Tourer		R	**42031**			✓		Vented	350	61.5	26	**24**	67.4	5

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

HOLDEN - HSV

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - HRT & HSVDT CLUBSPORT														
VZ Special Edition	1/05 - 8/06	F	**52018**				✓	Vented	350	83	32	**30**	71.6	5
Performance Brakes -		R	**42019**			✓		Vented	332	75.2	24	**22**	70.1	5
AP 4 Piston Calipers														
VZ Special Edition	1/05 - 8/06	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers (Not Suitable for use with OE hat/bell)		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
HSV - COUPE LE														
VY II	10/02 - 8/04	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
VY II Premium Brakes	10/02 - 8/04	F	**5055**				✓	Vented	343	82.5	32	**30**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
HSV - FORMULA														
VP	1991 - 93	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**020**	✓		✓		Vented	278	83.6	20	**19**	70	5
HSV - GRANGE														
VS	1995 - 97	F	**046**	✓		✓	✓	Vented	328	82	28	**25**	70	5
		R	**047**	✓		✓		Vented	280	86	20	**19**	70	5
WH	6/99 - 03	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
Standard Brakes		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
WH Performance Brakes	6/99 - 03	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
WH Premium Brakes	6/99 - 03	F	**5055**				✓	Vented	343	82.5	32	**30**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
WK Performance Brakes	2004	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
WK Premium Brakes	2004	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
WL	2005 - 06	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
WL Premium Brakes	2005 - 06	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VE (LS2 V8), VE (LS3 V8)	2006 - 09	F	**42030**			✓	✓	Vented	365	54	32	**30**	67.4	5
		R	**42031**			✓		Vented	350	61.5	26	**24**	67.4	5
VE2 (LS3 V8)	9/09 - on	F	**42030**			✓	✓	Vented	365	54	32	**30**	67.4	5
		R	**42031**			✓		Vented	350	61.5	26	**24**	67.4	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - HSV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - GTO COUPE														
(V2) - 2 Door Coupe	10/02 - 8/04	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
(V2) - 2 Door Coupe	10/02 - 8/04	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Premium Brakes														
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY	10/02 - 8/04	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
VY Premium Brakes	10/02 - 8/04	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VZ	8/04 - 1/05	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
VZ (Not Suitable for use with OE hat/bell)	8/04 - 1/05	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
HSV - GTO LE														
VZ Special Edition	8/04 - 8/06	F	**52018**				✓	Vented	350	83	32	**30**	71.6	5
Performance Brakes -		R	**42019**			✓		Vented	332	75.2	24	**22**	70.1	5
AP 4 Piston Calipers														
VZ Special Edition	1/05 - 8/06	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers (Not Suitable for use with OE hat/bell)		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - HSV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - GTS														
VP	1991 - 93	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**045**	✓		✓		Vented	280	67	20	**19**	70	5
VR	1993 - 95	F	**046**	✓		✓	✓	Vented	328	82	28	**25**	70	5
		R	**047**	✓		✓		Vented	280	86	20	**19**	70	5
VS	1995 - 97	F	**046**	✓		✓	✓	Vented	328	82	28	**25**	70	5
		R	**047**	✓		✓		Vented	280	86	20	**19**	70	5
VT	9/97 - 10/02	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VT Premium Brakes	9/97 - 10/02	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VX Premium Brakes	9/97 - 10/02	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY (Not Suitable for use with OE hat/bell)	10/02 - 8/04	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VY II (Not Suitable for use with OE hat/bell)	10/02 - 8/04	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VE (LS2 V8), VE (LS3 V8)	2006 - 09	F	**42030**			✓	✓	Vented	365	54	32	**30**	67.4	5
		R	**42031**			✓		Vented	350	61.5	26	**24**	67.4	5
VE2 (LS3 V8) 4 Piston Caliper	9/09 - on	F	**42030**			✓	✓	Vented	365	54	32	**30**	67.4	5
**(Front not suitable for SV Enhanced 6 piston caliper)		R	**42031**			✓		Vented	350	61.5	26	**24**	67.4	5
HSV - GTS-R														
VS	1995 - 97	F	**046**	✓		✓	✓	Vented	328	82	28	**25**	70	5
		R	**047**	✓		✓		Vented	280	86	20	**19**	70	5
HSV - GTS COUPE														
(V2) - 2 Door Coupe	10/02 - 8/04	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
(V2) - 2 Door Coupe	10/02 - 8/04	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Premium Brakes Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY (Not Suitable for use with OE hat/bell)	10/02 - 8/04	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VZ (Not Suitable for use with OE hat/bell)	8/04 - on	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5

DISC BRAKES AUSTRALIA ™

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

HOLDEN - HSV

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HSV - MALOO

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
VN	1988 - 91	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
VP	1991 - 93	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
VR	1993 - 95	F	046	✓		✓	✓	Vented	328	82	28	25	70	5
		R	016	✓		✓		Solid	279	83	10.5	8.5	70	5
VS	1995 - 97	F	046	✓		✓	✓	Vented	328	82	28	25	70	5
		R	016	✓		✓		Solid	279	83	10.5	8.5	70	5
VU	9/97 - 10/02	F	040	✓	✓	✓	✓	Vented	296	83	28	25	71.5	5
Standard Brakes		R	041	✓	✓	✓		Vented	286	78.6	16	14	70	5
VU	9/97 - 10/02	F	4048			✓	✓	Solid	330	83	32	29	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VU Premium Brakes	9/97 - 10/02	F	5055				✓	Vented	343	83	32	29	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VY	10/02 - 8/04	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VY Premium Brakes	10/02 - 8/04	F	5055				✓	Vented	343	83	32	29	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VY II	10/02 - 8/04	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VY II Premium Brakes	10/02 - 8/04	F	5055				✓	Vented	343	83	32	29	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VZ	8/04 - 1/05	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VZ Premium Brakes	8/04 - 1/05	F	5055				✓	Vented	343	83	32	29	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VZ II	1/05 - 8/06	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
Performance Brakes - PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5

DBA™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - HSV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - MALOO R8														
VU	9/97 - 10/02	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
VU Premium Brakes	9/97 - 10/02	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VY + VY II Premium Brakes	10/02 - 8/04	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VZ	8/04 - 1/05	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
VZ Premium Brakes	8/04 - 1/05	F	**5055**				✓	Vented	343	83	32	**29**	71.5	5
Harrop 4 Piston Calipers		R	**4049**			✓		Vented	315	71	18	**16**	70	5
VZ (Not Suitable for use with OE hat/bell)	8/04 - 1/05	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VZ II	1/05 - 8/06	F	**52018**				✓	Vented	350	83	32	**30**	71.6	5
Performance Brakes -		R	**42019**			✓		Vented	332	75.2	24	**22**	70.1	5
AP 4 Piston Calipers														
VZ II (Not Suitable for use with OE hat/bell)	1/05 - 8/06	F	**52024**				✓	Vented	362	83	32	**30**	71.5	5
AP 6 Piston Calipers		R	**42025**			✓		Vented	343	76.3	26	**24**	70.1	5
VE (LS2 V8), VE (LS3 V8)	2006 - 09	F	**42030**			✓	✓	Vented	365	54	32	**30**	67.4	5
VE2 (LS3 V8)	9/09 - on	R	**42031**			✓		Vented	350	61.5	26	**24**	67.4	5
HSV - MANTA														
VS (Sedan & Wagon)	1995 - 97	F	**046**	✓		✓	✓	Vented	328	82	28	**25**	70	5
		R	**047**	✓		✓		Vented	280	86	20	**19**	70	5
VT	9/97 - 10/02	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
Standard Brakes		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
VT	9/97 - 10/02	F	**4048**			✓	✓	Vented	330	83	32	**29**	71.5	5
Performance Brakes -		R	**4049**			✓		Vented	315	71	18	**16**	70	5
PBR 2 Piston Calipers														
HSV - NITRON														
VP	1991 - 93	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**020**	✓		✓		Vented	278	83.6	20	**19**	70	5
HSV - PLUS6														
VP	1991 - 93	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**045**	✓		✓		Vented	280	67	20	**19**	70	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

HOLDEN - HSV

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - PLUS8														
VN	1988 - 91	F	019			✓		Vented	327	82	28	25	HUB	5
		R	045	✓		✓		Vented	280	67	20	19	70	5
HSV - SENATOR														
VP inc. Senator 5000i	1991 - 93	F	019			✓		Vented	327	82	28	25	HUB	5
		R	045	✓		✓		Vented	280	67	20	19	70	5
VR	1993 - 95	F	046	✓		✓	✓	Vented	328	82	28	25	70	5
		R	047	✓		✓		Vented	280	86	20	19	70	5
VS (Sedan & Wagon)	1995 - 97	F	046	✓		✓	✓	Vented	328	82	28	25	70	5
		R	047	✓		✓		Vented	280	86	20	19	70	5
VT	9/97 - 10/02	F	040	✓	✓	✓	✓	Vented	296	83	28	25	71.5	5
Standard Brakes		R	041	✓	✓	✓		Solid	286	78.6	16	14	70	5
VT Performance Brakes	9/97 - 10/02	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VT Premium Brakes	9/97 - 10/02	F	5055				✓	Vented	343	82.5	32	30	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VX Standard Brakes	9/97 - 10/02	F	040	✓	✓	✓	✓	Vented	296	83	28	25	71.5	5
		R	041	✓	✓	✓		Solid	286	78.6	16	14	70	5
VX Performance Brakes	9/97 - 10/02	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VX Premium Brakes	9/97 - 10/02	F	5055				✓	Vented	343	82.5	32	30	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VY Performance Brakes	10/02 - 8/04	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VY II Performance Brakes	10/02 - 8/04	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VY II Premium Brakes	10/02 - 8/04	F	5055				✓	Vented	343	82.5	32	30	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VZ Performance Brakes	8/04 - on	F	4048			✓	✓	Vented	330	83	32	29	71.5	5
PBR 2 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
VZ AP 6 Piston Calipers	8/04 - on	F	52024				✓	Vented	362	83	32	30	71.5	5
(Not Suitable for use with OE hat/bell)		R	42025			✓		Vented	343	76.3	26	24	70.1	5
VE (LS2 V8), VE (LS3 V8)	2006 - 09	F	42030			✓	✓	Vented	365	54	32	30	67.4	5
VE2 (LS3 V8)	9/09 - on	R	42031			✓		Vented	350	61.5	26	24	67.4	5

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - HSV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - SIGNATURE COUPE														
VZ Special Edition	8/04 - on	F	52024				✓	Vented	362	83	32	30	71.5	5
AP 6 Piston Calipers (Not Suitable for use with OE hat/bell)		R	42025			✓		Vented	343	76.3	26	24	70.1	5
HSV - SKAIFE SENATOR														
VZ Special Edition	1/05 - on	F	52018				✓	Vented	350	83	32	30	71.6	5
Performance Brakes - AP 4 Piston Calipers		R	42019			✓		Vented	332	75.2	24	22	70.1	5
HSV - SPORTS WAGON														
VP	1991 - 93	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
HSV - SS GROUP A														
VN	1988 - 91	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
HSV - STATESMAN SV93														
VP	1991 - 93	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
HSV - SV LE														
VN (Sedan & Wagon)	1988 - 91	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
HSV - SV300														
VX Premium Brakes	10/02 - 8/04	F	5055				✓	Vented	343	82.5	32	30	71.5	5
Harrop 4 Piston Calipers		R	4049			✓		Vented	315	71	18	16	70	5
HSV - SV3800														
VN	1988 - 91	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
HSV - SV5000														
VN	1988 - 91	F	019			✓		Vented	327	82	28	25	HUB	5
		R	020	✓		✓		Vented	278	83.6	20	19	70	5
HSV - SV6000														
VZ Special Edition	8/04 -on	F	52024				✓	Vented	362	83	32	30	71.5	5
AP 6 Piston Calipers (Not Suitable for use with OE hat/bell)		R	42025			✓		Vented	343	76.3	26	24	70.1	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - HSV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HSV - SV89														
VN	1988 - 91	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**020**	✓		✓		Vented	278	83.6	20	**19**	70	5
HSV - SV91														
VN	1988 - 91	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**045**	✓		✓		Vented	280	67	20	**19**	70	5
VP	1991 - 93	F	**019**			✓		Vented	327	82	28	**25**	HUB	5
		R	**045**	✓		✓		Vented	280	67	20	**19**	70	5
HSV - XU6														
VX	9/97 - 10/02	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
Standard Brakes		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
HSV - XU8														
VT	9/97 - 10/02	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
Standard Brakes		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MONARO														
VT:VY CV6 & CV8	12/2001 - 04	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
(V2) - 2 Door Coupe		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
VZ CV8 GEN III V8 250kW	2005 - 06	F	**2020™**	✓	✓	✓	✓	Vented	320	83	32	**30**	71.6	5
except V5B - model 37 coupe		R	**2021™**	✓	✓	✓		Vented	286	80	18	**16**	70	5
VZ V5B model 37 coupe	2005 - 06	F												
with HSV brake option		R												
NOVA														
LE, LF	1989 - 10/94	F	**701**	✓				Solid	243	48	13.5	**12.5**	54	4
	1989 - 9/92	F	**704**	✓				Vented	238	48	18	**17**	54	4
	6/91 - 94	F	**708**	✓				Vented	258	48	22	**20**	54	4
LE Opt., LF GS (Rear)	1989 - 10/94	R	**703**	✓				Solid	242	37	9	**8**	54	4
LG, GS, SLX	10/94 - 4/96	F	**709**	✓				Vented	255	48.5	22	**20**	55	4
		R	**710**	✓				Solid	266	37	9	**8**	55	4
PIAZZA														
Piazza (Impulse)	1983 - 89	F	**811**	PART NOT AVAILABLE REFERENCE ONLY				Vented	250	32	18	**16.6**	68	4
		R	**812**	PART NOT AVAILABLE REFERENCE ONLY				Vented	266	60	18	**16.6**	57	4
TIGRA														
1.3L CDTi, 1.4L, 1.8L	4/2001 - 06	F	**847**	✓				Vented	260	41.2	24	**21**	60	4
Convertible		R	**849**	✓				Solid	240	41	10	**8**	57	4
TORANA / SUNBIRD														
HB, TA, LC, LJ, 4 Cyl	1969 - 72	F	**009**	✓				Solid	215	28.5	10	**9**	61	4
LC, LJ 6 Cyl	1969 - 72	F	**008**	✓				Solid	256	60	12.7	**12**	72	5
LJ XU-1	1972 - 73	F	**004**	✓				Solid	256	60	15.7	**14.7**	72	5
LH, LX, UC Complete with Studs and Cups	1974 - 79	F	**010**	✓				Solid	256	77	16	**14.3**	HUB	5
A9X	1977 - 78	F	**014**	✓		✓		Vented	276	72	25.4	**24.5**	HUB	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
VECTRA														
JR, JS, JSII - 2.0L, 2.2L, 2.5L	6/97 - 2/03	F	**825**	✓				Vented	288	42	25	**22**	70	5
(CD & GL Sedans)		R	**826**	✓				Solid	286	69	10	**8**	65.5	5
ZC 2.2L	2/03 - 05	F	**2820**	✓				Vented	285	43	25	**22**	70	5
ZC V6 up to VIN No. 38047796	2003 - 05	F	**2817**	✓				Vented	302	46	28	**25**	70	5
ZC V6 after VIN No. 38047796	2003 - 05	F	**2819**	✓		✓		Vented	314	46	28	**25**	70	5
ZC V6 rear suits all models	2003 - 05	R	**2818**	✓				Vented	292	42	20	**18**	66	5
ZAFIRA														
TT 2.2 Litre DOHC	6/2001 - on	F	**815**	✓				Vented	280	42	25	**22**	70	5
4D Wagon		R	**816**	✓				Solid	264	42	10	**8**	65	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - COMMERCIAL / 4WD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
COMBO														
SB Van	2/96 - 2000	F	**821**	✓				Vented	236	41	20	**17**	60	4
XC VAN	4/01 - 05	F	**847**	✓				Vented	260	41.2	24	**21**	60	4
	2005 - on	F	**2036**	✓				Vented	280	42.3	25	**23**	60	4
DROVER														
QB 4WD	3/85 - 87	F	**510**	✓				Solid	290	46.5	10	**8.5**	107	5
FRONTERA 4 X 4														
2.0i with & without ABS Sport 4 X 4 **UT** S & SE - V6 & 4Cyl	3/95 - on 10/95 - 6/99 2/99 - on	F	**840**	4x4		4x4		Vented	280	36	26	**24.6**	87.5	6
		R	**841**	4x4		4x4		Vented	313	81	18	**16.6**	101	6
JACKAROO / TROOPER - ISUZU (GM)														
Monterey U8 3.5 Litre ABS	2/98 on	F	**840**	4x4		4x4		Vented	280	36	26	**24.6**	87.5	6
		R	**841**	4x4		4x4		Vented	313	81	18	**16.6**	101	6
UBS 13, UBS 52	11/81 - 85	F	**031**	PART NOT AVAILABLE REFERENCE ONLY				Solid	259	37.5	12.5	**11.1**	80	6
UBS 16, UBS 521, 522	8/85 - 88	F	**032**	4x4				Vented	250	35	18	**16.7**	80	6
UBS 17, UBS 55	1988 - 91	F	**033**	4x4				Vented	257	36	22	**20.6**	88	6
UBS 16, 17, 52, 55	1987 - 91	R	**034**	4x4				Solid	265	47	12	**10.6**	97	6
UBS 25	1992 - on	F	**840**	4x4		4x4		Vented	280	36	26	**24.6**	87.5	6
US / U8 : S & SE, Monterey	2/98 - on	R	**841**	4x4		4x4		Vented	313	81	18	**16.6**	101	6
PANTHER - ISUZU (GM)														
Panther		F	**844**	PART NOT AVAILABLE REFERENCE ONLY				Vented	231	35	22	**20.6**	63	4

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HOLDEN - COMMERCIAL / 4WD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
RODEO / COLORADO														
KB, KBD, 2, 4 Series	1980 - 82	F	**030**	✓				Solid	250	35	18	**17**	80	6
KB, KBD, 2, 4 Series	1982 - 84	F	**031**	PART NOT AVAILABLE REFERENCE ONLY				Solid	259	37.5	12.5	**11**	80	6
KB 28, 29, 43, 49, KBD 27, 28, 43, 47	Late 84 - 88	F	**032**	✓				Vented	250	35	18	**16.7**	80	6
TFR, TFS17, 54, G3, G6 R7 4x2 2.6, 2.8 Litre R9 4x2, 4x4 2.6, 2.8 Litre	1988 - 94 1996 - 02 1996 - 02	F	**033**	✓				Vented	257	36	22	**20.6**	88	6
Rodeo - Sth Africa (special)	1996 - 02	F	**2033**	4x4				Vented	252	36	22	**20.6**	88	6
R7 & R9 - V6 3.2 Litre 4x2 & 4x4 versions	1997 - 02	F	**840**	4x4		4x4		Vented	280	36	26	**24.6**	87.5	6
RA V6 PFI 4X2 + all 4X4 Hi-ride Suspension. (Torsion Bar)	12/2002 - 08	F	**2840**	4x4		4x4		Vented	280	40.5	27	**25.6**	88	6
RA 2.4L 4cyl, 3.0L Turbo Diesel Non Hi-ride Suspension (Coil Front)	11/02 - 08	F	**2839**	4x4				Vented	256	40.1	26	**24.6**	88	6
RC V6 PFI 4X2 + all 4X4 Hi-ride Suspension. (Torsion Bar Front)	2008 - on	F	**2840**	4x4		4x4		Vented	280	40.5	27	**25.6**	88	6
RC 2.4L 4cyl, 3.0L Turbo Diesel Non Hi-ride Suspension (Coil Front)	2008 - on	F	**2839**	4x4				Vented	256	40.1	26	**24.6**	88	6
SCURRY														
NB	7/85 - 87	F	**012**	✓				Solid	215	33.5	10	**8**	86	4
SHUTTLE														
WFR	1982 - 84	F	**031**	PART NOT AVAILABLE REFERENCE ONLY				Solid	259	37.5	12.5	**11**	80	6
WFR	1982 - 90	F	**032**	✓				Vented	250	35	18	**16.7**	80	6
SUBURBAN														
1500 (K8) LS & LT 5.7L	2/98 - 00	F	**773**	PART NOT AVAILABLE REFERENCE ONLY				Vented	295	63.5	32.5	**30.8**	78.7	6
2500 (K8) LS & LT 6.5L	2/98 - 00	F	**774**	4x4				Vented	317.5	70	33	**30.8**	137.2	8

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

HONDA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

ACCORD

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SJ 1600, 1602	1976 - 81	F	**189**	✓				Solid	231	41	12	**10.5**	86	4
SY, SZ 1602	1981 - 83	F	**190**	✓				Solid	231	50	12	**10**	61	4
SY, SZ Hatchback 4-Door	5/82 - 83	F	**195**	✓				Vented	231	50	17	**15**	61	4
AC, AD, 1600, 1800	1984 - 86	F	**196**	✓				Vented	242	50	19	**17**	61	4
CA4 SOHC, CA5														
CA4 2000 AD, CA4 CXi	1986 - 89	F	**184**	✓				Vented	262	51	21	**19**	64	4
CA4, CA5	1988 - on	R	**198**	PART NOT AVAILABLE REFERENCE ONLY				Solid	239	48.2	10	**8**	61	4
CB 2WS, CC Sedan/Wagon	11/89 - 94	R	**471**	✓				Solid	260	49	10	**8**	64	4
CB 4WS	11/89 - 94	R	**481**	✓				Solid	260	43	10	**8**	64	4
2.2i (CB75/76, CC7, CE9)	1990 - 98	F	**179**	✓				Vented	282	34	25	**23**	92	4
Acura Vigor	1992 - 94													
Acura TL 2.5L Sedan	1995 - on													
1.8i (CE7-auto, 2.0i (CE8-auto)	1996 - 9/98													
CB, CC Wagon, Aerodeck	1992 - 94	F	**472**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	34	25	**23**	92	4
CCB, CC Sedan Only	11/89 - 94	F	**470**	✓				Vented	260	34	23	**21**	92	4
CD	1994 - 97													
Note: Check dimensions		R	**471**	PART NOT AVAILABLE REFERENCE ONLY				Solid	260	49	10	**8**	64	4
CE Wagon	6/94 - on	F	**472**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	34	25	**23**	92	4
		R	**471**	✓				Solid	260	49	10	**8**	64	4
CG V6-L 2.3L + 3.0L	1998 - 04	F	**488**	✓		✓		Vented	282	47	23	**21**	64	5
		R	**489**	✓				Solid	260	48	9	**8**	64	5
CG2 V6 J30A1 (UK Model)	7/98 - 2002	F	**405**	✓				Vented	282	47	28	**26**	64	5
R 2.2i (VTEC)	2000 - on	F	**476**	✓		✓		Vented	300	47.5	28	**26**	70	5
V 4DR (USA + Europe)	2000 - 2003	F	**2506**	✓		✓		Vented	282	48	25	**23**	64	5
2.4L + 3.0L V6 VTEC	2004 - on	F	**488**	✓		✓		Vented	282	47	23	**21**	64	5
EURO.2.4L i-VTEC	2004 - on	F	**2510**	✓		✓	✓	Vented	300	48	28	**26**	64	5
Rear disc fits both 2004 models		R	**2511**	✓				Solid	260	49	9	**8**	64	5
(rear hat diameter is 154 mm)														
EURO V6	2005 - on	F	**2514**	✓		✓		Vented	282	47	28	**26**	64	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

HONDA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CIVIC														
SBI, SC Sedan 1200 SF Hatchback 1200 SB, SE Sedan, Wagon 1500	1973 - 79 1978 - 79 1975 - 78	F	**188**	✓				Solid	225	44.5	10	**9**	92	4
SL, SS, SR, ST, VC - Hatch WC 1300 Wagon SR, ST Wagon	1979 - 83 1980 - 81 1982 - 83	F	**193**	✓				Solid	215	50	11	**9**	61	4
1.3, 1.5L (AH-AK), CRX 1.5 Hatch + Wagon 2WD/4WD (USA) 1.4 (EC9-ED2), HF (USA) 1.3 16V (EG33)	1984 - 87 1984 - 87 1988 - 91 1991 - 94	F	**178**	✓				Vented	231	43.8	17	**15**	61	4
AA	1984 - 87	F	**191**	✓				Solid	231	44	12	**10**	61	4
CITY VF	1984 - 86	F	**194**	PART NOT AVAILABLE REFERENCE ONLY				Solid	212	40	10	**8**	61	4
ED 4WD Wagon ED 4-Door	3/88 - 5/89 1988 - 91	F	**187**	✓				Vented	242	44.5	19	**17**	61	4
EG GL, GLi, VEi, Sedan, DX/HX Coupe/Sedan (USA) Del Sol, Wagovan (USA)	11/91 - 94 1993 - on	F	**473**	✓				Vented	240	45	21	**19**	61	4
EE9, EF, EG 1.6i VTEC VTi EH1 4WD, EJ1 Coupe 1.6i Coupe /Sedan EX/LX (USA) MA8 1.4i, MA9, MB1/4 MB2, MB3, MB7/8/9, MC1 MC3 2.0TDi, EJ6/8 EK 3 Door	11/91 - 95 1990 - 95 12/94 - on 1997 - on	F	**474**	✓		✓		Vented	262	45	21	**19**	64	4
		R	**475**	✓		✓		Solid	239	48	9	**8**	61	4
EX - with ABS	1993 - 95	F	**474**	✓		✓		Vented	262	45	21	**19**	64	4
		R	**475**	✓		✓		Solid	239	48	9	**8**	61	4
DX & HX,	1996 - 2000	F	**473**	✓				Vented	240	45	21	**19**	61	4
EX	1996 - 2000	F	**474**	✓		✓		Vented	262	45	21	**19**	64	4

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HONDA

CIVIC - CONTINUED

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Si	1999 - 2000	F	**474**	✓		✓		Vented	262	45	21	**19**	64	4
		R	**475**	✓		✓		Solid	239	48	9	**8**	61	4
all models	2001 - 2005	F	**474**	✓		✓		Vented	262	45	21	**19**	64	4
Civic 1.7L SOHC 4/5dr	2001 - on	R	**2502**	✓				Solid	260	48	9	**8**	61	4
1.8 SOHC Vti & Vti-L	2006 - ON	F	**488**	✓		✓		Vented	282	47	23	**21**	64	5
2.0L DOHC SPORT		R	**2517**					Solid	260	42.2	9.1	**8**	64	5
2.0i SPORT VI Hatchback	01/04 - 12/05	R	**2515**	✓		✓		Solid	259.5	49	10	**8**	64	5
2.0L -R EP3 (UK)	2001 - 06	F	**2500**	✓		✓	✓	Vented	300	47.5	25	**23**	64	5
VI Hatchback (EU_, EP_)		R	**2515**	✓		✓		Solid	259.5	49	10	**8**	64	5
FD2 -R	2007 - on	F	**2518**	✓		✓		Vented	320	62	25	**23**	64	5
		R	**2519**	✓		✓		Solid	282	49	9	**8**	64	5
FN2 Type-R	2007 - on	F	**2500**	✓		✓	✓	Vented	300	47.5	25	**23**	64	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HONDA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CONCERTO														
EXI, Reprise, EXI-Reprise	5/91 - on	F	**187**	✓				Vented	242	44.5	19	**17**	61	4
		R	**182**	✓				Solid	239	48	10	**8**	61	4
CR-V														
CR-V 4 Door Wagon 2.0i 16V (RD1)	10/97 - 01	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5
CR-V 4 Door Wagon	2002 - 04	F	**488**	✓		✓		Vented	282	47	23	**21**	64	5
HR-V														
1.6i 16V (GH1/2)	1999 - on	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5
CRX														
ED 1.6 litre 2-Door DX-Si	1987 - 91	F	**187**	✓				Vented	242	44.5	19	**17**	61	4
		R	**182**	✓				Solid	239	48	10	**8**	61	4
1500/1600 Si	1990 - 91	F	**187**	✓				Vented	242	44.5	19	**17**	61	4
		R	**475**	✓		✓		Solid	239	48	9	**8**	61	4
EE8 VTEC 1.6L EG21 VTi, EH61 ESi 1.6L EG VTec	1989 - 92 1992 - 97 6/92 - on	F	**474**	✓		✓		Vented	262	45	21	**19**	64	4
		R	**475**	✓		✓		Solid	239	48	9	**8**	61	4
INTEGRA														
Quint 1.6 (AV)	1984 - 86	F	**178**	PART NOT AVAILABLE REFERENCE ONLY				Vented	231	43.8	17	**15**	61	4
DA3, DA4, 1.6L	1986 - 88	F	**187**	✓				Vented	242	44.5	19	**17**	61	4
		R	**192**	✓				Solid	239	27.5	10	**8**	48	4
1.8L DOHC 16V 1.8L GSi, VTi - R Acura Integra, 2.0L GSi	1989 - 94 1993 - 98 1990 - on	F	**474**	✓		✓		Vented	262	45	21	**19**	64	4
		R	**475**	✓		✓		Solid	239	48	9	**8**	61	4
TYPE-R	2000 - 01	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5
		R	**477**	✓				Solid	260	48	9	**8**	64	5
Integra Type-R DC5 Japanese domestic Brembo Caliper Models	2001 - on	F	**2508**	✓		✓	✓	Vented	300	57.8	25	**23**	64	5
TYPE-S TYPE-R - Australian Model	2002 - on	F	**2500**	✓		✓	✓	Vented	300	47.5	25	**23**	64	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HONDA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
JAZZ														
GLi 1.3L SOHC	10/2002 - on	F	**2504**	✓				Vented	240	39	21	**19**	61	4
LEGEND														
KA2 4-Door Sedan	1986 - 87	F	**186**	✓				Vented	262	51.5	21	**19**	64	4
KA3 4D Sedan, KA4 2D Coupe	11/87 - 91	F	**185**	✓				Vented	282	51	21	**19**	64	4
		R	**199**	✓				Solid	260	43	10	**8**	64	4
KA7, KA8, KA9 3.5L V6 15" wheels	3/91 - 95 1996 - on	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5
		R	**479**	✓		✓		Solid	282	61	9	**7.5**	70	5
3.5L V6 16" wheels	1996 - on	F	**476**	✓		✓		Vented	300	47.5	28	**26**	70	5
		R	**499**	✓				Solid	282	61	12	**10**	64	5
NSX														
NSX 4 Auto	1991 - 98	F	**484**	✓		✓		Vented	282	36	28	**26**	70	5
NSX-T 5 Manual		R	**485**	✓				Vented	282	32.5	21	**19**	69	5
6 SPEED MANUAL	4/97 - ON	F	**486**	✓		✓		Vented	298	36.5	28	**26**	70	5
NSX, NSX-T		R	**487**	✓		✓		Vented	303	32.5	23	**21**	64	5
PRELUDE														
SU, SN	1979 - 82	F	**190**	✓				Solid	231	50	12	**10**	61	4
AB, ALB 1800	1983 - 87	F	**197**	✓				Vented	231	50	19	**17**	61	4
BA3	1986 - 87	F	**196**	✓				Vented	241	50	19	**17**	61	4
AB, BA3 Non-ABS	1983 - 87	R	**183**	✓				Solid	239	45	10	**8**	HUB	4
BA4, Si, SE	1988 - 91	F	**184**	✓				Vented	262	51	21	**19**	64	4
	10/87 - 91	R	**198**	PART NOT AVAILABLE REFERENCE ONLY				Solid	239	48.2	10	**8**	61	4
V-TEC	1992 - 96	F	**200**	✓		✓		Vented	282	47	23	**21**	64	4
		R	**481**	✓				Solid	260	43	10	**8**	64	4
5-lug	1997 - 2001	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5
		R	**438**	✓				Solid	260	42	9	**8**	64	5
BB incl. 4WS	12/91 - 94	F	**480**	✓				Vented	260	47	23	**21**	64	4
		R	**481**	✓				Solid	260	43	10	**8**	64	4
VTi-S & Si	2/94 - on	F	**480**	✓				Vented	260	47	23	**21**	64	4
Stepped hat		R	**481**	✓				Solid	260	43	10	**8**	64	4
Straight hat		R	**2513**	✓				Solid	260	42	9	**8**	64	4
VTi-R	2/94 - 97	F	**200**	✓		✓		Vented	282	47	23	**21**	64	4
		R	**481**	✓				Solid	260	43	10	**8**	64	4
2.2L DOHC VTi-R	1997 - 2001	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5
		R	**438**	✓				Solid	260	42	9	**8**	64	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HONDA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
S 2000														
S 2000	1999 - 03	F	**482**	✓		✓		Vented	300	40	25	**23**	70	5
		R	**483**	✓		✓		Solid	282	40	12	**10**	64	5
all models	2003 - 05	F	**488**	✓		✓		Vented	282	47	23	**21**	64	5
		R	**2503**	✓				Solid	282	61	9	**7.5**	64	5
ODYSSEY														
Odyssey - 4 Door Wagon	6/95 - 2000	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5
		R	**479**	✓		✓		Solid	282	61	9	**7.5**	70	5
Odyssey 2.3L + V6	2000 - 05	F	**476**	✓		✓		Vented	300	47.5	28	**26**	70	5
		R	**2503**	✓				Solid	282	61	9	**7.5**	64	5
PASSPORT														
all models	1996 - 01	F	**842**	✓				Vented	280	36	26	**24.6**	88	6
		R	**841**	✓				Vented	313	80.6	18.1	**16.6**	101	6
PILOT														
all models	2003 - 05	F	**476**	✓		✓		Vented	300	47.5	28	**26**	70	5
SHUTTLE														
2.3i (RA1), 2.3i ES/LS (RA3)	6/95 - on	F	**478**	✓		✓		Vented	282	47	23	**21**	70	5

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HUMBER

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Snipe, Hawk Series II, III, IV	1960 - 69	F	**094**	✓				Solid	290	39	12.75	**11**	79.5	5

HUMMER

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HUMMER														
H1 - 6.5L D	01/92 - on													
H1 - 6.5L TURBO D	01/92 - on													
H2 - 6.0L All wheen drive	09/02 - 09/04	F	**2048**	4x4		4x4		Vented	325	89.5	38	**36.5**	118.2	8
H2 - 6.0L SUT pickup	09/04 - on	R	**2049**	4x4		4x4		Vented	330	85.6	29	**26.5**	118.2	8
H3 - 3.5L H3 - 3.7L AWD H3 - 5.3L V8	04/05 - on 09/06 - on 10/08 - on	F	**2054**	4x4		4x4		Vented	315	70.4	28	**26.5**	100.7	6
		R	**2055**	4x4		4x4		Solid	312	67.9	12	**10.5**	101	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HYUNDAI

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ACCENT														
1.3i 12V, 1.5i 12V, 1.5i 16V	1994 - 99	F	**451**	✓				Vented	242	40.5	19	**17.7**	86	4
GL, GLS, Sprint, Lifesyle	1999 - 11/05	F	**450**	✓				Vented	241	52	19	**17.7**	63	4
COUPE														
FX, SX, SFX, Tiburon	8/96 - 98	F	**453**	✓				Vented	257	34	22	**20**	86	4
		R	**457**	✓				Solid	257	40.5	10	**8**	76	4
Coupe, Turbulence	8/98 - on	F	**456**	✓		✓		Vented	257	45	24	**22.4**	69	4
Scoupe 1.5i, incl. USA	1989 - 4/95	F	**451**	✓				Vented	242	40.5	19	**17.7**	86	4
ELANTRA / LANTRA / LAVITA														
J1 & J2, incl. 1.9L Diesel,	5/91 - 5/98	F	**453**	✓				Vented	257	34	22	**20**	86	4
	5/91 - 8/95	R	**459**	✓				Solid	257	40	10	**8**	90	4
J2	5/98 - on	F	**456**	✓		✓		Vented	257	45	24	**22.4**	69	4
	9/95 - on	R	**457**	✓				Solid	257	40	10	**8**	76	4
Elantra XD GL 1.8L, GLS 2.0L Lavita, (Hatchback & Sedan)	5/2000 - on	F	**456**	✓		✓		Vented	257	45	24	**22.4**	69	4
		R	**457**	✓				Solid	257	40	10	**8**	76	4
EXCEL														
X1	11/85 - 1/88	F	**215**	✓				Solid	228	40	13	**11.5**	86	4
X1, X3, XZ, XL Van, S Coupe Pony/Excel 1.3-1.5i (MU)	1/88 - 00 1989 - 94	F	**451**	✓				Vented	242	40.5	19	**17.7**	86	4
GETZ														
1.3L XL	7/2002	F	**2450**	✓				Vented	241	48	19	**17**	62	4
1.5L GL, GLS - FX 1.6 (TB)	7/2002 9/02 - 2/09	F	**2451**	✓				Vented	256	48	19	**17**	69	4
GRANDUER														
XG - 4D Sedan V6 DOHC	7/99 - on	F	**460**	✓				Vented	276	46.5	26	**24**	69	5
		R	**461**	✓				Solid	262	66	10	**8.4**	76	5
i30														
All Models 2.0L Petrol, 1.6 CRDi	2007 - on	F	**2464**	✓				Vented	280	47.5	26	**24**	69	5
		R	**2459**	✓				Solid	262	61	10	**8.4**	76	5

DBA™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HYUNDAI - SONATA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
i-LOAD / i-MAX														
2.4L, 2.5L CRDI	2007 - on	F	**2460**	✓		✓		Vented	300	52.5	30	**28.4**	96.2	6
		R	**2461**					Vented	320	82.6	18	**16.4**	96.2	6
SONATA														
Y1, Y2 Sonica all models	1/89 - 4/98	F	**452**	✓				Vented	257	45.5	22	**20**	69	4
Y1 (Rear)	1/89 - 94	R	**454**	✓				Solid	263	46	12	**10**	90	4
Y2 (Rear)	7/93 - 4/98	R	**455**	✓				Solid	260	59.5	12	**10.5**	90	4
Y3 all models	4/98 - 4/01	F	**456**	✓		✓		Vented	257	45	24	**22.4**	69	4
		R	**458**	✓				Solid	262	61	10	**8**	76	4
EF-B (GL) - 2.3L, 2.7L V6	4/01 - on	F	**463**	✓				Vented	257	47.5	25	**22.4**	69	4
		R	**458**	✓				Solid	262	61	10	**8**	76	4
2.4L GL + 2.7L V6	2004 - 06	F	**2458**	✓				Vented	257	47	24.5	**22.4**	64	4
NF 3.3L V6	2006 - on	F	**2456**	✓		✓		Vented	300	47.5	28	**26**	69	5
		R	**2457**	✓				Solid	284	54.6	10	**8**	76	5
TIBURON														
2.7L V6 + 2.0L : GT Coupe 1.6S, 2.0SE, 2.7L	9/01 - on	F	**468**	✓		✓	✓	Vented	280	48	26	**22.4**	69	5
		R	**469**	✓		✓		Solid	258	45	10	**8**	75.5	5
TRAJET														
GL, GLS V6 2.7L Wagon	3/00 - on	F	**464**	✓				Vented	276	47	26	**24**	69	5
		R	**465**	✓				Solid	284	61	10	**8.4**	76	5
SANTA FE														
GL 2.4, GL/GLS 2.7L V6	11/00 - 8/06	F	**2452**	✓				Vented	294	46	26	**24**	69	5
(Rear for GLS V6 only)		R	**465**	✓				Solid	284	61	10	**8.4**	76	5
All models	9/06 - on	F	**2462**	4x4		4x4		Vented	298	49.5	28	**26.4**	69	5
		R	**2463**	4x4				Solid	302	72	11	**9.4**	69	5
TUCSON														
All Models	8/04 - on	F	**468**	✓		✓	✓	Vented	280	48	26	**22.4**	69	5
AWD Only		R	**465**	✓				Solid	284	61	10	**8.4**	76	5
2WD Only		R	**TBA**											

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

HYUNDAI - 4WD / SUV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
TERRACAN 4WD														
3.5 V6 + 2.9L TCi Diesel	2001 - 03	F	**466**	✓				Vented	280	43	27	**25.4**	87	6
3.5 V6 + 2.9L TCi Diesel	12/03 - on	F	**2454**	4x4				Vented	303	43	28	**26.4**	87	6
rear suits all models		R	**467**	4x4				Vented	315	86.5	20	**18.4**	108	6
GALLOPER 4WD														
V6 3.0L LWB	9/88 - 92	F	**2229**	4x4				Vented	276	45.5	22	**20.4**	87	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

ISUZU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
JACKAROO / TROOPER														
Monterey U8 3.5 Litre ABS	2/98 on	F	**840**	4x4		4x4		Vented	280	36	26	**24.6**	87.5	6
		R	**841**	4x4		4x4		Vented	313	81	18	**16.6**	101	6
UBS 13, UBS 52	11/81 - 85	F	**031**	✓				Solid	259	37.5	12.5	**11.1**	80	6
UBS 16, UBS 521, 522	8/85 - 88	F	**032**	✓				Vented	250	35	18	**16.7**	80	6
UBS 17, UBS 55	1988 - 91	F	**033**	✓				Vented	257	36	22	**20.6**	88	6
UBS 16, 17, 52, 55	1987 - 91	R	**034**	✓				Solid	265	47	12	**10.6**	97	6
UBS 25 without ABS	1992 - on	F	**840**	4x4		4x4		Vented	280	36	26	**24.6**	87.5	6
US / U8 : S & SE, Monterey	2/98 - on	R	**841**	4x4		4x4		Vented	313	81	18	**16.6**	101	6
PANTHER- ISUZU (GM)														
Panther		F	**844**	PART NOT AVAILABLE REFERENCE ONLY				Vented	231	35	22	**20.6**	63	4
RODEO														
KB, KBD, 2, 4 Series	1980 - 82	F	**030**	✓				Solid	250	35	18	**17**	80	6
KB, KBD, 2, 4 Series	1982 - 84	F	**031**	✓				Solid	259	37.5	12.5	**11**	80	6
KB 28, 29, 43, 49, KBD 27, 28, 43, 47	Late 84 - 88	F	**032**	✓				Vented	250	35	18	**16.7**	80	6
TFR, TFS17, 54, G3, G6 R7 4x2 2.6, 2.8 Litre R9 4x2, 4x4 2.6, 2.8 Litre	1988 - 94 1996 - 02 1996 - 02	F	**033**	✓				Vented	257	36	22	**20.6**	88	6
R7 & R9 - V6 3.2 Litre 4x2 & 4x4 versions	1997 - 02	F	**840**	4x4		4x4		Vented	280	36	26	**24.6**	87.5	6
RA V6 PFI 4X2 + all 4X4 Hi-ride Suspension. (Torsion Bar)	12/2002 - on	F	**2840**	4x4		4x4		Vented	280	40.5	27	**25.6**	88	6
RA 2.4L 4cyl, 3.0L Turbo Diesel Non Hi-ride Suspension (Coil Front)	11/02 - on	F	**2839**	4x4				Vented	256	40.1	26	**24.6**	88	6
D-MAX														
2.4L, 2.5D, 3.0DiTD, 3.5L V6 Hi-ride Suspension. (Torsion Bar)	5/02 - on	F	**2840**	4x4		4x4		Vented	280	40.5	27	**25.6**	88	6
2.4L, 2.5D, 3.0DiTD, 3.5L V6 Non Hi-ride Suspension (Coil Front)	5/02 - on	F	**2839**	4x4				Vented	256	40.1	26	**24.6**	88	6
2.5DiTD, 3.0D Hi-ride Suspension. (Torsion Bar)	1/07 - on	F	**2840**	4x4		4x4		Vented	280	40.5	27	**25.6**	88	6
2.5DiTD, 3.0D Non Hi-ride Suspension (Coil Front)	1/07 - on	F	**2839**	4x4				Vented	256	40.1	26	**24.6**	88	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

JAGUAR

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MK SERIES														
Mk 2 - all Models	1959 - 67	F	**072**	✓				Solid	280	51.5	9.75	**8.5**	82.5	5
Mk 10	1961 - 66													
240, 340	1967 - 69													
Mk 2 All Models	1959 - 67	R	**073**	✓				Solid	287	53	9.5	**8**	82.5	5
240, 340	1967 - 69													
XJ SERIES														
XJ6 Series 1	1968 - 2/74	F	**074**	PART NOT AVAILABLE REFERENCE ONLY				Solid	283	60	12.5	**11.5**	82	5
		R	**075**	✓				Solid	264	25.5	12.7	**11.4**	70	4
XJ6 Series 2, 3	1974 - 10/86	F	**076**	✓				Vented	285	60.5	24	**22.9**	82.7	5
XJS, XJ12	1973 - 1990													
		R	**075**	✓				Solid	264	25.5	12.7	**11.4**	70	4
XJ6, XJ12, XJS with Dana Diff.	11/86 - 90	R	**075B**	✓				Solid	262	25.5	12.5	**11.4**	70	4
XJ40 3.6	11/86 - 90	F	**077**	PART NOT AVAILABLE REFERENCE ONLY				Vented	295	67	22.3	**21**	80	5
		R	**078**	✓				Solid	278	68	10	**8.8**	74	5
XJ40 3.2 & 4.0 Litre	1990 - 1994	F	**098**	✓				Vented	291	66.8	28	**27**	80	5
		R	**099**	✓				Solid	294	67	10	**8.8**	74	5
E-SERIES														
E- 3.8, 4.2	1961 - 68	F	**072**	✓				Solid	280	51.5	9.75	**8.5**	82.5	5
E- V12 4.2	1968 - 74	F	**076**	✓				Vented	285	60.5	24	**22.9**	82.7	5
		R	**075**	✓				Solid	265	25.5	12.7	**11.4**	70	4
S-SERIES														
S- 3.4, 3.8	1963 - 68	F	**072**	✓				Solid	280	51.5	9.75	**8.5**	82.5	5
		R	**075**	✓				Solid	264	25.5	12.7	**11.4**	70	4
S- (X200) 3.0i V6 / 4.0i	1999 - on	F	**2044**					Vented	300	43	30	**28**	71	5
Rear suits all S- (X200)		R	**2045**					Vented	288	32.5	20	**18.5**	64.5	5
XKR														
XKR 4.0L V8 Turbo	1998 - on	F	**2046**	✓				Vented	305	49.5	28	**26**	73.8	5
		R	**2047**	✓				Vented	305	67.8	20	**18.5**	73.8	5
with Brembo Calipers	2003 - on	F	**52070**				✓	Vented	356	50.5	32	**30**	73.8	5
XK8														
4.0L V8	1996 - on	F	**2046**	✓				Vented	305	49.5	28	**26**	73.8	5
		R	**2047**	✓				Vented	305	67.8	20	**18.5**	73.8	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

JEEP / CHRYSLER

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CHEROKEE														
CJ Universal	1977 - 78	F	**095**	✓				Vented	298	56	30	**28.5**	96	5
CJ7, Renegade	9/78 - 81	F	**181**	✓				Vented	298	56.5	22.5	**21**	95.5	5
all J, MJ & SJ models	1974 - 83	F	**180**	✓				Vented	300	59	32.5	**31**	101.5	6
J10	1983 - 85	F												
CJ8, Hawk	1981 - 85	F	**181**	✓				Vented	298	56.5	22.5	**21**	95.5	5
Overlander 4 Cyl	1981 - 85													
4WD	1988 - 92	F	**096**	4×4		4×4		Vented	280	81	24	**22.7**	72	5
CHEROKEE / WAGONEER / BRAIRWOOD - XJ SERIES														
4WD	1990 - 1/92	F	**096**	4×4		4×4		Vented	280	81	24	**22.7**	72	5
all models	2/92 - 98													
w/ OE composite disc (82mm)	1990 - 99													
w/ OE full cast disc (78mm)	1999 - 01	F	**888**	4×4		4×4		Vented	280	78	24.5	**22.7**	72	5
CHEROKEE / WAGONEER / BRAIRWOOD - KJ SERIES														
2.4, 2.5 CRD	09/01 - on	F	**889**	4×4		4×4		Vented	288	65	28	**26**	72	5
2.8 CRD	11/02 - on													
3.7 V6	08/03 - on													
2.8 CRD	11/04 - on													
COMANCHE														
4WD	1990 - 92	F	**096**	4×4		4×4		Vented	280	81	24	**22.7**	72	5
COMMANDER														
all models	2006	F	**2530**	4×4		4×4		Vented	328	53	30	**28.5**	72	5
		R	**2531**	4×4		4×4		Solid	320	67	14	**12.5**	72	5
GRAND CHEROKEE														
all models	1993 - 98	F	**096**	4×4		4×4		Vented	280	81	24	**22.7**	72	5
		R	**097**	4×4		4×4		Solid	285	59.5	11	**9.5**	72	5
all models	1999 - 04	F	**540**	4×4		4×4		Vented	305	64	26	**24.5**	72	5
		R	**541**	4×4		4×4		Solid	305	75.5	10	**8.5**	72	5
all except SRT-8	2005 - on	F	**2530**	4×4		4×4		Vented	328	53	30	**28.5**	72	5
		R	**2531**	4×4		4×4		Solid	320	67	14	**12.5**	72	5
SRT8	2006 - on	F	**2532**	4×4		4×4		Vented	360	53.5	32	**31.8**	72	5
		R	**2533**	4×4		4×4		Solid	350	68.5	28	**27.85**	72	5
LIBERTY														
all models	2002 - 2006	F	**889**	4×4		4×4		Vented	288	65	28	**26**	72	5
With Rear Disc Brakes	2003 - 2006	R	**2535**	4×4		4×4		Solid	285	59.6	12	**11**	72	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

JEEP / CHRYSLER

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
WRANGLER														
w/ OE composite disc (82mm)	1990 - 99	F	**096**	4x4		4x4		Vented	280	81	24	**22.7**	72	5
w/ OE full cast disc (78mm) all models - excl. Rubicon Drum rear brakes	1999 - 00 2001 - 06	F	**888**	4x4		4x4		Vented	280	78	24.5	**22.7**	72	5
all models incl Rubicon Disc rear brakes	2003 - 06	F	**888**	4x4		4x4		Vented	280	78	24.5	**22.7**	72	5
		R	**2535**	4x4		4x4		Solid	285	59.6	12	**11**	72	5
SRT-8	2005 - 06	F	**2532**	4x4		4x4		Vented	360	53.5	32	**31.8**	72	5
		R	**2533**	4x4		4x4		Vented	350	68.5	28	**27.85**	72	5
JK 3.8L V6 + Rubicon	2007 - on	F	**2536**	4x4		4x4		Vented	302	55.4	28	**26.4**	72	5
		R	**2537**	4x4		4x4		Solid	316	76.7	12	**10.4**	72	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

KIA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CARNIVAL														
Carnival (Suits single piston caliper)	1999 - on	F	**877**	✓				Vented	274	48	24	**22**	72	5
Carnival (Suits twin piston caliper)	5/00 - 11/03	F	**878**	✓		✓		Vented	274	48	26	**24**	72	5
Carnival (Suits twin piston caliper)	12/03 - 05	F	**2870**	✓		✓		Vented	274	50.5	28	**26**	72	5
Grand Carnival 3.8Ltr V6 DOHC 24V	2006 - on	F	**2871**	✓		✓		Vented	300	54.1	28	**26**	96.3	6
CERATO														
2.0Ltr DOHC	2004 - on	F	**2872**	✓				Vented	275	47.5	26	**24**	69	4
		R	**2873**	✓				Solid	258	41.5	10	**8**	76	4
CREDOS														
Credos 2.0 Litre	5/98 on	F	**873**	✓				Vented	258	48.5	24	**22**	72	4
		R	**874**	✓				Solid	260	40	10	**8**	72	4
MENTOR														
Mentor 1.5 Litre & 1.8 Litre Shuma /Spectra	11/96 - on 1997 - 2000	F	**875**	✓				Vented	240	44	20	**18**	57	4
		R	**879**	✓				Solid	260	40	10	**8**	57	4
OPTIMA														
Optima 2.5L V6 GL/GLS	6/2001 - on	F	**2894**	✓				Vented	257	47.5	25	**22.4**	69	4
		R	**2895**	✓				Solid	261	61.5	9.8	**8.4**	76	4

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

KIA - 4WD / SUV

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
RIO														
Rio 1.5L	2002 - on	F	**2896**	✓				Vented	235	50	22	**20**	55	4
Rio 1.6L DOHC CVVT	2005 - on	F	**2893**	✓				Vented	256	47	22	**20**	62	4
SEDONA														
3.8Ltr V6 DOHC 24V	2006 - on	F	**2871**	✓		✓		Vented	300	54.1	28	**26**	96.3	6
SPECTRA														
all - 4 & 5 door	2001 - 03	F	**2898**	✓		✓		Vented	302	54	28	**26**	96.2	5
SORENTO														
Sorento 4WD 3.5L V6	2003 - on	F	**2898**	✓		✓		Vented	302	54	28	**26**	96.2	5
		R	**2899**	✓				Vented	315	87.5	20	**18.4**	96.2	5
SPORTAGE														
Sportage/Sportswagon 4WD All 4WD (USA)	11/96 - 03 2001 - 03	F	**876**	4x4				Vented	284	51	24	**22.4**	96	5
Sportage 2.7L V6 4WD	2004 - on	F	**468**	4x4		4x4		Vented	280	47	26	**22.4**	69	5
2.0 CRDi 2WD	2005	F	**468**	4x4		4x4		Vented	280	47	26	**22.4**	69	5
		R	**458**	4x4				Solid	262	61	10	**8**	76	4
2.0 16V 4WD, 2.7 V6 4WD	2005	F	**468**	4x4		4x4		Vented	280	47	26	**22.4**	69	5
2.0 CRDi 4WD		R	**465**	4x4				Solid	284	61	10	**8.4**	76	5
PREGIO														
Pregio 2.7L Diesel	2002 - on	F	**2897**	✓				Vented	258	57	26	**24**	87	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

LADA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
NIVA 2121, 4WD	1984 - 9/92	F	**872**	✓				Solid	272	50.5	11	**10**	108	5
Samara, Cevaro 2108	1988 - 5/91	F	**870**	✓				Solid	239	42.5	12	**11**	58.5	4
Volante, Sable	12/93 - on	F	**870**	✓				Solid	239	42.5	12	**11**	58.5	4

LANCIA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Beta	1972 - 84	F	**390**	✓				Solid	251	51	12.7	**11.5**	48.5	4
		R	**391**	PART NOT AVAILABLE REFERENCE ONLY				Solid	251	55	10	**9**	48.5	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

LANDROVER / RANGE ROVER

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
110 & DEFENDER														
110, 130 TD4 200, 300 TDi 90	up to 1994 1984 - on	F	**087**	4x4		4x4		Solid	298	70	14	**13**	101.6	5
110, 130 TD4 + TD5 200, 300 TDi + LF Crew Cab	1994 - on	F	**086**	4x4		4x4		Vented	298	70	24	**22**	101.6	5
	1994 - 98	R	**088**	4x4		4x4		Solid	290	61	12.7	**11.7**	101.6	5
110 series	1999 - on	R	**549**	4x4		4x4		Solid	298	59	14	**13**	101.6	5
90, 110 series	2008 - on	F	**087**	4x4		4x4		Solid	298	70	14	**13**	101.6	5
		F	**086**	4x4		4x4		Vented	298	70	24	**22**	101.6	5
90 series	2008 - on	R	**088**	4x4		4x4		Solid	290	61	12.7	**11.7**	101.6	5
110 series	2008 - on	R	**549**	4x4		4x4		Solid	298	59	14	**13**	101.6	5
DISCOVERY I (LJ)														
V8 Petrol 2.5 TDi Diesel (check if vented or solid)	1989 - 98	F	**087**	4x4		4x4		Solid	298	70	14	**13**	101.6	5
		F	**086**	4x4		4x4		Vented	298	70	24	**22**	101.6	5
		R	**088**	4x4		4x4		Solid	290	61	12.7	**11.7**	101	5

PLEASE NOTE: DISCOVERY I SERIES MAY HAVE EITHER SOLID OR VENTED DISCS. NOT INTERCHANGEABLE.

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISCOVERY II (LT)														
V8 Petrol, TD5 Diesel	1999 - on	F	**528**	4x4		4x4		Vented	297	91.5	25	**22**	70	5
S, SE & HSE		R	**093**	4x4		4x4		Solid	304	62.7	12.6	**11.7**	70	5
DISCOVERY III (LM)														
4.0L V6, 2.7L TDV6	2004 - on	F	**2090**	4x4		4x4		Vented	317	62.2	30	**27**	79	5
		R	**2091**	4x4		4x4		Solid	325	59.6	20	**17**	79	5
4.4L V8 Petrol	2004 - on	F	**2094**	4x4		4x4		Vented	337.5	62.2	30	**27**	79	5
		R	**2095**	4x4		4x4		Solid	350	59.6	20	**17**	79	5
FREELANDER														
1.8L Petrol + 2.0L Diesel	up to 12/2000	F	**526**	4x4		4x4		Solid	262	51	14	**11**	66	5
V6 Petrol + TD4 Diesel	2001 - on	F	**527**	4x4		4x4		Vented	277	51.5	21	**18**	66	5
RANGE ROVER CLASSIC														
Classic	1972 - 1986	F	**087**	4x4		4x4		Solid	298	70	14	**13**	101	5
Classic (Vented Disc)	1990 - on	F	**086**	4x4		4x4		Vented	298	70	24	**22**	101.6	5
Classic (Rear)	1972 - on	R	**088**	4x4		4x4		Solid	290	61	12.7	**11.7**	101	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

LANDROVER / RANGE ROVER

RANGE ROVER II

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
4.0 & 4.6L V8 P38 Turbodiesel 2.5L 6cyl.	1995 - 01	F	**092**	4x4		4x4		Vented	297	64.6	25	**22**	70	5
		R	**093**	4x4		4x4		Solid	304	62.7	12.6	**11.7**	70	5

RANGE ROVER III

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	A	B	C	D	E	F
3.0L TD6 4.4L V8 Petrol (210kw)	3/02 - 4/05 72mm pad face depth	F	**2092**	4x4		4x4		Vented	344	76.2	30	**28.4**	79	5
		R	**2093**	4x4		4x4		Solid	354	75	12	**10.4**	79	5
4.2L V8 Supercharged	2005 - on	F	**2098**	4x4		4x4		Vented	360	81.3	30	**27**	79	5
		R	**2097**	4x4		4x4		Vented	354	75.1	20	**17**	79	5
3.0L TD6 4.4L V8 Petrol (225kw)	5/05 - on 57mm pad face depth	F	**2099**	4x4		4x4		Vented	344	76.2	30	**27**	79	5
		R	**2097**	4x4		4x4		Vented	354	75.1	20	**17**	79	5

RANGE ROVER III SPORT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	A	B	C	D	E	F
2.7L TDV6	2005 - on	F	**2090**	4x4		4x4		Vented	317	62.2	30	**27**	79	5
		R	**2091**	4x4		4x4		Vented	325	59.6	20	**17**	79	5
4.4L V8 Petrol	2005 - on	F	**2094**	4x4		4x4		Vented	337.5	62.2	30	**27**	79	5
		R	**2095**	4x4		4x4		Vented	350	59.6	20	**17**	79	5
4.2L V8 Supercharged	2005 - on	F	**2096**	4x4		4x4		Vented	360	62.2	30	**27**	79	5
		R	**2095**	4x4		4x4		Vented	350	59.6	20	**17**	79	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

LEXUS

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
RX 300														
MCU10, ACU10	1998 - 11/01	F	**2712**	✓				Vented	296	49.5	28	**26**	62	5
		R	**734**	✓				Solid	288	65	10	**9**	62	5
RX 330 + RX 350														
3.3L V6 4WD + FWD	3/03 - on	F	**2702**	✓	✓	✓		Vented	320	49.3	28	**26**	62	5
3.5L	2006 - on	R	**2703**	✓	✓	✓		Solid	288	69.5	10	**8.5**	62	5
ES 300														
ES 300	1992 - 99	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
		R	**734**	✓				Solid	288	65	10	**9**	62	5
ES 300	8/99 - 01	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
ES 300	7/01 - ON	F	**2705**	✓				Vented	296	49.3	28	**26**	62	5
3.0L V6 (MCV30)		R	**2711**	✓				Solid	269	65	12	**10.5**	62	5
GS 450H														
all models	2007 - on	F	**2720**	✓				Vented	334	51	30	**27**	62	5
		R	**2721**	✓				Vented	310	67.5	18	**16.5**	62	5
GS SERIES														
all models	1993 - 05	F	**4748**			✓		Vented	296	51	32	**30**	62	5
		R	**749**	✓		✓		Solid	307	63	12	**10.5**	62	5
GX SERIES														
All models	9/02 - 09	F	**2700**	✓	✓	✓		Vented	338	68	28	**26**	108	6
		R	**793**	✓	✓			Vented	312	68	18	**16**	106	6
IS 200														
IS 200	99 - 2/02	F	**4748**			✓		Vented	296	51	32	**30**	62	5
		R	**749**	✓		✓		Solid	307	63	12	**10.5**	62	5
IS 250														
All models	2006 - on	F	**2726**	✓				Vented	296	49.5	28	**26**	62	5
		R	**2727**	✓				Solid	291	61.5	10	**8.5**	62	5
IS 300														
all models	2000 - 05	F	**4748**			✓		Vented	296	51	32	**30**	62	5
		R	**749**	✓		✓		Solid	307	63	12	**10.5**	62	5
IS 350														
all models	2007 - on	F	**2720**	✓				Vented	334	51	30	**27**	62	5
		R	**2721**	✓				Vented	310	67.5	18	**16.5**	62	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

LEXUS

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LS 400														
LS 400	4/90 - 92	F	**737**	✓				Vented	276	51	28	**26**	60	5
		R	**738**	✓				Vented	291	67.5	16	**15**	60	5
LS 400	1993 - 94	F	**4748**			✓		Vented	296	51	32	**30**	62	5
LS 400	1995 - 2000	F	**745**	✓				Vented	315	53.5	28	**26**	62	5
		R	**746**	✓				Vented	307	67	16	**15**	62	5
LS 430														
V8 4.2 litre	5/01 - 11/02	F	**845**	✓				Vented	315	50.25	30	**28**	62	5
		R	**846**	PART NOT AVAILABLE REFERENCE ONLY				Vented	310	67.5	16	**14.5**	62	5
LS 460														
All models	2007 - on	F	**2728**	PART NOT AVAILABLE REFERENCE ONLY				Vented	357.1	60.5	34	**31**	62	5
		R	**2729**					Vented	334.9	66	22	**20**	62	5
LX 470														
V8 DOHC 4.7L 4WD	4/1998 - 07	F	**788**	4x4		4x4		Vented	312	71	32	**30**	115	5
		R	**789**	4x4		4x4		Vented	330	103	18	**16**	110	5
LX 570														
5.7-liter V8	2008	F	**2722**	4x4		4x4		Vented	340	83.6	29	**112**	115	5
		R	**2723**	4x4		4x4		Vented	345	76.5	18	**16**	112	5
SC SERIES														
SC 300	1999 - 00	F	**4748**			✓		Vented	296	51	32	**30**	62	5
SC 400	1992 - 00	R	**749**	✓		✓		Solid	307	63	12	**10.5**	62	5
SC 430	2002 - 05													
SOARER														
JZZ30 Eng: 1JZGTE 2.5L TURBO UZZ32 Eng: 1UZFE 4.0L V8	1991 - on	F	**4748**			✓		Vented	296	51	32	**30**	62	5
		R	**746**	✓		✓		Vented	307	67	16	**15**	62	5
JZZ31 Eng: 2JZGE 3.0L UZZ30 Eng: 1UZFE 4.0L V8 UZZ31 Eng: 1UZFE 4.0L V8	1994 - on 1991 - on	F	**568**	✓				Vented	275	49.5	28	**26**	62	5
		R	**586**	✓				Vented	291	67.5	16	**15**	60	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

LEYLAND

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
P76	1973 - 74	F	**068**	✓				Vented	273	62	25.4	**22.74**	HUB	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

LOTUS

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ELISE S1														
All except SPORT	3/2000 - on	F&R	**5355**				✓	Vented	280	26	26	**24.5**	56.6	4
Sport 135, 190, 111S (models with Lotus OEM cross-drilled rotors)	3/2000 - on	F&R	**52356**				✓	Vented	280	29.4	26	**24.5**	56.6	4
ELISE S2 / EXIGE														
Elise S2	2001 - on	F&R	**42355**			✓	✓	Vented	288	44.5	26	**24.5**	60.1	4
LOTUS UPGRADE OPTION														
Elise S2	2001 - on	F&R	**52358**				✓	Vented	296	44.5	26	**24.5**	60.1	4

MASERATI

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Biturbo 2.0, 2.5	1982 - on	F	**439**	PART NOT AVAILABLE REFERENCE ONLY				Solid	282	59	12.7	**11.4**	60	4

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MAZDA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
EARLY SERIES														
1500 SUE	11/66 - 68	F	**330**	✓				Solid	250	31	10	**9**	80	4
1500 SS, 1800 SUA	1967 - 68													
808, 1300 STC	1972 - 75	F	**331**	PART NOT AVAILABLE REFERENCE ONLY				Solid	230	33	11	**10**	72	4
1300 FA3, STB	1970 - 75	F	**332**	✓				Solid	244	50	10	**9**	72	4
Capella SNA 1600	1973 - 74	F	**338**	PART NOT AVAILABLE REFERENCE ONLY				Solid	230	34.5	12	**11**	72	4
121, 121L SERIES														
121, 121L CD2, CD5	1976 - 80	F	**335**	✓				Vented	250	37.5	18	**17**	80	4
121 DA (Shades)	86 - 11/90	F	**635**	✓				Solid	219	37	13	**11**	75	4
121 DB 1.5 Litre	11/90 on	F	**530**	✓				Vented	235	45.5	18	**16**	55	4
121 DB 1.3 Litre	11/90 on	F	**525**	✓				Solid	235	45	12	**10**	55	4
121 DW Metro	8/96 on	F	**530**	✓				Vented	235	45.5	18	**16**	55	4
323 SERIES														
FA4 RWD	11/76 - 8/80	F	**339**					Solid	206	54	13	**12**	HUB	4
FA4 P/Van, S/Wagon RWD	1978 - 85	F	**337**	PART NOT AVAILABLE REFERENCE ONLY				Solid	229	54	13	**12**	HUB	4
BD10 FWD	1981 - 85	F	**100**	✓				Solid	228	31	11	**10**	75	4
BF	11/85 - 89	F	**930**	✓				Vented	238	31	18	**16**	75	4
BF Wagon	6/86 - 88							Check Disc Diamater						
BF10 All with rear disc	4/87 - 89	F	**101**	✓				Vented	260	32	18	**16**	75	4
except wagon, Turbo only								Check Disc Diamater						
BF Wagon	6/86 - 88	R	**933**	PART NOT AVAILABLE REFERENCE ONLY				Solid	221	35	10	**8**	HUB	4
								Hub Seal Dia. 65mm						
BF10 Turbo, 2WD	4/87 - 89	R	**931**	✓				Solid	222	35	10	**8**	HUB	4
All except 4WD								Hub Seal Dia. 54mm						
BF10 Turbo 4WD	4/87 - 89	R	**932**	PART NOT AVAILABLE REFERENCE ONLY				Solid	247	30	10	**8**	75	4
BG Astina 1.6L, 1.8L SOHC	1990 - 94	F	**532**	✓		✓		Vented	235	45.5	22	**20**	55	4
BG 1.8L SOHC	1990 - 94	R	**531**	✓		✓		Solid	231	35	9	**8**	55	4
BG Astina 1.8L DOHC	1990 - 94	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
BA Protege 1.6L, 1.8 DOHC	94 - 4/98													
		R	**534**	✓		✓		Solid	250.5	34.5	9	**8**	55	4
BA Astina 2.0L & V6	5/94 - 4/98	F	**535**	✓				Vented	274	45	22	**20**	72	5
		R	**536**	✓				Solid	251	34.5	9	**8**	72	5
BJ Astina, Protege 1.6L	1998 - on	F	**532**	✓		✓		Vented	235	45.5	22	**20**	55	4
BJ Astina Protege 1.8L,	1998 - on	F	**537**	✓				Vented	258	47	24	**22**	55	4
		R	**539**	✓				Solid	261	40	10	**8**	55	4
BJ Astina Protege 2.0L SP20	1998 - on	F	**577**	✓				Vented	258	48.5	24	**22**	72	5
		R	**951**	✓				Solid	261	40	9.5	**8**	72	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MAZDA - 626

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
626 SERIES														
CB2MS RWD	1978 - 82	F	**333**					Solid	231	50	13	**12**	HUB	4
GC FWD	2/83 - 2/84	F	**119**	✓				Solid	250	35	14	**12.5**	75	4
GC FWD & Turbo	1984 - 87	F	**334**	✓				Vented	250	35	20	**18.5**	75	4
		R	**945**	✓				Solid	254	50.2	10.2	**9**	HUB	4
GD FWD	1987 - 91	F	**633**	✓				Vented	264	47	24	**22**	64	5
GD (2 wheel steer)	1987 - 91	R	**634**	PART NOT AVAILABLE REFERENCE ONLY				Solid	258	64	10	**8**	HUB	5
GD (4 wheel steer)	5/89 - 91	R	**948**	PART NOT AVAILABLE REFERENCE ONLY				Solid	260	40	10	**8**	HUB	5
GE, EE 2.0 Litre, V6 GF 2.0 Litre	1992 - 3/97 4/97 - on	F	**950**	✓				Vented	258	49	24	**22**	72	5
incl. GF Series II		R	**951**	✓				Solid	261	40	9.5	**8**	72	5
GV 626 Wagon 2WD/4WD	1988- 9/97	F	**633**	✓				Vented	264	47	24	**22**	64	5
929 / 929L SERIES														
LA2 RWD	1974 - 76	F	**338**	PART NOT AVAILABLE REFERENCE ONLY				Solid	230	34.5	12	**11**	72	4
LA2 RWD	1976 - 79	F	**335**	✓				Vented	250	37.5	18	**17**	80	4
929L LA4, LA5 RWD P.C.D. 120mm	1978 - 2/82	F	**630**	✓				Vented	250	56	18	**17**	HUB	4
HBES Coupe, Sedan (Hardtop)	1984 - 87	F	**940**	✓				Vented	246	56	20	**18**	HUB	4
HBES	1984 - 87	R	**942**	PART NOT AVAILABLE REFERENCE ONLY				Solid	255	45	10	**9**	66	4
HC10 V6 non-ABS Series I	1987 - 91	F	**638**	✓				Vented	255	57	22	**20**	HUB	5
HC10 V6	1987 - 91	R	**639**	✓				Solid	265	57	10	**8**	68	5
HC10 V6 Series II	11/89 - on	F	**659**	✓				Vented	255	72.4	22	**20**	HUB	5
HD10	5/91 - on	F	**955**	PART NOT AVAILABLE REFERENCE ONLY				Vented	274	47.5	24	**22**	72	5
		R	**956**	PART NOT AVAILABLE REFERENCE ONLY				Vented	286	56.5	18	**16**	72	5

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MAZDA - 3 / MPS / SPEED 3

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MAZDA 2														
1.5L Hatch	2003 - on	F	**2958**	✓				Vented	258	43.5	22	**20**	55	4
MAZDA 3 + MPS - AUSTRALIA														
2.0L Sedan, Hatch	2003 - on	F	**2954**	✓				Vented	278	49	25	**23**	72	5
NEO, MAXX, MAXX sport		R	**2955**	✓				Solid	264	41	11	**9**	72	5
2.3L SP23	2003 - 08	F	**2956**	✓		✓		Vented	300	49	25	**23**	72	5
2.5L SP25	2009 - on	R	**2957**	✓		✓		Solid	279.5	41.5	11	**9**	72	5
MPS 2.3L 4 Cyl Turbo	2006 - on	F	**2962**	✓		✓		Vented	320	49	25	**23**	72	5
		R	**2957**	✓		✓		Solid	279.5	41.5	11	**9**	72	5
MAZDA 6														
2.3L DOHC MZR	2002 - on	F	**2950**	✓				Vented	274	47.5	24	**22**	72	5
Sedan, Hatch, Wagon		R	**2951**	✓				Solid	280	40	10	**8**	72	5
MPS 2.3L 4cyl TURBO	2005 - on	F	**2960**	✓		✓		Vented	320	46.5	25	**23**	72	5
		R	**2961**	✓		✓		Solid	314	41	11	**9**	72	5
MX-3														
with rear drum	1992 - 95	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
with rear disc	1992 - 95	F	**533**	✓		✓		Vented	257	45.5	22	**20**	55	4
		R	**534**	✓		✓		Solid	250	34.5	9	**8**	55	4
MX-5 - MIATA														
NA 1.6 & 1.8	10/89 - 9/93	F	**530**	✓				Vented	235	45.5	18	**16**	55	4
		R	**531**	✓				Solid	231	35	9	**8**	55	4
NA & NB 1.8	9/93 - 2000	F	**538**	✓		✓		Vented	255	45	20	**18**	55	4
incl. Titanium & SP Turbo Auto.	2000 - on													
Rear suits all models	1998 - on	R	**534**	✓		✓		Solid	250	34.5	9	**8**	55	4
incl. Titanium & SP Turbo Auto.														
NB 1.8L Titannium & SP Turbo	8/03 - 5/05	F	**545**	✓		✓		Vented	270	46	22	**20**	55	4
* Manual models only *														
NB 1.8L Roadster 2005 model	2005													
		R	**546**	✓		✓		Solid	276	35	10	**8**	55	4
NC 2.0L	5/05 - on	F	**2959**	✓		✓		Vented	290	45.1	22	**20**	72	5
		R	**2951**	✓		✓		Solid	280	40	10	**8**	72	5
MAZDA 5 (EUROPE)														
All models with 16" wheels	2005 - on	F	**2956**	✓		✓		Vented	300	49	25	**23**	72	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MAZDA - 6 / MX-5 / RX-7

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MX 6														
GC & Turbo	1986 - 87	F	**334**	✓				Vented	250	35	20	**18.5**	75	4
		R	**945**	✓				Solid	254	50.2	10.2	**9**	HUB	4
GD Turbo	1987 - 91	F	**633**	✓				Vented	264	47	24	**22**	64	5
GD 2WS	1987 - 91	R	**634**	PART NOT AVAILABLE REFERENCE ONLY				Solid	258	50	10	**8**	HUB	5
GD 4WS	5/89 - 91	R	**948**	✓				Solid	260	40	10	**8**	HUB	5
GE	11/91 on	F	**950**	✓				Vented	258	49	24	**22**	72	5
		R	**951**	✓				Solid	261	40	9.5	**8**	72	5
PREMACY														
1.8L (rear drum brakes)	1999 - 01	F	**950**	✓				Vented	258	49	24	**22**	72	5
2.0L	2001 - on	R	**951**	✓				Solid	261	40	9.5	**8**	72	5
RX-1 & 2														
R100	1969 - 72	F	**332**	✓				Solid	244	50	10	**9**	72	4
RX2 S122A	1970 - 76	F	**338**	PART NOT AVAILABLE REFERENCE ONLY				Solid	230	34.5	12	**11**	72	4
RX-3 & 5														
RX3 S102A	1972 - 76	F	**331**	PART NOT AVAILABLE REFERENCE ONLY				Solid	230	33	11	**10**	72	4
RX3, S124A RX4	1972 - 78	F	**338**	PART NOT AVAILABLE REFERENCE ONLY				Solid	230	34.5	12	**11**	72	4
RX5 CD23	1976 - 79	F	**335**	✓				Vented	250	37.5	18	**17**	80	4
RX-7														
RX7 Series 1, 2 SA22	1979 - 83	F	**336**					Vented	228	59	18	**17**	HUB	4
RX7 Series 2 SA22C	1981 - 83	R	**935**	PART NOT AVAILABLE REFERENCE ONLY				Solid	235	50	10	**9**	47.5	4
RX7 Series 3 SA22	1983 - 1/86	F	**946**	✓				Vented	250	65	22	**20**	HUB	4
RX7 Series 3 SA22	1983 - 1/86	R	**936**	PART NOT AVAILABLE REFERENCE ONLY				Vented	257	63	20	**18**	66	4
RX7 Series 4 FC1	2/86 - 4/92	F	**636**	✓				Vented	276	65	22	**20**	77	5
RX7 Series 4 (Turbo) FC1	2/86 - 4/92	R	**637**	✓				Vented	273	53	20	**18**	66	5
RX7 FD 103	4/92 - on	F	**947**	✓		✓		Vented	294	67	22	**20**	72	5
		R	**952**	PART NOT AVAILABLE REFERENCE ONLY				Vented	294	45	20	**18**	72	5
RX7 SP Series 6	4/92 - on	F	**2558**	✓				Vented	314	67.5	32	**30**	72	5
		R	**2559**	✓				Vented	314	45.5	20	**18**	72	5
RX-8														
RX8 - Standard Suspension Models	2003 - on	F	**42552**			✓		Vented	302.5	45	24	**22**	72	5
		R	**42551**			✓		Vented	302	43	18	**16**	72	5
RX8 - Sports Suspension Models	2003 - on	F	**42550**			✓	✓	Vented	323	46	24	**22**	72	5
(AUSTRALIA)		R	**42551**			✓		Vented	302	43	18	**16**	72	5

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MAZDA - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
B SERIES														
B1800 - B2000 - B2200	1980 - 85	F	**941**	PART NOT AVAILABLE REFERENCE ONLY				Solid	255	36	20	**19**	80	4
B2000 - B2200 - B2600 2 W.D.	1985 - 96	F	**631**	✓				Vented	256	20	20	**18**	86	6
B2000 - B2200 - B2600 4 W.D.	1985 - 96	F	**965**	✓				Vented	272	25	22	**20**	93	6
B2500 - B2600 2 W.D.	1996 - 02	F	**958**	✓				Vented	255.5	24	24	**22**	86	6
B2500 - B2600 4 W.D.	1996 - 02	F	**959**	✓				Vented	274	28	28	**26**	93	6
B2500 - B2600 4 W.D.	2002 - on	F	**2952**	✓		✓		Vented	288.5	70.5	28	**26**	98	6
B2600 4WD	1998 - on	F	**964**	✓				Vented	275	24	24	**22**	93	6
BT50	2006 - on	F	**2952**	✓		✓		Vented	288.5	70.5	28	**26**	98	6
CX-7														
All Models	2007 - on	F	**2562**	4×4				Vented	296	48.5	28	**26**	72	5
		R	**2563**	4×4				Vented	302	57	18	**16**	72	5
E SERIES														
E1400 - E1800 Van Wagon & Short Body Traveller / Esky	1984 - 97	F	**632A**					RH Vented	231.5	58.5	18	**16**	HUB	4
			632B					LH Vented ID Groove						
E2000 - E2200 Van STD & LWB	1984 - 5/92	F	**631**	✓				Vented	256	20	20	**18**	86	6
E2000 - 2200 Pickup	1984 - 97	F	**934**	✓				Vented	268	20	20	**18**	86	6
E2000 - 2200 Van	5/92 - on	F	**958**	✓				Vented	255.5	24	24	**22**	86	6
MPV														
LV10E1	1993 - on	F	**960**	✓				Vented	276	64	28	**26**	72	5
LV10E2	12/95 - on	F	**961**	PART NOT AVAILABLE REFERENCE ONLY				Vented	276	58	28	**26**	72	5
		R	**956**	PART NOT AVAILABLE REFERENCE ONLY				Vented	286	57	18	**16**	72	5
LVW (D) 2.5L V6, 3.0L 4 Door Wagon	9/1999 - on	F	**962**	✓				Vented	274	51	28	**26**	72	5
		R	**956**	PART NOT AVAILABLE REFERENCE ONLY				Vented	286	57	18	**16**	72	5
TRIBUTE														
all models	2000 - 05	F	**957**	✓		✓		Vented	278	47	24	**22**	72	5
2.3L 4 cyl, 3.0L V6	2006 - on	F	**2560**	✓		✓		Vented	302.7	47.2	26	**24**	72	5
		R	**2561**	✓				Solid	302	56.1	12	**11**	72	5
XEDOS 6														
1.6L / 1.8L / 2.0L.	1992 - 00	F	**950**	✓				Vented	258	49	24	**22**	72	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MERCEDES BENZ

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
C111 - COUPE														
250, 280 SE/C	1965 - 68	F	**250**	✓				Solid	273	63.3	12.7	**10.6**	70	5
280 SE/, 280 SE/C 3.5 250, 280 SE/C 3.5	1968 - 72 1965 - 72	F	**256**	PART NOT AVAILABLE REFERENCE ONLY				Vented	273	67.4	19.1	**18**	69	5
		R	**251**	✓				Solid	279	72	10	**8.3**	67	5
C140 - COUPE														
500 SEC, S500 Coupe	1993 - 95	F	**284**	✓				Vented	320	82	30	**27.4**	67	5
		R	**285**	PART NOT AVAILABLE REFERENCE ONLY				Vented	300	60	22	**19.4**	67	5
R107 - SPORTS														
350 SL > 009599 350 SLC > 005715	1972 - 73	F	**257**	✓				Vented	273	67	22	**20**	80	5
280, 350, 450 SL, SLC	1973 - 80	F	**255**	PART NOT AVAILABLE REFERENCE ONLY				Vented	278	67	22	**20**	80	5
380, 500 SL, SLC	1980 - 85	F	**258**	PART NOT AVAILABLE REFERENCE ONLY				Vented	278	69	22	**19.4**	80	5
560 SL	1986 - 89	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
All R107	1972 - 89	R	**251**	✓				Solid	279	72	10	**8.3**	67	5
R129 - SPORTS														
R129, 500 SL	1985 - 90	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
500 SL, SL500	1990 - 94	F	**280**	PART NOT AVAILABLE REFERENCE ONLY				Vented	300	45.5	28	**25.4**	67	5
		R	**281**	✓				Solid	278	58.5	9.1	**7.3**	67	5
W108 / W109														
250, 280 S, SE	1965 - 68	F	**250**	✓				Solid	273	63.3	12.7	**10.6**	70	5
250, 280 S, SE, SEL, 3.5 300 SEL 3.5, 6.3	1968 - 72 1968 - 72	F	**256**	PART NOT AVAILABLE REFERENCE ONLY				Vented	273	67.4	19.1	**18**	69	5
		R	**251**	✓				Solid	279	72	10	**8.3**	67	5
W110 / W111														
190C, 190D, 200, 230 220B, S, SB, SEB, 230S	Up to 1965 Up to 1965	F	**253**	✓				Solid	253	67.3	12.7	**11.1**	69.5	5
		R	**251**	✓				Solid	279	72	10	**8.3**	67	5

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
W113 - SPORTS														
230 SL	1965 - 68	F	**253**	✓				Solid	253	67.3	12.7	**11.1**	69.5	5
250, 280 SL	1968 - 72	F	**250**	✓				Solid	273	63.3	12.7	**10.6**	70	5
230, 250, 280 SL	1965 - 72	R	**251**	✓				Solid	279	72	10	**8.3**	67	5
W114 / W115														
200, 220, 230 230/6, 250, 250 C, CE	1968 - 71	F	**250**	✓				Solid	273	63.3	12.7	**10.6**	70	5
250, 230/6 250 C, CE 240 D, 230	1971 - 74	F	**252**	✓				Solid	273	63.3	12.7	**10.6**	80	5
230/6, 250 C, CE 280 E, C, CE	1973 - 76	F	**254**	✓				Solid	278	63.3	12.7	**10.6**	80	5
All W114, W115	1968 - 76	R	**251**	✓				Solid	279	72	10	**8.3**	67	5
W116														
280 S, SE, SEL 350, 450 SE, SEL	1972 - 80	F	**255**	PART NOT AVAILABLE REFERENCE ONLY				Vented	278	67	22	**20**	80	5
All W116	1972 - 80	R	**251**	✓				Solid	279	72	10	**8.3**	67	5
W123														
230, 240 D, 250 280 E, CE, TE 230 E, 300 D, 300 TD	1976 - 78 1976 - 84 1976 - 84	F	**254**	✓				Solid	278	63.3	12.7	**10.6**	80	5
All W123	1976 - 84	R	**251**	✓				Solid	279	72	10	**8.3**	67	5
W126														
280, 380, 500 SE, SEL	1981 - 86	F	**258**	PART NOT AVAILABLE REFERENCE ONLY				Vented	278	69	22	**19.4**	80	5
300, 420, 560 SE, SEL	1986 - 91	F	**262**	✓				Vented	300	68.5	27.5	**25.4**	80	5
380, 500 SEC	1981 - 86	F	**259**	✓				Vented	286	60	22	**19.4**	80	5
560 SEC	1986 - 91	F	**262**	✓				Vented	300	68.5	27.5	**25.4**	80	5
All W126 Rears	1981 - 91	R	**251**	✓				Solid	279	72	10	**8.3**	67	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
W124														
230 E, TE, 300 D	1986 - 89	F	**263**	✓				Solid	284	46	12	**10**	67	5
260, 300 E, TE 230 TE 300 CE	1986 - 91 1986 - 91 1986 - 89	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
230, 260, 300 E, 300 D 300 CE	1986 - 91 1986 - 89	R	**261**	✓				Solid	258	55	9	**7.3**	67	5
220 E, E220, 230 E 280 E, E280, 300 E	1991 - 95	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
300 E 24V	1990 - 92	F	**266**	PART NOT AVAILABLE REFERENCE ONLY				Vented	295	49.5	22	**19.4**	67	5
320 E, E320	1993 - 94	F	**266**					Vented	295	49.5	22	**19.4**	67	5
320 E, E320	1994 - 95	F	**268**	✓				Vented	294	50	24	**22.4**	67	5
220 E, E220, 230 E 260 E, 280 E, E280 300 E, 300 D, E300 D	1990 - 95	R	**261**	✓				Solid	258	55	9	**7.3**	67	5
300 E 24V, 320 E, E320	1990 - 95	R	**267**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	56	9	**7.3**	67	5
300 D	1990 - 93	F	**263**	✓				Solid	284	46	12	**10**	67	5
E300 D	1990 - 94	F	**263**	✓				Solid	284	46	12	**10**	67	5
E220 Coupe, Convertible	1995 on	F	**269**	✓				Vented	284	43	22	**19.4**	67	5
E220 Convertible	1990 - 95	R	**267**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	56	9	**7.3**	67	5
E220 Coupe	1995 on	R	**261**	✓				Solid	258	55	9	**7.3**	67	5
300 CE 24V Coupe	1990 -92	F	**266**	PART NOT AVAILABLE REFERENCE ONLY				Vented	295	49.5	22	**19.4**	67	5
		R	**267**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	56	9	**7.3**	67	5
E320, 320 CE (Up to Chassis No. B162121)	1993 - 94	F	**266**	✓				Vented	295	49.5	22	**19.4**	67	5
E320, 320 CE (Chassis No. B162121 on)	1993 - 94	F	**268**	✓				Vented	294	50	24	**22.4**	67	5
E320, 320 CE	1993 - 94	R	**267**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	56	9	**7.3**	67	5

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
W140														
300 SE 3.2 (Up to Chassis No. A050548)	1992 - 93	F	**282**	✓				Vented	310	82	28	**25.4**	67	5
300 SE 3.2 (Chassis No. A050548 on)	1993 - 95	F	**284**	✓				Vented	320	82	30	**27.4**	67	5
S280, 300 SE 3.2, S320	1992 - 95	R	**283**	✓				Solid	290	60	12	**9.8**	67	5
S280, S320, 400 SE, S420 400, 500 SEL, S500 S600, 600 SEL V12	1992 - 98 1992 - 98 1992 - 98	F	**284**	✓				Vented	320	82	30	**27.4**	67	5
400 SE, S420, 420 SEL, 500 SEL, S500, S600, 600 SEL V12	1992 - 95	R	**285**	PART NOT AVAILABLE REFERENCE ONLY				Vented	300	60	22	**19.4**	67	5
W201														
190 E, 190 D 2.5 190 E, 190 E 1.8	1985 - 88 1988 - 91	F	**260**	✓				Solid	262	43	11	**9**	67	5
190 E 2.3 16 Valve	1985 - 88	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
190 E 2.3, 2.6	1986 - 93	F	**279**	✓				Vented	262	44.5	22	**19.4**	67	5
190 E 1.8, 190 D 2.5, 190 E	1985 - 91	R	**261**	✓				Solid	258	55	9	**7.3**	67	5
W168														
A140	07/97 - 08/04	F	**556**	✓				Solid	260	40.5	12	**10**	67	5
A140	07/97 - 08/04	F	**557**	✓				Vented	260	40.5	22	**19**	67	5
A160	07/97 - 08/04	F	**557**	✓				Vented	260	40.5	22	**19**	67	5
		R	**559**	✓				Solid	258	55.2	8	**7**	67	5
A190	03/99 - 08/04	F	**558**	✓				Vented	276	35.5	22	**19**	67	5
		R	**559**	✓				Solid	258	55.2	8	**7**	67	5
A160 CDI	07/98 - 08/04	F	**556**	✓				Solid	260	40.5	12	**10**	67	5
A170 CDI	07/98 - 02/01	F	**557**	✓				Vented	260	40.5	22	**19**	67	5
A170 CDI	02/01 - 08/04	F	**557**	✓				Vented	260	40.5	22	**19**	67	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ - 4WD / SUV

W202

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
C180	03/93 - 05/00	F	**265**	✓				Solid	284	43.5	12	**10**	67	5
C200	01/94 - 05/00	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
C200 KOMPRESSOR	10/95 - 05/00	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C220	03/93 - 05/00	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
C230	03/93 - 05/00	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
C230 KOMPRESSOR	10/95 - 05/00	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C240	10/95 - 05/00	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C280	05/93 - 05/00	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
C280	05/93 - 05/00	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C200 CDI	09/97 - 05/00	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
C200 D	03/93 - 05/00	F	**265**	✓				Solid	284	43.5	12	**10**	67	5
C220 CDI	09/97 - 05/00	F	**264**	✓				Vented	284	43	22	**19.4**	67	5
C220 D	03/93 - 05/00	F	**265**	✓				Solid	284	43.5	12	**10**	67	5
C250 D	05/93 - 05/00	F	**265**	✓				Solid	284	43.5	12	**10**	67	5
C250 TD	10/95 - 05/00	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C36 AMG	9/95 - 8/97	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ

S202

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
C180 T	06/96 - 09/00	F	264	✓				Vented	284	43	22	19.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200 T	06/96 - 03/01	F	264	✓				Vented	284	43	22	19.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200T KOMPRESSOR	06/96 - 03/01	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C230 T	06/96 - 06/98	F	264	✓				Vented	284	43	22	19.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C230T KOMPRESSOR	06/97 - 09/00	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C240 T	06/96 - 09/00	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C240 T	09/00 - 03/01	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C280 T	06/97 - 03/01	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200 T CDI	06/96 - 03/01	F	264	✓				Vented	284	43	22	19.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200 T D	06/96 - 03/01	F	264	✓				Vented	284	43	22	19.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C220 T CDI	06/96 - 03/01	F	264	✓				Vented	284	43	22	19.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C220 T D	06/96 - 03/01	F	264	✓				Vented	284	43	22	19.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C250 T TURBO-D	06/96 - 03/01	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MERCEDES BENZ - 4WD / SUV

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
W203														
C180 KOMPRESSOR	05/02 - ON	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C22 CGI KOMPRESSOR	05/02 - ON	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C200 KOMPRESSOR	05/00 - ON	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C230 KOMPRESSOR	05/02 - ON	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C180	05/00 - 05/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C230	01/05 - ON	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C240	05/00 - ON	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C240 4-MATIC	07/02 - ON	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
C280	01/05 - ON	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
C280 4-MATIC	01/05 - ON	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
C320	05/00 - ON	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C320 4-MATIC	07/02 - ON	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
C200 CDI	05/00 - ON	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C220 CDI	05/00 - ON	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
C270 CDI	12/00 - ON	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ

S203

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
C180	03/01 - 05/02	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C180	03/01 - 05/02	F	286	✓				Vented	288	47	25	22.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C180 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C180 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200 CGI KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C200 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C200 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C230 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C230	01/05 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C240	03/01 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C240 4-MATIC	03/01 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C280	01/05 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C280 4-MATIC	01/05 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C320	03/01 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C320 4-MATIC	03/01 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C200 CDI	03/01 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
C220 CDI	03/01 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
C270 CDI	03/01 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MERCEDES BENZ - 4WD / SUV

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

CL203

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
C160 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C180 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200 CGI KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C230 KOMPRESSOR	05/02 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C180	03/01 - 05/02	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C200 KOMPRESSOR	03/01 - 05/02	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C230	01/05 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C230 KOMPRESSOR	03/01 - 05/02	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C320	09/02 - ON	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5
C200 CDI	03/01 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
C220 CDI	03/01 - ON	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5

C203

CLK200	06/97 - 06/02	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
CLK200 KOMPRESSOR	06/97 - 06/02	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
CLK230 KOMPRESSOR	06/97 - 06/02	F	286	✓				Vented	288	47	25	22.4	67	5
		R	287	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	7.3	67	5
CLK320	06/97 - 06/02	F	288	✓				Vented	300	47	28	25.4	67	5
		R	289	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	8.3	67	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
A208														
CLK200	03/98 - 03/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
CLK200 KOMPRESSOR	03/98 - 03/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
CLK230 KOMPRESSOR	03/98 - 03/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
CLK320	03/98 - 03/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
C208 / 209														
CLK200 CGI	09/02 - on	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
CLK200 KOMPRESSOR	09/02 - on	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
CLK240	06/02 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
CLK320	06/02 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
CLK270 CDI	10/02 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
A209														
CLK200 CGI	02/03 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
CLK200 KOMPRESSOR	02/03 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
CLK240	02/03 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
CLK320	02/03 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5
W210														
E200	6/95 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E200 D	6/95 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E200 CDI	1998 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**289**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	54	10	**8.3**	67	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MERCEDES BENZ

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

W210 - continued

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
E200 KOMPRESSOR (120Kw)	2000 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E200 KOMPRESSOR (137Kw)	1997 - 3/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E220 D	6/95 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E220 CDI	1998 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E230	6/95 - 97	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E240 V6	1997 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E240 V6 w/ ESP	1997 - 3/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E250 D	6/95 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E250 TD	6/95 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E270 CDI	1999 - 3/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E280	1996 - 3/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E280 4-MATIC	1997 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E290 TD	1996 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E300 D	6/95 - 3/02	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E300 TD	1996 - 99	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E320	6/95 - 3/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E320 CDI	1999 - 3/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5
E320 4-Matic	1997 - 3/02	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**289**	✓				Solid	290	54	10	**8.3**	67	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MERCEDES BENZ

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
S210														
E200	5/96 - 00	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
E200 KOMPRESSOR (120Kw)	2000 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E200 KOMPRESSOR (137Kw)	1997 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E220 CDI (Short Wheelbase)	1998 - 3/03	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
E220 CDI (Long Wheelbase)	1998 - 3/03	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
E240 V6	1997 - 3/03	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
E240 V6 w/ ESP	1997 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E250 D (Short Wheelbase)	5/96 - 99	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
E250 D (Long Wheelbase)	5/96 - 99	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
E270 CDI	1999 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E280	1997 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E280 4-MATIC	1997 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E290 TD (Short Wheelbase)	1996 - 99	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
E290 TD (Long Wheelbase)	1996 - 99	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
E300 TD	1996 - 99	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E320	1997 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E320 CDI	1999 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
E320 4-Matic	1997 - 3/03	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
R170														
SLK 200	1996 - 00	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
SLK 200 KOMPRESSOR	1996 - 2/04	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
SLK 230 KOMPRESSOR	1996 - 2/04	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
SLK 320	2000 - 2/04	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
R171														
SLK 200 KOMPRESSOR	3/04 - on	F	**286**	✓				Vented	288	47	25	**22.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
SLK 280	2005 - on	F	**288**	✓				Vented	300	47	28	**25.4**	67	5
		R	**287**	PART NOT AVAILABLE REFERENCE ONLY				Solid	278	55	9	**7.3**	67	5
G - CLASS - 4WD														
G500 4Dr 5.0L V8 SOHC	2002 - 03	F	**2250**	✓		✓		Vented	315	83	30	**27.4**	85	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MERCEDES BENZ

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
M - CLASS (W163 & W16														
ML 230	1998 - 00	F	**550**	✓				Vented	303	51	26	**23**	67	5
ML 270 Turbo Diesel	1999 - 01	R	**551**	✓				Solid	285	53	15	**13**	67	5
(ch.>A289558)														
ML 320 V6 (ch.>A289558)	1998 - 01													
ML 270 Turbo Diesel	2002 - 03/05	F	**552**	✓		✓		Vented	345	51	32	**30**	67	5
(ch.A289559>)		R	**553**	✓		✓		Solid	331	55.5	14	**12**	67	5
ML 320 V6 (ch.A289559>)	2002 - 03/05													
ML 400 Turbo Diesel	2001 - 03/05	F	**552**	✓		✓		Vented	345	51	32	**30**	67	5
ML 430 V8	1998 - 01													
ML 500 4WD Luxury V8	2001 - 03/05	R	**553**	✓		✓		Solid	331	55.5	14	**12**	67	5
ML 55 AMG 4WD V8	1999 - 03/05													
ML 280, 320, 350 (W164)	4/05 - on	F	**2252**					Vented	330	55	32	**29.4**	67	5
		R	**2253**					Solid	330	63	14	**11.4**	67	5
ML 420, 500 (W164)	4/05 - on	F	**2254**					Vented	350	55	32	**29.4**	67	5
ML 63 AMG (W164)	1/06 - on	R	**2255**					Vented	330	63	22	**19.4**	67	5
MB100 / MB140														
MB100, MB100D - Van	11/99 - 03	F	**2266**	✓				Vented	294	68.5	24	**22**	85	5
MB100D 2.9 Van	12/01 - 03													
MB140, MB140D - Van	11/99 - 03													
R - CLASS														
R 280, R 320, R 350	1/06 - on	F	**2252**					Vented	330	55	32	**29.4**	67	5
R 500, R 63 AMG	1/06 - on	F	**2254**					Vented	350	55	32	**29.4**	67	5
Solid Rear 14mm Thick	1/06 - on	R	**2253**					Solid	330	63	14	**11.4**	67	5
Vented Rear 22mm Thick	1/06 - on	R	**2255**					Vented	330	63	22	**19.4**	67	5
SPRINTER														
All models	1995 - 5/06	F	**566**	✓				Vented	276	77	22	**19.5**	85	5
Rear 12mm Thick		R	**2267**					Solid	258	96.5	12	**10**	85	5
Rear 16mm Thick		R	**567**					Solid	272	97	16	**14**	85	5
Rear 22mm Thick		R	**2268**					Vented	285	93	22	**19**	120	6
3T, 3.5T	6/06 - on	F	**2270**					Vented	299.5	68.5	28	**25**	85	6
		R	**2269**					Solid	298	71.5	16	**14**	85	6
5T	6/06 - on	F	**2270**					Vented	299.5	68.5	28	**25**	85	6
VITO														
108D, 110D, 113D	1999 - 9/03	F	**564**	✓				Vented	276	60	22	**19.5**	67	5
112		R	**565**	✓				Solid	280	63	10	**8.5**	67	5

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MG

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MG Midget Mk I-II MG Midget Mk III	1963 - 67 1967 - 72	F	**060**	✓				Solid (Wire Wheels)	209.8	39.5	7.5	**7**	63.5	4
MG Midget Mk I-II MG Midget Mk III	1963 - 67 1967 - 72	F	**061**	✓				Solid (Disc Wheels)	209.8	60	7.7	**7**	63	4
MG B, GT MG B Mk II, GT Mk II	1962 - 66 1967 - 72	F	**062**	✓				Solid	273.4	44.5	8.7	**7.6**	73	4
MGF	1995 - 02	F	**063**	✓				Vented	240	44	22	**20**	66	4
		R	**064**	✓				Solid	240	44	10	**8.5**	66	4

MINI - COOPER

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Mini Moke California DB815 Pads	1971 - 73	F	**079**	PART NOT AVAILABLE REFERENCE ONLY				Solid	213	61	10	**8.5**	55	4
Mini Cooper S Mini Clubman, GT	1964 - 67 1970 - 73	F	**081**	PART NOT AVAILABLE REFERENCE ONLY				Solid	190	77.5	9.5	**8.5**	73.5	4

MINI COOPER - R50

COUPE W10 Eng. COUPE ONE 1.4d W17 Eng. COUPE ONE 1.4i W10 Eng. COUPE ONE 1.6i W10 Eng.	9/00 - on 6/02 - on 2/02 - on 9/00 - on	F	**542**	✓		✓		Vented	276	44	22	**19**	64	4
		R	**543**	✓		✓		Solid	259	44	10	**8.4**	64	4

MINI COOPER - R52 CONVERTIBLE

COOPER S W11 Eng. COOPER W10 Eng. CONVERTIBLE ONE 1.4i	11/02 - on 11/02 - on 2/02 - on	F	**542**	✓		✓		Vented	276	44	22	**19**	64	4
		R	**543**	✓		✓		Solid	259	44	10	**8.4**	64	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MINI - COOPER

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MINI COOPER - R53

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
COUPE COOPER S W11 Eng.	9/00 - on	F	**542**	✓		✓		Vented	276	44	22	**19**	64	4
		R	**543**	✓		✓		Solid	259	44	10	**8.4**	64	4

MINI COOPER - R56

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	A	B	C	D	E	F
COUPE & CLUBMAN	10/05 - on	F	**2526**	✓		✓		Vented	280	44	22	**20.4**	64	4
N12 Eng. exc. JCW upgrade		R	**543**	✓		✓		Solid	259	44	10	**8.4**	64	4
COOPER S inc. CLUBMAN	10/05 - on	F	**2524**	✓		✓		Vented	294	44	22	**20.4**	64	4
N14 Eng. exc. JCW upgrade		R	**543**	✓		✓		Solid	259	44	10	**8.4**	64	4
JOHN COOPER WORKS	2007 - on	F	**2528**	✓		✓		Vented	316	45	22	**20.4**	64	4
Coupe & Clubman		R	**2529**	✓		✓		Solid	280	44	10	**8.4**	64	4

MINI COOPER - 2 PIECE UPGRADE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	A	B	C	D	E	F
COOPER, COOPER S Replacement for Brembo Gran Turismo Big Brake System 5000 series 2-piece assembled	2003	F	**52525**				✓	Vented	320	48.5	28	**27**	64	4

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

MITSUBISHI

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
3000 GT														
JF	10/92 - 5/94	F	**213**	✓		✓		Vented	296	45.2	30	**28.4**	69	5
		R	**214**	✓		✓		Vented	284	52.8	20	**18.4**	90	5
3000 GT	5/94 - on	F	**216**	✓		✓		Vented	314	45.5	30	**28.4**	69	5
		R	**217**	✓		✓		Vented	297	50.5	20	**18.4**	90	5
3000 GT. GT-SL, GT-VR4 (USA)														
GT & GT-SL	4/90 - 95	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
		R	**423**	✓				Vented	266	65.5	18	**16.4**	90	5
GT-VR4	1990 - 5/93	F	**213**	✓		✓		Vented	296	45.2	30	**28.4**	69	5
		R	**214**	✓		✓		Vented	284	52.8	20	**18.4**	90	5
GT-VR4	6/93 - 99	F	**216**	✓		✓		Vented	314	45.5	30	**28.4**	69	5
		R	**217**	✓		✓		Vented	297	50.5	20	**18.4**	90	5
380														
ES, SX, VRX, LX, GT	2005 - on	F	**2206**	✓		✓		Vented	294	46	28	**26.4**	69	5
		R	**2207**	✓		✓		Vented	302	59.2	18	**16.4**	69	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MITSUBISHI

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
COLT														
RA, RB, RC, RD, RE	1980 - 6/90	F	**215**	✓				Solid	228	40	13	**11.4**	86	4
CORDIA														
AA, AB Non Turbo	4/83 - 11/85	F	**227**	✓				Solid	243	34.5	13	**11.4**	86	4
AC Non Turbo AA, AB Turbo	12/85 - 7/89 5/84 - 11/85	F	**219**	✓				Vented	242	34.5	18	**16.4**	86	4
AC Turbo	12/85 - 7/89	F	**409**	✓				Vented	266	34	24	**22.4**	86	4
FTO / ECLIPSE 1.8LITRE: 2.0LITRE														
1.8GS + 2.0L 14 inch wheels	9/94 - 9/97	F	**411B**	✓				Vented	256	45	24	**22.4**	69	5
2.0L Mivec V6 15 inch wheels	9/94 - 9/97	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
1.8GS + 2.0L 14 inch wheels	10/97 - 8/00	F	**421**	✓				Vented	256	45.2	24	**22.4**	69	5
All models	9/94 - 8/00	R	**547**	PART NOT AVAILABLE REFERENCE ONLY				Solid	260	41	10	**8.4**	90	5
Eclipse Turbo 2WD	1/1994 - 98	R	**2203**	✓				Solid	262	60	10	**8.4**	90	5
GALANT														
GA, GB DB1026 Pads	1971 - 74	F	**209**	PART NOT AVAILABLE REFERENCE ONLY				Solid	239	46	10	**8.4**	67	4
GC, GD	1974 - 77	F	**210**	✓				Solid	229	30	13	**11.4**	67	4
HG	5/89 - 8/90	F	**221**	✓				Vented	265	45.5	24	**22.4**	69	4
HH - Except VR4 Turbo	9/90 - 93	F	**411**	✓				Vented	256	45	24	**22.4**	69	4
HH5 VR4 Turbo	9/90 - 93	F	**402**	✓		✓		Vented	276	45	24	**22.4**	69	4
HG, HH	5/89 - 93	R	**403**	✓				Solid	265	49	10	**8.4**	90	4
HJ	1994 - on	F	**411**	✓				Vented	256	45	24	**22.4**	69	4
		R	**404**	✓				Solid	262	60	10	**8.4**	90	4

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

MITSUBISHI

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LANCER														
LA, LB, LC	1974 - 81	F	**210**	✓				Solid	229	30	13	**11.4**	67	4
CA	1988 - 8/90	F	**219**	✓				Vented	242	34.5	18	**16.4**	86	4
CB 1, 2, 3, 4 1.5 Litre	9/90 - 93	F	**412**	✓				Vented	236	34	18	**16.4**	86	4
CC GSR Turbo Sedan	10/92 - on	F	**411**	✓				Vented	256	45	24	**22.4**	69	4
		R	**406**	✓				Solid	260	41	10	**8.4**	90	4
CB 1.5 & 1.6L GSR	90 - 10/92	F	**407**	PART NOT AVAILABLE REFERENCE ONLY				Vented	256	34	24	**22.4**	86	4
		R	**403**	✓				Solid	265	49	10.1	**8.4**	90	4
CC (Hatch 1.5 Litre)	10/92 - 02	F	**412**	✓				Vented	236	34	18	**16.4**	86	4
CE 1.5 & 1.8 Litre CC 1.8L Coupe CC Sedan/Wagon	10/92 - 02	F	**413**	✓				Vented	235	45	18	**16.4**	64	4
CC 1.5 Litre	10/92 - 02	F	**408**	✓				Solid	235	45	13	**11.4**	64	4
CG 2.0L 14-inch wheels CH 2.0L 14-inch wheels	2/2002 - 03 7/2003 - 05	F	**2200**	✓				Vented	256	45	24	**22.4**	64	4
CH VR-X 2.0L 15-inch wheels	7/2003 - 05	F	**2201**	✓				Vented	276	45.5	26	**24.4**	69	5
CH 2.4L all models	2006 - 08	R	**2203**	✓				Solid	262	60	10	**8.4**	90	5
CJ Saloon + Sportback	03/2008 - on	F	**2201**	✓				Vented	276	45.5	26	**24.4**	69	5
(non-turbo) excl. VRX/Ralliart		R	**2209**	✓				Solid	262	60	10	**8.4**	80	5
CJ Ralliart	2008 - 3/09	F	**417**	✓		✓	✓	Vented	294	46	24	**22.4**	69	5
EVOLUTION (LANCER)														
EVO I, II, III	1993 - 95	F	**402**	✓		✓		Vented	276	45	24	**22.4**	69	4
* Check Dimensions *		R	**406**	✓				Solid	260	41	10	**8.4**	90	4
EVO IV, V, VI - RS models Eng:4G63 15 inch wheels	1996 - on	F	**4428**			✓		Vented	276	45.5	24	**22.4**	69	5
suits 2-pot calipers		R	**429**	✓		✓		Vented	284	60.2	20	**18.4**	90	5
EVO IV GSR Eng:4G63 16 inch wheels	1996	F	**417**	✓		✓	✓	Vented	294	46	24	**22.4**	69	5
		R	**419**	✓		✓		Vented	300	58	22	**20**	90	5
EVO V, VI, VII, VIII, IX GSR & RS-2	1996 - 08	F	**4418**			✓		Vented	320	43.5	32	**29.8**	69	5
Eng:4G63 17 inch wheels		F	**52218**				✓	Vented	320	43.5	32	**29.8**	69	5
suits 4-pot Brembo calipers		F	**5418**				This part number now supersedes to 52218 replacement rotors for owners of 5418 are still available and the part number is 5418.1							
		R	**419**	✓		✓		Vented	300	57	22	**20**	90	5
EVO X incl MR models	2008 - 2010	F	**42224**			✓	✓	Vented	350	44	32	**30**	69	5
		R	**42225**			✓		Vented	330	59	22	**20**	80	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

MITSUBISHI

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MAGNA														
TM, TN, TP	1985 - 91	F	**221**	✓				Vented	266	45.5	24	**22.4**	69	4
		R	**222**	✓				Solid	251	49	10	**8.4**	HUB	4
TN, TP Wagon Only	7/87 - 92	R	**223**	✓				Solid	276	84	10	**8.4**	HUB	4
TR, TS - 4 Cyl models only Except TR 4cyl with an 'X' in the chassis no. - Manf. up to 8/92	4/91 - on	F	**421**	✓				Vented	256	45.2	24	**22.4**	69	5
TR 4 cyl with an 'X' in the chassis no.	up to 8/92	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
TR, TSV6 Non ABS models	1993 - on	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
TR, TS V6 ABS models only	1993 - on	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
TR, TS 4 Cyl + V6 Non ABS	4/91 - on	R	**422**	✓				Solid	258	66	10.4	**8.4**	90	5
TS V6 Sedan ABS	3/94 - on	R	**423**	✓				Vented	266	65.5	18	**16.4**	90	5
TS V6 Wagon ABS	3/94 - on	R	**427**	PART NOT AVAILABLE REFERENCE ONLY				Vented	284	65.5	20	**18.4**	90	5
TE 4 Cyl, V6	4/96 - on	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
ABS & non ABS		R	**426**	✓				Solid	258	56.5	10.5	**8.4**	90	5
TF, TH, TJ, VR-X, Sports V6	6/97 - on	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
TL (ES, LS, VR, VR-X) V6		R	**426**	✓				Solid	258	56.5	10.5	**8.4**	90	5
TJ (II) AWD V6	1/2003 - on	F	**417**	✓		✓		Vented	294	46	24	**22.4**	69	5
TL AWD V6	8/2003 - on	R	**429**	✓		✓		Vented	284	60.2	20	**18.4**	90	5
TJ Ralliart	2002 - 03	R	**42429**			✓		Vented	284	57	20	**18.4**	90	5
MIRAGE / SPACE STAR														
CE 1.5 Litre	7/96 - on	F	**413**	✓				Vented	235	45	18	**16.4**	64	4
NIMBUS / SPACEWAGON / CHARIOT GRANDIS														
UA, UB, UC	1984 - 91	F	**219**	✓				Vented	242	34.5	18	**16.4**	86	4
UF 2.4 Litre	1/92 - 98	F	**411**	✓				Vented	256	45.3	24	**22.4**	69	4
UG	7/98 - 2001	F	**437**	✓				Vented	276	45.5	24	**22.4**	69	5
		R	**429**	✓		✓		Vented	284	60.2	20	**18**	90	5

DBA DISC BRAKES AUSTRALIA ™

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

MITSUBISHI

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SCORPION														
GE, GH, GJ, GK, GL	1978 - 84	F	**211**	PART NOT AVAILABLE REFERENCE ONLY				Solid	255	28	12.5	**11**	80	4
		R	**212**	PART NOT AVAILABLE REFERENCE ONLY				Solid	247	48	10	**8.4**	90	4
SIGMA														
GE 1.6, 2.0, 2.6	1978 - 80	F	**210**	✓				Solid	229	30	13	**11.4**	67	4
GH, GJ, GK, GN	1980 - 87	F	**205**	✓				Solid	256	32.5	13	**11.5**	80	4
		R	**207**	✓				Solid	280	73	10.5	**8.8**	68	4
STARION														
JA, JB, JD	5/82 - 8/87	F	**400**	PART NOT AVAILABLE REFERENCE ONLY				Vented	256	36	24	**22.4**	80	4
		R	**401**	PART NOT AVAILABLE REFERENCE ONLY				Vented	247	47.5	18	**16.4**	90	4
VERADA / DIAMANTE														
KR, KS V6 ABS & non-ABS	8/91 - on	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
KR, KS V6 non-ABS	8/91 - on	R	**422**	✓				Solid	258	66	10.4	**8.4**	90	5
KR, KS V6 Sedan with ABS	3/94 - on	R	**423**	✓				Vented	266	65.5	18	**16.4**	90	5
KS V6 Wagon with ABS	3/94 - on	R	**427**	PART NOT AVAILABLE REFERENCE ONLY				Vented	284	65.5	20	**18.4**	90	5
KE	10/96 - 6/97	F	**425**	✓		✓		Vented	276	45	24	**22.4**	69	5
KF, KJ 2.4, 3.0, 3.5 Litre	6/97 - on													
KL (Ei, GTVi, Xi) V6	1/2003 - on	R	**426**	✓				Solid	258	56.5	10.5	**8.4**	90	5
KJ (II) AWD V6	1/2003 - on	F	**417**	✓		✓		Vented	294	46	24	**22.4**	69	5
KL AWD V6	8/2003 - on	R	**429**	✓		✓		Vented	284	60.2	20	**18.4**	90	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MITSUBISHI - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CANTER														
CANTER 4.0DT FE659	1996 - on	F	**2220**	✓				Vented	310	55	40		114	6
		R	**2221**	✓				Vented	310	70	40		139	12
CHALLENGER														
Challenger (PA) 3.0L V6	12/97 - on	F	**663**	✓		✓		Vented	276	45.3	24	**22.4**	87	6
XS, LS - Door Wagon		R	**233**	✓				Solid	315	84	18	**16.4**	108	6
EXPRESS														
SJ 2.4 Litre	12/94 - on	F	**229**	✓				Vented	276	45.5	22	**20.4**	87	6
SJ 2.0/2.5	12/94 - on	F	**230**	✓				Vented	258	33.5	22	**20.4**	84	5
L200 - LATER MODELS, SEE TRITON														
MA, MB, MC, MD - 2WD	1981 - 86	F	**220**	✓				Solid	255	34	20	**18.4**	84	6
MA, MC, MD - 4WD	1981 - 86	F	**228**	✓				Vented	255	45	20	**18.4**	87	6
L200 2.5L 2WD Diesel		F	**218**	PART NOT AVAILABLE REFERENCE ONLY				Vented	254	39	24	**22.4**	87	6
L300														
SA	1980 - 82	F	**225**	✓				Vented	232	29.5	20	**18.4**	84	5
SB, SC, SD, SE	1982 - 9/86	F	**226**	✓				Vented	255	34	20	**18.4**	84	5
SF, SG, SH, SJ 2WD	10/86 - on	F	**230**	✓				Vented	258	33.5	22	**20.4**	84	5
SC, SD, SE 4WD	1983 - 9/86	F	**228**	✓				Vented	255	45	20	**18.4**	87	6
SF, SG, SH, SJ 4WD	10/86 - on	F	**229**	✓				Vented	276	45.5	22	**20.4**	87	6
WA LWB 2.4L	9/94 - on	F	**208**	✓				Vented	254	39	24	**22.4**	87	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MITSUBISHI - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
OUTLANDER / AIRTREK														
ZE 2S45 AWD	2002 - on	F	**2201**	4x4				Vented	276	45.5	26	**24.4**	69	5
PAJERO / SHOGUN														
NA, NB, NC, ND SWB	1983 - 9/87	F	**228**	4x4				Vented	255	45	20	**18.4**	87	6
NA, NB, NC, ND LWB	1983 - 9/87	F	**224**	4x4				Vented	275	45	20	**18.4**	87	6
NE, NF, NG, NH SWB NE, NF, NG, NH LWB	10/87 - 92	F	**232**	4x4				Vented	258	45	22	**20.4**	87	6
NF, NG, NH V6 LWB	9/88 - 92	F	**229**	4x4				Vented	276	45.5	22	**20.4**	87	6
NH, NJ V6 SOHC NJ V6 DOHC	1992 - on 1992 - on	F	**234**	4x4				Vented Check Bolt Holes - use **DBA-234T** if holes are tapped/threaded	276	45	24	**22.4**	87	6
NJ 3.5L	12/93 - on	F	**236**	4x4				Vented	276	45.3	27	**25.4**	87	6
NF, NG, NH, NJ	5/91 - 94	R	**233**	4x4				Solid	315	84	18	**16.4**	108	6
NK 2.8L & 3.0L 15" Wheels	11/96 - 9/97	F	**234**	4x4				Vented Check Bolt Holes - use **DBA-234T** if holes are tapped/threaded	276	45	24	**22.4**	87	6
NK 3.5L	6/96 - on	F	**236**	4x4				Vented	276	45.3	27	**25.4**	87	6
All NK Rears	6/96 - on	R	**233**	4x4				Solid	315	84	18	**16.4**	108	6
NL 2.8L 15" Wheels	6/96 - on	F	**234**	4x4				Vented Check Bolt Holes - use **DBA-234T** if holes are tapped/threaded	276	45	24	**22.4**	87	6
NL GLX 3.5L 15" Wheels	6/96 - on	F	**236**	4x4				Vented	276	45.3	27	**25.4**	87	6
NL GLS 3.5L & NK 3.5L 16",18" Wheels	6/96 - on	F	**237**	4x4				Vented	314	45.5	24	**22.4**	87	6
All NL Rears	6/96 - on	R	**233**	4x4				Solid	315	84	18	**16.4**	108	6
NL o/seas only	6/96 - on	R	**238**	4x4				Solid	323	76	10	**8**	93.5	6
iO Series (QA)	1999 - on	F	**239**	4x4				Vented	286	39	22	**20**	69	5
NM 3.2L T/Diesel, 3.5L V6 NP 3.2L T/Diesel, 3.5L V6	5/2000 - 02 11/02 - 06	F	**660**	4x4		4x4		Vented	290	46	26	**24.4**	94	6
Shogun 2.8DT 3.2DT, 3.5i		R	**661**	4x4		4x4		Vented	300	72	22	**20.4**	94	6
NS 3.8L V6 Petrol	2006 - on	F	**660**	4x4		4x4		Vented	290	46	26	**24.4**	94	6
NS 3.2L Turbo Diesel		F	**2216**	4x4	4x4	4x4		Vented	332	56.7	28	**26**	94	6
Rear All Models		R	**2219**	4x4	4x4	4x4		Vented	332	74.6	18	**16**	94	6

SPECIAL NOTE: NL REARS - CHECK DIMENSIONS

ROSA BUS

NS 3.8L V6 Petrol	2006 - on	F	**2222**	✓				Vented	293	54	40	**37.7**	110	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MITSUBISHI - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
STARWAGON / DELICA SPACE GEAR / LZ6460 FUTURE														
WA	9/94 - on	F	**208**	✓				Vented	254	39	24	**22.4**	87	5
SF, SG, SH 2WD	10/86 - 8/94	F	**230**	✓				Vented	258	33.5	22	**20.4**	84	5
SF, SG, SH 4WD	10/86 - 8/94	F	**229**	✓				Vented	277	45.5	22	**20.4**	87	6
SJ Satellite	9/95 - on	F	**230**	✓				Vented	258	33.5	22	**20.4**	84	5
TRITON														
ME, MF, MG, MH, MJ 2WD	1986 - on	F	**231**	✓				Vented	258	33.5	22	**20.4**	84	6
ME, MF, MG, MH, MJ 4WD	1986 - on	F	**229**	✓				Vented	276	45.5	22	**20.4**	87	6
MJ 4X2	12/94 -10/96	F	**231**	✓				Vented	258	33.5	22	**20.4**	84	6
MJ 4X4	12/94 -10/96	F	**229**	✓				Vented	276	45.5	22	**20.4**	87	6
MK 4X2 14inch all except 3.0L V6	10/96 - on	F	**662**	✓				Vented	254	39	24	**22.4**	87	6
MK 4X2 15inch MK 4X4 3.0L V6 GLX	10/96 - on	F	**663**	4x4		4x4		Vented	276	45.3	24	**22.4**	87	6
MK 4X4 16inch GLS	6/01 - on	F	**237**	4x4				Vented	314	45.5	24	**22.4**	87	6
ML 4x2, 4x4 all models	2007 - on	F	**2208**	4x4		4x4		Vented	295	46.5	28	**26.4**	94	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

MORRIS - AUSTIN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Austin 1800 Mk 1, 2, 3	1964 - 75	F	**080**	PART NOT AVAILABLE REFERENCE ONLY				Solid	236	79	12.5	**11.5**	73	5
Morris 1100 Mk 1, 2	1963 - 67	F	**082**	PART NOT AVAILABLE REFERENCE ONLY				Solid	203	61	7.7	**7.3**	55	4
Morris 1100 Mk 2, 3 Morris 1300 (All Models)	1968 - 74 1967 - 74	F	**083**	✓				Solid	214	61.5	11	**10.1**	55	4
Morris Marina 1300, 1800	1971 - 80	F	**084**	✓				Solid	248	46	9.5	**8.6**	66	4

AUSTIN HEALEY

Sprite Mk II-III (1100) Sprite Mk IV (1275)	1962 - 71	F	**060**	✓				Solid	209.8	39.5	7.5	**7**	63.5	4
Sprite Mk II-III (1100) Sprite Mk IV (1275)	1962 - 71	F	**061**	✓				Solid	209.8	60	7.7	**7.3**	63	4
3000 Mk II-III 3 LITRE	1960 - 68	F	**094B**	PART NOT AVAILABLE REFERENCE ONLY				Solid	281	38	12.7	**11.4**	82.6	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

NISSAN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
1200 / 120Y														
B110 1200 B210 120Y	1970 - 4/74 3/74 - 11/75	F	**314**	PART NOT AVAILABLE REFERENCE ONLY				Solid	212	35.6	9.5	**8.4**	70	4
B210 120Y	12/75 - 3/79	F	**310**	✓				Solid	219	32.5	9.6	**8.6**	70	4
1600, 180B														
510 1600 all models 610 180B all models	1968 - 9/72 9/72 - 8/74	F	**306**	✓				Solid Small Stub Axle	232	40	10	**8.4**	68	4
610 180B all models	9/74 - 8/78	F	**307**	✓				Solid Large Stub Axle	245	35.5	10	**8.4**	73	4
610 Sedan *Rare Model * Check Dimensions	8/73 - 9/77	F	**308**	✓				Solid	232	35	10	**8.5**	73	4
180SX														
RS13 (180SX) 1.8L Turbo	1989 - 1/91	F	**918**	✓				Vented	250	49	18	**16**	68	4
		R	**904**	✓				Solid	258	46.5	9	**8**	68	4
RS13 (180SX) 2.0L Turbo	1/91 - on	F	**919**	✓				Vented	280	49	22	**20**	68	4
		R	**904**	✓				Solid	258	46.5	9	**8**	68	4
200B														
810 Local 810 Import	10/77 - 7/79 1980 - 81	F	**315**	PART NOT AVAILABLE REFERENCE ONLY				Solid	253	48	12.7	**10.5**	73	4
810 Local (Girlock Brakes) DB1091 Pads	8/79 - 4/81	F	**326**	PART NOT AVAILABLE REFERENCE ONLY				Solid	244	43.6	12.7	**10.5**	73	4
200SX														
S14	8/94 - on	F	**909**	✓		✓		Vented	280	54	30	**28**	68	5
		R	**906**	✓		✓		Solid	258	47	9	**8**	68	5
S15	2000 - on	F	**909**	✓		✓		Vented	280	54	30	**28**	68	5
		R	**906**	✓		✓		Solid	258	47	9	**8**	68	5
240C														
230 all models	1971 - 73	F	**320**	PART NOT AVAILABLE REFERENCE ONLY				Solid	271	52	12.5	**10.5**	81	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

NISSAN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
240K														
C110 4D	12/72 - 11/75	F	**306**	✓				Solid	232	41	10	**8.5**	68	4
C110 4D	12/75 - 78	F	**315**	PART NOT AVAILABLE REFERENCE ONLY				Solid	253	48	12.7	**10.5**	73	4
C110 2D	12/75 - 78	F	**316**	PART NOT AVAILABLE REFERENCE ONLY				Solid	270	48	12.5	**10.5**	73	4
240Z														
240Z S30	1970 - 73	F	**324**	PART NOT AVAILABLE REFERENCE ONLY				Solid	271	52	12.7	**10.5**	81	4
260C														
230 all models	2/73 - 10/75	F	**320**	PART NOT AVAILABLE REFERENCE ONLY				Solid	271	52	12.5	**10.5**	81	5
330 all models	11/75 - 80	F	**321**	PART NOT AVAILABLE REFERENCE ONLY				Solid	271	43.5	12.5	**10.5**	81	5
260Z														
260Z S30	1973 - 78	F	**325**	PART NOT AVAILABLE REFERENCE ONLY				Solid	271	43.5	12.7	**10.5**	81	4
280C														
330 & 430 all models	1978 - 9/80	F	**321**	PART NOT AVAILABLE REFERENCE ONLY				Solid	271	43.5	12.5	**10.5**	81	5
430 all models	10/80 - 84	F	**322**	✓				Vented	250	29	20	**18**	81	5
280ZX														
280ZX S130	2/79 - 5/84	F	**323**	PART NOT AVAILABLE REFERENCE ONLY				Vented	250	29	20	**18**	81	4
280ZX S130 (Check REAR)	2/79 - 8/81	R	**601**	PART NOT AVAILABLE REFERENCE ONLY				Solid	269	69	10	**8.6**	68	4
280ZX S130 (Check REAR)	9/81 - 4/84	R	**600**	✓				Solid	258	47	10	**9**	68	4
300C														
Y 30 all models	10/83 - 85	F	**613**	PART NOT AVAILABLE REFERENCE ONLY				Vented	250	53	22	**20**	HUB	5
		R	**905**	PART NOT AVAILABLE REFERENCE ONLY				Solid	266	69	10	**9**	73	5
300ZX														
300ZX All Z31 Models	1/84 - 9/85	F	**608**	PART NOT AVAILABLE REFERENCE ONLY				Vented	274	35.5	22	**20**	81	4
		R	**605**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	47	10	**9**	68	4
300ZX All Z31 Models ZR1, ZR2 (Jap Import) 300ZX non-turbo Z32	9/85 - 2/87 10/86 - on	F	**604**	PART NOT AVAILABLE REFERENCE ONLY				Vented	274	35.5	22	**20**	81	5
Rear: ZR1, ZR2, ZX	10/85 -10/86	R	**607**	✓				Solid	290	47	10	**9**	68	5
300ZX All Z31 Models 300ZR (Jap Import)	2/87 - on 3/88 - on	F	**907**	✓				Vented	280	54	26	**24**	68	5
300ZX All Models	10/86 - on	R	**927**	✓				Vented	282	57.2	20	**18**	68	5
300ZX Z32 VG30DTT	1989 - 99	F	**909**	✓		✓		Vented	280	54	30	**28**	68	5
		R	**908**	✓		✓		Vented	297	63	18	**16**	68	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

dba™
DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

NISSAN - 350Z / 370Z

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
350Z														
350Z 3.5L V6 (Touring model)	2003 - 05	F	**954**	✓		✓		Vented	296	49.2	24	**22**	68	5
		R	**574**	✓		✓		Vented	292	62	16	**14**	68	5
350Z 3.5L V6 (17" Wheels)	10/05 - on	F	**2308**	✓		✓		Vented	320	49.7	28	**26**	68	5
		R	**2309**	✓		✓		Vented	308	62.5	16	**14**	68	5
350Z 3.5L V6 (Track model) Brembo 4-pot front brake caliper	2003 - on	F	**4600**			✓	✓	Vented	324	49	30	**28**	68	5
Brembo 2-pot rear brake caliper		R	**4601**			✓		Vented	322	62.5	22	**20.2**	68	5
370Z														
3.7L V6 (Brembo calipers)	2008 - on	F	**2314**	✓		✓	✓	Vented	354.6	49.5	32	**30**	68	5
		R	**2315**	✓		✓		Vented	350	62	20	**18**	68	5
BLUEBIRD														
910 All Models	1981 - 86	F	**609**	✓				Solid	250	43	12	**10.5**	HUB	4
		R	**611**	✓				Solid	280	77	10.5	**9.5**	68	4
U13	7/93 - 3/97	F	**903**	✓				Vented	280	49.2	22	**20**	68	4
		R	**614**	✓				Solid	258	45	10	**8**	68	4
FAIRLADY														
Fairlady 311, 2000 Sport	1966 - 71	F	**610**	✓				Solid	284	44.5	10.4	**9.4**	76	4
GAZELLE														
S12 All Models	1984 - 88	F	**612**	✓				Vented	250	22	18	**16**	73	4
EXA - TWIN CAM - KN13														
KN13 EXA 1.6L	2/87 - 91	F	**603**	✓				Vented	240	45.5	18	**16**	61	4
KN13 EXA 1.8L	1988 - 91	F	**628**	✓				Vented	250	45	18	**16**	61	4
All Rears	5/87 - 91	R	**606**	✓				Solid	234	481	10	**9**	HUB	4
GT-R (R35 MY10) - REFER TO SKYLINE														
MAXIMA / CEFIRO														
J30 All Models	1990 -11/94	F	**910**	✓				Vented	280	49.3	22	**20**	68	5
	2/90 -10/92	R	**912**	✓				Solid	258	45	10	**9**	68	5
	10/92 -11/94	R	**925**	✓				Solid	258	44.5	9	**8**	68	5
A32 All Models	11/94 -10/99	F	**914**	✓				Vented	280	50	26	**24**	68	5
		R	**915**	✓				Solid	278	45	9	**8**	68	5
A33 6 cyl 3.0L	10/99 - 10/03	F	**914**	✓				Vented	280	50	26	**24**	68	5
		R	**915**	✓				Solid	278	45	9	**8**	68	5

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

NISSAN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MICRA / MARCH K11														
K11E All Models	5/95 - on	F	**920**	✓				Solid	234	45.5	12	**10**	59	4
		R	**921**					Solid	240	41	7	**6**	61	4
NX COUPE														
B13 2 Litre DOHC (ABS & non-ABS) Check disc diameter dimensions	10/91 - 94	F	**901**	✓	✓	✓		Vented	257	45	26	**24**	61	4
		R	**917**	✓	✓			Solid	234	40	7	**6**	68	4
PINTARA (BLUEBIRD)														
R31 All Models	1986 - 90	F	**615**	✓				Vented	250	48	22	**20**	HUB	4
		R	**616**	✓				Solid	260	60	10.4	**9.4**	68	4
U12 All Models	1989 - 92	F	**617**	✓				Vented	258	49	22	**20**	68	4
		R	**614**	✓				Solid	258	45	10	**8**	68	4
PRAIRIE														
M10 All Models	1982 - 86	F	**319**	✓				Vented	232	36.5	18.2	**16**	76	4
PULSAR N10														
A14 - E15 P.C.D. 96mm	1980 -11/82	F	**301**	✓				Solid	239	40	9.5	**8.6**	64	4
E13 P.C.D. 90mm	10/81-10/82	F	**305**	✓				Solid	239	40	9.5	**8.5**	64	4
PULSAR N12 & EXA - SINGLE CAM														
Import DB293 Pads	1982 - 5/87	F	**302**	✓				Solid	240	35.5	12	**11**	76	4
Local & ET DB1103 Pads	1983 - 5/87	F	**303**	✓				Solid	240	35.5	12	**11**	76	4
EXA Turbo	9/84 - 5/87	F	**319**	✓				Vented	232	36.5	18.2	**16**	76	4
Local & ET	1983 - 5/87	R	**304**	✓				Solid	235	36.5	10	**9**	HUB	4
PULSAR N13														
1.6 & 1.8 Litre Vector Sedan Model & Hatch	1987 - 91	F	**603**	✓				Vented	240	45.5	18	**16**	61	4
		R	**606**	✓				Solid	235	42	10	**9**	HUB	4

SPECIAL NOTE: DBA 614 and DBA 902 share the same dimensions (page 63) but have a different P.C.D. They are not interchangeable.

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

NISSAN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
PULSAR N14 - IMPORT & LOCAL														
1.6L	8/91 - 8/95	F	**628**	✓				Vented	250	45	18	**16**	61	4
		R	**917**					Solid	234	40	7	**6**	68	4
2.0L	10/91 - 8/95	F	**900**	✓				Vented	252	45	20	**18**	61	4
		R	**917**					Solid	234	40	7	**6**	68	4
GTi-R 2.0 Litre Turbo	10/90 - 1994	F	**901**	✓		✓		Vented	257	45	26	**24**	61	4
		R	**898**	PART NOT AVAILABLE REFERENCE ONLY				Solid	258	33	9	**8**	68	4
PULSAR N15 / ALMERA (UK)														
1.6L	8/95 - 00	F	**899**	✓				Vented	247	45	18	**16**	61	4
Almera 2.0D (UK)	1992 - 00	R	**917**					Solid	234	40	7	**6**	68	4
2.0L	8/95 - 00	F	**901**	✓				Vented	257	45	26	**24**	61	4
		R	**902**	✓				Solid	258	45	9	**8**	68	4
PULSAR N16 / ALMERA (UK)														
N16 Sedan 1.6L, 1.8L	6/00 - on	F	**2300**	✓				Vented	257	49	22	**20**	68	4
N16E Hatchback 1.8L	4/01 - on	F	**919**	✓				Vented	280	49	22	**20**	68	4
		R	**2303**	✓				Solid	257	45	10	**9**	68	4
Almera Tino (UK) 1.8L, 2.2L (112 &136)	2002 - on	R	**2301**	✓		✓		Solid	278	45	10	**9**	68	4
SERENA														
C23 2 Litre	9/92 - 97	F	**913**	PART NOT AVAILABLE REFERENCE ONLY				Vented	257	52	26	**24**	68	4
SILVIA														
S13 Eng: CA 18 DE	5/88 - on	F	**918**	✓				Vented	250	49	18	**16**	68	4
S13 Eng: CA 18 DT (Turbo)		R	**904**	✓				Solid	258	46.5	9	**8**	68	4
S13 Eng: SR 20 DE, DT,1.8L	1991 - on	F	**919**	✓				Vented	280	49	22	**20**	68	4
2.0L 2 x wheel steering only		R	**904**	✓				Solid	258	46.5	9	**8**	68	4
S13 Eng: SR 20 DE, DT 4 X wheel steering only	1992 - on	R	**904**	✓				Solid	258	46.5	9	**8**	68	4
S15 2.0L non-Turbo	1999 - 2/00	F					NOT AVAILABLE							
S15 2.0L TURBO	1999 - on	F	**909**	✓		✓		Vented	280	54	30	**28**	68	5
S15 (Rear) all models	1/99 - on	R	**906**	✓		✓		Solid	258	47	9	**8**	68	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

NISSAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SKYLINE														
C210	1978 - 80	F	**316**	PART NOT AVAILABLE REFERENCE ONLY				Solid	270	48	12.5	**10.5**	73	4
		R	**601**	PART NOT AVAILABLE REFERENCE ONLY				Solid	269	69	10	**8.6**	68	4
R30	1982 - 85	F	**317**	✓				Vented	250	43	18	**16**	HUB	4
R30 GTS FJ20DET	1982 - 85	F	**608**	PART NOT AVAILABLE REFERENCE ONLY				Vented	274	35.5	22	**20**	81	4
		R	**600**	✓				Solid	258	47	10	**9**	68	4
R31 Except GTS	1986 - 90	F	**615**	✓				Vented	250	48	22	**20**	HUB	4
R31 GTS Import & Local	1986 - 90	F	**924**	PART NOT AVAILABLE REFERENCE ONLY				Vented	274	47	22	**20**	68	4
		R	**616**	✓				Solid	260	60	10.4	**9.4**	68	4
R32T + R33 GTS-4 (4WD)		F	**953**	✓				Vented	280	49	26	**24.2**	68	4
R32 GTST 2.0L Eng:RB20DET	5/89 - 7/93	F	**909**	✓		✓		Vented	280	54	30	**28**	68	5
		R	**908**	✓		✓		Vented	297	63	18	**16**	68	5
R32 GT-R Eng:RB26DET	6/89 - 8/93	F	**4926**			✓		Vented	296	54	32	**30**	68	5
2.6L DOHC Twin-Turbo		R	**908**	✓		✓		Vented	297	63	18	**16**	68	5
R32 GT-R Eng:RB26DETT	8/93 - 12/94	F	**4928**			✓	✓	Vented	324	53.75	30	**28**	68	5
R33+R34 GT-R Eng:RB26DETT	1/95 - on													
Twin Turbo 2.6L V-SPEC		R	**929**	✓		✓		Vented	300	63	22	**20**	68	5
(fitted with Brembo Calipers)														
R33 GTST Eng:RB25DET	8/93 - 7/98	F	**4963**			✓		Vented	296	53.75	30	**28**	68	5
R34 GT Eng:RB25DE	8/98 - on	R	**908**	✓		✓		Vented	297	63	18	**16**	68	5
R34 GTT Eng:RB25DET	8/98 - on	F	**42304**			✓		Vented	310	53.75	30	**28**	68	5
2.5L Turbo		R	**908**	✓		✓		Vented	297	63	18	**16**	68	5
GT-R (R35 - MY10)														
3.8L Twin-Turbo	2009 - on	F	**52320**				✓	Vented	380	49.3	34	**32**	68	5
		R	**52321**				✓	Vented	380	62	30	**28**	68	5
Replacement for Original Brembo disc rotor only	2009 - on	F	**52322.1**				✓	Vented	380		34	**32**		
		R	**52323.1**				✓	Vented	380		30	**28**		
STANZA														
A10 Import	5/78 - 6/79	F	**307**	✓				Solid	245	35.5	10	**8.4**	73	4
A10 SSS Import	5/78 - 6/79	F	**308**	✓				Solid	232	35	10	**8.5**	73	4
Rare Model Check Dimensions														
A10 Local	up to - 6/79	F	**315**	PART NOT AVAILABLE REFERENCE ONLY				Solid	253	48	12.7	**10.5**	73	4
A10 Local Girlock Brakes	7/79 - 83	F	**326**	PART NOT AVAILABLE REFERENCE ONLY				Solid	244	43.6	12.7	**10.5**	73	4
SUNNY B310														
A12	1979 - 81	F	**310**	✓				Solid	219	32.5	9.6	**8.6**	70	4
A14, A15	1979 - 81	F	**307**	✓				Solid	245	35.5	10	**8.4**	73	4
2.0 Litre GTi	10/90 - 94	F	**901**	✓		✓		Vented	257	45	26	**24**	61	4
		R	**898**	PART NOT AVAILABLE REFERENCE ONLY				Solid	258	33	9	**8**	68	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

NISSAN - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ARMADA														
All models	2004 - 05	F	**2306**	4x4		4x4		Vented	319	43.5	26	**24.5**	82	6
		R	**2307**	4x4		4x4		Solid	319.5	58.5	14	**12**	82	6
CABSTAR														
PF22	1/82 -10/87	F	**313**	PART NOT AVAILABLE REFERENCE ONLY				Vented	260	29	20	**18**	81	6
DUALIS														
ST & Ti 2WD Hatch + AWD (J10, JJ10) 1.5, 2.0 DCi	02/07 - 2010	F	**2316**	✓				Vented	296	44	26	**24**	68	5
		R	**574**	✓		✓		Vented	292	62	16	**14**	68	5
FRONTIER														
6 cyl. - 2WD 4WD	4/99 - 02 1998 - 02	F	**624**	✓				Vented	277	39	26	**24**	100	6
all models - V6	2003 - 04	F	**626**	✓				Vented	283	38	28	**26**	100	6
MURANO														
ST, TI 3.5L V6	07/05 - on	F	**2308**	✓		✓		Vented	320	49.7	28	**26**	68	5
		R	**2313**	✓		✓		Vented	308	62.8	18	**16**	68	5
NAVARA D21 & D22 4X2														
D21 4X2 all except KA24E D22 4X2 TD27	9/85 - on 2/97 - 10/01	F	**620**	✓				Vented	250	37.5	22	**20**	81	6
D21 4X2 KA24E D22 4X2 Except TD27 D22 4X2 2.4L 4cyl DOHC D22 4X2 3.0L V6 SOHC	3/92 - on 2/97 - 10/01 12/2001 - on	F	**618**	✓				Vented	260	37.5	26	**24**	81	6
NAVARA D21 & D22 4X4														
D21 4X4	9/85 - 3/92	F	**621**	✓				Vented	266	39.5	22	**20**	100	6
D21 4X4	3/92 - on	F	**618**	✓				Vented	260	37.5	26	**24**	81	6
D22 4X4 - all models	1/97 - 4/01	F	**624**	4x4				Vented	277	39	26	**24**	100	6
D22 3.0L V6 SOHC 4X4 D22 3.0L 4cyl T/Dies 4X4 D22 3.3L V6 SOHC 4X4	10/01 - on 2/2003 - on	F	**629**	4x4				Vented	300	38	28	**26**	100	6
NAVARA D40 4X2, 4X4														
4X2, 4X4 16" wheels	05/05 - on	F	**2310**	4x4		4x4		Vented	295.6	38.3	28	**26**	68	6
4X2, 4X4 17" wheels	05/05 - on	F	**2312**	4x4		4x4		Vented	320	38.5	28	**26**	68	6

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

NISSAN - 4WD / SUV / VAN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
NOMAD														
GC 22 Van	1986 - 93	F	**627**	✓				Vented	250	30	22	**20**	73	4
PATHFINDER / TERRANO														
WD21 4 Cyl.	8/86 - 7/92	F	**621**	✓				Vented	266	39.5	22	**20**	100	6
WD21 V6	8/92 - on	F	**624**	✓				Vented	277	39	26	**24**	100	6
R50 All Models *	9/95 - 11/98	F	**626**	✓				Vented	283	38	28	**26**	100	6
R50 All Models * R50 Series III 3.3L V6	11/98 - 04	F	**629**	✓				Vented	300	38	28	**26**	100	6
R51 2.5L TD 16" wheels	2005 - on	F	**2310**	4x4		4x4		Vented	295.6	38.3	28	**26**	68	6
R51 4.0L V6 Petrol 17" wheels		R	**2311**	4x4		4x4		Vented	308	62.8	18	**16**	68	6
R51 2.5L TD 17" wheels	2005 - on	F	**2312**	4x4		4x4		Vented	320	38.5	28	**26**	68	6
R51 4.0L V6 Petrol 17" wheels		R	**2311**	4x4		4x4		Vented	308	62.8	18	**16**	68	6
PICK-UP / KINGCAB														
620 2WD 720 2WD	1979 80 - 12/82	F	**327**	PART NOT AVAILABLE REFERENCE ONLY				Solid	271	44	12.5	**10.5**	81	6
720 2WD	1/83 - 85	F	**311**	PART NOT AVAILABLE REFERENCE ONLY				Vented	250	30	22	**20**	81	6
720 4WD + Kingcab	1980 - 3/83	F	**328**	✓				Solid	271	60.5	12.5	**10.5**	104	6
720 4WD	4/83 - 85	F	**312**	✓				Vented	267	40	22	**20**	100	6
PATROL / SAFARI														
MQ 160, Classic 160 GQ Y60 non EFi Safari X60	1/81 - 12/87 1988 - on	F	**329**	4x4		4x4		Vented DB321 Pads	295	30	20	**18**	104	6
GQ Y60 EFI TB42E	2/92 - on	F	**623**	4x4				Vented	306	35.5	26	**24**	104	6
GQ Y60 ALL	1988 - on	R	**622**	4x4		4x4		Vented	315	80	18	**16**	111	6
GU (II) Y61 (DX, ST - Wagon)	10/97 - on	F	**625**	4x4		4x4		Vented	306	47	32	**30**	109	6
except 4.8L		R	**622**	4x4		4x4		Vented	315	80	18	**16**	111	6
GU (II) Y61 (Ti - Wagon)	9/01 - on	F	**698**	4x4		4x4		Vented	316	47	34	**32**	109	6
only 4.8L		R	**699**	4x4		4x4		Vented	330	89	18	**16**	111	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

NISSAN - 4WD / SUV / VAN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
PULSAR PANEL VAN														
VB11 Panel Van DB293 Pads	6/83 - 84	F	**302**	✓				Solid	240	35.5	12	**11**	76	4
TERANO														
R20	11/96-10/99	F	**624**	✓				Vented	277	39	26	**24**	100	6
URVAN														
E23 Diesel, Petrol	11/80 - 86	F	**318**	✓				Vented	252	27.5	20	**18**	81	6
E24	3/87 - 93	F	**618**	✓				Vented	260	37.5	26	**24**	81	6
VANETTE														
C20	10/80 - 5/81	F	**307**	✓				Solid	245	36.2	10	**8.4**	73	4
C20, C120 Check disc diameter	6/81 - 11/86	F	**619**	✓				Vented	232	22	18	**16**	73	4
C120, GC22 Check disc diameter	1983 - 92	F	**627**	✓				Vented	250	30	22	**20**	73	4
X-TRAIL														
T30 (ST & Ti) 2.5L	10/2001 - 07	F	**573**	4x4		4x4		Vented	280	49	28	**26**	68	5
		R	**574**	4x4		4x4		Vented	292	62	16	**14**	68	5
T31 2.0L FWD	03/07 - 2010	F	**2316**	4x4				Vented	296	44	26	**24**	68	5
		R	**574**	4x4		4x4		Vented	292	62	16	**14**	68	5
XTERRA														
all models	2000 - 04	F	**626**	✓				Vented	283	38	28	**26**	100	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

OPEL

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ASTRA														
TR 1.8 & 2.0	8/96 - on	F	**023**	✓				Vented	256	41.1	24	**21**	60	4
		R	**819**	✓				Solid	260	69	10	**8**	57	4
TS (City) with ABS	9/1998 - on	F	**815**	✓				Vented	280	42	25	**22**	70	5
TS Series II		R	**816**	✓				Solid	264	42	10	**8**	65	5
TS (City) without ABS	9/1998 - on	F	**817**	✓				Vented	256	41	24	**21**	60	4
TS Series II		R	**818**	✓				Solid	240	42	10	**8**	57	4
TS SRI Turbo	2002 - 04	F	**2815**	✓				Vented	308	42.3	25.1	**22**	70	5
AH - CD, CDX, CDXi	2005 - on	F	**815**	✓				Vented	280	42	25	**22**	70	5
Coupe, Hatch, Wagon		R	**816**	✓				Solid	264	42	10	**8**	65	5
AH07 - SRi, Twin Top, CDTi	2007 - on	F	**2815**	✓		✓		Vented	308	42.3	25.1	**22**	70	5
2.2L Petrol, 1.9L Diesel		R	**816**	✓				Solid	264	42	10	**8**	65	5
AH07 - SRi Turbo	2007 - on	F	**2815**	✓		✓		Vented	308	42.3	25.1	**22**	70	5
2.0L Turbo		R	**2035**	✓				Solid	278	42.2	10	**8**	65	5
VECTRA														
JR, JS, JSII - 2.0L, 2.2L, 2.5L	6/97 - 2/03	F	**825**	✓				Vented	288	44	25	**22**	70	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

PEUGEOT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
205														
GTi 1.9 Litre, 1.8 TDi	1987 - on	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
206														
1.6i 16V 2.0i 16V GT /Gti / S16 2.0 HDI Turbo Diesel CC 1.6i, 2.0i	2000 - 01 1999 - 01 1999 - 01	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.6i 16V 2.0i 16V GT/GTi/S16 2.0 HDI Turbo-Diesel All from Chassis No. 09079 "S.W. 1.6i 16V, 2.0i 16V 2.0 HDI"	2002 - on 2002 - 2005 2002 - on 2002 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
All models above	1999 - on	R	**276**	✓				Solid	246.5	25	8	**6**	71	4
2.0i 16V GT/GTi/S16	2005 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
305														
GT 1.6L + GTX 1.9L	10/85 - 89	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
306														
N3 1.8 Litre, 2 Litre	1993 - 1997	F	**273**	✓				Vented	247	35	20.5	**18.6**	66	4
2.0i, 2.0i 16V Break + ABS, 1.8i 16V Break 1.9L Turbodiesel Break 2.0 HDi Turbodiesel Cabrio 2.0i 16V Cabrio 1.8i 16V	1993 - 03 1997 - 02 1997 - 1999 1999 - 03 1994 - 03 1997 - 03	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
N5 Series I GTi-6	1997 - 1999	F	**275**	✓				Vented	283	27.5	22	**20**	66	4
		R	**276**	✓				Solid	246.5	25	8	**6**	71	4
307														
"1.4i 16V inc S.W., 1.6 16V HDI (-ESP)" 1.6i 16V (-ESP)	2004 - on 2001 - on	F	**2274**	✓				Vented	266	34.2	22	**20**	66	4
"1.4i 16V, 1.6 16V HDI inc S.W. (+ESP)" 1.6i 16V (+ESP) "2.0i 16V, 2.0 HDI" CC 2.0i 16V "S.W. 1.6i 16V, 2.0i 16V, 2.0HDI"	2004 - on 2001 - on 2001 - on 2003 - on 2002 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4
308														
All Models	07 - on	F	**2275**	✓				Vented	283	34.2	26	**24**	66	4

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

PEUGEOT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
405														
1.6/i	1991 - 1996	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
1.8i	1992 - 1996													
1.9/i	1990 - 1992													
1.9i GRI / SRI	1987 - 1992													
1.8L Turbodiesel, 1.9 Diesel, 2.0i	8/92 - 1996													
MI 16 1.9i 16V	1987 - 1992													
MI 16 2.0i 16V	8/92 - 1996													
406														
all models - except Coupe	1997 - on	F	**277**	✓				Vented	283	28.2	26	**24**	66	4
		R	**278**	✓				Solid	290	60	10	**8**	71	4
Coupe with Brembo Caliper	1997 - on	F	PART NOT AVAILABLE											
		R	**278**	✓				Solid	290	60	10	**8**	71	4
504														
504	1970 - 82	F	**270**	✓				Solid	273	43	12.5	**10.7**	76	4
504	1970 - 82	F	**272**	PART NOT AVAILABLE REFERENCE ONLY				Vented	273	43	20	**18.5**	76	4
		R	**271**	PART NOT AVAILABLE REFERENCE ONLY				Solid	273	24.5	12	**10.8**	79	4
505														
505	1980 - 88	F	**270**	✓				Solid	273	43	12.5	**10.7**	76	4
505	1980 - 88	F	**272**	PART NOT AVAILABLE REFERENCE ONLY				Vented	273	43	20	**18.5**	76	4
		R	**271**	PART NOT AVAILABLE REFERENCE ONLY				Solid	273	24.5	12	**10.8**	79	4
604														
604	1978 - 82	F	**272**	PART NOT AVAILABLE REFERENCE ONLY				Vented	273	43	20	**18.5**	76	4
604 Turbo Diesel	1978 - 82	F	**270**	✓				Solid	273	43	12.5	**10.7**	76	4
604	1978 - 82	R	**271**	PART NOT AVAILABLE REFERENCE ONLY				Solid	273	24.5	12	**10.8**	79	4
PARTNER / RANCH / LIGHT COMMERCIAL														
Partner 1.4i, 1.8i, 1.9 diesel	1996 - on	F	**274**	✓				Vented	266	27.5	20.5	**18.6**	66	4
Ranch, Light Commercial	1996 - on													
306 Light Commercial Van + ABS	1993 - on													
Partner Light Commercial	1996 - on													

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

PONTIAC

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CAMARO														
All models	1998 - 2002	F	**2996**	✓		✓		Vented	303	52.5	32	**30.7**	71	5
		R	**2997**	✓		✓		Vented	305	62	26	**24.7**	71	5
GRAND AM														
W/ Performance Pkg. WS6	1990	F	**2600**	✓	✓			Solid	246	48	22	**20**	59	5
G5, G5 PURSUIT														
w/ rear disc	2005 - 2006	F	**2052**	✓	✓	✓		Vented	270	45.2	14	**12**	66	5
		R	**2053**	✓	✓	✓		Solid	315	70.4	28	**26.5**	100.7	6
G6														
w/o ABS	2005 - 2006	F	**2052**	✓	✓	✓		Vented	270	45.2	14	**12**	66	5
		R	**2053**	✓	✓	✓		Solid	315	70.4	28	**26.5**	100.7	6
G8														
V6	2009	F	**2026™**	✓	✓	✓		Vented	298	52.2	30	**28**	67.5	5
		R	**2027™**	✓	✓	✓		Vented	302	56	22	**20**	67.4	5
V8	2009	F	**2028™**	✓	✓	✓		Vented	321	52.2	30	**28**	67.5	5
		R	**2029™**	✓	✓	✓		Vented	324	56.1	22	**20**	67.4	5
GXP 6.2L V8 LS3	2009	F	**2604**	✓		✓	✓	Vented	355	50	32	**30**	67.4	5
GTO														
ALL	2004	F	**040**	✓	✓	✓	✓	Vented	296	83	28	**25**	71.5	5
		R	**041**	✓	✓	✓		Solid	286	78.6	16	**14**	70	5
ALL	2005	F	**2020™**	✓	✓	✓	✓	Vented	320	83	32	**30**	71.6	5
		R	**2021™**	✓	✓	✓		Vented	286	80	18	**16**	70	5
PURSUIT														
w/ rear disc	2005 - 2006	F	**2052**	✓	✓	✓		Vented	270	45.2	14	**12**	66	5
		R	**2053**	✓	✓	✓		Solid	315	70.4	28	**26.5**	100.7	6
SUNBIRD														
ALL	1989 - 1991	F	**2600**	✓	✓			Solid	246	48	22	**20**	59	5
VIBE														
2WD/4WD - w/ rear drum	2003 - 2006	F	**562**	✓	✓	✓		Vented	275	49.5	25	**23**	55	5
2WD GT - w/ rear disc	2003 - 2006	F	**562**	✓	✓	✓		Vented	275	49.5	25	**23**	55	5
		R	**563**	✓	✓	✓		Solid	269	56	9	**7.5**	55	5

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

PORSCHE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
911 / 912														
356C 911, 911T 912 1.6 L	1963 - 65 1965 - 69 1965 - 69	F	**396**	PART NOT AVAILABLE REFERENCE ONLY				Solid	282	35	12.5	**11**	107	5
911 E, T, S, SC, Sportsmatic Carrera 2.2, 2.4, 2.7 L 914/6, 911 Turbo	1969 - 83	F	**394**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	35	20	**19.1**	107	5
911 E, T, S, SC, Sportsmatic Carrera 2.2, 2.4, 2.7, 3.0 L	1969 - 83	R	**395**	PART NOT AVAILABLE REFERENCE ONLY				Vented	289	84	20	**18.7**	90	5
911 Carrera 3.2 L 911 Speedstar 3.2 L	1984 - 9/89 1989 - 92	F	**593**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	35	24	**22.6**	107	5
911 Carrera 2, 4 3.6 L	10/89 - on	F	**590**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	80	28	**26**	103	5
		R	**591**					Vented	299	100	24	**22**	103	5
911 (993)														
911 3.6 Turbo 4, GT2,	03/95 - 9/97	F	**52390**	2 piece disc rotor design			✓	Vented	322	72.2	32	**30**	103	5
911 (996)														
911 3.4 Carrera, Carrera 4 911 3.6 Carrera 4	06/97 - 9/01 10/01 - on	F	**2394**	✓		✓		Vented	318	67	28	**26**	98	5
911 Turbo, C4S	1999 - 2004	F	**52386**	2 piece disc rotor design			✓	Vented	330	69.5	34	**32**	98	5
911 Turbo DBA 52388 = Brake upgrade using 6 piston caliper		F	**52388**	2 piece disc rotor design			✓	Vented	350	69.5	34	**32**	98	5
	Rear suits all models	R	**42397**			✓		Vented	330	75.5	28	**26**	98	5
911 **GT2, GT3, GT3RS**	2003 - 2005	F	**52396**	2 piece disc rotor design			✓	Vented	350	67.5	34	**32**	98	5
	Rear suits all models	R	**42397**			✓		Vented	330	75.5	28	**26**	98	5
911 (997)														
911 3.6 Carrera, 4	07/04 - on	F	**2394**	✓		✓		Vented	318	67	28	**26**	98	5
911 C2S C4S	2004 - 2010	F	**52386**	2 piece disc rotor design			✓	Vented	330	69.5	34	**32**	98	5
	Rear suits all models	R	**42397**			✓		Vented	330	75.5	28	**26**	98	5
911 GT3, GT3RS	2005 - 2008	F	**52396**	2 piece disc rotor design			✓	Vented	350	67.5	34	**32**	98	5
	Rear suits all models	R		Planned release 2011				Vented	350			**34**		
911 GT3 incl. PCCB cars Direct replacement disc rotor as per Original Equipment (FLAT DISC ONLY) **DBA 52399.1**	2006 - on	F	**52399.1**	Planned release 2011			✓	Vented	380	32	32	**30**		
	Rear suits all models	R		Planned release 2011				Vented	350			**34**		

PORSCHE CONTINUED ON NEXT PAGE

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

PORSCHE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
924														
924 2.0 L	1980 - 82	F	**397**	PART NOT AVAILABLE REFERENCE ONLY				Solid	257	42	13	**11.5**	HUB	5
924 2.0 L Turbo	1980 - 82	F	**394**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	35	20	**19.1**	107	5
		R	**399**					Vented	289	71	20	**18.6**	103	5
CAYMAN														
Cayman S 3.4L	11/05 - on	F	**2394**	✓		✓		Vented	318	67	28	**26**	98	5
928														
928 4.5 L	11/81-12/82	F	**398**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	60	20	**18**	90	5
		R	**399**	PART NOT AVAILABLE REFERENCE ONLY				Vented	289	71	20	**18.6**	103	5
928 S4.7 L	1/80 - 8/86	RHF	**597A**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	60	32	**30.6**	90	5
		LHF	**597B**					Vented	282	60	32	**30.6**	90	5
928 S4.7 L	1984 - 9/87	R	**399**	PART NOT AVAILABLE REFERENCE ONLY				Vented	289	71	20	**18.6**	103	5
928 - All models	9/86 - 8/92	RHF	**392A**	PART NOT AVAILABLE REFERENCE ONLY				Vented	304	77	32	**30**	103	5
Vane Pattern Direction		LHF	**392B**					Vented	304	77	32	**30**	103	5
928 S4	1986 - 95	R	**393**	PART NOT AVAILABLE REFERENCE ONLY				Vented	299	71	24	**22**	103	5
928 - All Models	1992 - 95	F	**2392**	✓				Vented	322	77.5	32	**30**	103	5
	1986 - 95	R	**393**	PART NOT AVAILABLE REFERENCE ONLY				Vented	299	71	24	**22**	103	5
930														
930 Turbo 3.3L	11/81 - 85	RHF	**592A**	PART NOT AVAILABLE REFERENCE ONLY				Vented	304	57	32	**30**	107	5
Drill Hole Direction		LHF	**592B**					Vented	304	57	32	**30**	107	5
930 Turbo 3.3L	11/81 - 88	RHR	**598A**	PART NOT AVAILABLE REFERENCE ONLY				Vented	309	82	28	**26**	103	5
		LHR	**598B**					Vented	309	82	28	**26**	103	5
944														
944 2.5L SOHC	4/82 - 89	F	**394**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	35	20	**19.1**	107	5
944 2.5L SOHC	4/82 - 89	R	**399**					Vented	289	71	20	**18.6**	103	5
944 S 2.5L 16V DOHC	10/87 - 88													
944 Turbo	1985 - 86	R	**393**	PARTS NOT AVAILABLE REFERENCE ONLY				Vented	299	71	24	**22**	103	5
944 2.5 L Turbo	1985 - 86	F	**595**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	45	28	**26**	103	5
		R	**596**	PART NOT AVAILABLE REFERENCE ONLY				Vented	299	71	24	**22**	103	5
944 2.5 L Turbo	9/86 - 7/89	F	**949**	PART NOT AVAILABLE REFERENCE ONLY				Vented	298	74	28	**26**	103	5
		R	**585**					Vented	299	100	24	**22**	103	5
944 All Turbo Models	8/89 - 91	RHF	**392A**	PART NOT AVAILABLE REFERENCE ONLY				Vented	304	77	32	**30**	103	5
Vane Pattern Direction		LHF	**392B**					Vented	304	77	32	**30**	103	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

PORSCHE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
BOXTER														
2.5, 2.7	9/96 - on	F	**42398**			✓		Vented	298	67	24	**22**	98	5
BoxsterS 3.2L, (986) BoxsterS 3.4L (987) + CaymanS	2000 - 2010	F	**2394**	✓	✓	✓		Vented	318	67	28	**26**	98	5
CAYENNE (SUV)														
V6 Turbo + Cayenne S	2004 - on	F	**42246**			✓		Vented	350	69	34	**32**	85	5
		R	**42245**			✓		Vented	329	74	28	**26**	85	5

PROTON

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
M21 1.8 L	10/97 - on	F	**414**	PART NOT AVAILABLE REFERENCE ONLY				Vented	256	45	24	**22.4**	64	4
		R	**410**	✓				Solid	260	41	10	**8.4**	64	4
Persona 1.5L Satria GLI	11/96 - on	F	**413**	✓				Vented	235	45	18	**16.4**	64	4
Persona 1.6L	11/96 - on	F	**414**	PART NOT AVAILABLE REFERENCE ONLY				Vented	256	45	24	**22.4**	64	4
Satria XLI & GTi 1.8L		R	**410**	✓				Solid	260	41	10	**8.4**	64	4
Wira 1.5L	5/95 - on	F	**413**	✓				Vented	235	45	18	**16.4**	64	4
Wira 1.6L	5/95 - on	F	**414**	PART NOT AVAILABLE REFERENCE ONLY				Vented	256	45	24	**22.4**	64	4
Wira 1.5L, 1.6L (Rear)	5/95 - on	R	**410**	✓				Solid	260	41	10	**8.4**	64	4
Waja 1.6L Sedan	2001 - on	F	**415**	✓				Vented	256	45	24	**22.4**	69	4
		R	**416**	✓				Solid	260	41	10	**8.4**	90	4
Gen.2 S4PH 1.6L DOHC	2004 - on	F	**42140**			✓		Vented	266	44	22	**20.4**	69	4
		R	**2141**	✓				Solid	280	41	12	**10.4**	90	4
Jumbuck	5/2002 - on	F	**2200**	✓				Vented	256	45	24	**22.4**	64	4
Satria GTi - Race Spec (4 x 100 PCD)	11/96 - on	F	**402B**	✓		✓		Vented	276	45	24	**22.4**	69	4

RANGEROVER

Please refer to Land Rover section

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

RENAULT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
RENAULT														
Dauphine, Caravelle, Floride	1962 - 68	F	**350**	PART NOT AVAILABLE REFERENCE ONLY				Solid	260	40	7	**6**	60	3
Virage, 1.4	1976 - 80	F	**345**	✓				Solid	227.5	38.5	10	**9**	83	6
RENAULT 12														
R12	1971 - 76	F/R	**345**	✓				Solid	227.5	38.5	10	**9**	83	6
R12 Gordini	1971 - 75	F	**343**	✓				Vented	228	45.5	20	**19**	83	6
		R	**345**	✓				Solid	227.5	38.5	10	**9**	83	6
RENAULT 15														
R15 TS	1973 - 76	F	**343**	✓				Vented	228	45.5	20	**19**	83	6
R15 TL, GTL	1973 - 76	F/R	**345**	✓				Solid	227.5	38.5	10	**9**	83	6
RENAULT 16														
R16 (R1150)	1865 - 68	F	**347**	✓				Solid	250	45	9	**8**	84	3
R16	1968 - 77	F	**344**	✓				Solid	254	40	12	**11**	84	3
RENAULT 17														
R17 TL, TS, Gordini	1973 - 76	R	**345**	✓				Solid	227.5	38.5	10	**9**	83	6
RENAULT 18														
R18 GTS (R1340, R1341) R18 GTS (R1350, R1351)	1980 - 82 1982 - 83	F	**345**	✓				Solid	227.5	38.5	10	**9**	83	6
R18 GTS (R1342, R1343) R18 GTS (R1352, R1353)	1980 - 83 1980 - 83	F	**346A**	✓				Vented	238.5	46.5	20	**17.7**	60	4
R18 All Models	1979 - 83	R	**345**	✓				Solid	227.5	38.5	10	**9**	83	6
RENAULT 19														
R19 GTX / TXE	7/88 - 12/95	F	**351**					Vented	238	41	20.1	**17.7**	61	4
RENAULT 20														
R20 TS (R1270) R20 TS, (R1276, R1277)	1980 - 83	F	**346A**	✓				Vented	238.5	46.5	20	**17.7**	60	4
RENAULT FUEGO														
GTX (R1362, R1363)	1982 - 87	F	**346A**	✓				Vented	238.5	46.5	20	**17.7**	60	4
TX, GTX (R1362, R1363)	1982 - 87	F	**346B**	✓				Vented	238.5	46.5	20	**17.7**	61	4

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

RENAULT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
RENAULT CLIO														
1.4i 16V +ABS,1.6i +ABS, 1.6i 16V	1998 - on	F	**2352**	✓				Vented	259	41	20.6	**17.7**	61	4
2.0i 16V SPORT + ABS	2000 - on	F	**2353**	✓				Vented	280	44	24	**21.8**	61	4
rear only fits non ABS models		R	**2354**					Solid	238	74.6	8	**7**	HUB	4
MEGANE														
1.6i 16V (BAO4), 2.0i 16V (BAOH) 1.8i 16V, Turbodiesel 1.9 dCi Turbodiesel 1.5 dCi	3/99 - on 2001 - on 11/02 - on	F	**2353**	✓				Vented	280	44	24	**21.8**	61	4
2.0i 16V (BAOH) 2.0i 16V Cabriolet 2.0i 16V (DAOH/DAO3) Coupe	1996 - 10/02 1997 - 06/03 11/95 - 06/03	R	**2354**					Solid	238	74.6	8	**7**	HUB	4
SCENIC														
1.4i 16V 1.6i 16V, 2.0i 16V (JA1B) Turbodiesel 1.9 dCi all models	09/99 - 05/03 06/03 - on	F	**2353**	✓				Vented	280	44	24	**21.8**	61	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

ROLLS ROYCE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Shadow & Bentley 'T'	1966 - 71	F	**RRF**	✓				Solid	280	35	16	**14**	90	10
(NOT AVAILABLE)		R	**RRR**	✓				Solid	275	40	13	**12**	90	10
Shadow II		F	**2948**	✓				Vented	281	44	31.5	**29.5**	89	10
		F	**2949**					Vented	298.5	43.7	31.5	**30**	88.9	10

ROVER

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
ROVER														
3500 SDI	1979 - 83	F	**089**	PART NOT AVAILABLE REFERENCE ONLY				Solid	257	75	14.5	**13**	75.5	5
3500 SE,	1982 - 87													
Vanden Plas	1982 - 87													
Quintet SU	1983 - 86	F	**190**	✓				Solid	231	50	12	**10**	61	4
12.5mm Dia. Holes														
416i BA1	5/86 - 90	F	**187**	✓				Vented	242	44.5	19	**17**	61	4

* Range Rover - refer to Land Rover section

dba™ DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SAAB

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
95 V4 Station Wagon	9/66 - 70	F/R	**386**	✓				Solid	267	51	9.7	**8**	87.5	5
96 V4 Sports	9/66 - 70													
Sonnet V4 Coupe	1967 - 70													
Sonnet 97 III	1970 - 71													
99 E, EMS, Coupe	1968 - 74	F/R	**387**	PART NOT AVAILABLE REFERENCE ONLY				Solid	269	66.2	10.5	**9.5**	86	4
99 L, EMS, Coupe	1975 - 79	F	**385**	✓				Solid	280	47.5	12.7	**11.7**	86	4
		R	**387**	PART NOT AVAILABLE REFERENCE ONLY				Solid	269	66.2	10.5	**9.5**	86	4

9.3 / 9.5 SERIES

9.3, 9.5	1997 - on	F	**825**	✓				Vented	288	42	25	**22**	70	5
Sedan / Coupe / Convert		R	**826**	✓				Solid	286	69	10	**8**	65.5	5
2.0L, 2.3L, 2.0L Turbo														
9.3 Series		F	**2819**	✓	✓	✓	✓	Vented	314	46	28	**25**	70	5
2.0L TTI (YS3F)	09/02 - on													
2.0L T Convertible (YS3F)	08/03 - on													
2.0L T ESTATE	03/05 - on													
9.5 Series		F	**2815**	✓	✓	✓	✓	Vented	308	42.3	25.1	**22**	70	5
2.3L Turbo Estate (YS3E)	7/03 - on													
3.0 TiD Estate (YS3E)	7/01 - on													
3.0 V6t Estate (YS3E)	10/98 - on													

900 SERIES

900 Coupe, GL, GLE, GLT	1979 - 80	F	**385**	✓				Solid	280	47.5	12.7	**11.7**	86	4
900	1981 - 88	F	**388**	✓				Solid	280	65.6	12.8	**11.7**	86	4
900 Turbo 16	1986 - 88	F	**389**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	70	20	**18.9**	86	4
900 i	1986 - 88	F	**388**	✓				Solid	280	65.6	12.8	**11.7**	86	4
900 Turbo 16	1989 - 93	F	**430**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	43	23.5	**21.5**	68	4
900 i 16	1989 - 93													
900, 900 i	1981 - 88	R	**387**	PART NOT AVAILABLE REFERENCE ONLY				Solid	269	66.2	10.5	**9.5**	86	4
900 Turbo 16	1988 - 9/93	R	**432**	✓				Solid	258	43	9	**7.5**	68	4
900 i Turbo 16														
900i , 900i Turbo	1994 - 97	F	**433**	✓				Vented	284	41	24	**21**	70	5
		R	**434**	✓				Solid	260	69	10	**8**	65.5	5
900S	1996 - on	F	**825**	✓				Vented	288	42	25	**22**	70	5
Model 93		R	**826**	✓				Solid	286	69	10	**8**	65.5	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SAAB

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
9000 SERIES														
9000 2.0 16V	1987 - 90	F	**430**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	43	23.5	**21.5**	68	4
9000 2.3 16V	1990 - 93	F	**431**	✓				Vented	280	44.5	25	**23**	68	4
9000 Turbo 16V	1987 - 88	F	**430**	PART NOT AVAILABLE REFERENCE ONLY				Vented	280	43	23.5	**21.5**	68	4
9000 Turbo 16V 9000 Turbo 2.3 16V	1987 - 97 1990 - 97	F	**431**	✓				Vented	280	44.5	25	**23**	68	4
9000 All Models	1985 - on	R	**432**	✓				Solid	258	43	9	**7.5**	68	4

SEAT

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Cordoba, Ibiza, Toledo1.6, 1.8L	1994 - on	F	**240**	✓				Solid	239	35.2	12	**10**	65	4
Cordoba, Ibiza, Toledo 2.0L	1994 - on	F	**446**	✓				Vented	256	38.7	20	**18**	65	4
		R	**832**	✓				Solid	226	71.2	10	**8**	39.8	4
Cordoba, Ibiza, Toledo	1995 - on	F	**446**	✓				Vented	256	38.7	20	**18**	65	4

SSANYONG

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
MUSSO	1996 - on	F	**554**	✓				Vented	278	41	24	**22**	88	6
		R	**555**	✓				Solid	300	67	10.5	**8.5**	105	6

SKODA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Octavia 2.0 RS (1Z3) Octavia 2.0 RS Combi (1Z5)	01/06 - on 01/06 - on	F	**2806**	✓		✓		Vented	312	49.8	25	**22**	65	5
		R	**2807**	✓		✓		Solid	285.6	48.4	11.7	**10**	65	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUBARU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
1400, A22, A32 All 1600, A26, A27, A67 All	1974 - 79 1974 - 81	F	**342**	✓				Solid	229	46	10	**8.5**	70	4
1600 4WD, 1800, Leone DL, DLA	1980 - 84	F	**340**	✓				Solid	229	52	12.5	**10**	70	4
1600, 1800, Leone	1984 - 85	F	**640**	✓				Vented	230	52	18	**15.5**	70	4
Leone DL, GL, All models	1985 - 94	F	**641**	✓				Vented	242	44	18	**16**	70	4

BRUMBY

Brumby A69	1978 - 89	F	**342**	✓				Solid	229	46	10	**8.5**	70	4
Brumby AU	1985 - 93	F	**640**	✓				Vented	230	52	18	**15.5**	70	4

FORESTER

Forester Wagon SF5	8/97 - 2002	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
Forester X, XS, XT 2.5L	2002 - on	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
Suits 2-pot/piston caliper		F	**4650***			✓		Vented	295	57.5	25	**23**	58	5
		F	**5010***				✓	Vented	295	57.5	25	**23**	58	5
rear Vented		R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
rear Solid		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5

IMPREZA

Impreza 2WD	1993 - 99	F	**645**	✓				Vented	242	53	18	**16**	58	5
Impreza 4WD	1993 - 99	F	**642**	✓				Vented	260	57	24	**22**	58	5
		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
Impeza 4WD	1999 - 02	F	**648**	✓		✓		Vented	277	57	24	**22**	58	5
(Check Dimensions)		F	**642**	✓				Vented	260	57	24	**22**	58	5
		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
Impeza 4WD - GX, RX, RV - RS	2002 - on	F	**648**	✓		✓		Vented	277	57	24	**22**	58	5
Sedan/Hatch 2.0L Non - Turbo all models		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUBARU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
IMPREZA WRX														
WRX 2.0L AWD Turbo	1994 - 98	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
WRX **MY99 - MY00**	1999 - 2000	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
		F	**4000**			✓		Vented	295	57.5	25	**23**	58	5
		F	**5000**				✓	Vented	295	57.5	25	**23**	58	5
		R	**649**	✓		✓		Vented	266	67.5	18	**16**	58	5
WRX **MY01**	2001	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
		F	**4000**			✓		Vented	295	57.5	25	**23**	58	5
		F	**5000**				✓	Vented	295	57.5	25	**23**	58	5
		R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
WRX **MY02 - MY05**	2002 - 2005	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
With 2-piston front caliper		F	**4650**			✓		Vented	295	57.5	25	**23**	58	5
USA Spec		F	**5010**				✓	Vented	295	57.5	25	**23**	58	5
		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
WRX **MY02 - MY05**	2002 - 2005	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
2.0L Turbo		F	**4000**			✓		Vented	295	57.5	25	**23**	58	5
With 4-piston front caliper		F	**5000**				✓	Vented	295	57.5	25	**23**	58	5
JAP Spec		R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
WRX **MY06 - MY07**	2006 - 2007	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
2.5L Turbo		F	**4650**			✓		Vented	295	57.5	25	**23**	58	5
With 2-piston front caliper		F	**5010**				✓	Vented	295	57.5	25	**23**	58	5
USA Spec		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
WRX **MY06 - MY07**	2006 - 2007	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
2.5L Turbo		F	**4000**			✓		Vented	295	57.5	25	**23**	58	5
With 4-piston front caliper		F	**5000**				✓	Vented	295	57.5	25	**23**	58	5
JAP Spec		R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
GH SGT **MY08** 2.0L Turbo	06/07 - ON	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
Japanese spec		F	**4650***			✓		Vented	295	57.5	25	**23**	58	5
08 WRX 2.5L		F	**5010**				✓	Vented	295	57.5	25	**23**	58	5
With 2-piston front caliper	2008 - ON	R	**2659**	✓		✓		Solid	286	63.5	10	**8.5**	58	5

* Note: Not suitable for pre 2002 models with external ABS tone ring. For these earlier models use DBA-650, DBA-4000 or DBA-5000

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUBARU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
IMPREZA WRX STI														
WRX STI **MY99 - MY00**	1999 - 2000	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
		F	**4000**			✓		Vented	295	57.5	25	**23**	58	5
		F	**5000**				✓	Vented	295	57.5	25	**23**	58	5
		R	**649**	✓		✓		Vented	266	67.5	18	**16**	58	5
WRX STI **MY01**	2001	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
		F	**4000**			✓		Vented	295	57.5	25	**23**	58	5
		F	**5000**				✓	Vented	295	57.5	25	**23**	58	5
R180 (190 mm Hand Brake)		R	**656**	✓		✓		Vented	290	67.5	18	**16**	58	5
WRX STI MY02 - MY04 2.0L Turbo With Brembo calipers	2002 - 2004	F	**4654-10**			✓	✓	Vented	326	53	30	**28**	58	10
		R	**655-10**	✓		✓		Vented	316	67.5	20	**18**	58	10
WRX STI MY05 2.0L Turbo	2005	F	**4654-10**			✓	✓	Vented	326	53	30	**28**	58	10
WRX STI MY06 - MY07 2.5L Turbo With Brembo calipers 114.3 (4.5") Stud PCD	2006 - 2007	R	**4655-10**			✓		Vented	316	67.5	20	**18**	58	10
WRX STI MY08 2.5L Turbo	2008 - ON	F	**4654-10**			✓	✓	Vented	326	53	30	**28**	58	10
GRB model		R	**42656**			✓		Vented	316	63.5	20	**18**	58	5

* Note: Not suitable for pre 2002 models with external ABS tone ring. For these earlier models use DBA-650, DBA-4000 or DBA-5000

PART SUPERCESSION for SUBARU WRX STi

DBA is now introducing a 10 stud hole pattern disc brake rotor to suit the Subaru WRX STi range of models combining two sets of PCD's together on the one disc:

2002-2004 – disc rotor stud hole PCD (pitch circle diameter) = 100 mm
2005-2009 – disc rotor stud hole PCD (pitch circle diameter) = 114.3 mm

DBA 4654SL-10

- Part # (4654)
- Slotted Left (SL)
- 10 stud hole pattern (-10)

The benefits:

1. **Universal fitting**
2. **Eliminates variations in part numbers**
3. **Reduced stock levels**

Figure 1. (right side of the page) illustrates the combined PCD patterns, including the two smaller extraction holes.

One part fits all.

All other rotor dimensions remain the same.

Figure 1.

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUBARU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LIBERTY														
BC6 14" Wheels	10/89 - 94	F	**642**	✓				Vented	260	57	24	**22**	58	5
GX incl. 4WD	6/94 - 9/98	R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
GX SKI-FX LE	7/96 -10/96													
Heritage incl. 4WD 2.0 Litre	6/94 -11/96													
LX & 4WD	6/94 - on													
Rallye	11/94 -11/96													
Ski FX Enduro	5/97 - 8/97													
Touring	3/96 - 11/96													
Rear for all above models														
RS Turbo EJ20 2.0L Turbo	1990 - 93	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**649**	✓		✓		Vented	266	67.5	18	**16**	58	5
RX AWD, LE + S port	11/96 - on	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
Heritage 4WD 2.45 Litre		R	**649**	✓		✓		Vented	266	67.5	18	**16**	58	5
All sedan/wagon models	10/98 - 02	R	**657**	✓		✓		Solid	290	67.5	10	**8.5**	58	5
Liberty B4 (2003 model)	2002 - 2003	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
Suits 2-pot/piston caliper		F	**4650***			✓		Vented	295	57.5	25	**23**	58	5
		F	**5010***				✓	Vented	295	57.5	25	**23**	58	5
		R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
Liberty B4 Blitzen 2.0R BL5	6/2003 - on	F	**2650**	✓	✓	✓	✓	Vented	316	56.7	30	**28**	58	5
Liberty 3.0R Spec B	2006	R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
GT/L	2000 - 01	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**657**	✓		✓		Solid	290	67.5	10	**8.5**	58	5
GT-LTD	2001	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
		F	**4650**			✓		Vented	295	57.5	25	**23**	58	5
		F	**5010**				✓	Vented	295	57.5	25	**23**	58	5
		R	**657**	✓		✓		Solid	290	67.5	10	**8.5**	58	5
L/L-S	2002 - 04	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**657**	✓		✓		Solid	290	67.5	10	**8.5**	58	5
GT/GT-LTD (2 pot front)	2002 - 04	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
		F	**4650**			✓		Vented	295	57.5	25	**23**	58	5
		F	**5010**				✓	Vented	295	57.5	25	**23**	58	5
		R	**657**	✓		✓		Solid	290	67.5	10	**8.5**	58	5

* Note: Not suitable for pre 2002 models with external ABS tone ring. For these earlier models use DBA-650, DBA-4000 or DBA-5000

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUBARU

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LIBERTY (CONTINUED)														
GT/GT-LTD (4 pot front)	2002 - 04	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
		F	**4650**			✓		Vented	295	57.5	25	**23**	58	5
		F	**5000**				✓	Vented	295	57.5	25	**23**	58	5
		R	**657**	✓		✓		Solid	290	67.5	10	**8.5**	58	5
2.5i - except. GT	2005	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**2661**					Solid	274	67.5	10	**8.5**	58	5
GT	2005 - 06	F	**2650**	✓	✓	✓	✓	Vented	316	56.7	30	**28**	58	5
		R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
GT	2010	F	**2650**	✓	✓	✓	✓	Vented	316	56.7	30	**28**	58	5
OUTBACK														
LE Wagon	9/96 - 6/98	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**644**	✓	✓	✓		Solid	266	67.5	10	**8.5**	58	5
All models	10/98 - 02	F	**648**	✓	✓	✓		Vented	277	57	24	**22**	58	5
		R	**657**	✓		✓		Solid	290	67.5	10	**8.5**	58	5
Outback H6 (2003 model)	2002 - on	F	**650**	✓	✓			Vented	294	57	24	**22**	58	5
Suits 2-pot/piston caliper		F	**4650***			✓		Vented	295	57.5	25	**23**	58	5
		F	**5010***				✓	Vented	295	57.5	25	**23**	58	5
		R	**653**	✓	✓	✓		Vented	290	67.5	18	**16**	58	5
SHERPA														
Sherpa KM3 2 Cyl	10/82 - 1/88	F	**646**	PART NOT AVAILABLE REFERENCE ONLY				Solid	212	28	10	**8.5**	65	4
Sherpa KN3 4 Cyl KN4 Fiori	2/88 -12/89 12/89 -10/92	F	**647**	PART NOT AVAILABLE REFERENCE ONLY				Solid	212	18	9	**7.5**	65	4
SVX														
SVX	3/92 - 8/97	F	**652**	PART NOT AVAILABLE REFERENCE ONLY				Vented	301.1	57	28	**26**	58	5
		R	**651**	PART NOT AVAILABLE REFERENCE ONLY				Solid	290	67.5	10	**8.5**	58	5
SUBARU REAR UPGRADE														
316mm Sti rear rotor to suit Subaru's with 170mm handbrake	3/92 - 8/97	R	**2657**	✓	✓	✓		Vented	316	67.5	20	**18**	58	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUBARU WRX UPGRADE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SUBARU REAR UPGRADE														
316mm Sti rear rotor to suit Subaru's with 170 mm handbrake	1998 - on	R	**2657**	✓		✓		Vented	316	67.5	20	**18**	58	5

UP TO 2000 WRX : REQUIRES CALIPER ADAPTER BRACKET (BSM) AND STI REAR BREMBO CALIPERS.
UP TO 2002 FORESTER : REQUIRES CALIPER ADAPTER BRACKET (BSM) AND STI REAR BREMBO CALIPERS.
UP TO 2002 LIBERTY : REQUIRES CALIPER ADAPTER BRACKET (BSM) AND STI REAR BREMBO CALIPERS.
FROM 2000 WRX : REQUIRES BACKING PLATE TO BE MODIFIED AND STI REAR BREMBO CALIPERS.
FROM 2002 FORESTER : REQUIRES BACKING PLATE TO BE MODIFIED AND STI REAR BREMBO CALIPERS.
FROM 2002 LIBERTY : REQUIRES BACKING PLATE TO BE MODIFIED AND STI REAR BREMBO CALIPERS.

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUZUKI

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
Hatch SS80 V	1981 - 85	F	511	PART NOT AVAILABLE REFERENCE ONLY				Solid	213	33.5	11	10	86	4
Mighty Boy SS40 T	1984 - 88	F	511					Solid	213	33.5	11	10	86	4
Super Carry SK410	1985 - 88	F	012	✓				Solid	215	33.5	10	8	86	4
BALENO														
1.6 Litre, GA, GL, GLX, GS	4/95 - on	F	519	✓				Vented	235	50	20	18	60	4
GTX 1.8 Litre	3/96 - on	F	520	✓				Vented	246	50	20	18	60	4
		R	521	✓				Solid	240	33	10	8	58	4
CARRY VAN/UTE														
1.3 Litre GA413	1999 - on	F	522	✓				Vented	231	44	17	15	60	4
CINO / IGNIS														
Cino SF413 1.3L 3/5Dr	1994 - on	F	022	✓				Vented	231	50	17	15	64	4
Ignis 1.3 Litre 3/5Dr, RG413	10/2000 - on	F	523	✓				Vented	257	49	17	15	60	4
LIANA														
"1.3, 1.5, 1.6, 1.8L sedan & Hatch"	11/2001 - on	F	520	✓				Vented	246	50	20	18	60	4
SAMURAI														
1.3 (SJ70)	1998 - on	F	513	✓				Solid	290	46.5	10	8	107	5
SIERRA / JIMNY														
1.0 4WD SJ40, SJ410, SJ413 1.3 4WD SJ50, SJ70, SJ80 Stockman MG 410 Ute	1983 - 86 10/84 - 1/96 1990 -1999	F	510	✓				Solid Flange Thickness 7mm	290	46.5	10	9	107	5
413 SJ80	4/96 -10/98	F	513	4x4				Solid	290	46.5	10	8	107	5
Jimny SWB 1.3 SN413, 513	1998 - on	F	513	4x4				Solid Flange Thickness 6mm	290	46.5	10	8	107	5
Wagon R 1.0 SR410	1997 - 98	F	515	4x4				Vented	231	49	17	15	60	4
SWIFT														
SA310. SA413	2/85 - 88	F	012	✓				Solid	215	33.5	10	8	86	4
GT i SA413, AA33S	10/86 - 88	F	512	PART NOT AVAILABLE REFERENCE ONLY				Vented	231	52	17	15	64	4
SF310, 413	1989 - 94	F	022	✓				Vented	231	50	17	15	64	4
SF416, SF413, GTi, Sedan	1989 - 98	F	516	✓				Vented	250	47	18.5	16.5	64	4
GTi SF413	1989 - 98	R	517	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	35	10	8	64	4
1.6L 3D & 5D	2004 - on	F												

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

SUZUKI

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
VITARA														
JX, JLX SWB SE 416 X90 SZ 416 2 Door 1.6L	1988 - 98 1996 - 97	F	**513**	4x4				Solid Flange Thickness 6mm	290	46.5	10	**8**	107	5
4 Door "Estate" LWB	1991 - 98	F	**514**	✓				Vented	287	46	17	**15**	107	5
JLX Estate 2.0L V6 SV620	1996 - 4/98	F	**518**	✓				Vented	310	46	22	**20**	107	5
GRAND VITARA														
Grand 1.6L SQ416 Soft-top	10/98 - 06	F	**524**	✓				Vented	287	29	17	**15**	108	5
Grand 2.0L SQ420 SWB Hard-top	10/98 - 06	F	**578**	✓				Vented	287	29	17	**15**	107	5
Grand 2.0L SQ420W LWB + 2.5L SQ625W + XL-7	4/98 - 06	F	**579**	✓				Vented	310	29	22	**20**	108	5
Grand Vitara - all models	2006 - on	F	**2580**	4x4		4x4		Vented	295	49.5	25	**23**	62	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
AURION V6														
3.5L V6 (GSV40R)	11/06 - on	F	**2709**	✓	✓	✓		Vented	296	49.3	28	**25**	62	5
		R	**2707**	✓	✓	✓		Solid	286	65	10	**8.5**	62	5
AVALON														
MCX10R - V6 3.0L DOHC	07/00 - 08/03	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
all models rear	07/00 - 08/03	R	**757**	✓				Solid	291	65.5	9	**8**	62	5
all models rear	09/03 - on	R	**2707**	✓	✓	✓		Solid	286	65	10	**8.5**	62	5
all models USA	1995 - 04	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
AVENSIS VERSO (ACM20/21)														
GLX, Ultima - 7 seater	5/01 - on	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
(MPV Australian Model)		R	**697**	✓				Solid	291	68.5	12	**10.5**	62	5
CAMRY														
SV11	1982 - 86	F	**149**	✓				Vented	243	45	22	**21**	54	5
SV20 Series I, II	1987 - 10/92	F	**730**	✓				Vented	255	47.5	22	**21**	54	5
SV21, SV22		R	**741**	✓				Solid	269	65	10	**9**	54	5
VZV20 Series I, II	2/88 - 10/92	F	**732**	✓				Vented	255	48	25	**24**	54	5
VZV21, VZV22		R	**741**	✓				Solid	269	65	10	**9**	54	5
SDV10, SVX10 4 Cyl	11/92 -7/97	F	**733**	✓				Vented	255	49	28	**26**	62	5
VCV10, VDV10 Vienta V6	11/92 -7/97	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
SDV10, VDV10 All Sedans	11/92- 7/97	R	**736**	✓				Solid	269	65	10	**9**	62	5
VDV10 V6 All Wagons	11/92 -7/97	R	**734**	✓				Solid	288	65	10	**9**	62	5
SXV20	7/97 - 2002	F	**733**	✓				Vented	255	49	28	**26**	62	5
MCV20	7/97 - 2002	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
Rear disc fits all sedans and wagons		R	**736**	✓				Solid	269	65	10	**9**	62	5
3.0L V6 (MCV36R)	8/02 - 8/06	F	**735**	✓		✓		Vented	275	49.5	28	**26**	62	5
2.4L 4cyl (ACV36R)														
Rear fits all sedans & wagons		R	**2707**	✓	✓	✓		Solid	286	65	10	**8.5**	62	5
3.0L V6 (MCV30) -16inch wheels	07/2001 - on	F	**2705**	✓		✓		Vented	296	49.3	28	**26**	62	5
(Europe & USA)		R	**2711**	✓				Solid	269	65	12	**10.5**	62	5
2.4L CYL (ACV40R)	06/06 - on	F	**2709**	✓	✓	✓		Vented	296	49.3	28	**25**	62	5
		R	**2707**	✓	✓	✓		Solid	286	65	10	**8.5**	62	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA

CELICA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
TA 22	1971 - 7/77	F	**139**	✓				Solid	228	17.9	10	**9**	64	4
RA 23, RA 28 Liftback RA 40, RA 40 B	1976 - 7/77 8/77 - 7/81	F	**140**	✓				Solid	254	16	12.7	**11.5**	73	4
RA 60, Coupe, Liftback SA 63, 2.0 L RA 65, 2.4 L	8/81 - 9/83 10/83 - 84 10/84 - 85	F	**146**	✓				Vented	258	26	20	**19**	76	4
ST 162 SX, GTS, 2.0 GT Coupe	8/85 - 8/89	F	**739**	✓				Vented	258	47.5	22	**21**	54	5
ST 162 ST	10/86 - 8/89	F	**740**	✓				Vented	243	48	22	**21**	54	4
ST 184 2WD, 2.0 GT Coupe	10/89 - 8/91	F	**742**	✓				Vented	255	46	22	**20**	54	5
ST 184 2WD ST 185 4WD (incl. Group A)	8/91-11/93	F	**743**	PART NOT AVAILABLE REFERENCE ONLY				Vented	278	46	25	**23**	54	5
ST 162 SX, 2.0 GT Coupe ST 184	8/85 - 8/89 10/89 -11/93	R	**741**	✓				Solid	269	65	10	**9**	54	5
ST 185 4WD (Incl. Group A)	10/89 -11/93	R	**744**	✓				Solid	288	60	10	**9**	54	5
ST 204 2WD & GT	11/93 - 8/99	F	**747**	PART NOT AVAILABLE REFERENCE ONLY				Vented	275	49	28	**26**	55	5
	11/93 - 8/95	R	**741**	✓				Solid	269	65	10	**9**	54	5
	8/95 - 8/99	R	**764**	✓				Solid	269	65	9	**8**	55	5
ST 205 4WD	2/94 - on	F	**560**	✓		✓		Vented	315	59	32	**30**	55	5
		R	**561**	PART NOT AVAILABLE REFERENCE ONLY				Vented	315	59	16	**15**	55	5
ZZT231 1.8L DOHC 1.8 WTI 190 BHP	11/99-06/00 2000 - on	F	**562**	✓		✓		Vented	275	49.5	25	**23**	55	5
		R	**563**	✓		✓		Solid	269	56	9	**7.5**	55	5

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

TOYOTA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

COROLLA / RUNX / ALLEX

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
KE 10#, KE 20#	3/68 - 7/74	F	**141**	PART NOT AVAILABLE REFERENCE ONLY				Solid	200	36	10	**9**	64	4
KE 30#, KE 50# Series with Imported Brakes	8/74 - 9/81	F	**142**	✓				Solid	218	30	10	**9**	64	4
KE 30#, KE50#, KE 70, AE 71 Series with Local Brakes	10/81-12/84	F	**144**	✓				Solid	218	30	12.7	**11.5**	64	4
KE 70 Panel Van	10/81- 9/83	F	**145**	✓				Solid	228	32	12.7	**11.5**	64	4
AE 71 Panel Van AE 86 Sprinter	9/83 -12/84 5/83 -11/84	F	**700**	PART NOT AVAILABLE REFERENCE ONLY				Solid	234	38	12.5	**11.5**	64	4
AE 80, 82 SOHC	1985 -12/88	F	**701**	✓				Solid	243	48	13.5	**12.5**	54	4
AE 82 D.O.H.C	1986 -12/88	F	**702**	✓				Vented	243	48	18	**17**	54	4
		R	**703**	✓				Solid	242	37	9	**8**	54	4
AE 90, 92 S.O.H.C.	2/89 -10/94	F	**701**	✓				Solid	243	48	13.5	**12.5**	54	4
AE 90, 92, 93 D.O.H.C. AE 95 4WD	8/89 - 6/91 2/88 - 94	F	**704**	✓				Vented	238	48	18	**17**	54	4
AE 92 SX (Eng:4AGE) Fuel Injected AE 92 GT, GS, ULTIMA (Eng:4AGE) Fuel Injected	8/89 - 6/91 6/91 - 10/92	R	**703**	✓				Solid	242	37	9	**8**	54	4
AE 93 DOHC	6/91 -10/94	F	**708**	✓				Vented	258	48	22	**20**	54	4
AE 93 (Eng:4AGE) Fuel Injected	10/92 - 94	R	**703**	✓				Solid	242	37	9	**8**	54	4
AE 101	2/94 - 7/99	F	**711**	✓				Vented	238	48	22	**20**	55	4
AE 102, AE 102 Sprinter AE 112 Import + turbo	7/94 - 7/99 2/94 - 5/96 5/97 - 2001	F	**709**	✓				Vented	255	48	22	**20**	55	4
		R	**710**	✓				Solid	266	37	9	**8**	55	4
ZZE 122 - all models	12/01 - on	F	**712**	✓				Vented	255	49.5	25	**23**	55	4
(Except Sth African model)		R	**713**	✓				Solid	269	56	9	**8**	55	4
ZZE 122 - Sth African model	12/01 - on	F	**712**	✓				Vented	255	49.5	25	**23**	55	4
		R	**2719**	✓				Solid	258	56	9	**8**	55	4
ZZE 123 - Sportivo Corolla Verso 2.0L (UK)	2003 - 7/07	F	**759**	✓				Vented	275	50	25	**23**	55	4
Toyota Corolla ZRE 152	07/07 - on	F	**2742**	✓				Vented	275	46.3	22	**19**	62	5
		R	**2743**	✓				Solid	259	30.5	9	**7.5**	62	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
CORONA														
RT 40, RT 40 L	1967 -1/70	F	**137**	✓				Solid	241	56	10	**9**	74	4
RT 80, RT 81	2/70 - 7/73	F	**139**	✓				Solid	228	17.9	10	**9**	64	4
RT 104, RT 118 XT 130, XT 131 RT 132, RT 133	8/73 - 9/79 10/79 - 5/83 2/82 - 5/83	F	**138**	✓				Solid	266	42	12.7	**11.5**	76	4
ST 141 2.0 L, RT 142 2.4 L	6/83 - 4/87	F	**705**	✓				Solid	250	25	12.7	**11.5**	76	4
ST 141 2.0 L DB1098 Pads	6/83 - 4/87	R	**706**	PART NOT AVAILABLE REFERENCE ONLY				Solid	280	79	10.5	**9.4**	60	4
RT 142 with IRS	10/85 -12/86	R	**707**	PART NOT AVAILABLE REFERENCE ONLY				Solid	269	60.5	10	**9**	60	4
CORONA MKII														
RT 72	9/68 - 12/71	F	**143**	✓				Solid	243	53.5	10	**9**	74	4
MX 10, 13, 22, 23	1972 - 11/76	F	**138**	✓				Solid	266	42	12.7	**11.5**	76	4
CRESSIDA														
MX 32, MX 36	12/76 - 8/80	F	**138**	✓				Solid	266	42	12.7	**11.5**	76	4
MX 62	9/80 - 7/84	F	**720**	✓				Vented	248	28.5	18	**17**	76	4
MX 73	8/84 - 8/88	F	**721**	✓				Vented	248	40	22	**21**	76	4
		R	**722**	PART NOT AVAILABLE REFERENCE ONLY				Vented	269	61	18	**17**	60	4
MX 83	9/88 - 8/90	F	**570**	✓				Vented	256	68	20	**19**	60	5
MX 83	8/90 - 2/93	F	**572**	PART NOT AVAILABLE REFERENCE ONLY				Vented	256	68	22	**21**	60	5
MX 83	9/88 - 2/93	R	**571**	PART NOT AVAILABLE REFERENCE ONLY				Solid	272	66	10	**9**	60	5
CROWN														
MS 65 Sedan MS 83 Wagon, MS 85	2/71 - 9/74 1974 - 78	F	**724**	✓				Solid	266	42	12.7	**11.3**	76	5
MS 85 Sedan All Except Royal MS 112 Royal	2/78 - 8/79 4/79 - 7/83	F	**727**	PART NOT AVAILABLE REFERENCE ONLY				Vented	252	26	20	**19**	76	5
MS 85, MS 112	11/75 - 7/83	R	**725**	PART NOT AVAILABLE REFERENCE ONLY				Solid	261	60	12.5	**11.5**	67	5
MS 123	8/83 - 6/86	F	**728**	PART NOT AVAILABLE REFERENCE ONLY				Vented	252	40	20	**19**	76	5
Internal Drum = 167mm		R	**729**	PART NOT AVAILABLE REFERENCE ONLY				Vented	268	64	18	**17**	67	5
MS 123 Royal	8/83 - 6/86	R	**731**	✓				Solid	269	65	12	**11**	67	5
ECHO / PLATZ														
NCP 10, NCP 12	10/99 - on	F	**723**	✓				Vented	235	43	18	**16**	55	4
all models USA	2001 - 04	F	**753**	✓				Vented	255	43.25	20	**18**	55	4

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LEXCEN														
VN 1, 3, VP 1, 3 Except ABS	6/89 - 5/92	F	**015**	✓		✓		Vented	270	82	22	**20***	HUB	5
VP 1, VP 3	5/92 - 7/92	F	**025**	✓		✓		Vented	270	82	23	**20***	HUB	5
VP 1, VP 3 Including ABS	7/92 - 5/93	F	**027**	✓		✓		Vented	290	82	23	**20***	HUB	5
VR, VS	6/93 - on	F	**035**	✓		✓		Vented	289	83	23	**20**	70	5
VN 1, 3, VP 1, 3 except IRS VR, VS except IRS	6/89 - 5/93 6/93 - on	R	**016**	✓		✓		Solid	279	83	10.5	**8.5***	70	5
VP with IRS	9/91 - 5/93	R	**026**	✓		✓		Solid	279	67	10.5	**8.5**	70	5
VR, VS with IRS	6/93 - on	R	**036**	✓		✓		Solid	279	86	10.7	**8.5**	70	5
MR2 / MR-S														
AW 11 non-turbo USA	11/87 - 89 6/86 - 12/89	F	**750**	PART NOT AVAILABLE REFERENCE ONLY				Vented	258	47	22	**21**	54	4
		R	**751**	✓				Solid	258	40.5	10	**9**	54	4
SW 20 non-turbo USA turbo USA	12/89 -12/91 1/90 - 95 90 - 12/91	F	**580**	PART NOT AVAILABLE REFERENCE ONLY				Vented	258	47.5	25	**24**	62	5
		R	**581**	PART NOT AVAILABLE REFERENCE ONLY				Vented	263	45	16	**15**	62	10
SW 20 turbo USA	12/91 - on 1992 - 95	F	**582**	PART NOT AVAILABLE REFERENCE ONLY				Vented	275	47	30	**28**	62	5
		R	**583**	✓				Vented	281	46.5	22	**21**	62	10
SPYDER turbo & non-turbo (ZZW30R)	12/99 - on	F	**753**	✓				Vented	255	43.25	20	**18**	55	4
		R	**754**	✓				Vented	263	41.5	16	**15**	55	4
PASEO														
EL 44 1.5L Coupe	4/91 - 94	F	**695**	✓				Vented	254	43	18	**17**	55	4
	8/92 - 94	R	**696**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	80	9	**8**	HUB	4
EL54	8/95 - on	F	**695**	✓				Vented	254	43	18	**17**	55	4
		R	**696**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	80	9	**8**	HUB	4
PRIUS														
HNW11R 4D Sedan 1.5L	2001 - 2/02	F	**712**	✓				Vented	255	49.5	25	**23**	55	4
		R	**713**	✓				Solid	269	56	9	**8**	55	4

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SECA														
AE 82 SOHC, AE 93/94 Non SX	9/85 -12/88	F	**701**	✓				Solid	243	48	13.5	**12.5**	54	4
AE 82 DOHC	1986 -12/88	F	**702**	✓				Vented	243	48	18	**17**	54	4
		R	**703**	✓				Solid	242	37	9	**8**	54	4
AE 93 SX D.O.H.C.	8/89 - 6/91	F	**704**	✓				Vented	238	48	18	**17**	54	4
AE 93 SX D.O.H.C.	6/91 - 10/94	F	**708**	✓				Vented	258	48	22	**20**	54	4
	8/89 - 10/94	R	**703**	✓				Solid	242	37	9	**8**	54	4
AE 101	2/94 - 7/99	F	**711**	✓				Vented	238	48	22	**20**	55	4
AE 102	7/94 - 7/99	F	**709**	✓				Vented	255	48.5	22	**20**	55	4
		R	**710**	✓				Solid	266	37	9	**8**	55	4
SOARER														
JZZ30 Eng: 1JZGTE 2.5L TURBO UZZ32 Eng: 1UZFE 4.0L V8 (active susp., 4 wheel steer)	1991 - on	F	**4748**			✓		Vented	296	51	32	**30**	62	5
(check your dimensions)		R	**746**	✓		✓		Vented	307	67	16	**15**	62	5
JZZ31 Eng: 2JZGE 3.0L UZZ30 Eng: 1UZFE 4.0L V8 (coil susp., 2 wheel steer) UZZ31 Eng: 1UZFE 4.0L V8 air susp., 2 wheel steer)	1994 - on 1991 - on	F	**568**	✓				Vented	275	49.5	28	**26**	62	5
(check dimensions)		R	**586**	✓				Vented	291	67.5	16	**15**	60	5
STARLET														
EP 91	1996 - on	F	**714**	✓				Vented	238	43	18	**17**	55	4

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
SUPRA (GTE = TURBO : TT = TWIN TURBO : GE = NON TURBO : NA = STANDARD MODEL)														
MK II MA 61	8/81 -12/85	F	**146**	✓				Vented	258	26	20	**19**	76	4
		R	**717**	PART NOT AVAILABLE REFERENCE ONLY				Vented	266	60.5	18	**17**	60	4
SUPRA (MK III) JZA70														
MA-70, MA-71 7M-GTE 3.0iL Turbo (TT)	1986 - 5/93	F	**715**	✓				Vented	300	53.5	22	**21**	60	5
7M-GE 3.0iL (NA)		R	**716**	✓				Vented	291	68.5	18	**17**	60	5
SUPRA (MK IV) JZA80 (GZ, RZ, RZ-S, SZ, SZ-R - 3.0-LITRE TWIN-CAM 24-VALVE)														
Jap 2JZ-GTE TT 2 pot caliper Jap 2JZ-GE (NA) 2 pot caliper Export 2JZ-GE (NA) 2 pot caliper	5/93 - 1995 5/93 - on 5/93 - on	F	**4748**			✓		Vented	296	51	32	**30**	62	5
1 pot caliper on the rear 16 inch rim's		R	**746**	✓		✓		Vented	307	67	16	**15**	62	5
Export 2JZ-GTE TT 4 pot caliper Export 2JZ-GE (NA) 4 pot caliper Jap 2JZ-GTE TT 4 pot caliper	5/93 - 10/98 5/93 - on 1995 - on	F	**4718**			✓	✓	Vented	323	50	30	**28**	62	5
2 pot caliper on the rear 17 inch rim's		R	**719**	✓		✓		Vented	324	67.5	16	**15**	62	5
T-18														
TE 72 SE	8/79 - 5/83	F	**148**	✓				Solid	230	24	12.7	**11.5**	64	4
YARIS VERSO														
T-SPIRIT (UK)	2003 - on	F	**2708**	✓				Vented	255	43.3	20	**18**	55	4
YARIS - all models (Australia)	2003 - on	F	**2718**	✓				Vented	255	46.5	22	**19**	55	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
4 RUNNER														
2WD TURBO 4WD - Turbo 4WD - exc. Turbo LN, YN 61 4 Runner LN, YN, VZN 130 4 Runner RN 61 4 Runner	8/89 - 95 1986 - 98 1986 - 87 6/91 - 10/95 8/85 - 3/89 8/89 - 91 1988 - 91	F	**780**	✓				Vented	289	64.5	20	**18**	100	6
4WD - exc. Turbo	8/91 - 95	F	**775**	✓				Vented	291	66	25	**23**	100	6
KUN, GGN, TGN	2005 - on	F	**2714**	4x4		4x4		Vented	297	67	25	**23**	108	6
GRN21#, UZN21# LIMD	6/05 - on	F	**2716**	4x4		4x4		Vented	319	67.5	28	**26**	108	6
SR5, UZN210 LIMD		R	**793**	4x4		4x4		Vented	312	68	18	**16**	106	6
BLIZZARD														
LD 10 4WD	1982 - 4/84	F	**292**	✓				Solid	277	30	12.5	**11.5**	96	5
COASTER														
RB 20 BB 20, BB 21 HB 30, HZB	5/82 -1/93 5/82 -1/93	F	**770**	✓				Vented	300	49	30	**29**	106.5	5
BB 40, HZB 50	1/93 - on	F	**771**					Vented	296	101	35	**33**	126	5
DYNA 100, 150 SERIES														
LH 80R. YH 81-100	8/85 - 3/88	F	**156**	✓				Vented	257	47	25	**24**	84	5
YY 5#, 6#, LY 6#-150	8/85 - 94	F	**772**	✓				Vented	258	52	25	**24**	91	6
DYNA 200, 300, 400 SERIES														
BU, YU, WU, BU 100 All except WU 90	9/84 - on	F	**770**	✓				Vented	300	49	30	**29**	106.5	5
FJ CRUISER														
all models	2006 - on	F	**2716**	4x4		4x4		Vented	319	67.5	28	**26**	108	6
		R	**793**	4x4		4x4		Vented	312	68	18	**16**	106	6
FORTUNER / VIGO / PRERUNNER														
all models	2005 - on	F	**2714**	4x4		4x4		Vented	297	67	25	**23**	108	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HI-ACE														
RH 11, 20, 22, 32, 42 LH 11, 20, 30	12/81 - 11/82 12/81 - 7/85	F	**155**	✓				Vented	252	26.5	20	**19**	79	5
YH 5, 6, 7, LH 5, 6, 7	12/82 - 7/89	F	**156**	✓				Vented	257	47	25	**24**	84	5
LH, RZH 103, 113, 125, 184	8/89 - on	F	**766**	✓				Vented	255	47	25	**23**	84	5
Hi-Ace, LH162, LH172 15" wheels	11/94 - on 8/00 - on	F	**767**	✓				Vented	285	46	28	**26**	84	5
SB RCH 12 6 stud holes	8/95 - on	F	**768**	✓				Vented	285	46	28	**26**	84	6
KDH, TRH	2005 - on	F	**2732**	✓				Vented	285	48.7	28	**26**	105	6

HIGHLANDER - REFER TO KLUGER

HI-LUX 2WD														
RN 30, 31, 40, 41 LN 30, 40	8/78 - 7/83	F	**155**	✓				Vented	252	26.5	20	**19**	79	5
RN 41, RMSQ SR5	8/78 - 7/83	F	**152**	✓				Solid	266	43	12.7	**11.5**	79	5
YN 57 SR5	8/85 - 3/87	F	**781**	✓				Vented	248	46	22	**21**	84	5
RN 90 (rare model)	8/88 - 7/97	F	**783**	✓				Vented	254	46	22	**20**	84	5
YN56 1.8L RN 50, YN 50 Series YN85/90 1.8L LN50/51/55/56 2.2L & 2.4L RN 85 LN85/90 2.4L Diesel RZN 147, 149 LN 147, 152	8/83 - 88 8/83 - 3/89 1989 - 97 8/83 - 88 8/88 - 8/97 8/97 - on 8/97 - on 8/97 - on	F	**156**	✓				Vented	257	47	25	**24**	84	5
KUN 10#, GGN 15# LAN 15#, TGN 15#	2009 - on	F	**2715**	✓		✓		Vented	275	58.6	28	**26**	62	5

DISC BRAKES AUSTRALIA ™

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
HI-LUX 4WD / 4 RUNNER / SURF / SW4														
RN 36,46 10.5mm Stud Holes	1/79 - 8/80	F	**153**	✓				Solid	302	49	12.7	**11.5**	100	6
RN 36, 45, 46 LN 36, 46 LN 60, 65, YN 60, 62, 65, 67	8/80 - 7/83 8/80 - 7/83 8/83 - 3/89	F	**154**	✓				Solid 15mm Stud Holes	302	49	12.7	**11.5**	100	6
RN 105, LN 106, YN 106	8/88 - 7/97	F	**151**	4x4		4x4		Vented	302	49	20	**19**	100	6
LN, YN 61 4 Runner RN 61 4 Runner LN, YN, VZN 130 4 Runner LN 107, 111, 125, 135, 172 RN 106, 110, 125, 135 LN 165, 167, 170, 172 RZN 154, 168, 169, 173, 174 LN 192R 3.0Lt Diesel 4WD KZN 165 VZN 167	8/85 - 3/89 1988 - 91 8/89 - 91 8/88 - 04 8/88 - 04 8/97 - 04 8/97 - 04 8/88 - 04 8/97 - 04 8/88 - 04	F	**780**	4x4				Vented	289	64.5	20	**18**	100	6
LN, RN, VZN, KZN	8/91 - 95	F	**775**	4x4				Vented	291	66	25	**23**	100	6
KUN 20#, GGN 25#, LAN 25#, TGN 26#	08/04 - on	F	**2714**	4x4		4x4		Vented	297	67	25	**23**	108	6
KLUGER / HIGHLANDER														
CV, CVX, Grande - V6 3.3L	8/03 - 07	F	**2710**	✓				Vented	296	50	28	**26**	62	5
GSU40 FWD V6 4D Wagon GSU45 4WD V6 4D Wagon GSU40 FWD GRANDE GSU45 4WD GRANDE	2007 - 2008 2007 - 2008 2007 - 2008 2007 - 2008	F	**2734**	✓				Vented	328	49.5	28	**25**	62	5
		R	**2735**	✓				Solid	309	69.7	10	**8.5**	62	5
LITE-ACE														
KM 20 RV 4 Door Van	10/79 -10/82	F	**755**	✓				Vented	230	37	18	**17**	74	4
CM 20, KM 20, YM 21	10/82 - 8/85	F	**756**	✓				Vented	230	44	20	**19**	74	4
CM 30, 35, KM 36, YM 30, 35	9/85 - 8/88	F	**158**	✓				Vented	255	42	20	**19**	74	4
YM 40	1986 - 8/88	F	**758**	✓				Vented	260	45	20	**19**	95	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LANDCRUISER, BUNDERA														
BJ 40, HJ 45, FJ 40, 55 10.5mm Stud Holes	9/79 - 7/80	F	**150**	✓				Vented	302	49	20	**19**	100	6
BJ 42 BJ 60, 70, 73, 74	8/80 -10/84 11/84 -1/90	F	**151**	4x4		4x4		Vented 15 mm Stud Holes	302	49	20	**19**	100	6
HJ 47, 60, 61, 75 HZJ 70, 73, 75 PZJ 70, 73, 75	1980 - 99	F	**151**	4x4		4x4		Vented 15 mm Stud Holes	302	49	20	**19**	100	6
FJ 40, FJ 60, FJ 70 Series FZJ 75, KZJ70	1980 - 92 8/92 - on	F	**151**	4x4		4x4		Vented 15 mm Stud Holes	302	49	20	**19**	100	6
RJ 70, LJ 70	11/84 - 8/92	F	**154**	4x4				Solid	302	49	12.7	**11.5**	100	6
FJ HZJ 70, 73, 75, FZJ 75	1990 - on	R	**787**	4x4				Vented	312	68	18	**16**	106	6
LANDCRUISER - FJ CRUISER														
all models	2006 - on	F	**2716**	4x4		4x4		Vented	319	67.5	28	**26**	108	6
		R	**793**	4x4	✓	4x4		Vented	312	68	18	**16**	106	6
LANDCRUISER - 70 SERIES														
78 and 79 Series	8/99 - on	F	**790**	4x4		4x4		Vented	322	65	32	**30**	115	5
HZJ78, HDJ78,		R	**794**	4x4				Vented	312	102.5	18	**16**	110	5
VDJ76 V8 Turbo Diesel	2/07 - on	F	**790**	4x4		4x4		Vented	322	65	32	**30**	115	5
HZJ76 6cyl Turbo Diesel	2/07 - on	R	**794**	4x4				Vented	312	102.5	18	**16**	110	5
LANDCRUISER - 80 SERIES														
FJ 80, HDJ 80, HZJ 80	1990 - 8/92	F	**782**	4x4				Vented	286	58	25	**23**	106	6
Early 80 Series (Rear)		R	**785**	4x4				Vented	312	103	18	**16**	106	6
FZJ 80, HDJ 80, HZJ 80	8/92 - 1/98	F	**784**	4x4		4x4		Vented	311	58	32	**30**	105	6
Late 80 Series (Rear)		R	**786**	4x4				Vented	336	103	18	**16**	106	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
LANDCRUISER / PRADO - 90 SERIES														
VZJ90, KZJ90, LJ90, RZJ90	7/96 - on	F	**792**	4x4		4x4		Vented	319	70	22	**20**	108	6
RV4, RV6, GXL, VX, VT, GRANDE		R	**793**	4x4		4x4		Vented	312	68	18	**16**	106	6
LANDCRUISER / PRADO - 120 SERIES														
All models	9/02 - 09	F	**2700**	4x4		4x4		Vented	338	68	28	**26**	108	6
		R	**793**	4x4		4x4		Vented	312	68	18	**16**	106	6
LANDCRUISER - 100 SERIES														
UZJ 100 R : HDJ 100 R	1998 - 2006	F	**788**	4x4		4x4		Vented	312	71	32	**30**	115	5
LEXUS LX 470 V8														
6 and 8 Cylinder		R	**789**	4x4		4x4		Vented	330	103	18	**16**	110	5
FZJ 105 R : HZJ 105 R	1998 - 2006	F	**790**	4x4		4x4		Vented	322	65	32	**30**	115	5
6 Cylinder		R	**791**	4x4		4x4		Vented	335	103	18	**16**	110	5
(Fixed front axle version only)														
LANDCRUISER - 200 SERIES														
4.0L, 4.5L, 4.7L	2008	F	**2722**	4x4		4x4		Vented	340	83.6	32	**39**	112	5
		R	**2723**	4x4		4x4		Vented	345	76.5	18	**16**	112	5
PRADO - 90 SERIES														
VZJ90, KZJ90, LJ90, RZJ90	7/96 - on	F	**792**	4x4		4x4		Vented	319	70	22	**20**	108	6
RV4, RV6, GXL, VX, VT, GRANDE		R	**793**	4x4		4x4		Vented	312	68	18	**16**	106	6
PRADO - 120 SERIES														
All models	9/02 - 09	F	**2700**	4x4		4x4		Vented	338	68	28	**26**	108	6
		R	**793**	4x4		4x4		Vented	312	68	18	**16**	106	6
PRADO - 150 SERIES														
All models	11/09 - on	F	**2736**	4x4		4x4		Vented	338	68.5	32	**29**	108	6
		R	**2737**	4x4		4x4		Vented	312	68	18	**16**	108	6

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

TOYOTA - 4WD / SUV / VAN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
RAV 4														
SXA10	4/94 - 5/00	F	**690**	✓				Vented	302	46	18	**16**	62	5
		R	**691**	✓				Solid	303	58	9	**8**	62	5
ACA20R, ACA22R, ACA23R	5/2000 - 05	F	**692**	✓				Vented	275	49	25	**23**	62	5
		R	**693**	✓				Solid	303	62	9	**8**	62	5
ACA33R	11/2005 - on	F	**2744**	✓				Vented	296	49.5	28	**25**	62	5
		R	**2745**	✓				Solid	281	55	12	**10.5**	62	5
TARAGO / ESTIMA / PREVIA / SIENNA														
YR 20, 21, GL, DLX CR 21 DLX	11/82 - 8/85	F	**157**	PART NOT AVAILABLE REFERENCE ONLY				Vented	255	44.5	20	**19**	74	4
YR 21, 22	8/85 - 1/90	F	**158**	✓				Vented	255	42	20	**19**	74	4
YR 31 4WD	1986 - 1/90	F	**159**	✓				Vented	260	45	25	**24**	95	5
TCR 1, TCR 2 with rear drums	5/90 - 2/00	F	**760**	✓				Vented	255	53	25	**23**	62	5
TCR 1, TCR 2 with ABS	5/90 - 2/00	F	**762**	✓				Vented	271	53	25	**23**	62	5
TCR 1, TCR 2 with rear discs - non ABS	5/90 - 2/00	F	**761**	✓				Vented	279	53	22	**20**	62	5
TCR 1, TCR 2 (Rear)		R	**716**	✓				Vented	291	68.5	18	**17**	60	5
ACR30 Gli, GLX, Ultima	2/00 - 4/03	F	**735**	✓		✓		Vented	276	49.5	28	**26**	62	5
		R	**697**	✓				Solid	291	68.5	12	**10.5**	62	5
ACR30 Gli, GLX, Ultima	4/03 - 1/06	F	**2705**	✓		✓		Vented	296	49.3	28	**26**	62	5
		R	**697**	✓				Solid	291	68.5	12	**10.5**	62	5
ACR50 4DR WAGON GCR50 3DR VAN GCR50 4DR WAGON	2005 - 2007 2007 - 2008 2007 - 2008	F	**2730**					Vented	296	49.5	28	**25**	62	5
		R	**2731**					Solid	298	64.5	10	**8.5**	62	5
TOWNACE / SPACIA														
YR 2#, 39	1992 - 7/00	F	**778**	✓				Vented	255	42	25	**23**	74	4
TERCEL														
4WD	8/82 - 9/90	F	**147**	✓				Solid	243	39.1	11	**10**	54	4
TUNDRA														
4.7L V8 2WD & 4WD	2000 - 05	F	**7420**	4x4		4x4		Vented	318	70.5	28	**26**	108	6
All models	2005 - 08	F	**2724**	4x4		4x4		Vented	354	83.5	32	**29**	112	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DBA DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

TRIUMPH

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
1500 TC	1973 - 76	F	**173**	PART NOT AVAILABLE REFERENCE ONLY				Solid	221	37.5	9.5	**9**	67	4
2000 Mk I	1964 - 70	F	**170**	PART NOT AVAILABLE REFERENCE ONLY				Solid	247.6	32	8.7	**7.75**	67	4
2000, 2500 Mk II 2500 TC 2.5 Pi	1969 - 75 1973 - 78 1970 - 75	F	**171**	PART NOT AVAILABLE REFERENCE ONLY				Solid	247.6	32	12.7	**11.5**	67	4
TR3 late models TR4 early models		F	**163**	PART NOT AVAILABLE REFERENCE ONLY				Solid	280.7	38.2	12.7	**11.4**	79	4
TR3A TR4, TR4A TR5 TR6	1963 - 64 1962 - 67 10/67 - 69 1969 - 75	F	**174**	✓				Solid	275.4	38	12.7	**11.4**	79	4
TR7	1978 - 82	F	**172**	PART NOT AVAILABLE REFERENCE ONLY				Solid	240	57	10	**9**	67	4
Dolomite, Sprint	1975 - 78	F	**173**	PART NOT AVAILABLE REFERENCE ONLY				Solid	221	37.5	9.5	**9**	67	4
Spitfire - MK I, II, III Herald - 12/50 1200 13/60	1962 - 80 1963 - 71 1962 - 71 1967 - 71	F	**2170**	PART NOT AVAILABLE REFERENCE ONLY				Solid	232	26.3	9.6	**8.3**	66.7	4

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLKSWAGEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
BEETLE (CHECK PRODUCTION CODES E.G. IJ-Y.... AND ILS - THESE ARE FOUND INSIDE THE VEHICLES SERVICE BOOK)														
From 1C-X-400 001 1ZM From 1C-X-400 001 1ZP	2000 - on	F	**801**	✓				Vented	280	36.7	22	**19**	65	5
FROM 1C-X-400 001 1ZH, 1ZE, 1ZD		F	**802**	✓				Vented	288	34	25	**23**	65	5
Rear fits all models above		R	**803**	✓				Solid	232	39.5	9	**7**	65	5
From 1C-X-400 001 1LJ 'RSI' Only (V Limited)	2000	F	**838**	✓		✓		Vented	312	34.2	25	**23**	65	5
		R	**800**	✓				Vented	256	36.7	22	**19**	65	5
BORA														
FR. WHEEL DR (14in RIM) 1LQ	1998 - on	F	**800**	✓				Vented	256	36.7	22	**19**	65	5
FR. WHEEL DR (15in RIM)	1998 - on	F	**806**	✓				Vented	280	46.2	22	**20**	68	5
1KT (up to 1J-YP061677)	1998 - on	F	**806**	✓				Vented	280	46.2	22	**20**	68	5
1KT (up to 1J-YW238680)	1998 - on	R	**803**	✓				Solid	232	39.5	9	**7**	65	5
Fr Wheel Dr 1LN, 1LE, 1ZH, 1ZE, 1ZD	1998 - on	F	**833**	✓				Vented	288	28	25	**23**	65	5
V6 4MOTION 1ZQ, 1LJ	1998 - on	F	**838**	✓		✓		Vented	312	34.2	25	**23**	65	5
V6 4WD 16in Rim 1KU, 2EE	1998 - on	R	**800**	✓				Vented	256	36.7	22	**19**	65	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLKSWAGEN

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
GOLF MK1														
1.1L	4/74 - 7/75	F	**240**	✓				Solid	239	35.2	12	**10**	65	4
1.5L	8/76 - 7/83													
1.6L	8/75 - 9/83													
1.6L TD	3/82 - 7/83													
1.8L	3/79 - 10/83													
1.1L	8/75 - 7/83	F	**242**	✓				Solid	239	39	10	**8**	65	4
1.3L	8/78 - 7/83													
1.5L D	8/78 - 7/80													
1.6L D	8/80 - 7/83													
1.6L GTI	8/76 - 7/82	F	**444**	✓				Vented	239	38.5	20	**10**	65	4
1.8L GTI	8/82 - 10/83													
GOLF MK2														
1.0L w/ ABS	8/83 - 10/91	F	**240**	✓				Solid	226	71.2	10	**8**	39.8	4
1.3L w/ ABS	8/83 - 7/92													
1.6L (51/55kW)	8/83 - 12/92													
6L D (Auto)	11/83 - 7/92													
1.6L TD	8/83 - 10/91													
1.8L inc. ABS (Solid Disc)	8/83 - 10/91													
1.8L Syncro 4WD	1985 - 91													
1.8L w/ ABS only (Solid)	8/83 - 10/91	R	**240**	✓				Solid	226	71.2	10	**8**	39.8	4
1.0L wo/ ABS	8/83 - 10/91	F	**242**	✓				Solid	239	39	10	**8**	65	4
1.3L wo/ ABS	8/83 - 10/91													
1.6L (53kW)	8/83 - 10/91													
1.6L D	11/83 - 7/92													
1.8i GTI 16V (Early)	2/86 - 10/88	F	**444**	✓				Vented	239	38.5	20	**10**	65	4
1.8L inc. ABS (Vented Disc)	8/83 - 10/91													
1.8L GT	11/83 - 7/92													
1.8L GTI exc. 16V	11/83 - 7/92													
All above models rear disc	8/83 - 10/91	R	**832**	✓				Solid	226	71.2	10	**8**	39.8	4
1.8i GTI 16V (Late)	10/88 - 91	F	**446**	✓				Vented	256	39	20	**18**	65	4
		R	**832**	✓				Solid	226	71.2	10	**8**	39.8	4

DBA DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

VOLKSWAGEN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
GOLF MK3														
VR6 MK 3 Up to SW 400 000	1994 - 97	F	**835**	✓				Vented	280	28.2	22	**20**	65	5
VR6 MK 3 From to SW 400 001	1994 - 97	F	**833**	✓				Vented	288	28	25	**23**	65	5
All MK 3 models (Rear)	1991 - 97	R	**834**	✓				Solid	226	71.2	10	**8**	39.8	5
GTi - VR6	4/94 - 7/95	F	**835**	✓				Vented	280	28.2	22	**20**	65	5
		R	**834**	✓				Solid	226	71.2	10	**8**	39.8	5
GTi - VR6	8/95 - 98	F	**833**	✓				Vented	288	28	25	**23**	65	5
		R	**834**	✓				Solid	226	71.2	10	**8**	39.8	5
GOLF MK4														
MK 4 1LQ, 1ZF (14in RIM)	1998 - 04	F	**800**	✓				Vented	256	36.7	22	**19**	65	5
MK 4 1LS, 1ZM (15in RIM)	1998 - 04	F	**801**	✓				Vented	280	36.7	22	**19**	65	5
1LN, 1LE, 1ZH, 1ZE, 1ZD	1998 - 04	F	**802**	✓				Vented	288	34	25	**23**	65	5
1ZQ, 1LJ - IV models	1998 - 04	F	**838**	✓		✓		Vented	312	34.2	25	**23**	65	5
All MK 4 models (Rears)	1998 - 04	R	**803**	✓				Solid	232	39.5	9	**7**	65	5
GOLF MK5														
All Models (exc. GTi & R32)	2003 - on	F	TBA					Vented	280		22			
		F	TBA					Vented	288		25			
		R	**2811***					Solid	253	51.5	10	**8**	65	5
		R	**2813***					Solid	256	48.5	12	**10**	65	5
GTi 2.0L 4cyl TURBO	2003 - on	F	**2806**	✓		✓		Vented	312	49.8	25	**22**	65	5
		R	**2807**	✓		✓		Solid	285.6	48.4	11.7	**10**	65	5
R32 3.2L V6	2004 - on	F	**2808**	✓		✓		Vented	345	49.8	30	**27**	65	5
		R	**2809**	✓				Vented	310	48.5	22	**20**	65	5
JETTA														
2.0i 16V TFSI (147kW)	2005 - on	F	**2806**	✓		✓		Vented	312	49.8	25	**22**	65	5
		R	**2807**	✓		✓		Solid	285.6	48.4	11.7	**10**	65	5

***VOLKSWAGEN REVISED THE DIMENSIONS OF THE REAR DISCS FOR THESE MODELS. DBA 2811 WAS 255MM X 10MM AND IS NOW 253MM X 10MM. DBA 2813 WAS 260MM X 12MM AND IS NOW 256MM X 12MM. THESE DISCS WILL FIT THE EARLY VEHICLES PRIOR TO THE REVISION AS WELL AS THOSE VEHICLES AFTER THE REVISION.**

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

VOLKSWAGEN

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
PASSAT														
1.5, 1.6 Variant Diesel 1.5	1973 - 82 1979 - 82	F	**240**	✓				Solid	239	35.2	12	**10**	65	4
1.3 Coupe Diesel 1.5 GLD	1973 - 75 1979 - 82	F	**242**	✓				Solid	239	39	10	**8**	65	4
4WD 4CYL Only	1994 - 97	F	**446**	✓				Vented	256	39	20	**18**	65	4
		R	**832**	✓				Solid	226	71.2	10	**8**	39.8	4
VR6 AAA Engine (2WD)	1994 - 97	F	**833**	✓				Vented	288	28	25	**23**	65	5
		R	**834**	✓				Solid	226	49	10	**8**	39.8	5
ADR 1.8, 4WD Prod. Codes 1LZ, 1ZJ	1996 - 01	F	**806**	✓				Vented	280	46.2	22	**20**	68	5
		R	**810**	✓				Solid	245	63.9	10	**8**	68	5
IV 16" wheels	2001 - on	F	**838**	✓		✓		Vented	312	34.2	25	**23**	65	5
ADR 1LB (up to 3B-X-124107) 4WD 1LB/1ZC (up to 3B-X-124107) AEB, ACK 1LB (up to X-124107)	1996 - 01	F	**836**	PART NOT AVAILABLE REFERENCE ONLY				Vented	282	46	25	**23**	68	5
ADR 1ZC (from 3B-X-124107) 4WD 1LB/1ZC (from 3B-X-124107) AEB, ACK 1ZC (from X-124107) + all 1LB, 1ZC, 1LE from 3B-Y-000001	1996 - 01	F	**833**	✓				Vented	288	28	25	**23**	65	5
Rear fits all models above		R	**810**	✓				Solid	245	63.9	10	**8**	68	5
GP all ATE 1ZC (15in RIM) 4MOTION 1ZC/1LE (15in RIM)	2001 - on	F	**833**	✓				Vented	288	28	25	**23**	65	5
GP all ATE 1LT (16in RIM) 4MOTION 1LT (16in RIM)	2001 - on	F	**838**	✓		✓		Vented	312	34.2	25	**23**	65	5
Rear all GP ATE models	2001 - on	R	**810**	✓				Solid	245	63.9	10	**8**	68	5
Rear 4MOTION 1ZC/1LE (16in RIM)	2001 - on	R	**800**	✓				Vented	256	36.7	22	**19**	65	5
W8 4MOTION 1LC (17in RIM)	2001 - on	F			NOT AVAILABLE				334		32			
		R	**800**	✓				Vented	256	36.7	22	**19**	65	5
2.3 V5 / 4Motion, 2.8 V6 4Motion" Turbodiesel 2.5 V6 Tdi / 4Motion	11/00 - 05	F	**2800**	✓		✓		Vented	312	46.2	25	**23**	68	5
1.6i, 1.6i 16V FSI, 2.0i 16V FSI, 1.9 TDI, 2.0 16V TDI 103/125kW 2.0i 16V TFSI	4/05 - on 4/05 - on 8/05 - on	F	**2806**	✓		✓		Vented	312	49.8	25	**22**	65	5
Rear fits all models above		R	**2807**	✓		✓		Solid	285.6	48.4	11.7	**10**	65	5
POLO														
Polo	1995 - ON	F	**837**	✓				Vented	239	34	18	**16**	65	4

dba™ DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLKSWAGEN COMMERCIAL

TOUAREG

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
All models 16" wheels	10/02 - on	F	**2242**	4x4		4x4		Vented	308	55.6	29.5	**25.5**	76	5
3.2 V6, 2.5 R5 TDI, 30 V6		R	**2243**	4x4				Vented	314	76	22	**18**	76	5
All models 17" wheels	10/02 - on	F	**2244**	4x4				Vented	330	69	32	**30**	85	5
		R	**2245**	4x4				Vented	330	74	28	**26**	85	5
All models 18" & 19" wheels	10/02 - on	F	**42246**			4x4		Vented	350	69	34	**32**	85	5
		R	**42245**			4x4		Vented	330	74	28	**26**	85	5

VOLKSWAGEN

1300, 1500, 1600 1600 L, John929 S, LS	1965 - 75 1970 - 77	F	**243**	PART NOT AVAILABLE REFERENCE ONLY	Solid	278	63	9.5	**8**	HUB	4
Kombi	1970 - 7/72	F	**245**	PART NOT AVAILABLE REFERENCE ONLY	Solid	278	82.5	13	**11.5**	66	5
Kombi	8/72 - 7/79	F	**246**	PART NOT AVAILABLE REFERENCE ONLY	Solid	278	86	13	**11.5**	66	5
Kombi	8/79 - 9/85	F	**442**	PART NOT AVAILABLE REFERENCE ONLY	Solid	278	82.5	13	**11.5**	HUB	5

4x4 This symbol denotes that this part number is offered as a DBA 4X4 Survival Series disc, and is available under its heading (e.g. S = Slotted, 4000 series = Slotted, XS etc) and also available as a plain standard finish rotor

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLKSWAGEN COMMERCIAL

TRANSPORTER / CARAVELLE

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
T2, U.S.A Vanagon 2WD	8/85 - 92	F	**443**					Solid	258	54	16	**13**	HUB	5
								Floating Caliper Rear Drum Brakes for these models						
14" rims (up to 70-T-199 999)	1LA	F	**447**	✓				Solid	260	64.5	16	**13**	68	5
T4 1.8L, T4 2.0L / Diesel 1.9L	9/90 - 96							Girling Rear Drum Brakes for these models						
15" rims (up to 70-T-199 999)	ILP	F	**448**	✓				Solid	282	64.5	18	**15**	68	5
T4 2.0L / Diesel 1.9L	9/92 - 96							Girling Rear Drum Brakes for these models						
Syncro 4WD, Euro Van 2.4L	9/92 - 96													
15" rims (up to 70-T-199 999)	ILE	F	**449**	✓				Vented	280	64.5	24	**20**	68	5
T4 2.5L / Diesel 2.4L	9/90 - 6/96							Girling Rear Drum Brakes for these models						
Syncro 4WD, Euro Van 2.4L	11/92 - 6/96													
15" rims (from 70-T-200001	ILP	F	**830**	✓				Solid	282	55	18	**15**	68	5
T4 Caravelle / Multivan	6/96 - 03							Lucas Rear Disc Brakes DBA-831						
15" rims (from 70-T-200000)	ILE, ILU	F	**548**	✓				Vented	280	54	24	**20**	68	5
T4 2.5L TDi 111kW	6/96 - 03							Lucas, ITT Rear Disc Brakes DBA-831						
Transporter, Multivan, Caravelle								Square or Curved Pads						
all rear disc brake models	6/96 - 03	R	**831**	✓				Solid	280	40	12	**10**	68	5

(CHECK PRODUCTION CODES E.G.70-T-199.... AND ILE - THESE ARE FOUND INSIDE THE VEHICLES SERVICE BOOK)

DISC BRAKES AUSTRALIA

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLKSWAGEN COMMERCIAL

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
T5 - TRANSPORTER + MULTIVAN														
T5 - 16" wheels	04/03 - on	F	**2242**	✓		✓		Vented	308	55.6	29.5	**25.5**	76	5
T5 - 17" wheels	04/03 - on	F	**2248**					Vented	333	55.6	33	**28.5**	76	5
T5 4motion - 16" wheels	07/04 - on	F	**2242**	✓		✓		Vented	308	55.6	29.5	**25.5**	76	5
T5 4motion - 17" wheels	07/04 - on	F	**2248**					Vented	333	55.6	33	**28.5**	76	5
T5 - Rear All Models	04/03 - on	R	**2247**	✓		✓		Vented	294	44.4	22	**19.5**	76	5
LT (II)														
28	05/96 - 01	F	**566**	✓				Vented	276	77	22	**19.5**	85	5
		R	**2267**					Solid	258	96.5	12	**10**	85	5
35	05/96 - 01	F	**566**	✓				Vented	276	77	22	**19.5**	85	5
		R	**567**					Solid	272	97	16	**14**	85	5
46	05/96 - 01	F	**566**	✓				Vented	276	77	22	**19.5**	85	5
		R	**2268**					Solid	285	93	22	**19**	120	6

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLVO

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
140 / 160 SERIES														
142, 144, 145, 164, P1800 ATE Brakes	1968 - 75	F	**384**	✓				Solid	272	69	12.7	**11.4**	68	5
		R	**680**	✓				Solid	295	88.3	9.6	**8.6**	68	5
164 Girling Brakes	1968 - 75	F	**681**	✓				Solid	272	70.5	14.3	**13.1**	68	5
		R	**680**	✓				Solid	295	88.3	9.6	**8.6**	68	5
240 / 260 SERIES														
240, 260 Series	1974 - 93	F	**380**	✓				Solid	263	65	14.5	**13.1**	68	5
240, 260 Series DB 62 Pads ATE Calipers	1975 - 93	F	**382**	✓				Vented	263	64.3	24	**22.8**	68	5
240, 260 Series DB 549 Pads Girling Calipers	1976 - 93	F	**383**	✓				Vented	263	67.5	22	**20.4**	68	5
	1974 - 93	R	**381**	✓				Solid	281	73.5	9.6	**8.4**	68	5
360 SERIES														
GLE, GLT Hatch	1984 - 91	F	**687**	✓				Solid	239	29	12.7	**11.4**	68	4
740 SERIES														
GLE 14 inch Wheel GLE 15 inch Wheel/Turbo Non ABS	1984 - 88	F	**684**	✓	Girling Brakes Hub Seal No. 1329820-3				262.5	56	22	**20**	HUB	5
GLE 14 inch Wheel GLE 15 inch Wheel/Turbo	1984 - 88	F	**683**	✓	Bendix Brakes Hub Seal No. 1329820-3				287	56	22	**20**	HUB	5
GLE 14 inch Wheel	1988 - 92	F	**685**	✓				Vented	262.5	56	22	**20**	68	5
GLE 15 inch Wheel/Turbo	1980 - 1/92	F	**686**	✓				Vented	287	56	22	**20**	68	5
GLE with ABS	1991 - on	F	**688***	✓				Vented	280	56	26	**24**	68	5
All Rears Not Multilink	1984 - 1/92	R	**381**	✓				Solid	281	73.5	9.6	**8.4**	68	5
With Multilink	1984 - 1/92	R	**689**	✓				Solid	265	26	10	**8**	68	5

SPECIAL NOTE: *Easy Identification: DBA 688 Late Model Vehicles with ABS
" JUMBO " This particular disc has the single piston caliper fitted to it.

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLVO

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
760 SERIES														
GLE V6 Bendix Brakes Hub Seal No.1329820-3 (can use DBA 683)	2/83 - 1/84	F	**682**	✓				Vented	287	52	22	**20**	HUB	5
GLE V6, 4 Cyl. Turbo Bendix Brakes Hub Seal No. 1329820-3	1984 - 88	F	**683**	PART NOT AVAILABLE REFERENCE ONLY				Vented	287	56	22	**20**	HUB	5
GLE V6	1988 - 90	F	**686**	✓				Vented	287	56	22	**20**	68	5
GLE with ABS	1991 - on	F	**688***	✓				Vented	280	56	26	**24**	68	5
Without Multilink	1983 - 87	R	**381**	✓				Solid	281	73.5	9.6	**8.4**	68	5
With Multilink	1988 - on	R	**689**	✓				Solid	265	26	10	**8**	68	5
850 SERIES														
GLE / GLT 4 Stud Wheel	1993 only	F	**880**	✓				Vented	280	50.5	26	**23**	68	4
		R	**881**	✓				Solid	295	72	9.6	**8.4**	68	4
GLE / GLT 5 Stud Wheel 5 lug - USA	1994 - on 1993 - 97	F	**882**	✓		✓		Vented	280	50.5	26	**23**	68	5
		R	**883**	✓				Solid	295	72.5	10	**8.4**	68	5
940 SERIES														
940 GL/GLE with ABS	1990 - on	F	**688**	✓				Vented	280	56	26	**24**	68	5
940 GL, GLE, SE, Turbo Not Multilink		R	**381**	✓				Solid	281	73.5	9.6	**8.4**	68	5
960 SERIES														
960	1994 - 96	F	**688**	✓				Vented	280	56	26	**24**	68	5
		R	**381**	✓				Solid	281	73.5	9.6	**8.4**	68	5
960 With Multilink (Sedan Only)	1991 - 94	R	**689**	✓				Solid	265	26	10	**8**	68	5
C70 COUPE / CABRIOLET														
C70 15" Wheels	3/97 - 09/02	F	**882**	✓		✓		Vented	280	50.5	26	**23**	68	5
C70 Rear 2WD	3/97 - 9/02	R	**883**	✓				Solid	295	72.5	10	**8.4**	68	5
C70 Rear 4WD	3/97 - 9/02	R	**884**	PART NOT AVAILABLE REFERENCE ONLY				Solid	283	62	10	**8**	68	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

DISC BRAKES AUSTRALIA

VOLVO

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
S40														
S40 all models	7/95 - 6/97	F	**885**	✓				Vented	256	46	24	**21.5**	69	4
S40 all models	7/97 - 12/03	F	**886**	✓				Vented	281	46	24	**21.5**	69	4
S40 Rear - all models	7/95 - 12/03	R	**887**	✓				Solid	260	41	10	**8.4**	90	4
S40 II														
S40 II 15” wheels	01/04 - on	F	**2118**	✓				Vented	278	48.5	25	**23**	64	5
S40 II 16” wheels	01/04 - on	F	**2380**	✓				Vented	300	48.5	25	**23**	64	5
S60														
S60 15” wheels	11/00 - on	F	**2382**	✓				Vented	286	50.3	26	**23**	68	5
S60 16” wheels	11/00 - on	F	**2384**	✓				Vented	305	50.3	28	**25**	68	5
S60 Rear 15” & 16” wheels	11/00 - on	R	**2383**	✓				Solid	288	65	12	**10**	68	5
S70														
S70 15” wheels	1/97 - 11/00	F	**882**	✓		✓		Vented	280	50.5	26	**23**	68	5
S70 Rear 2WD	1/97 - 11/00	R	**883**	✓				Solid	295	72.5	10	**8.4**	68	5
S70 Rear 4WD	1/97 - 11/00	R	**884**	✓				Solid	283	62	10	**8**	68	5
S80														
S80 15” wheels	5/98 - on	F	**2382**	✓				Vented	286	50.3	26	**23**	68	5
S80 16” wheels	5/98 - on	F	**2384**	✓				Vented	305	50.3	28	**25**	68	5
S80 Rear 15” & 16” wheels	5/98 - on	R	**2383**	✓				Solid	288	65	12	**10**	68	5
S90														
S90 All models	1/97 - 05/98	F	**882**	✓		✓		Vented	280	50.5	26	**23**	68	5
V40														
V40 all models	7/95 - 6/97	F	**885**	✓				Vented	256	46	24	**21.5**	69	4
V40 all models	7/97 - 12/03	F	**886**	✓				Vented	281	46	24	**21.5**	69	4
V40 Rear - all models	7/95 - 12/03	R	**887**	✓				Solid	260	41	10	**8.4**	90	4
V50														
V50 15” wheels	04/04 - on	F	**2118**	✓				Vented	278	48.5	25	**23**	64	5
V50 16” wheels	04/04 - on	F	**2380**	✓				Vented	300	48.5	25	**23**	64	5
V70														
V70 15” wheels	1/97 - 05/00	F	**882**	✓		✓		Vented	280	50.5	26	**23**	68	5
V70 Rear 2WD	1/97 - 05/00	R	**883**	✓				Solid	295	72.5	10	**8.4**	68	5
V70 Rear 4WD	1/97 - 05/00	R	**884**	✓				Solid	283	62	10	**8**	68	5

DISC BRAKES AUSTRALIA

The Kangaroo Paw design is not available on all part numbers, ask your supplier for details.

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

VOLVO

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F
V70 II														
V70 II 15” wheels	03/00 - on	F	**2382**	✓				Vented	286	50.3	26	**23**	68	5
V70 II 16” wheels	03/00 - on	F	**2384**	✓				Vented	305	50.3	28	**25**	68	5
V70 II Rear 15” & 16” wheels	03/00 - on	R	**2383**	✓				Solid	288	65	12	**10**	68	5
V90														
V90 All models	1/97 - 05/98	F	**882**	✓		✓		Vented	280	50.5	26	**23**	68	5
XC70 CROSS COUNTRY														
XC70 15” wheels	03/00 - on	F	**2382**	✓				Vented	286	50.3	26	**23**	68	5
XC70 16” wheels	03/00 - on	F	**2384**	✓				Vented	305	50.3	28	**25**	68	5
XC70 Rear 15” & 16” wheels	03/00 - on	R	**2383**	✓				Solid	288	65	12	**10**	68	5
XC90 CROSS COUNTRY														
XC90 16” wheels	10/02 - on	F	TBA					Vented	316	50.4	28	**25**	68	5
XC90 17” wheels	10/02 - on	F	TBA					Vented	336	51.3	30	**27**	68	5
XC90 Rear all models	10/02 - on	R	TBA					Solid	308	65	20	**18**	68	5

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.

CONTENTS

VEHICLE MAKE	PAGE #	VEHICLE MAKE	PAGE #
BMW	206	LEYLAND	214
CHRYSLER	206	MAZDA	215
DAEWOO	207	MAZDA COMMERCIAL	215
DAIHATSU	207	MITSUBISHI	215
DAIHATSU COMMERCIAL	207	MITSUBISHI COMMERCIAL	216
FORD	208	NISSAN	217
FORD COMMERCIAL	209	NISSAN COMMERCIAL	218
HOLDEN	211	PORSCHE	219
HOLDEN COMMERCIAL	212	ROVER	219
HONDA	212	SUZUKI	219
HYUNDAI	213	TOYOTA	220
JEEP	213	TOYOTA COMMERCIAL	221
KIA	214		
LANDROVER	214		

DRUM BRAKES

BMW

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
1502 1600, 1602 E10 1802, 1802T E10 2002 Cabrio, Ti, E10 2002 Touring, Tii	1975 - 77 1967 - 73 1971 - 75 1969 - 75 1969 - 75	R	**1800**	E1462 Shoes	230	47	58	59	231	4
1800 E10 2000 E10 2002 Turbo E10 318, 318 i, 320 i E21 320/4, 320/6 E21	1963 - 67 1966 - 69 1973 - 75 1976 - 82 1976 - 82	R	**1801**	E1461 Shoes	250	47	58	63.5	251	4
2800 CS E3 520 i E12 518, 518 i, 520/4 E12 520/6 E12	1968 - 71 1968 - 71 1972 - 79 1977 - 6/81	R	**1802**	E1461 Shoes	250	47	75	63.5	251	5
316 i, 318 i E30	1982 - 91	R	**1803**	E1354/1	228.5	57	62	59	229.5	4
316 i, 318 i E36	9/90 - on	R	**1804**	E1354/1	228.5	47	75	59	229.5	5

dba™ DISC BRAKES AUSTRALIA

CHRYSLER

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
Valiant VH, VJ, VK, CH, CJ, CK, CL	1972 - 78	R	**1720**	Large Centre Hole E1264 Shoes	228.6	54	71.5	73	229.6	5
Neon		R	**1721**		200	39	57.5	60.5	201	5
Voyager		R	**1722**	E1756	250	65	72	78	251	5

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

DAEWOO

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
Cielo, Lanos, Espero, Nubria	2/95 - on	R	**1680**	E1710	200	53	57	67	201	4

DAIHATSU

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
CHARADE										
G100 G102 G200, G202, G203	1/87 - 94 1/90 - 93 1/89 - on	R	**1690**	E1658	180	36	HUB	72.5	181	4
G102	1/90 - 93	R	**1691**	E1682	200	41	56	56.5	201	4
MIRA										
L200, L201	1990 - on	R	**1692**	E1688	228	60	67	69	230.6	5
MOVE										
L601	1997 - on	R	**1692**		228	60	67	69	230.6	5
TERIOS										
5 DR Sedan	1997 - on	R	**1693**	E1747	228.6	53.5	66.5	69	230	5

dba™ DISC BRAKES AUSTRALIA

DAIHATSU COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
ROCKY										
Turbo & Non Turbo	1984 - on	R	**1694**	E1607	254	52	107	66	255	5
FEROSA										
F300, F301	1988 - on	R	**1694**	E1607	254	52	107	66	255	5

DRUM BRAKES

FORD

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
CORSAIR										
UA	1989 - 92	R	**1700**	E1656	228.6	54	68	67	229.5	4
FALCON										
XB, XC, XD, XE, XF	10/75 - 86	R	**1610**	E1271 Shoes	10" or 254	2 23/16" or 55	2 3/4" or 70	2 11/16" or 68.5	10.060" or 255.5	5
FAIRLANE										
Fairlane ZG, ZH, ZJ	10/75 - 81	R	**1610**	E1271 Shoes	10" or 254	2 23/16" or 55	2 3/4" or 70	2 11/16" or 68.5	10.060" or 255.5	5
LASER										
KA, KB	1981 - 85	R	**1611**	E1394	180	36	HUB	55	181	4
KC, KE } Not Wagon KF - KH} " "	1985 - 91	R	**1612**	E1604	200	32	HUB	65.5	201	4
Wagon	1985 - 89	R	**1613**	E1637	228.6	32.5	HUB	66.5	229.5	4
KF - KH KJ, KJ Series II	1991 - on	R		E1671 E1685	200	42	55	58	201	4
METEOR										
GA. GB	1981 - 85	R	**1611**	E1394	180	36	HUB	55	181	4
GC, GE	1985 - 89	R	**1612**	E1604	200	32	HUB	65.5	201	4
Wagon	1985 - 89	R	**1613**	E1637	228.6	32.5	HUB	66.5	229.5	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

FORD COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
BRONCO										
Bronco	1981 - 87	R	**1620**	E1323 Shoes	11.020" or 280	2 3/4" or 70	2 7/8" or 73	3 5/8" or 92	11.090" or 281.6	5
COURIER										
1.8, 2.0 2.0, 2.2, 2.6	1979 - 84 1984 - on	R	**1627**	E1389 Shoes	260	50	93	62	261	6
ECONOVAN / MAXI / SPECTRON										
1800, 2000,2200 Single Rear Wheel Except 1800 SWB	1/84 - on	R	**1625**		260	63	93	76	261.5	6
F100 / F150 SERIES										
F100 2WD, 4WD	79 - 12/86	R	**1620**	E1323 Shoes	11.020" or 280	2 3/4" or 70	2 7/8" or 73	3 5/8" or 92	11.090" or 281.6	5
F150 2WD, 4WD	1987 - on	R	**1630**	E1323	280	70	88	92	286.1	5
F250 SERIES										
F250 Not semi-floating axle	1974 - 85	R	**1621**	1621A 9/16" Studs (14mm holes) 1621B 5/8" Studs (16mm holes) E1014	12" or 304.8	3" or 76	4 11/16" or 119	4 3/4" or 120	12.060" or 306.3	8
F350 SERIES										
F350 Super Cab F350 2WD (SRW)	1974 - 79 1980 - 85	R	**1622**	* Rare * * Model *	12" or 304.8	3 5/8" or 92	5 3/8" or 136.5	5" or 127	12.060" or 306.3	8
F350 2WD (DRW)	10/71 - 83	R	**1628B**	PART NOT AVAILABLE REFERENCE ONLY	12" or 304.8	3 9/16" or 90	5 5/16" or 135	7 7/32" or 180	12.090" or 307	8
F350 4WD (DRW)	80 - 89	R	**1628B**	PART NOT AVAILABLE REFERENCE ONLY	304.8	90	135	180	307	8
MAVERICK										
GY, KY	1988 - 93	R	**1709**	E1668 Shoes	295	72	111	85	296.5	6

dba™ DISC BRAKES AUSTRALIA

DRUM BRAKES

FORD COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
RAIDER										
Raider 2.6L 4WD	1987 - 10/98	R	**1625**	E1665	260	63	93	76	261.5	6
RANGER										
4X2, 4X4 - 3.0L models	2007- on	R	**1642**		295	67	93	80.8	296.5	6
TRANSIT										
80-100-115-120	8/91 - on	R	**1640**	E1738	254	57.5	132	96	255.5	5
100-115-120-130-150-190	8/91 - on	R	**1641**	E1737	280	75.5	142.5	132.5	281.5	6

dba™ DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

HOLDEN

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
APOLLO										
JM	3/93 - on	R	**1603**	E1747	228.6	56	62	71	230	5
ASTRA										
TR	9/96 - on	R	**1680**	N1710	200	53	57	67	201	4
BARINA										
MF, MH	1/89 - 94	R	**1608**	E1616	180	36	HUB	74	181	4
SB without ABS	1994 - on	R	**1609**	E1705	200	35	HUB	84	201.4	4
COMMODORE										
VB, VC, VH, VK, VL, 6 cyl., 8 cyl.	1978 - 88	R	**1605**	E1385 Shoes	9.055” or 230	2 5/16” or 58	2 3/4” or 69	2 15/16” or 74.5	9.115” or 231.5	5
VC, VH, 4 cyl.	1980 - 83	R	**1606**	E1385 Shoes	9.055” or 230	2 5/16” or 58	2 3/4” or 69	2 15/16” or 74.5	9.115” or 231.5	5
EARLY SERIES - HQ										
HQ, HJ HX, HZ WB Utility, Panel Van	1971 - 76 1976 - 80 1980 - 84	R	**1604**	E1337 Shoes	10” or 254	2” or 50.8	2 13/16” or 71.5	2 3/4” or 69	10.060” or 255.5	5
GEMINI										
TX, TC, TD	3/75 - 4/78	R	**1600**	E1174 Shoes	9” or 228.6	2 1/8” or 54	2 1/8” or 54	2 5/8” or 67	9.060” or 230.1	4
RB FWD	5/85 - 87	R	**1601**	E1601	180	42	HUB	65.5	182	4
NOVA										
TX, TC, TD	3/75 - 4/78	R	**1600**	E1174	228.6	54	54	67	230.1	4
LE, LF, LG	1989 - on	R	**1602**	E1379 E1490	200	55	54	65.5	201.4	4
TORANA										
LC 6 cyl. LH 4, 6 cyl. LH 4, 6 cyl.	1969 - 72 1974 - 76 1974 - 76	F	**1607** **U/A**	No Longer Available in Australia	9” or 228.6	2 1/8” or 54	2 13/32” or 61	3 5/32” or 80	9.060” or 230.1	5

DISC BRAKES AUSTRALIA ™

DRUM BRAKES

HOLDEN COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
COMBO										
SB Van	2/1996 - on	R	**1650**	E1732	230	59.5	57	75.5	231.2	4
FRONTERA										
UT 2.0 Litre	3/1995 - on	R	**1651**	E1662	254	61.5	95	75	255.5	6
JACKAROO										
UBS 13, 52, 16, 521,	11/81 - 91	R	**1652**	E1595	254	61	96.5	71	255.5	6
522, 17, 55				E1662						
RODEO										
All models 2WD All models 4WD	1980 - on 80 - 11/96	R	**1652**	E1402 E1595	254	61	96.5	71	255.5	6
4WD	11/96 - 02	R	**1653**	T.B.A.	295	61	97	80	296.5	6
All models EXCEPT 4WD Hi-Ride Susp.	up to 11/02	R	**1654**		254	62.5	101	71	255.5	6
V6 4WD Hi-Ride Susp.	2002 - on	R	**1655**		295	59	101	80.6	296.5	6
SHUTTLE										
WFR	1982 - 90	R	**1652**	E1402 E1413	254	61	96.5	71	255.5	6

HONDA

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
ACCORD										
SJ	1977 - 12/81	R	**1823**	E1352 E1397	180	44.5	HUB	60.5	181	4
SY, AD	1982 - 12/85	R	**1824**	E1613	200	42.5	HUB	72	201	4
CA	1/86 - 89	R	**1825**	E1614	200	42.5	61	59	201	4
CIVIC										
SB, SC, SE, SF	1973 - 79	R	**1820**	E1352 E1397	180	43	HUB	72	181	4
SL, WC	1980 - 83	R	**1821**	E1393	180	34	HUB	51	181	4
AL, ED EG, EH, EK All models	1984 - 91 1990 - 96	R	**1822**	E1610	180	37	61	62	181	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

HYUNDAI

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
EXCEL										
HA3	8/89 - 7/92	R	**1670**	E1679	180	46.5	HUB	71.5	181	4
	8/92 - 5/96	R	**1671**	E1701	180	46.5	HUB	71.5	181	4
	6/96 - on	R	**1672**		180	42	HUB	70	182	4
Excel X3 1.5L	6/96 - on	R	**1677**		180	53.25	76	58.4	182	4
LANTRA										
KF2, KF3	5/1991 - on	R	**1673**	E1702 E1703	203	47	HUB	71.5	204	4
S / COUPE										
S / Coupe	5/90 - 7/92	R	**1670**	E1679	180	46.5	HUB	71.5	181	4
	7/92 - on	R	**1671**	E1695 E1701	180	46.5	HUB	71.5	181	4
SANTA FE / TRAGET										
V6 DOHC	9/2000 - on	R	**1676**		253.7	69.5	76	78.5	256	5
SONATA										
AF2, AF3	1988 - 94	R	**1674**	E1675	225	55	90	72	226.5	4
	1994 - 97	R	**1675**		228.6	55	90	63	230	4

dba™ DISC BRAKES AUSTRALIA

JEEP

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
CJ Series	1976 - 78	R	**1790**	E1470	279.4	80		95	281	5
	1978 - 86	R	**1791**	E1471	254	54	112	70	255.5	5
Cherokee	1979 - 91	R	**1792**	E1529	279.4	65	78	84	281	6
Cherokee 4WD	1994 - on	R	**1793**	E1715	229	77	72	90	230	5
		R	**1794**	E1716	254	75	72	102	255.5	5

DRUM BRAKES

KIA

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
Mentor	1993 - on	R	**1660**	E1753	200	42	57	58	201	4
Sportage	1995 - on	R	**1661**	E1754	250	68	43	81	251.4	5

LANDROVER

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
DEFENDER										
110 Series, 130 Series	1990 - on	R	**1751**		279.4	68	114	88	281	5
LANDROVER										
109 Series 2.5L	1971 - 85	F & R	**1751**	E1420 E1092	279.4	68	114	88	281	5
109 Series 2.6L – 14.5mm Stud Holes	1968 - 81	R	**1750**		279.4	68	114	88	281	5
109 Series 2.6L, 3.5 V8 110 Series 2.25, 2.5, 3.5 L	1971 - 85 1970 - 90	R	**1751**		279.4	68	114	88	281	5

LEYLAND

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
Mini Van Mini Moke	1964 - 79	F R	**1810**	E1332 E1333	177.8	47.5	74	60	179.3	4
Cooper	1962 - 65	R	**1810**	E1332	177.8	47.5	74	60	179.3	4
Copper S, Clubman GT	1965 - 71	R	**1811**	E1332 E1333	177.8	47.5	74	83	179.3	4

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trac

DRUM BRAKES

MAZDA

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
323 FWD 1.5, 1.3 BD 103, 51, EM 355	1981 - 85	R	**1611**	E1394 Shoes	180	36	HUB	55	181	4
323 FWD	1985 - 89	R	**1612**	E1604	200	32	HUB	65.5	201.4	4
323 FWD Wagon	1985 - 89	R	**1613**	1637	228.6	32.5	HUB	66.5	229.5	4
626 RWD 929	1978 - 82 1978 - 80	R	**1614**	E1348 E1408	228.5	50	NO HOLE	62	229.6	4

MAZDA COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
E1600, E1800 Single Rear Wheel E2000, E2200 Except Wagon B2000, B2200, B2600	1983 - 11/86	R	**1625**	E1587	260	63	93	76	261.5	6
B1800, B2000	1982 - 84	R	**1627**	E1389 E1411	260	50	93	62	261	6

MITSUBISHI

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
Sigma GE, GH, GJ, GK, GN	1978 - 87	R	**1700**	E1384 E1384i	228.6	54	68	67	230	4
Sigma GE, GH, GJ, GK, GN With Jap Diff	1978 - 87	R	**1700A**	E1384 E1384i	229	51	68	62.5	230	4
Lancer CA, CB	1988 - 93	R	**1725**	E1677 E1681	180	39	HUB	71.5	181	4
Lancer CC	10/92 - on	R	**1726**	E1699	203	42	64	64.5	204.2	4
Lancer CC, CE Mirage CE 1500, 1800	10/92 - on	R	**1727**	E1681	180	46	64	66	181	4
Pajero IO Series	1999 - on	R	**1728**		229	38.5	90	59.5	230.6	5

dba™ DISC BRAKES AUSTRALIA

DRUM BRAKES

MITSUBISHI COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
L200										
Petrol	1980 - 85	R	**1780**	E1444	241	58	93.5	80.5	242.7	6
Diesel	1982 - 85	R	**1781**	E1594	254	62	93.5	83	255.4	6
L300										
SB, SC, SD, SE All Models AWD	1982 - 9/86 1983 - on	R	**1781**	E1594 E1593	254	62	93.5	83	255.4	6
SF, SG, SH WA 2.0 Litre	10/86 - on 1994 - on	R	**1782**	E1594 -	254	62	75	70.5	255.4	5
SA	1980 - 82	R	**1783**	PART NOT AVAILABLE REFERENCE ONLY						
WA 2.4 Litre	1994 - on	R	**1784**							
WA 2.4 Litre V6	1994 - on	R	**1785**							
PAJERO										
NA, NB, NC, ND, NE, NF, NG	1/83 - 5/91	R	**1781**	E1594	254	62	93.5	83	255.4	6
NH	1991 - on	R	**1786**		254	62	83	93.5	256	6
10 Series	1999 - on	R	**1728**		229	38.5	90	59.5	230.6	5
TRITON										
ME, MF, MG, MH, MJ, 2WD ME, MF, MG, MH, MJ 4WD MK 4WD	10/86 - 12/96 1997 - on	R	**1781**	E1594	254	62	93.5	83	255.4	6

dba TM DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

NISSAN

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
1600										
510 Sedan + Wagon	1968 - 73	R	**1700**	E1339	228.6	54	68	67	230	4
510 Sedan + Wagon With Jap Diff	1968 - 73	R	**1700A**	E1339	229	51	68	62.5	230	4
180B										
610 Sedan + Wagon	1972 - 77	R	**1700**	E1339	228.6	54	68	67	230	4
610 Sedan + Wagon With Jap Diff	1972 - 77	R	**1700A**	E1339	229	51	68	62.5	230	4
200B										
810	10/77 - 81	R	**1700**	E1344 E1386	228.6	54	68	67	230	4
810 With Jap Diff	10/77 - 81	R	**1700A**	E1344 E1386	229	51	68	62.5	230	4
BLUEBIRD										
910 Sedan + Wagon	1981 - on	R	**1700**	E1384 E1384/3	228.6	54	68	67	230	4
910 Sedan + Wagon With Jap Diff	1981 - on	R	**1700A**	E1384 E1384/3	229	51	68	62.5	230	4
GAZELLE										
S12	1/84 - 4/85	R	**1700**	E1386	229	54	68	67	230	4
PINTARA										
U12	11/89 - 10/92	R	**1700**	E1656	229	54	68	67	229.5	4
N14 N15	10/91 - 9/95 10/95 - on	R	**1701**	E1697	180	37.5	68	57.5	181	4
SKYLINE										
C120 R30	3/78 - 2/81 3/81 - 6/86	R	**1700**	E1386	229	54	68	67	229.5	4
STANZA										
A10 Coupe, Sedan	1979 - 83	R	**1700**	E1384 E1386	228.6	54	68	67	230	4
A10 Coupe, Sedan With Jap Diff	1981 - on	R	**1700A**	E1384 E1386	229	51	68	62.5	230	4

dba™ DISC BRAKES AUSTRALIA

DRUM BRAKES

NISSAN COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
520 / 620 / 720										
720 2WD 720 4WD	1979 - 12/82 9/79 - 3/83	R	**1707**	E1075 E1400	254	51	90	56	255.5	6
720 2WD 720 4WD	1983 - 8/85	R	**1708**	E1584	254	55	90	69	255.5	6
NAVARA										
D21 2WD	9/85 - 8/89	R	**1706**	E1584 E1612	254	56	101	80.5	255.6	6
D21 4WD	8/89 - 97	R	**1704**		295	69	100.5	88.5	297	6
D21 2WD	8/89 - 97	R	**1716**	E1584	260	63.5	100.5	73	262	6
D22 2WD, 4WD	2/97 - on	R	**1704**	N1726	295	69	100.5	88.5	297	5
NOMAD										
GC22 Van	1986 - 93	R	**1700**		228.6	54	68	67	229.5	4
PATHFINDER										
WD21 (Z24) VG30	8/89 - 7/92 7/92 - on	R	**1702**	E1652	260	63.5	100.5	73	262	6
VG33 (R50)	9/95 - on	R	**1703**		295	67.7	100.4	88.5	296.5	6
PATROL										
MQ Series	1/81 - 12/87	R	**1705**	E1404 E1597	270	65.5	102	74	271.5	6
GQ Series Wagon	1988 - on	R	**1709**	E1668	295	75	111	85	296.5	6
URVAN										
E23 Diesel Some	85 - on	R	**1708**	N1584	254	55	90	69	255.5	6
E23	11/80 - 86	R	**1715**	E1075 E1400	254	52	90	59.5	255.5	6
E24	3/87 - 93	R	**1716**	E1584	260	63.5	100.5	73	262	6
UTE										
XFN, DX, ST	1989 - 91	R	**1610**	E1271	254	55	70	68.5	255.5	5

dba DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

PORSCHE

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
924	1977 - 82	R	**1850**		230	50.5	AXLE SPLIN	63.2	232	4

ROVER

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
QUINTET										
All Models	1983 - on	R	**1821**	E1393	180	34	HUB	51	181	4

SUZUKI

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
SIERRA										
SJ40/410/413/SJ 50 Series1-5	1983 - 86	R	**1830**	E1539, E1627	228.6	49	57	61	230	5
SJ50 Series 6+7 SJ 413 Series 8+9	1996 - on	R	**1831**	E1628	220	52	57	63	222	5
SWIFT										
SA310, 413	1985 - 88	R	**1832**	E1616	180	43	HUB	63	182	4
SF310 / 413 3+5 Door	1989 - 94	R	**1833**		180	43	HUB	63	182	4
SF413 4 Door / SF 416	1989 - 98	R	**1834**		200	40	64	56	202	4
VITARA										
2 Door Series 1, 2, 3	1988 - 97	R	**1835**	E1691	220	42	50	61	222	5
4 Door Series 1, 2, 3	1988 - 97	R	**1836**	E1758	254	53	50	66	255.6	5
2 Door Series 4	1991 - 98	R	**1837**	E1683	220	41	100	61	221.5	5
4 Door Series 4	1991 - 98	R	**1838**	E1735	254	54	100	66	255.6	5
Grande	1998 - on	R	**1839**		220.6	53.3	100	64.9	222	5
X90										
X90	1997 - on	R	**1837**	E1683.	220	41	100	61	221.5	5

dba TM DISC BRAKES AUSTRALIA

DRUM BRAKES

TOYOTA

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
CAMRY										
SDV10 4 Cyl.	1992 - on	R	**1603**	E1747	228.6	56	62	71	230	5
CELICA										
TA22, TA23 RA23, RA28 RA40 Coupe, Liftback RA60 Coupe, Liftback	1971 - 85	R	**1735**	E1358 Shoes	228.6	54	60	71	230.6	4
ST162	1986 - 89	R	**1602**	E1490	200	55	54	65.5	201.4	4
COROLLA										
KE30, KE35, KE38, KE55, Local Brakes KE70V Panel Van 1300 AE 80	1974 - 84	R	**1735**	E1356 Shoes	228.6	54	60	71	230.6	4
KE20, KE25, KE26V KE30, KE35, KE36, KE38, KE50, KE55 KE70 Sedan, Wagon AE71 Sedan, Wagon	1970 - 84 1981 - 84	R	**1737**	E1189 Shoes	200	46	60	63	202	4
AE82 SOHC	1985 - 88	R	**1602**	E1379	200	55	54	65.5	201.4	4
AE90, 92 SOHC	1989 - 94	R	**1602**	E1490						
AE95 4WD	1988 - 94	R	**1665**	E1591	200	59	54	70.5	201.4	4
CORONA										
RT80, RT81 with Drum Front/Rear	1970 - 73	R	**1735**	E1062 E1182	228.6	54	60	71	230.6	4
RT104 SE, CS Sedan RT118 SE Station Wagon XT130, XT131 RT132, RT133 Liftback ST141 Sedan, Wagon	1973 - 83 1983 - 86	R	**1735**	E1358 Shoes	228.6	59	60	71	230.6	4
CRESSIDA										
MX32, MX36 MX62 Sedan, Wagon	1976 - 84	R	**1735**	E1358 Shoes	228.6	54	60	71	230.6	4
PASEO										
EL54	1995 - on	R	**1666**		180	34.5	HUB	80.5	181.4	4
SPACIA										
CR27, KR2	4/92 on	R	1735		228.6	54	60	71	230.6	4

dba TM DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

TOYOTA

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
STARLET										
EP91	1996 - on	R	**1666**		180	34.5	HUB	80.5	181.4	4
T-18										
TE72 1800 Liftback	1979 - 83	R	**1735**	E1358	228.6	54	60	71	230.6	4

TOYOTA COMMERCIAL

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
DYNA										
YH81, LH 80 100 Series	1985 - on	R	**1732**	E1371	254	67	67	78	256	5
HI-ACE										
RH11	1967 - 74	F & R	**1731**	E1025 E1028	230	58	67	70	232	5
RH11	1974 - 75	F & R	**1748**	E1493 E1028	230	73	67	62.5	232	5
RH11 RH11, 20, 22, 32, 42 LH20, 30 RH11, LH 11 YH50, 60, 70 Series LH50, 60, 70 Series	1975 - 81 1982 - 87	R	**1732**	E1371	254	67	67	78	256	5
RH11 RH11, 20, 22, 32, 42 LH20, 30	1975 - 81	F	**1733**	E1388	254	64	67	70	256	5
YH53, 63, 73 LH51, 61, 71	1987 - 89	R	**1733**	E1405						
YH56, 66 LH 56, 66	1986 - 87	R	**1744**	E1647	295	66	106	83	297	6
RZH103, 113, 125 LH103, 113, 125	1989 - on	R	**1747**	E1678	270	66	67	81	272	5
SBV LXH12, 22 RCH12, 22	8/1995 - on	R	**1761**	E171A	270	66	69	84	272	6

dba TM DISC BRAKES AUSTRALIA

DRUM BRAKES

TOYOTA COMMERCIAL - CONTINUED

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
HI-LUX 2WD # = RN31, RN34										
RN10	1968 - 72	F & R	**1731**	E1025 E1028	230	58	67	70	232	5
RN10, 20	1972 - 78	F & R	**1732**	E1375 E1371	254	67	67	78	256	5
RN30, 31, 40, 41 LN30, 40 RN5#, LN5#, YN5# LN8#, 9#, YN8#, 9# RN85	1978 - 83 1983 - 89 1988 - 97	R	**1732**	E1371						
RN41, RMSQ SR5	1978 - 83	R	**1733**	E1396	254	64	67	70	256	5
YN57, SR5 RN90 LN14#, 15# RZN14#, RZN154#	1983 - 89 1988 - 91 1997 on	R	**1738**	E1396	254	62	67	72	256	5
RN30, 40 LN 30, 40	1978 - 83	F	**1749**	E1388	254	57	67	70	256	5
HI-LUX 4WD / 4 RUNNER										
RN36, 46 LN 36, 46 YN60, 62, 65, 67 LN65	1979 - 83 1983 - 89	R R	**1739**	E1371	254	66	91	78	256	6
RN105, LN 106, YN 106	1988 - 97	R	**1743**	E1660	295	66	91	83	297	6
RN61, LN 61, YN 63 RN106, 110, 130, LN107, 111, 130 YN130, VZN 130	1985 - 89 1988 - 97	R	**1744**	E1647	295	66	106	83	297	6

dba TM DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

DRUM BRAKES

TOYOTA COMMERCIAL - CONTINUED

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
LANDCRUISER										
BJ40	1979 - 81	F	**1730**	E1414	295	75	106	81	297	6
		R	**1740**	E1083	290	64	106	84	292	6
BJ42 BJ70, 73	1980 - 84 1984 - 90	R	**1730**	E1414	295	75	106	81	297	6
FJ40, 45, 55	1969 - 75	F & R	**1740**	E1083	290	64	106	84	292	6
FJ40, 45, 50	1975 - 80	F	**1730**	E1414	295	75	106	81	297	6
FJ40, 55	1975 - 80	R	**1740**	E1083	290	64	106	84	292	6
FJ45 FJ60, 62 FJ70, 73, 75 HJ45	1975 - 84 1984 - 90 1984 - 90 1979 - 80	R R R F & R	**1730**	E1414	295	75	106	81	297	6
HJ45, 47 HJ 60, 61 HJ75	1980 - 84 1980 - 90 1984 - 90	R	**1730**	E1414	295	75	106	81	297	6
FJ, FZJ, HDJ80, HZJ80	1990 - on	R	**1745**		295	68	106	81	297	6
FJ, FZJ70, 73, 75 HJ, HZJ70, 75 KZJ, PZJ, 70	1990 - 92	R	**1746**		295	75	106	81	297	6
HDJ80, HZJ80, FZJ80 (full floating axle)	8/1992 - on	R	**1755**		295	102	106	109	297	6
LITE-ACE										
KM20, CM20	1979 - 85	F	**1734**	E1358	228.6	58	60	75	230.6	4
KM36, YM30, 35CM, 36	1986 - 92	R	**1735**	E1358	228.6	54	60	71	230.6	4
PRADO										
KZJ9#, LZJ9#, RZJ9#	1996 on	R	**1744**	E1647	295	66	106	83	297	6
RAV4										
SXA10	4/94	R	**1741**	E1747	254	63	67	74	256	5
SXA1#	4/94 - 8/95	R	**1752**		228.5	66.25	62	70	230.5	5
ACA20, ACA21, CLA2#, 2CA2#	7/2003 - on	R	**1753**		228.5	58.75	61.75	64	230.5	5
SPACIA										
CR27, KR2	4/92 on	R	**1735**		228.6	54	60	71	230.6	4

dba TM DISC BRAKES AUSTRALIA

DRUM BRAKES

TOYOTA COMMERCIAL - CONTINUED

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
TARAGO										
YR 20, 21, 22, CR 21	1982 - 90	R	**1736**	E1492	254	61	60	74	256	4
TCR10, 20	1990, 96	R	**1742**	E1492	254	62.5	60	72	256	5
TERCEL										
AL25 4WD	10/82 - 4/88	R	**1665**		200	59	54	70.5	201.4	4
TOWNACE										
CR27, KR2	4/92 on	R	**1735**		228.6	54	60	71	230.6	4
YR22, 39			**1736**	N1396	254	61	60	74	256	4
SBV KR42, SR40	11/96 - on	R	**1736**	N1396	254	61	60	74	256	4

VOLKSWAGEN

Model	Years	F/R	Drum No.	Brake Shoe	Dia. Face A	Machine Face B	Centre Hole C	Drum Height D	Max. Diam. E	Stud Holes
SYNCHRO										
4WD 2.4L Diesel	89 on	R	**1744**		295	67	106	83	297	6

dba™ DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. **TRADEMARKS**: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd..

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 001	HOLDEN	253	9.7	3.9
DBA 002	HOLDEN	270	12.7	5.3
DBA 003	HOLDEN	270	15.9	5.8
DBA 004	HOLDEN	256	15.9	6
DBA 006	HOLDEN	239	10	3.3
DBA 007	HOLDEN	227	10	2.9
DBA 008	HOLDEN	256	12.7	4.8
DBA 009	HOLDEN	215	10	2.5
DBA 010	HOLDEN	256	16	8.8
DBA 011	HOLDEN	235	12.7	3.6
DBA 012	HOLDEN	215	10	2.6
DBA 013	HOLDEN	256	15.6	9
DBA 014	HOLDEN	276	25.4	10.3
DBA 015	HOLDEN	270	22	10.5
DBA 016	HOLDEN	279	10.5	5.1
DBA 017	HOLDEN	290	22	10.5
DBA 018	HOLDEN	292	15.9	8.4
DBA 019	HOLDEN	327	28	13.2
DBA 020	HOLDEN	278	20	4.3
DBA 021	HOLDEN	235	20	4.1
DBA 022	HOLDEN	231	17	3.5
DBA 023	HOLDEN	256	24	5.3
DBA 024	HOLDEN	270	10	4.7
DBA 025	HOLDEN	270	23	10
DBA 026	HOLDEN	279	10.5	5
DBA 027	HOLDEN	290	23	11.1
DBA 030	HOLDEN	250	18	5.4
DBA 031	PART NOT AVAILABLE	259	12.5	4.4
DBA 032	HOLDEN	250	18	4.3
DBA 033	HOLDEN	257	22	5.2
DBA 034	HOLDEN	265	12	5
DBA 035	HOLDEN	289	23	7.4
DBA 036	HOLDEN	279	10.7	5.3
DBA 036B	HOLDEN	279	10.7	5.5
DBA 037	HOLDEN	279	10.7	5.2
DBA 038	PART NOT AVAILABLE	284	24	6.6
DBA 039	HOLDEN	270	10	4.5
DBA 040	HOLDEN	296	28	9.1
DBA 040B	HOLDEN	296	28	9.35
DBA 041	HOLDEN	286	16	7
DBA 045	HOLDEN	280	20	5.8
DBA 046	HOLDEN	328	28	9.7
DBA 046B	HOLDEN	328	28	9.5
DBA 047	HOLDEN	280	20	6.3
DBA 048	HOLDEN	330	32	11.2
DBA 049	HOLDEN	315	18	7.7
DBA 050	PART NOT AVAILABLE	300	12	5.5
DBA 051	CITROEN	270	7	2.9
DBA 053	CITROEN	178	7	3
DBA 054	CITROEN	269	9	3.5
DBA 056	CITROEN	260	20	5.2
DBA 057	CITROEN	233	9	3.2
DBA 059	CITROEN	224	7	3
DBA 060	MG	209.8	7.5	2.2
DBA 061	MG	209.8	7.7	3

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 062	MG	273.4	8.7	4.5
DBA 063	MGF	240	22	4.2
DBA 064	MGF	240	10	3.2
DBA 065	PART NOT AVAILABLE	280	12.5	5.2
DBA 067A	CHEVROLET	325	32	10.5
DBA 067B	CHEVROLET	325	32	10.5
DBA 068	LEYLAND	273	25.4	12
DBA 069A	FORD	330	28	8.7
DBA 069B	FORD	330	28	8.7
DBA 070	PART NOT AVAILABLE	272	22	7.4
DBA 071	FERRARI	277	20	6
DBA 072	JAGUAR	280	9.75	4.7
DBA 073	JAGUAR	287	9.5	5.4
DBA 074	PART NOT AVAILABLE	283	12.5	5.8
DBA 075	JAGUAR	262	12.5	4.4
DBA 075B	JAGUAR	262	12.5	4.5
DBA 076	JAGUAR	285	24	7.5
DBA 077	PART NOT AVAILABLE	295	22.3	6.8
DBA 078	JAGUAR	278	10	4.8
DBA 079	PART NOT AVAILABLE	213	10	2.9
DBA 080	PART NOT AVAILABLE	236	12.5	4.7
DBA 081	MINI COOPER	190	9.5	2.9
DBA 082	PART NOT AVAILABLE	203	7.7	2.5
DBA 083	MORRIS	214	11	3
DBA 084	MORRIS	248	9.5	3.6
DBA 085	HILLMAN	244	8.8	2.9
DBA 086	LANDROVER	300	24	8.4
DBA 087	RANGE ROVER	298	14	7.4
DBA 088	RANGE ROVER	290	12.7	5.9
DBA 089	ROVER	257	14.5	6
DBA 090	CHEVROLET	317	32.5	17
DBA 091	CHEVROLET	317	32.5	17.2
DBA 092	RANGE ROVER	297	25	7.9
DBA 093	RANGE ROVER	304	12.6	6.7
DBA 094	HUMBER	290	12.75	5.2
DBA 094B	AUSTIN	280	12.75	5
DBA 095	INTERNATIONAL	298	30	7.4
DBA 096	JEEP	280	24	6.8
DBA 097	JEEP	285	11	5.1
DBA 098	JAGUAR	291	28	6.9
DBA 099	JAGUAR	294	10	5
DBA 100	FORD	228	11	2.9
DBA 101	FORD	260	18	4.2
DBA 102	FORD	296	18	0
DBA 103	FORD	287	24	5.9
DBA 104	FORD	272	12.7	5.1
DBA 105	FORD	279	16	6.4
DBA 106	FORD	287	24	5.9
DBA 106H	FORD	287	24	11
DBA 107	FORD	287	24	9.8
DBA 108	FORD	286	24	7.2
DBA 109	FORD	286	24	6.9
DBA 110B	FORD	287	24	9.8
DBA 111A	FORD	287	15	6.7
DBA 111B	FORD	287	13	6.1

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 112	PART NOT AVAILABLE	240	9.5	2.8
DBA 113	FORD	245	12.7	3.7
DBA 114A	FORD	273	12.7	5.3
DBA 114B	PART NOT AVAILABLE	273	12.7	5.1
DBA 115	FORD	246	12.5	4.8
DBA 116	FORD	237	22.4	4.6
DBA 117	PART NOT AVAILABLE	219	9.5	2.4
DBA 118	FORD	247	12.5	4
DBA 119	FORD	250	14	4.5
DBA 120	FORD	297	30	12.6
DBA 121	FORD	297	30	9
DBA 122	PART NOT AVAILABLE	320	32	16.2
DBA 123	FORD	300	30	12.3
DBA 124	FORD	320	30	16
DBA 125	FORD	320	32	16
DBA 126	FORD	270	24	5.7
DBA 127	FORD	270	14.3	5.6
DBA 128A	FORD	320	32	16.4
DBA 128B	FORD	320	32	15.6
DBA 129	PART NOT AVAILABLE	318	32	10.5
DBA 130	FORD	287	24	10.5
DBA 131	FORD	287	25	10
DBA 132	FORD	287	25	10.5
DBA 133	FORD	299	10.5	5.6
DBA 134	FORD	287	24	10
DBA 135	FORD	287	24	10
DBA 136	FORD	328	28	12
DBA 137	TOYOTA	241	10	3.8
DBA 138	TOYOTA	266	12.7	4.6
DBA 139	TOYOTA	228	10	2.6
DBA 140	TOYOTA	254	12.7	3.9
DBA 141	PART NOT AVAILABLE	200	10	2.2
DBA 142	TOYOTA	218	10	3
DBA 143	TOYOTA	243	10	3.5
DBA 144	TOYOTA	218	12.7	3.1
DBA 145	TOYOTA	228	12.7	3.3
DBA 146	TOYOTA	258	20	4.8
DBA 147	TOYOTA	243	11.1	3.3
DBA 148	TOYOTA	230	12.7	3.2
DBA 149	TOYOTA	243	22	4.6
DBA 150	TOYOTA	302	20	6.3
DBA 151	TOYOTA	302	20	6
DBA 152	TOYOTA	266	12.7	4.6
DBA 153	TOYOTA	302	12.7	6
DBA 154	TOYOTA	302	12.7	5.9
DBA 155	TOYOTA	252	20	4.1
DBA 156	TOYOTA	257	25	5.8
DBA 157	TOYOTA	255	20	5.4
DBA 158	TOYOTA	255	20	5.5
DBA 159	TOYOTA	260	25	6.3
DBA 160	FIAT	227	10.8	3.1
DBA 161	FIAT	251.5	11	5
DBA 162	PART NOT AVAILABLE	275	18.5	7
DBA 163	TRIUMPH	275	12.75	5
DBA 164	FIAT	257	12	5

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 165	CHRYSLER	257	22	4.6
DBA 166	CHRYSLER	270	9	3.9
DBA 167	CHRYSLER	280	23	5.8
DBA 168	FORD	240	20	4.2
DBA 170	PART NOT AVAILABLE	247.6	8.7	3
DBA 171	PART NOT AVAILABLE	247.6	12.7	4.1
DBA 172	TRIUMPH	240	10	3.3
DBA 173	PART NOT AVAILABLE	221	9.5	2.9
DBA 174	TRIUMPH	275.4	12.7	4.7
DBA 175	CHRYSLER	257	20	4.5
DBA 176	CHRYSLER	270	9	4
DBA 177	CHRYSLER	282	24	6.4
DBA 178	HONDA	231	17	0
DBA 179	HONDA	282	25	0
DBA 180	JEEP	300	32.5	8.6
DBA 181	JEEP	298	22.5	6.5
DBA 182	HONDA	239	10	3.4
DBA 183	HONDA	239	10	4.2
DBA 184	HONDA	262	21	5.2
DBA 185	HONDA	282	21	5.8
DBA 186	HONDA	262	21	5.1
DBA 187	HONDA	242	19	4
DBA 188	HONDA	225	10	3
DBA 189	HONDA	231	12	3.3
DBA 190	HONDA	231	12	3.3
DBA 191	HONDA	231	12	3.3
DBA 192	HONDA	239	10	3.1
DBA 193	HONDA	215	11	3
DBA 194	PART NOT AVAILABLE	212	10	2.5
DBA 195	HONDA	231	17	3.4
DBA 196	HONDA	242	19	4.2
DBA 197	HONDA	231	19	3.8
DBA 198	PART NOT AVAILABLE	242	10	3.5
DBA 199	HONDA	260	10	3.5
DBA 200	HONDA	282	23	6.1
DBA 201	PART NOT AVAILABLE	279.4	12.7	5.7
DBA 202	CHRYSLER	282	24	6.8
DBA 203	PART NOT AVAILABLE	282	25.4	7
DBA 204	PART NOT AVAILBALE	279.4	24	7
DBA 205	MITSUBISHI	256	13	4.1
DBA 206	MITSUBISHI	249	12.9	4.1
DBA 207	MITSUBISHI	280	10.5	5.1
DBA 208	MITSUBISHI	254	24	5.1
DBA 209	PART NOT AVAILABLE	239	10	3.1
DBA 210	MITSUBISHI	229	13	3.4
DBA 211	PART NOT AVAILABLE	255	12.5	3.9
DBA 212	MITSUBISHI	247	10	3.5
DBA 213	MITSUBISHI	296	30	7
DBA 214	MITSUBISHI	284	20	5.8
DBA 215	MITSUBISHI	228	13	3.6
DBA 216	MITSUBISHI	314	30	
DBA 217	MITSUBISHI	297	20	6.4
DBA 218	PART NOT AVAILABLE	254	24	4.8
DBA 219	MITSUBISHI	242	18	3.9
DBA 220	MITSUBISHI	255	20	5.7

dba™ DISC BRAKES AUSTRALIA

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 221	MITSUBISHI	266	24	7.8
DBA 222	MITSUBISHI	251	10	6.3
DBA 223	MITSUBISHI	276	10	7.7
DBA 224	MITSUBISHI	275	20	5.5
DBA 225	MITSUBISHI	232	20	4
DBA 226	MITSUBISHI	255	20	4.7
DBA 227	MITSUBISHI	243	13	3.5
DBA 228	MITSUBISHI	255	20	5.4
DBA 229	MITSUBISHI	277	22	6.1
DBA 230	MITSUBISHI	258	22	5.3
DBA 231	MITSUBISHI	258	22	5.2
DBA 232	MITSUBISHI	258	22	6.6
DBA 233	MITSUBISHI	315	18	8.5
DBA 234	MITSUBISHI	276	24	6.6
DBA 234T	MITSUBISHI	276	24	6.6
DBA 236	MITSUBISHI	276	27	6.6
DBA 237	MITSUBISHI	314	24	7.1
DBA 238	MITSUBISHI	323	10	7.1
DBA 239	MITSUBISHI	285	22	5.4
DBA 240	AUDI	239	12	3.4
DBA 241	AUDI	256	22	5.3
DBA 242	AUDI	239	10	3.1
DBA 243	PART NOT AVAILABLE	278	9.5	7
DBA 244	AUDI	245	10	3.3
DBA 245	VOLKSWAGEN	278	13	6.3
DBA 246	PART NOT AVAILABLE	278	13	6.3
DBA 247	AUDI	257	13	4.6
DBA 248	AUDI	291	10.5	4.5
DBA 249	PART NOT AVAILABLE	291	10.5	
DBA 250	MERCEDES BENZ	273	12.7	6.6
DBA 251	MERCEDES BENZ	279	10	4.4
DBA 252	MERCEDES BENZ	273	12.7	5.3
DBA 253	MERCEDES BENZ	253	12.7	4.8
DBA 254	MERCEDES BENZ	278	12.7	5
DBA 255	MERCEDES BENZ	278	22	6.2
DBA 256	MERCEDES BENZ	273	19.1	5.2
DBA 257	MERCEDES BENZ	273	22	6
DBA 258	MERCEDES BENZ	278	22	6.2
DBA 259	MERCEDES BENZ	286	22	6.6
DBA 260	MERCEDES BENZ	262	11	4
DBA 261	MERCEDES BENZ	258	9	3.3
DBA 262	MERCEDES BENZ	300	27.5	7.6
DBA 263	MERCEDES BENZ	284	12	5
DBA 264	MERCEDES BENZ	284	22	5.8
DBA 265	MERCEDES BENZ	284	12	5
DBA 266	MERCEDES BENZ	295	22	6.6
DBA 267	MERCEDES BENZ	278	9	3.7
DBA 268	MERCEDES BENZ	294	24	7.2
DBA 269	MERCEDES BENZ	284	22	6
DBA 270	PEUGEOT	273	12.5	5.1
DBA 271	PEUGEOT	273	12	4.1
DBA 272	PEUGEOT	273	20	5.3
DBA 273	PEUGEOT	247	20.5	4
DBA 274	PEUGEOT	266	20.5	4.6
DBA 275	PEUGEOT	283	22	5.9

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 276	PEUGEOT	246.5	8	2.6
DBA 277	PEUGEOT	273	12.5	7.2
DBA 278	PEUGEOT	290	10	4.8
DBA 279	MERCEDES BENZ	262	22	5.1
DBA 280	MERCEDES BENZ	300	28	7.5
DBA 281	MERCEDES BENZ	278	9.1	3.9
DBA 282	MERCEDES BENZ	310	28	8
DBA 283	MERCEDES BENZ	290	12	5
DBA 284	MERCEDES BENZ	320	30	8
DBA 285	PART NOT AVAILABLE	300	22	7.1
DBA 286	MERCEDES BENZ	288	25	6.3
DBA 287	MERCEDES BENZ	278	9	7.5
DBA 288	MERCEDES BENZ	300	28	7.5
DBA 289	MERCEDES BENZ	290	10	4.6
DBA 290	DAIHATSU	208	10	2.4
DBA 291	DAIHATSU	234	11	3.4
DBA 292	DAIHATSU	277	12.5	4.7
DBA 293	DAIHATSU	212	10	2.5
DBA 294	DAIHATSU	208	11	2.5
DBA 295	DAIHATSU	234	18	3.8
DBA 296	DAIHATSU	234	11	3.4
DBA 297	PART NOT AVAILABLE	211	10	2.5
DBA 298	PART NOT AVAILABLE	211	16	3.1
DBA 299	DAIHATSU	285	24	3
DBA 300	NISSAN	218	10	2.7
DBA 301	NISSAN	239	9.5	3.2
DBA 302	NISSAN	240	12	3.4
DBA 303	NISSAN	240	12	3.5
DBA 304	NISSAN	235	10	4.8
DBA 305	NISSAN	239	9.5	3.2
DBA 306	NISSAN	232	10	3.3
DBA 307	NISSAN	245	10	3.4
DBA 308	NISSAN	232	10	3
DBA 309	NISSAN	250	12	4
DBA 310	NISSAN	219	9.6	2.7
DBA 311	NISSAN	250	22	4.1
DBA 312	NISSAN	267	22	5.5
DBA 313	PART NOT AVAILABLE	260	20	5.1
DBA 314	PART NOT AVAILABLE	212	9.5	2.4
DBA 315	NISSAN	253	12.7	4.6
DBA 316	NISSAN	270	12.5	5.4
DBA 317	NISSAN	250	18	6
DBA 318	NISSAN	252	20	4.1
DBA 319	NISSAN	232	18.2	3
DBA 320	NISSAN	271	12.5	5
DBA 321	PART NOT AVAILABLE	271	12.5	5.1
DBA 322	NISSAN	250	20	4.2
DBA 323	NISSAN	250	20	4.3
DBA 324	PART NOT AVAILABLE	271	12.7	5.4
DBA 325	PART NOT AVAILABLE	271	12.7	5.1
DBA 326	NISSAN	244	12.7	4.2
DBA 327	NISSAN	271	12.5	5.2
DBA 328	NISSAN	271	12.5	6
DBA 329	NISSAN	294	20	6.7
DBA 330	MAZDA	250	10	3.6

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 331	PART NOT AVAILABLE	230	11	3
DBA 332	MAZDA	244	10	3.2
DBA 333	MAZDA	231	13	5.5
DBA 334	FORD	250	20	4.1
DBA 335	MAZDA	250	18	4
DBA 336	MAZDA	228	18	7.5
DBA 337	MAZDA	229	13	5.4
DBA 338	PART NOT AVAILABLE	230	12	4
DBA 339	MAZDA	206	13	5
DBA 340	SUBARU	229	12.5	3.8
DBA 341	SUBARU	226	10	4
DBA 342	SUBARU	229	10	4.2
DBA 343	RENAULT	228	20	3.8
DBA 344	RENAULT	254	12	3.9
DBA 345	RENAULT	227.5	10	3
DBA 346A	RENAULT	238.5	20	4
DBA 346B	RENAULT	238.5	20	4
DBA 347	RENAULT	250	9	3.5
DBA 348	RENAULT	238	11	3.9
DBA 349	RENAULT	252	22	5.5
DBA 350	PART NOT AVAILABLE	260	7	2.9
DBA 351	RENAULT	238	20.1	4.3
DBA 352	AUDI	239	9	
DBA 353	PART NOT AVAILABLE	267	10.9	5.2
DBA 354	PART NOT AVAILABLE	267	9.4	4.3
DBA 355	LOTUS	280	26	6.25
DBA 356	ALFA ROMEO	284	22	5.8
DBA 357	PART NOT AVAILABLE	272	12.5	5.9
DBA 358	ALFA ROMEO	272	12.6	5.8
DBA 359	ALFA ROMEO	251	10	3.6
DBA 360	PART NOT AVAILABLE	286	10	5
DBA 361	PART NOT AVAILABLE	261	11	4.2
DBA 362	ALFA ROMEO	249.5	10	3.1
DBA 363	ALFA ROMEO	258	10	2.6
DBA 364	ALFA ROMEO	233	9	4.9
DBA 365	ALFA ROMEO	250	10	3.2
DBA 366	PART NOT AVAILABLE	261	12.7	5
DBA 367	ALFA ROMEO	250	12.6	4.1
DBA 368	ALFA ROMEO	239	11	3.5
DBA 369	PART NOT AVAILABLE	239	22	4.2
DBA 370	BMW	240	10	3.4
DBA 371	BMW	272	12.7	5.6
DBA 372	BMW	256	12.7	4.8
DBA 373	BMW	272	12.7	5
DBA 374	BMW	273	9.5	4.1
DBA 375	BMW	272	22	7
DBA 376	BMW	255	12.7	4.8
DBA 377	BMW	280	12.7	5.6
DBA 378	PART NOT AVAILABLE	255	22	5.2
DBA 379	BMW	280	22	6.4
DBA 380	VOLVO	263	14.3	5.2
DBA 381	VOLVO	281	9.6	4.9
DBA 382	VOLVO	263	24	5.6
DBA 383	VOLVO	263	22	5.6
DBA 384	VOLVO	272	12.7	5.2

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 385	SAAB	280	12.7	5.1
DBA 386	SAAB	267	9.7	3.7
DBA 387	SAAB	269	10.5	4.4
DBA 388	SAAB	280	12.8	5.4
DBA 389	SAAB	280	20	5.7
DBA 390	LANCIA	251	12.7	4.3
DBA 391	LANCIA	251	10	4
DBA 392A/B	PART NOT AVAILABLE	304	32	9
DBA 393	PART NOT AVAILABLE	299	24	6.5
DBA 394	PART NOT AVAILABLE	282	20	5.1
DBA 395	PART NOT AVAILABLE	289	20	5.9
DBA 396	PORSCHE	282	12.5	5
DBA 397	PORSCHE	257	13	5.7
DBA 398	PORSCHE	282	20	5.6
DBA 399	PART NOT AVAILABLE	289	20	5.6
DBA 400	PART NOT AVAILABLE	256	24	5.5
DBA 401	PART NOT AVAILABLE	247	18	4
DBA 402	MITSUBISHI	276	24	5.9
DBA 402B	PROTON	276	24	6
DBA 403	MITSUBISHI	265	10	3.9
DBA 404	MITSUBISHI	262	10	4.1
DBA 405	HONDA	282	28	7.2
DBA 406	MITSUBISHI	260	10	3.4
DBA 407	PART NOT AVAILABLE	256	24	5
DBA 408	MITSUBISHI	235	13	3.6
DBA 409	MITSUBISHI	266	24	5.5
DBA 410	MITSUBISHI	260	10	3.5
DBA 411	MITSUBISHI	256	24	5.1
DBA 411B	MITSUBISHI	256	24	5
DBA 412	MITSUBISHI	236	18	4
DBA 413	MITSUBISHI	235	18	4
DBA 414	PART NOT AVAILABLE	256	24	5.2
DBA 415	MITSUBISHI	256	24	4.8
DBA 416	MITSUBISHI	260	10	3.7
DBA 417	MITSUBISHI	294	24	6.6
DBA 419	MITSUBISHI	300	22	6.7
DBA 421	MITSUBISHI	256	24	5
DBA 422	MITSUBISHI	258	10.4	4.2
DBA 423	MITSUBISHI	266	18	5
DBA 425	MITSUBISHI	276	24	5.9
DBA 426	MITSUBISHI	258	10.5	4
DBA 427	MITSUBISHI	284	20	5.2
DBA 429	MITSUBISHI	284	20	5.9
DBA 430	PART NOT AVAILABLE	280	23.5	6.1
DBA 431	SAAB	280	25	6.7
DBA 432	SAAB	258	9	3.2
DBA 433	SAAB	284	24	6.6
DBA 434	SAAB	260	10	4
DBA 436	SAAB	286	10	5
DBA 437	MITSUBISHI	276	24	
DBA 438	HONDA	260	9	3.4
DBA 439	MASERATI	282	12.7	5.8
DBA 440	AUDI	257	13	3.9
DBA 441	AUDI	257	20	4.5
DBA 442	VOLKSWAGEN	278	13	8.6

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 443	VOLKSWAGEN	258	16	7.7
DBA 444	VOLKSWAGEN	239	20	3.7
DBA 445	AUDI	245	10	3.5
DBA 446	SEAT	256	20	4.5
DBA 447	VOLKSWAGEN	260	16	5.6
DBA 448	VOLKSWAGEN	282	18	7.4
DBA 449	VOLKSWAGEN	280	24	6.8
DBA 450	HYUNDAI	242	19	5.2
DBA 451	HYUNDAI	242	19	4.2
DBA 452	HYUNDAI	257	22	4.9
DBA 453	HYUNDAI	257	22	5
DBA 454	HYUNDAI	263	12	3.9
DBA 455	HYUNDAI	260	12	4.2
DBA 456	HYUNDAI	257	24	4.8
DBA 457	HYUNDAI	257	10	3.8
DBA 458	HYUNDAI	262	10	4.4
DBA 459	HYUNDAI	257	10	2.4
DBA 460	HYUNDAI	276	26	6.5
DBA 461	HYUNDAI	262	10	4.8
DBA 463	HYUNDAI	257	24	5.8
DBA 464	HYUNDAI	276	26	6.4
DBA 465	HYUNDAI	284	10	4.7
DBA 466	HYUNDAI	280	27	7.1
DBA 467	HYUNDAI	315	20	8.2
DBA 468	HYUNDAI	280	26	6.6
DBA 469	HYUNDAI	258	10	4.1
DBA 470	HONDA	260	23	4.8
DBA 471	HONDA	260	10	4.2
DBA 472	HONDA	282	25	6.5
DBA 473	HONDA	240	21	4.3
DBA 474	HONDA	262	21	4.8
DBA 475	HONDA	239	9	3
DBA 476	HONDA	300	28	8.1
DBA 477	HONDA	260	9	3.4
DBA 478	HONDA	282	23	5.8
DBA 479	HONDA	282	9	4.2
DBA 480	HONDA	260	23	5
DBA 481	HONDA	260	10	3.6
DBA 482	HONDA	300	25	6.3
DBA 483	HONDA	282	12	4.5
DBA 484	HONDA	282	28	6.5
DBA 485	HONDA	282	21	5.5
DBA 486	HONDA	298	28	6.8
DBA 487	HONDA	303	23	6.5
DBA 488	HONDA	282	23	6
DBA 489	HONDA	260	9	3.6
DBA 490	PART NOT AVAILABLE	236	10	2
DBA 491	DAIHATSU	277	18	4.8
DBA 492	DAIHATSU	211	10	3.3
DBA 493	DAIHATSU	179	10	1.8
DBA 494	DAIHATSU	236	10	2.9
DBA 495	DAIHATSU	234	16	3.3
DBA 496	DAIHATSU	273	16	5.49
DBA 497	DAIHATSU	250	18	4.4
DBA 498	DAIHATSU	234	16	3.8

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 499	HONDA	282	12	
DBA 500	FORD	287	24	7.6
DBA 501	FORD	287	10.5	5.3
DBA 502	FORD	287	28	8.2
DBA 503	FORD	287	16	5
DBA 504	FORD	298	28	8.9
DBA 505	FORD	303	16	7.2
DBA 506	FORD	329	28	11
DBA 507A/B	FORD	300	28	10
DBA 508	FORD	278	24	6.3
DBA 509	FORD	253	20	4.2
DBA 510	SUZUKI	290	10	4.6
DBA 511	SUZUKI	213	11	2.6
DBA 512	SUZUKI	231	17	3.5
DBA 513	SUZUKI	290	10	4.4
DBA 514	SUZUKI	287	17	4.4
DBA 515	SUZUKI	231	17	3.6
DBA 516	SUZUKI	250	18.5	4.5
DBA 517	PART NOT AVAILABLE	240	10	3.5
DBA 518	SUZUKI	310	22	7
DBA 519	SUZUKI	235	20	4.1
DBA 520	SUZUKI	246	20	4.3
DBA 521	SUZUKI	240	10	3
DBA 522	SUZUKI	231	17	3.4
DBA 523	SUZUKI	257	17	4.3
DBA 524	SUZUKI	287	17	4.3
DBA 525	MAZDA	235	12	3.5
DBA 526	LANDROVER	262	14	4.9
DBA 527	LANDROVER	277	21	5.3
DBA 528	LANDROVER	297	25	8.2
DBA 529	FORD	240	12	3.6
DBA 530	FORD	235	18	3.7
DBA 531	FORD	231	9	2.6
DBA 532	FORD	235	22	4.5
DBA 533	FORD	257	22	5.2
DBA 534	FORD	250.5	9	3
DBA 535	MAZDA	274	22	5.3
DBA 536	MAZDA	251	9	3
DBA 537	MAZDA	258	24	6
DBA 538	MAZDA	255	20	4.6
DBA 539	MAZDA	261	10	3.6
DBA 540	JEEP	305	26	7.7
DBA 541	JEEP	305	10	5.7
DBA 542	MINI COOPER	276	22	5.8
DBA 543	MINI COOPER	259	10	3.4
DBA 544	MAZDA	270	22	4.8
DBA 545	MAZDA	270	22	5.4
DBA 546	MAZDA	276	10	3.7
DBA 547	MITSUBISHI	260	10	3.4
DBA 548	VOLKSWAGEN	280	24	6.8
DBA 549	LANDROVER	298	14	6.8
DBA 550	MERCEDES BENZ	303	26	7.5
DBA 551	MERCEDES BENZ	285	15	6
DBA 552	MERCEDES BENZ	345	32	11.2
DBA 553	MERCEDES BENZ	331	14	8

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 554	SSANYONG MUSSO	278	24	6.4
DBA 555	SSANYONG MUSSO	300	10.5	5.7
DBA 556	MERCEDES BENZ	260	12	3.7
DBA 557	MERCEDES BENZ	260	22	4.7
DBA 558	MERCEDES BENZ	276	22	5.1
DBA 559	MERCEDES BENZ	258	8	3
DBA 560	TOYOTA	315	32	9
DBA 561	PART NOT AVAILABLE	315	16	6.75
DBA 562	TOYOTA	275	25	6.2
DBA 563	TOYOTA	269	9	3.6
DBA 564	MERCEDES BENZ	276	22	6
DBA 565	MERCEDES BENZ	280	10	4.3
DBA 566	MERCEDES BENZ	276	22	6.6
DBA 567	MERCEDES BENZ	272	16	7
DBA 568	TOYOTA	275	28	7.34
DBA 570	TOYOTA	256	20	5.5
DBA 571	PART NOT AVAILABLE	272	10	4.5
DBA 572	PART NOT AVAILABLE	256	21	5.5
DBA 573	NISSAN	280	28	7.5
DBA 574	NISSAN	292	16	5.5
DBA 576	FORD	258	24	5.8
DBA 577	FORD	258	24	5.3
DBA 578	SUZUKI	287	17	4.1
DBA 579	SUZUKI	310	22	6
DBA 580	TOYOTA	258	25	5.5
DBA 581	PART NOT AVAILABLE	263	16	4
DBA 582	TOYOTA	275	30	8
DBA 583	TOYOTA	281	22	6
DBA 586	TOYOTA	291	16	0
DBA 590	PORSCHE	298	27.5	8
DBA 591	PORSCHE	299	24	8
DBA 592A/B	PART NOT AVAILABLE	304	32	7
DBA 593	PART NOT AVAILABLE	282	24	6
DBA 594	PART NOT AVAILABLE	304	32	7
DBA 595	PORSCHE	298	28	6.8
DBA 596	PORSCHE	299	24	6.8
DBA 597A/B	PART NOT AVAILABLE	282	32	7
DBA 598A/B	PART NOT AVAILABLE	282	32	7
DBA 600	NISSAN	258	10	4.5
DBA 601	NISSAN	269	10	5
DBA 602	HOLDEN	240	18	4.5
DBA 603	NISSAN	240	18	4.5
DBA 604	PART NOT AVAILABLE	274	22	7
DBA 605	NISSAN	290	10	5
DBA 606	NISSAN	235	10	5
DBA 607	NISSAN	290	10	5.5
DBA 608	PART NOT AVAILABLE	274	22	6.5
DBA 609	NISSAN	250	12	7
DBA 610	NISSAN	284	10.4	5
DBA 611	NISSAN	280	10.5	5.5
DBA 612	NISSAN	250	18	4.5
DBA 613	PART NOT AVAILABLE	250	22	8.5
DBA 614	FORD	258	10	4
DBA 615	NISSAN	250	22	8
DBA 616	NISSAN	260	10.4	4.5

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 617	NISSAN	257	22	6
DBA 618	NISSAN	260	26	6.5
DBA 619	NISSAN	232	18	3.5
DBA 620	NISSAN	250	22	5
DBA 621	NISSAN	266	22	6
DBA 622	NISSAN	315	18	8
DBA 623	NISSAN	306	26	8.6
DBA 624	NISSAN	277	26	7.5
DBA 625	NISSAN	306	32	10.5
DBA 626	NISSAN	283	28	7
DBA 627	NISSAN	250	22	5.5
DBA 628	NISSAN	250	18	4.5
DBA 629	NISSAN	300	28	8.6
DBA 630	MAZDA	250	18	7
DBA 631	FORD	256	20	4.5
DBA 632A/B	FORD	231.5	18	7
DBA 633	MAZDA	264	24	5.5
DBA 634	PART NOT AVAILABLE	258	10	5.5
DBA 635	MAZDA	219	13	3
DBA 636	MAZDA	276	22	6.5
DBA 637	MAZDA	273	20	5
DBA 638	MAZDA	255	22	7
DBA 639	MAZDA	265	10	4.5
DBA 640	SUBARU	230	18	4.5
DBA 641	SUBARU	242	18	4.5
DBA 642	SUBARU	260	24	5.5
DBA 643	RENAULT	238.5	12	4
DBA 644	SUBARU	266	10	4.5
DBA 645	SUBARU	242	18	4
DBA 646	SUBARU	212	10	2.5
DBA 647	SUBARU	212	9	2
DBA 648	SUBARU	277	24	8
DBA 649	SUBARU	266	18	6
DBA 650	SUBARU	294	24	7
DBA 651	PART NOT AVAILABLE	290	10	5
DBA 652	SUBARU	301.1	28	8
DBA 653	SUBARU	290	18	6
DBA 655	SUBARU	316	20	8
DBA 656	SUBARU	290	18	5.7
DBA 657	SUBARU	290	10	4.9
DBA 658	PART NOT AVAILABLE	239	12.7	4
DBA 659	MAZDA	255	22	6.9
DBA 660	MITSUBISHI	290	26	6.5
DBA 661	MITSUBISHI	300	22	6.5
DBA 662	MITSUBISHI	245	24	6
DBA 663	MITSUBISHI	276	24	6
DBA 664	MITSUBISHI	293	40	12.1
DBA 665	ALFA ROMEO	284	22	6.5
DBA 666	ALFA ROMEO	251	10	
DBA 667	ALFA ROMEO	250	9.9	4
DBA 668	ALFA ROMEO	268	22	5.5
DBA 669	ALFA ROMEO	258	10	4
DBA 670	BMW	284	10	5
DBA 671	BMW	258	10	4
DBA 672	BMW	284	12	6

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 673	BMW	272	19	6
DBA 674	BMW	284	10	5
DBA 675	BMW	284	22	6
DBA 676	BMW	280	10	5
DBA 677	BMW	280	25	7
DBA 678	BMW	260	12.7	4.5
DBA 679	BMW	260	22	5
DBA 680	VOLVO	295	9.6	6
DBA 681	VOLVO	272	14.3	6
DBA 682	VOLVO	287	22	8
DBA 683	VOLVO	287	22	9.5
DBA 684	VOLVO	262.5	22	8
DBA 685	VOLVO	262.5	22	5.5
DBA 686	VOLVO	287	22	6.7
DBA 687	VOLVO	239	12.7	3.5
DBA 688	VOLVO	280	26	6.5
DBA 689	VOLVO	265	10	4
DBA 690	TOYOTA	302	18	5
DBA 691	TOYOTA	303	9	5
DBA 692	TOYOTA	275	25	6.5
DBA 693	TOYOTA	303	9	5.2
DBA 695	TOYOTA	254	18	4
DBA 696	PART NOT AVAILABLE	240	9	4.5
DBA 697	TOYOTA	291	12	0
DBA 698	TOYOTA	316	34	10.85
DBA 699	TOYOTA	330	18	7.6
DBA 700	PART NOT AVAILABLE	234	12.5	4
DBA 701	TOYOTA	243	13.5	4.5
DBA 702	TOYOTA	243	18	4
DBA 703	TOYOTA	242	9	3
DBA 704	TOYOTA	238	18	4.5
DBA 705	TOYOTA	250	12.7	3.5
DBA 706	TOYOTA	280	10.5	5
DBA 707	PART NOT AVAILABLE	269	10	4.5
DBA 708	TOYOTA	258	22	5
DBA 709	HOLDEN	255	22	5
DBA 710	HOLDEN	266	9	3.5
DBA 711	TOYOTA	238	22	5.5
DBA 712	TOYOTA	255	25	5.2
DBA 713	TOYOTA	269	9	3.7
DBA 714	TOYOTA	238	18	4
DBA 715	TOYOTA	300	22	8
DBA 716	TOYOTA	291	18	6
DBA 717	TOYOTA	266	18	5
DBA 719	TOYOTA	324	16	5.7
DBA 720	TOYOTA	248	18	4
DBA 721	TOYOTA	248	22	5
DBA 722	TOYOTA	269	18	5
DBA 723	TOYOTA	235	18	3.7
DBA 724	TOYOTA	266	12.7	5
DBA 725	PART NOT AVAILABLE	261	12.5	0
DBA 726	DAEWOO	256	24	5.6
DBA 727	PART NOT AVAILABLE	252	20	4
DBA 728	TOYOTA	252	20	4.5
DBA 729	PART NOT AVAILABLE	268	18	5

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 730	TOYOTA	255	22	5.5
DBA 731	TOYOTA	269	12	4.5
DBA 732	TOYOTA	255	25	5.5
DBA 733	TOYOTA	255	28	6
DBA 734	TOYOTA	288	10	5
DBA 735	TOYOTA	276	28	7
DBA 736	TOYOTA	269	10	4.5
DBA 737	TOYOTA	276	28	7
DBA 738	TOYOTA	291	16	5
DBA 739	TOYOTA	258	22	5.5
DBA 740	TOYOTA	243	22	5
DBA 741	TOYOTA	269	10	4.5
DBA 742	TOYOTA	255	22	5
DBA 743	TOYOTA	278	25	7
DBA 744	TOYOTA	288	10	5
DBA 745	TOYOTA	315	28	10
DBA 746	TOYOTA	307	16	5.6
DBA 747	PART NOT AVAILABLE	275	28	6.5
DBA 749	TOYOTA	307	12	6
DBA 750	PART NOT AVAILABLE	258	22	5
DBA 751	TOYOTA	258	10	4
DBA 753	TOYOTA	255	20	4.5
DBA 754	TOYOTA	263	16	4.1
DBA 755	TOYOTA	230	18	4
DBA 756	TOYOTA	230	20	4.5
DBA 757	TOYOTA	291	9	5
DBA 758	TOYOTA	260	20	5.5
DBA 759	TOYOTA	275	25	6.2
DBA 760	TOYOTA	255	25	5.5
DBA 761	TOYOTA	279	22	6.5
DBA 762	TOYOTA	271	25	6.5
DBA 763	PART NOT AVAILABLE	284	22	6.2
DBA 764	TOYOTA	269	9	4
DBA 766	TOYOTA	255	25	6.5
DBA 767	TOYOTA	285	28	7.6
DBA 768	TOYOTA	285	28	7.5
DBA 769	ALFA ROMEO	305	28	7.6
DBA 770	TOYOTA	300	30	10.5
DBA 771	TOYOTA	296	35	12
DBA 772	TOYOTA	258	25	6
DBA 773	HOLDEN	295	32.5	8
DBA 774	HOLDEN	317.5	33	9.2
DBA 775	TOYOTA	291	25	7
DBA 776	CHRYSLER	302	28	7.7
DBA 777	CHRYSLER	290	12.5	3.7
DBA 778	TOYOTA	255	25	4.5
DBA 779	ALFA ROMEO	240	11	3.5
DBA 780	TOYOTA	289	20	6.5
DBA 781	TOYOTA	248	22	4.5
DBA 782	TOYOTA	286	25	7.5
DBA 783	TOYOTA	254	22	5
DBA 784	TOYOTA	311	31.9	9
DBA 785	TOYOTA	312	18	7.5
DBA 786	TOYOTA	336	18	8.5
DBA 787	TOYOTA	312	18	6.5

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 788	TOYOTA	312	32	8.5
DBA 789	TOYOTA	330	18	8
DBA 790	TOYOTA	322	32	8.5
DBA 791	TOYOTA	335	18	7.5
DBA 792	TOYOTA	319	22	6.5
DBA 793	TOYOTA	312	18	6
DBA 794	TOYOTA	312	18	7.5
DBA 795	FORD	330	38	20.8
DBA 796	FORD	326	30	11.2
DBA 797	FORD	330	38	20.2
DBA 798	FORD	331	38	13
DBA 799	FORD	326	30	11.3
DBA 800	AUDI	256	22	6
DBA 801	AUDI	280	22	6
DBA 802	AUDI	288	25	7
DBA 803	AUDI	232	9	2.6
DBA 804	AUDI	280	13	5.3
DBA 805	AUDI	288	15	6.6
DBA 806	AUDI	280	22	6.2
DBA 807	AUDI	288	25	7.5
DBA 808	AUDI	245	10	5.5
DBA 809	AUDI	245	10	3.5
DBA 810	AUDI	245	10	3.5
DBA 811	HOLDEN	250	18	4
DBA 812	PART NOT AVAILABLE	266	18	5
DBA 813	BMW	332	30	11.2
DBA 814	BMW	324	12	
DBA 815	HOLDEN	280	25	6.2
DBA 816	HOLDEN	264	10	3.8
DBA 817	HOLDEN	256	24	5.8
DBA 818	HOLDEN	240	10	3
DBA 819	HOLDEN	260	10	4
DBA 820	HOLDEN	236	12	4
DBA 821	HOLDEN	236	20	4
DBA 822	HOLDEN	256	20	4
DBA 823	BMW	356	36	14
DBA 824	BMW	324	20	8.1
DBA 825	HOLDEN	288	25	6.9
DBA 826	HOLDEN	286	10	5
DBA 827	AUSTRALIA POST	254	14.7	5
DBA 828	VOLKSWAGEN	270	24.13	7
DBA 829	VOLKSWAGEN	254	24	4
DBA 830	VOLKSWAGEN	282	18	7
DBA 831	VOLKSWAGEN	280	12	5
DBA 832	VOLKSWAGEN	226	10	4.5
DBA 833	VOLKSWAGEN	288	25	7
DBA 834	VOLKSWAGEN	226	10	4
DBA 835	VOLKSWAGEN	280	22	4.5
DBA 836	VOLKSWAGEN	283	25	7.3
DBA 837	VOLKSWAGEN	239	18	4
DBA 838	AUDI	312	25	8
DBA 840	HOLDEN	280	26	7.5
DBA 841	HOLDEN	313	18.1	7
DBA 842	HOLDEN	280	26	7.3
DBA 844	PART NOT AVAILABLE	231	22	4.8

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 845	TOYOTA	315	30	9.5
DBA 846	TOYOTA	310	16	
DBA 847	HOLDEN	260	24	5
DBA 848	GMC	317	32.5	17
DBA 849	HOLDEN	240	10	3.1
DBA 850	FORD	260	24	5.5
DBA 851	FORD	253	20	4
DBA 852	FORD	276	26	7
DBA 853	FORD	257	14	5
DBA 854	FORD	239.5	20	4
DBA 855	FORD	276	26	6.75
DBA 856	FORD	267	14	5
DBA 857	FORD	256	24	5
DBA 859A/B	FORD	256	18	
DBA 860	FORD	286	26	7.5
DBA 861	FORD	285	12	5.5
DBA 862	FORD	308	30	12.25
DBA 863	FORD	334	14	8.6
DBA 864	PART NOT AVAILABLE	305	26	8.5
DBA 865	FORD	301	12	8.6
DBA 866	PART NOT AVAILABLE	296	28	8.5
DBA 867	EUNOS	286	9.5	4.5
DBA 868	EUNOS	274	28	7
DBA 869	EUNOS	286	9.5	4.5
DBA 870	LADA	239	12	4
DBA 871	FORD	294	24	7.17
DBA 872	LADA	272	11	6
DBA 873	KIA	258	24	6
DBA 874	KIA	260	10	4
DBA 875	KIA	240	20	4.5
DBA 876	KIA	284	24	5.7
DBA 877	KIA	274	24	6
DBA 878	KIA	274	26	6.1
DBA 879	KIA	260	10	3.7
DBA 880	VOLVO	280	26	5
DBA 881	VOLVO	295	9.6	5
DBA 882	VOLVO	279	26	6.5
DBA 883	VOLVO	295	9	5
DBA 884	VOLVO	283	10	4.5
DBA 885	VOLVO	256	24	5
DBA 886	VOLVO	281	24	6.4
DBA 887	VOLVO	260	10	3.5
DBA 888	JEEP	280	24.5	6.9
DBA 889	JEEP	288	28	7.5
DBA 890	DAEWOO	236	12	4
DBA 891	DAEWOO	256	24	5.5
DBA 892	DAEWOO	256	24	5.1
DBA 893	DAEWOO	258	10	4.5
DBA 894	DAEWOO	256	24	5.2
DBA 895	DAEWOO	258	10	4.6
DBA 896	DAEWOO	235	20	4.5
DBA 897	DAEWOO	236	12.7	3.7
DBA 898	PART NOT AVAILABLE	258	9	3.1
DBA 899	NISSAN	247	18	4
DBA 900	NISSAN	252	20	5

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 901	NISSAN	257	26	6.5
DBA 902	NISSAN	258	9	3.5
DBA 903	NISSAN	280	22	7
DBA 904	NISSAN	258	9	3.7
DBA 905	PART NOT AVAILABLE	266	10	5
DBA 906	NISSAN	258	9	3.5
DBA 907	NISSAN	280	26	8.5
DBA 908	NISSAN	292	18	7
DBA 909	NISSAN	280	30	7
DBA 910	NISSAN	280	22	7
DBA 911	PART NOT AVAILABLE	278	9.5	6.5
DBA 912	NISSAN	258	10	4
DBA 913	NISSAN	257	26	6
DBA 914	NISSAN	280	26	8
DBA 915	NISSAN	278	9	4
DBA 917	NISSAN	234	7	2.5
DBA 918	NISSAN	250	18	4.5
DBA 919	NISSAN	280	22	6.2
DBA 920	NISSAN	234	12	3.5
DBA 921	NISSAN	240	7	2.5
DBA 922	NISSAN	280	28	8
DBA 923	NISSAN	292	9	5.5
DBA 924	PART NOT AVAILABLE	274	22	6.6
DBA 925	NISSAN	258	9	3.5
DBA 927	NISSAN	282	20	6.18
DBA 929	NISSAN	300	22	8
DBA 930	MAZDA	238	18	4
DBA 931	MAZDA	222	10	4.5
DBA 932	MAZDA	247	10	4.5
DBA 933	PART NOT AVAILABLE	221	10	4.5
DBA 934	FORD	268	20.5	4.5
DBA 935	PART NOT AVAILABLE	235	10	4
DBA 936	PART NOT AVAILABLE	258	20	5
DBA 937	FORD	298	30	11
DBA 938	FORD	320	26	9.5
DBA 939	FORD	275	20	5
DBA 940	MAZDA	246	20	6.5
DBA 941	PART NOT AVAILABLE	255	20	6
DBA 942	MAZDA	255	10	3.5
DBA 943	PART NOT AVAILABLE	256	24	5
DBA 945	FORD	254	10.2	5.5
DBA 946	MAZDA	250	22	7.5
DBA 947	MAZDA	294	22	7
DBA 948	MAZDA	260	10	5.5
DBA 949	PART NOT AVAILABLE	298	28	7.3
DBA 950	FORD	258	24	5
DBA 951	FORD	261	9.5	5
DBA 952	MAZDA	294	20	5.5
DBA 953	NISSAN	280	26	6.8
DBA 954	NISSAN	296	24	7.6
DBA 955	PART NOT AVAILABLE	274	24	6
DBA 956	MAZDA	286	18	6
DBA 957	FORD	278	24	6.3
DBA 958	MAZDA	255.5	24	5.2
DBA 959	MAZDA	274	28	6.7

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 960	MAZDA	276	28	8
DBA 961	PART NOT AVAILABLE	276	28	8
DBA 962	MAZDA	274	28	7
DBA 964	FORD	275	24	6
DBA 965	FORD	272	22	5.5
DBA 966	BMW	300	22	6.7
DBA 967	BMW	294	19	6.3
DBA 968	PART NOT AVAILABLE	315	28	9.25
DBA 969	BMW	300	20	6
DBA 970	BMW	282	25	6.5
DBA 971	BMW	302	28	8
DBA 972	PART NOT AVAILABLE	300	12	6
DBA 973	BMW	300	20	6
DBA 974	BMW	302	22	7.5
DBA 975	BMW	302	12	6.5
DBA 976	BMW	300	10	5
DBA 977	PART NOT AVAILABLE	300	10	5
DBA 978	BMW	286	12	5.2
DBA 979	BMW	286	22	7
DBA 980	BMW	276	19	5
DBA 981	BMW	272	10	4.5
DBA 982	BMW	272	10	4.7
DBA 983	BMW	280	10	4.5
DBA 984	BMW	315	28	9.5
DBA 985A/B	PART NOT AVAILABLE	312	19.9	6.6
DBA 986	BMW	296	22	7.5
DBA 987	BMW	298	10	5
DBA 988	BMW	324	30	10.25
DBA 989	PART NOT AVAILABLE	298	20	6
DBA 990	BMW	316	28	8.5
DBA 991	BMW	324	12	6.5
DBA 995	PART NOT AVAILABLE	319	32	18
DBA 996A/B	CHEVROLET	330	28	12.7
DBA 997A/B	CHEVROLET	304.8	20.5	6.4
DBA 998	CHEVROLET	318	32.5	9.5
DBA 999A/B	CHEVROLET	304.8	20.5	6
DBA RRF	ROLLS ROYCE	280	16	5.5
DBA RRR	ROLLS ROYCE	275	13	5.5
DBA 2000	CHEVROLET	305	29	8.4
DBA 2001	CHEVROLET	330	30	10
DBA 2010	CHEVROLET	330	30	11.6
DBA 2011	CHEVROLET	345	20	10.2
DBA 2020	HOLDEN	320	32	11.4
DBA 2021	HOLDEN	286	18	6.65
DBA 2026	HOLDEN	298	30	8.2
DBA 2027	HOLDEN	302	22	7.2
DBA 2028	HOLDEN	321	30	9.2
DBA 2029	HOLDEN	324	22	8.3
DBA 2032	HOLDEN	236	20	3.9
DBA 2033	HOLDEN	252	22	5.5
DBA 2034	VAUXHAUL	321	28	9.4
DBA 2035	HOLDEN	278	10	4
DBA 2036	HOLDEN	280	25	
DBA 2038	HOLDEN	278	24	6.76
DBA 2039	HOLDEN	276	12	5.3

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 2040	HOLDEN	295	29	7.5
DBA 2044	JAGUAR	300	30	
DBA 2045	JAGUAR	288	20	
DBA 2046	JAGUAR	305	38	
DBA 2047	JAGUAR	305	20	
DBA 2048	HUMMER	325	38	18
DBA 2049	HUMMER	330	29	10.9
DBA 2050	HOLDEN	302	28	8.27
DBA 2051	CHEVROLET	330	29	11.7
DBA 2052	CHEVROLET	296	26	7.5
DBA 2053	CHEVROLET	270	14	5
DBA 2054	CHEVROLET	315	28	9.6
DBA 2055	CHEVROLET	312	12	6.4
DBA 2090	LANDROVER	317	30	9.9
DBA 2091	LANDROVER	325	20	7.7
DBA 2092	LANDROVER	344	30	12
DBA 2093	LANDROVER	354	12	9.6
DBA 2094	LANDROVER	337.5	30	11.4
DBA 2095	LANDROVER	350	20	8.9
DBA 2096	LANDROVER	360	30	12
DBA 2097	LANDROVER	354	20	9.2
DBA 2098	LANDROVER	360	30	12.2
DBA 2099	LANDROVER	344	30	12
DBA 2100	FORD	258	22	5.5
DBA 2101	FORD	300	24	7.1
DBA 2103	FORD	280	10	3.9
DBA 2107	FORD	322	28	10.3
DBA 2108	FORD	322	26	9.2
DBA 2109	FORD	253	10	3.3
DBA 2113	FORD	316	30	9.25
DBA 2114	FORD	300	19	6
DBA 2115	FORD	293	30	7.4
DBA 2118	FORD	278	25	6.3
DBA 2119	FORD	265	11	4.1
DBA 2120	FORD	320	25	9.1
DBA 2121	FORD	280	11	4.5
DBA 2124	FORD MUSTANG GT500	355	32	11.1
DBA 2125	FORD MUSTANG GT500	330	20.7	6.6
DBA 2141	PROTON	280	12	4.7
DBA 2150	FORD	308	26	
DBA 2151	FORD	308	30	
DBA 2160	FIAT	305	28	8.6
DBA 2170	TRIUMPH	232	9.6	2.75
DBA 2200	MITSUBISHI	256	24	4.9
DBA 2201	MITSUBISHI	276	26	6
DBA 2202	MITSUBISHI	276	26	6
DBA 2203	MITSUBISHI	262	10	4.1
DBA 2205	MITSUBISHI	262	10	
DBA 2206	MITSUBISHI	294	28	7.2
DBA 2207	MITSUBISHI	302	18	6
DBA 2208	MITSUBISHI	294.4	28	7.1
DBA 2209	MITSUBISHI	262	10	
DBA 2216	MITSUBISHI	332	28	9.2
DBA 2219	MITSUBISHI	332	18	8.0
DBA 2220	MITSUBISHI	310	40	13.3

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 2221	MITSUBISHI	310	40	13.7
DBA 2222	MITSUBISHI	293	40	11.4
DBA 2229	HYUNDAI	276	22	6
DBA 2241	AUDI	276	25	
DBA 2242	VOLKSWAGEN	308	29.5	9.4
DBA 2243	VOLKSWAGEN	314	22	
DBA 2244	VOLKSWAGEN	330	32	
DBA 2245	PORSCHE	329	28	8.5
DBA 2246	PORSCHE	350	34	12
DBA 2247	VOLKSWAGEN	294	22	6.9
DBA 2248	VOLKSWAGEN	333	33	11.7
DBA 2250	MERCEDES BENZ	315	30	10.6
DBA 2252	MERCEDES BENZ	330	32	11.7
DBA 2253	MERCEDES BENZ	330	14	7.6
DBA 2254	MERCEDES BENZ	350	32	13.1
DBA 2255	MERCEDES BENZ	330	22	8.2
DBA 2266	MERCEDES BENZ	294	24	7.7
DBA 2267	MERCEDES BENZ	258	12	6.2
DBA 2268	MERCEDES BENZ	285	22	
DBA 2269	MERCEDES BENZ	298	16	7.2
DBA 2270	MERCEDES BENZ	299.5	28	9.26
DBA 2274	PEUGEOT	266	22	5.5
DBA 2275	PEUGEOT	283	26	7.1
DBA 2300	NISSAN	257	22	6
DBA 2301	NISSAN	278	10	4.5
DBA 2303	NISSAN	257	10	3.7
DBA 2306	NISSAN	319	26	8.25
DBA 2307	NISSAN	319	14	7.5
DBA 2308	NISSAN	320	28	10.5
DBA 2309	NISSAN	308	16	6
DBA 2310	NISSAN	296	28	7.9
DBA 2311	NISSAN	308	18	6
DBA 2312	NISSAN	320	26	9.1
DBA 2313	NISSAN	308	16	6
DBA 2314	NISSAN	354.6	32	13.2
DBA 2315	NISSAN	350	20	8.8
DBA 2316	NISSAN	296	26	
DBA 2352	RENAULT	259	20.6	5
DBA 2353	RENAULT	280	24	7.3
DBA 2354	RENAULT	238	8	4
DBA 2360	ALFA ROMEO	272	22	6.1
DBA 2380	VOLVO	300	25	8.1
DBA 2382	VOLVO	286	26	6.9
DBA 2383	VOLVO	288	12	5.4
DBA 2384	VOLVO	305	28	9.3
DBA 2390	PORSCHE	322	32	
DBA 2392	PORSCHE	322	32	9.6
DBA 2394	PORSCHE	318	38	8.2
DBA 2396	PORSCHE	350	34	
DBA 2397	PORSCHE	330	28	
DBA 2398	PORSCHE	298	24	
DBA 2431	DODGE	330	22.6	7.4
DBA 2438	CHRYSLER	345	28	10.5
DBA 2439	CHRYSLER	320	22	8.5
DBA 2440	DODGE	287	24	7

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 2442	DODGE	336	28	10.4
DBA 2443	DODGE	352	22	10.5
DBA 2444	DODGE	360	32	12.5
DBA 2445	DODGE	350	28	10.5
DBA 2446	DODGE	280	28	7.2
DBA 2447	DODGE	270	11.9	4.8
DBA 2448	DODGE	355	32	12.2
DBA 2449	DODGE	355	32	12.2
DBA 2450	HYUNDAI	241	19	
DBA 2451	HYUNDAI	256	19	4.9
DBA 2452	HYUNDAI	294	26	7.3
DBA 2454	HYUNDAI	303	28	
DBA 2456	HYUNDAI	300	28	8
DBA 2457	HYUNDAI	284	10	4.88
DBA 2458	HYUNDAI	257	24.5	5.9
DBA 2460	HYUNDAI	300	30	9.8
DBA 2461	HYUNDAI	324	18	7.5
DBA 2498	DAIHATSU	246	17	5.3
DBA 2500	ACURA	300	25	6.6
DBA 2502	HONDA	260	9	3.9
DBA 2503	HONDA	282	9	4.5
DBA 2504	HONDA	240	21	4.4
DBA 2506	HONDA	282	25	6.4
DBA 2508	HONDA	300	25	7.5
DBA 2510	HONDA	300	28	7.7
DBA 2511	HONDA	260	9	3.75
DBA 2513	HONDA	260	9	3.6
DBA 2514	HONDA	282	28	7.1
DBA 2515	HONDA	259.5	10	4.3
DBA 2516	HONDA	282	23	6.4
DBA 2517	HONDA	260	9.1	3.5
DBA 2518	HONDA	320	25	8.44
DBA 2519	HONDA	282	9	4.06
DBA 2524	MINI COOPER	294	22	6.35
DBA 2526	MINI COOPER	280	22	5.8
DBA 2528	MINI COOPER	316	22	7.44
DBA 2529	MINI COOPER	280	10	3.76
DBA 2530	JEEP	328	30	10.5
DBA 2531	JEEP	320	14	8
DBA 2532	JEEP	360	32	13.2
DBA 2533	JEEP	350	28	12
DBA 2535	JEEP	285	12	5.56
DBA 2536	JEEP	302	28	7.46
DBA 2537	JEEP	316	12	7.2
DBA 2558	MAZDA	314	32	8.62
DBA 2559	MAZDA	314	20	6.2
DBA 2560	MAZDA	302.7	26	8.5
DBA 2561	MAZDA	302	12	5.8
DBA 2580	SUZUKI	295	25	6.8
DBA 2602	CHEVROLET	321	30	
DBA 2603	CHEVROLET	315	23	
DBA 2604	CHEVROLET	355	32	
DBA 2605	CHEVROLET	365	28	
DBA 2606	CHEVROLET	303	30	
DBA 2607	CHEVROLET	278	9	

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 2650	SUBARU	316	30	9.69
DBA 2657	SUBARU UPGRADE	316	20	9.75
DBA 2659	SUBARU	286	10	4.96
DBA 2670	BMW	334	32	11.3
DBA 2671	BMW	328	20	7.9
DBA 2700	TOYOTA	338	28	9.4
DBA 2701	TOYOTA	271	10	4.6
DBA 2702	LEXUS	319	28	10
DBA 2703	LEXUS	288	10	5.3
DBA 2705	TOYOTA	296	28	8
DBA 2707	TOYOTA	286	10	5.7
DBA 2708	TOYOTA	255	20	4.8
DBA 2709	TOYOTA	296	28	7.3
DBA 2710	TOYOTA	296	28	8.86
DBA 2711	TOYOTA	269	12	5.2
DBA 2712	LEXUS	296	28	8
DBA 2714	TOYOTA	297	25	7.7
DBA 2715	TOYOTA	255	28	5.86
DBA 2716	TOYOTA	319	28	8.3
DBA 2718	TOYOTA	255	22	5.1
DBA 2719	TOYOTA	258	9	3.46
DBA 2720	LEXUS	334	30	11.6
DBA 2721	LEXUS	310	18	
DBA 2722	TOYOTA	340	32	10.5
DBA 2723	TOYOTA	345	18	7.5
DBA 2724	TOYOTA	254	32	11.2
DBA 2726	TOYOTA	296	28	7.3
DBA 2727	LEXUS	291	10	4.8
DBA 2728	LEXUS	357	34	13.3
DBA 2730	TOYOTA	296	28	7.8
DBA 2731	TOYOTA	298	10	5.16
DBA 2732	TOYOTA	285	28	7.8
DBA 2734	TOYOTA	328	28	
DBA 2735	TOYOTA	309	10	
DBA 2736	TOYOTA PRADO	338	32	
DBA 2737	TOYOTA PRADO	312	18	
DBA 2797	FORD	347	38	
DBA 2798	FORD	347	38	
DBA 2799	FORD	340	34	
DBA 2800	AUDI	312	25	8.8
DBA 2801	AUDI	245	10	3.2
DBA 2802	AUDI	255	12	3.8
DBA 2803	AUDI	245	10	3.8
DBA 2805	AUDI	255	10	4
DBA 2806	VOLKSWAGEN	312	25	8.6
DBA 2807	VOLKSWAGEN	285.6	11.7	4.7
DBA 2808	VW	345	30	11.9
DBA 2809	VW	310	22	7.3
DBA 2815	HOLDEN	308	25	7.8
DBA 2817	HOLDEN	302	28	8.5
DBA 2818	HOLDEN	292	20	5.2
DBA 2819	HOLDEN	314	28	9.2
DBA 2820	HOLDEN	285	25	6.8
DBA 2839	HOLDEN	256	26	5.7
DBA 2840	HOLDEN	280	27	7

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 2852	BMW	300	20	6
DBA 2854	BMW	324	30	
DBA 2855	BMW	328	25	8.9
DBA 2856	BMW	320	22	7.6
DBA 2858	BMW	348	30	11.5
DBA 2859	BMW	336	22	9
DBA 2860	BMW	330	24	9.06
DBA 2861	BMW	300	20	6.64
DBA 2862	BMW	300	24	8
DBA 2868	BMW	324	30	10.4
DBA 2869	BMW	320	20	7.44
DBA 2870	KIA	274	28	7
DBA 2871	KIA	300	28	7.6
DBA 2872	KIA	275	26	6.7
DBA 2873	KIA	258	10	4.1
DBA 2893	KIA	256	22	5.1
DBA 2894	KIA	257	25	
DBA 2895	KIA	261	9.8	
DBA 2896	KIA	235	22	4.8
DBA 2897	KIA	258	26	7.3
DBA 2898	KIA	302	28	7.64
DBA 2899	KIA	315	20	
DBA 2948	ROLLS ROYCE	281	31.5	7.9
DBA 2949	ROLLS ROYCE	299	31.5	9
DBA 2950	MAZDA	274	24	5.75
DBA 2951	MAZDA	280	10	8.68
DBA 2952	MAZDA	288.5	28	4
DBA 2954	MAZDA	278	25	7.23
DBA 2955	MAZDA	264	11	4
DBA 2956	MAZDA	300	25	7.95
DBA 2957	MAZDA	280	11	4.5
DBA 2958	MAZDA	258	22	5.3
DBA 2959	MAZDA	290	22	6.25
DBA 2960	MAZDA	320	25	9.4
DBA 2961	MAZDA	314	11	5.5
DBA 2962	MAZDA	320	25	9.6
DBA 2990	CHEVROLET	340	32	10.1
DBA 2991	CHEVROLET	330	26	9.1
DBA 2992	CHEVROLET	355	32	11.8
DBA 2993	CHEVROLET	340	26	9.4
DBA 2994	CHEVROLET	325	32	10
DBA 2995	CHEVROLET	305	26	6.8
DBA 2996	CHEVROLET	303	32	9.75
DBA 2997	CHEVROLET	305	26	7.3
DBA 7420	TOYOTA	318	28	8.3

4000 SERIES

DBA 4000	SUBARU	295	25	7.8
DBA 4014	HOLDEN	276	25.4	11
DBA 4015	HOLDEN	270	22	10.5
DBA 4016	HOLDEN	279	10.5	5.5
DBA 4017	HOLDEN	290	22	11
DBA 4019	HOLDEN	330	28	13
DBA 4020	HOLDEN	278	20	6

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 4027	HOLDEN	290	23	10.5
DBA 4035	HOLDEN	289	23	9
DBA 4036	HOLDEN	279	10.7	5.5
DBA 4036B	HOLDEN	279	10.7	5.5
DBA 4037	HOLDEN	279	10.7	5.5
DBA 4040	HOLDEN	296	28	9.5
DBA 4040B	HOLDEN	296	28	9.5
DBA 4041	HOLDEN	286	16	7
DBA 4045	HOLDEN	280	20	6
DBA 4046	HOLDEN	328	28	9.5
DBA 4046B	HOLDEN	328	28	9.5
DBA 4047	HOLDEN	280	20	7
DBA 4048	HOLDEN	330	32	11.3
DBA 4049	HOLDEN	315	18	8
DBA 4067	CHEVROLET	325	32	10.1
DBA 4069	FORD	330	28	9.1
DBA 4086	LANDROVER	298	24	7.5
DBA 4087	LANDROVER	298	14	7.75
DBA 4088	LANDROVER	290	12.7	6.5
DBA 4092	LANDROVER	297	25	8
DBA 4093	LANDROVER	304	12.6	7
DBA 4096	JEEP	280	24	6.8
DBA 4097	JEEP	285	11	5.1
DBA 4106H	FORD	287	24	11
DBA 4107	FORD	287	24	11
DBA 4110B	FORD	287	24	9
DBA 4111A	FORD	287	15	6.5
DBA 4111B	FORD	287	13	6.5
DBA 4118	FORD	247	13	4
DBA 4130	FORD	287	24	10.5
DBA 4131	FORD	287	25	10.5
DBA 4132	FORD	287	25	10.5
DBA 4133	FORD	299	10.5	5.6
DBA 4134	FORD	287	24	10
DBA 4135	FORD	287	24	10
DBA 4166	CHRYSLER	270	9	3.9
DBA 4167	CHRYSLER	280	23	5.8
DBA 4200	HONDA	282	23	6
DBA 4213	DODGE	296	30	7
DBA 4214	DODGE	284	20	5.8
DBA 4216	DODGE	314	30	8.6
DBA 4217	DODGE	297	20	6.5
DBA 4240	AUDI	321	30	9.5
DBA 4241	AUDI	269	22	5
DBA 4242	AUDI	321	30	10
DBA 4329	NISSAN	295	20	7
DBA 4356	ALFA ROMEO	284	22	5.8
DBA 4402	MITSUBISHI	276	24	6
DBA 4417	MITSUBISHI	294	24	6.3
DBA 4418	MITSUBISHI	320	32	9.75
DBA 4419	MITSUBISHI	300	22	7
DBA 4425	MITSUBISHI	276	24	6
DBA 4428	MITSUBISHI	276	24	5.6
DBA 4429	MITSUBISHI	284	20	6.1
DBA 4456	HYUNDAI	257	24	4.8

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 4468	HYUNDAI	280	26	7
DBA 4469	HYUNDAI	258	10	4.1
DBA 4474	HONDA	262	21	5
DBA 4475	HONDA	239	9	3
DBA 4476	HONDA	300	28	8
DBA 4478	HONDA	282	23	6.5
DBA 4479	HONDA	282	9	4.2
DBA 4482	HONDA	300	25	7
DBA 4483	HONDA	282	12	4.5
DBA 4484	HONDA	282	28	6.5
DBA 4486	HONDA	298	28	6.8
DBA 4487	HONDA	303	23	6.5
DBA 4488	HONDA	282	23	6.5
DBA 4500	FORD	287	24	7
DBA 4501	FORD	287	10.5	5
DBA 4502	FORD	287	28	7
DBA 4503	FORD	287	16	6.5
DBA 4504	FORD	298	28	9
DBA 4505	FORD	303	16	7.5
DBA 4506	FORD	329	28	9
DBA 4507A	FORD	330	28	9.9
DBA 4507B	FORD	330	28	9.9
DBA 4526	LANDROVER	262	14	4.9
DBA 4527	LANDROVER	277	21	5.9
DBA 4528	LANDROVER	297	25	8.8
DBA 4531	FORD	231	9	3
DBA 4532	FORD	235	22	4.5
DBA 4533	FORD	257	22	5.2
DBA 4534	MAZDA	250	9	3
DBA 4538	MAZDA	255	20	5
DBA 4540	JEEP	305	26	8
DBA 4541	JEEP	305	10	6
DBA 4542	MINI COOPER	276	22	3.4
DBA 4543	MINI COOPER	259	10	3.4
DBA 4545	MAZDA	270	22	6
DBA 4546	MAZDA	276	10	4
DBA 4549	LANDROVER	298	14	6.8
DBA 4552	MERCEDES BENZ	345	32	11.2
DBA 4553	MERCEDES BENZ	331	14	8
DBA 4560	TOYOTA	315	32	10.5
DBA 4562	TOYOTA	275	25	6.2
DBA 4563	TOYOTA	269	9	3.6
DBA 4569	AUDI	256	22	4.8
DBA 4573	NISSAN	280	28	7.5
DBA 4574	NISSAN	292	16	5
DBA 4575	AUDI	321	30	10
DBA 4600	NISSAN	324	30	9.5
DBA 4601	NISSAN	322	22	8
DBA 4622	NISSAN	315	18	7.5
DBA 4625	NISSAN	306	32	10.4
DBA 4644	SUBARU	266	10	4.5
DBA 4648	SUBARU	277	24	8
DBA 4649	SUBARU	266	18	5
DBA 4650	SUBARU	294	24	7
DBA 4653	SUBARU	290	18	6

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 4654-10	SUBARU	326	30	9.5
DBA 4655-10	SUBARU	316	20	8
DBA 4656	SUBARU	290	18	5.7
DBA 4657	SUBARU	290	10	4.9
DBA 4660	MITSUBISHI	290	26	0
DBA 4661	MITSUBISHI	300	22	6.5
DBA 4663	MITSUBISHI	276	24	6
DBA 4665	ALFA ROMEO	284	22	6.5
DBA 4698	NISSAN	316	34	10.5
DBA 4699	NISSAN	330	18	7.6
DBA 4718	LEXUS	323	30	9.3
DBA 4719	TOYOTA	324	16	5.7
DBA 4735	TOYOTA	275	28	7
DBA 4746	LEXUS	307	16	5.6
DBA 4748	LEXUS	296	32	9
DBA 4749	TOYOTA	307	12	6
DBA 4769	ALFA ROMEO	305	28	7.6
DBA 4773	CHEVROLET	295	33	8
DBA 4784	TOYOTA	311	32	9.66
DBA 4788	LEXUS	312	32	9.5
DBA 4789	LEXUS	330	18	8.25
DBA 4790	TOYOTA	322	22	8.5
DBA 4791	TOYOTA	335	18	7.5
DBA 4796	FORD	326	30	11.2
DBA 4798	FORD	331	38	13
DBA 4799	FORD	326	30	11.5
DBA 4838	AUDI	312	25	8
DBA 4840	GM	280	26	6.5
DBA 4841	GM	313	18	7
DBA 4878	KIA	274	26	7.2
DBA 4888	JEEP	280	24.5	6.8
DBA 4901	NISSAN	257	26	6.5
DBA 4906	NISSAN	258	9	3.5
DBA 4908	NISSAN	292	18	6.5
DBA 4909	NISSAN	280	30	7
DBA 4926	NISSAN	296	32	8.1
DBA 4928	NISSAN	324	30	9
DBA 4929	NISSAN	300	22	8
DBA 4947	MAZDA	294	22	7
DBA 4954	NISSAN	296	24	7.07
DBA 4957	FORD	278	24	7
DBA 4963	NISSAN	296	30	8
DBA 4966	BMW	300	22	6.7
DBA 4979	BMW	286	22	6
DBA 4984	BMW	315	28	9.5
DBA 4993	FORMULA FORD	248	7	1.55
DBA 4994	FORMULA FORD	248	7	2.5
DBA 4996	CHEVROLET	330	28	9.9
DBA 42000	CHEVROLET	305	29	8.5
DBA 42001	CHEVROLET	330	30	10
DBA 42019	HOLDEN	332	24	
DBA 42020	HOLDEN	320	32	11.48
DBA 42021	HOLDEN	286	18	6.8
DBA 42022	HOLDEN	336	32	10.8
DBA 42025	HOLDEN	343	26	9.8

DBA DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 42028	HOLDEN	321	30	9.2
DBA 42030	HOLDEN	365	32	11
DBA 42031	HOLDEN	350	26	10.3
DBA 42034	VAUXHAUL	321	28	9.4
DBA 42035	HOLDEN	278	10	4
DBA 42048	CHEVROLET	325	38	12
DBA 42049	CHEVROLET	330	29	10.9
DBA 42050	HOLDEN	302	28	7.2
DBA 42051	CHEVROLET	330	29	11.5
DBA 42052	CHEVROLET	296	26	0
DBA 42053	CHEVROLET	270	14	5
DBA 42054	CHEVROLET	315	28	9.6
DBA 42055	CHEVROLET	312	12	6.4
DBA 42090	LANDROVER	317	30	9.9
DBA 42091	LANDROVER	325	20	7.6
DBA 42092	LANDROVER	344	30	12
DBA 42093	LANDROVER	354	12	9.6
DBA 42094	LANDROVER	338	30	11.4
DBA 42095	LANDROVER	350	20	8.8
DBA 42096	LANDROVER	360	30	11.9
DBA 42097	LANDROVER	354	20	9
DBA 42098	LANDROVER	360	30	12
DBA 42100	FORD	258	22	5.5
DBA 42102	FORD	355	32	12.6
DBA 42104	FORD	325	32	9.5
DBA 42107	FORD	322	28	10.3
DBA 42108	FORD	328	26	9.5
DBA 42113	FORD	316	30	9.25
DBA 42114	FORD	300	19	6
DBA 42115	FORD	293	30	7.4
DBA 42120	FORD	320	25	9.1
DBA 42121	FORD	280	11	4.5
DBA 42140	PROTON	266	22	4.7
DBA 42160	FIAT	305	28	8
DBA 42206	MITSUBISHI	294	28	7.2
DBA 42207	MITSUBISHI	302	18	6
DBA 42224	MITSUBISHI	350	32	11.8
DBA 42225	MITSUBISHI	330	22	8.8
DBA 42245	PORSCHE	330	28	8.5
DBA 42246	PORSCHE	350	34	12
DBA 42250	MERCEDES BENZ	315	30	10
DBA 42301	NISSAN	278	10	4.5
DBA 42304	NISSAN	310	30	9.5
DBA 42306	NISSAN	319	26	8.1
DBA 42307	NISSAN	319.5	14	7.5
DBA 42308	NISSAN	320	28	10.5
DBA 42309	NISSAN	308	16	6
DBA 42310	NISSAN	296	28	7.9
DBA 42311	NISSAN	308	18	6
DBA 42313	NISSAN	308	16	6
DBA 42355	LOTUS	288	26	6.1
DBA 42360	ALFA ROMEO	272	22	6.25
DBA 42390	PORSCHE	322	32	
DBA 42392	PORSCHE	322	32	9.6
DBA 42394	PORSCHE	318	28	8.2

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 42396	PORSCHE	350	34	11.6
DBA 42397	PORSCHE	330	28	9.1
DBA 42398	PORSCHE	298	24	
DBA 42429	MITSUBISHI	284	20	
DBA 42431	DODGE	330	22.6	7.4
DBA 42438	CHRYSLER	345	28	10.5
DBA 42439	CHRYSLER	320	22	8.5
DBA 42444	CHRYSLER	360	32	12.5
DBA 42445	CHRYSLER	350	28	10.5
DBA 42448	CHRYSLER	345	32	12.4
DBA 42449	CHRYSLER	320	32	12.3
DBA 42456	HYUNDAI	300	28	8
DBA 42500	HONDA	300	25	6.6
DBA 42506	HONDA	282	25	6.37
DBA 42508	HONDA	300	25	7.5
DBA 42510	HONDA	300	28	7.5
DBA 42514	HONDA	282	28	7.1
DBA 42515	HONDA	260	10	4.3
DBA 42524	MINI COOPER	294	22	6.5
DBA 42526	MINI COOPER	280	22	5.8
DBA 42530	JEEP	328	30	10.5
DBA 42531	JEEP	320	14	8
DBA 42532	JEEP	360	32	13.2
DBA 42533	JEEP	350	28	12
DBA 42550	MAZDA	320	24	8.44
DBA 42551	MAZDA	300	18	5.5
DBA 42552	MAZDA	302.5	24	7.5
DBA 42560	MAZDA	302.7	26	8.5
DBA 42561	MAZDA	302	12	5.8
DBA 42575	AUDI	344.5	30	10.5
DBA 42576	AUDI	300	22	6
DBA 42580	SUZUKI	295	25	6.8
DBA 42650	SUBARU	316	30	9.7
DBA 42656	SUBARU	316	20	7.73
DBA 42657	SUBARU REAR UPGRADE	316	20	9.2
DBA 42700	TOYOTA	338	28	9.4
DBA 42702	TOYOTA	320	28	8.2
DBA 42705	TOYOTA	296	28	8
DBA 42709	TOYOTA	296	28	7.3
DBA 42714	TOYOTA	297	25	7.5
DBA 42715	TOYOTA	255	28	5.86
DBA 42716	TOYOTA	319	28	8.3
DBA 42800	AUDI	312	25	8.8
DBA 42806	VOLKSWAGEN	312	25	8.6
DBA 42807	VOLKSWAGEN	285.6	11.7	4.7
DBA 42815	HOLDEN	308	25.1	7.8
DBA 42819	HOLDEN	314	28	9.2
DBA 42840	HOLDEN	280	27	7
DBA 42850	BMW	325	28	9
DBA 42851	BMW	327	20	8
DBA 42858	BMW	348	30	11.5
DBA 42859	BMW	336	22	9
DBA 42870	KIA	274	28	7
DBA 42871	KIA	300	28	7.6
DBA 42898	KIA	302	28	8

DISC BRAKES AUSTRALIA ™

WEIGHTS & DIMENSIONS CHART

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 42951	MAZDA	280	10	4.3
DBA 42952	FORD	288.5	28	8.5
DBA 42956	MAZDA	300	25	7.5
DBA 42957	MAZDA	280	11	4.5
DBA 42959	MAZDA	290	22	6.2
DBA 42960	MAZDA	320	25	9
DBA 42961	MAZDA	314	11	5.5
DBA 42962	MAZDA	320	25	9.6
DBA 42990	CHEVROLET	340	32	10.5
DBA 42991	CHEVROLET	330	26	9.1
DBA 42992	CHEVROLET	355	32	12.25
DBA 42993	CHEVROLET	340	26	9.25
DBA 42994	CHEVROLET	325	32	10.25
DBA 42995	CHEVROLET	305	26	6.75
DBA 42996	CHEVROLET	303	32	9.75
DBA 42997	CHEVROLET	305	26	7.25
DBA 42999	FORMULA FORD	254	9.65	2.21

5000 SERIES

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 5000	SUBARU	294	25	6
DBA 5003.1	FORMULA 3	278	15.9	2.7
DBA 5010	SUBARU	294	25	6.9
DBA 5040	GM	296	28	7.75
DBA 5046	HOLDEN	328	28	9.4
DBA 5046B	HOLDEN	328	28	9.4
DBA 5048	GM	330	32	8.55
DBA 5055	GM	343	32	8.8
DBA 5067	GM	325	32	8.5
DBA 5069	FORD	330	28	8.2
DBA 5240	AUDI	321	30	9.25
DBA 5242	AUDI	321	30	8.4
DBA 5355	LOTUS	282	26	5.6
DBA 5417	MITSUBISHI	294	24	6.6
DBA 5418.1	MITSUBISHI	320	32	8
DBA 5468	HYUNDAI	320	28	8.3
DBA 5506	FORD	329	28	9.2
DBA 5575	AUDI	320	30	9
DBA 5600	NISSAN	324	30	9
DBA 5654-10	SUBARU	326	30	8.96
DBA 5718	TOYOTA	323	30	8.6
DBA 5928	NISSAN	324	30	8.4
DBA 52018	HOLDEN	350	32	9.6
DBA 52020	HOLDEN	320	32	9.5
DBA 52024	HOLDEN	362	32	10.5
DBA 52030	HOLDEN	365	32	11
DBA 52070	JAGUAR	355	32	9.7
DBA 52102	FORD	355	32	9.7
DBA 52104	FORD	325	32	9
DBA 52113	FORD	319	30	8.5
DBA 52218	MITSUBISHI	320	32	9
DBA 52320	NISSAN GTR35 FRONT	380	34	11
DBA 52321	NISSAN GTR35 REAR	380		
DBA 52322	NISSAN GTR35 - OE FRONT	380	34	10.2

DBA#	APPLICATION / MAKE	DIAM (mm)	THICK (mm)	WEIGHT (kg)
DBA 52323	NISSAN GTR35 - OE REAR	380		
DBA 52355	LOTUS	288	25.7	5.4
DBA 52356	LOTUS	280	26	6
DBA 52358	LOTUS UPGRADE OPTION	296	26	5.5
DBA 52386	PORSCHE	330	34	
DBA 52390	PORSCHE	322	32	9.1
DBA 52396	PORSCHE	350	34	
DBA 52398	PORSCHE	298	24	
DBA 52399	PORSCHE	379.5	32	9.76
DBA 52430	DODGE	330	32	9.5
DBA 52448	DODGE	355	32	10.7
DBA 52468	HYUNDAI	320	27	7.2
DBA 52500	ACURA	300	25	6.3
DBA 52508	ACURA	300	25	6.5
DBA 52525	MINI COOPER	320	28	6.8
DBA 52550	MAZDA	320	24	8.1
DBA 52604	CHEVROLET	355	32	
DBA 52650	SUBARU	316	30	9
DBA 52804	AUDI	360	32	
DBA 52850	BMW	325	28	7.5
DBA 52880	BMW	325	28	7.5
DBA 52990	CHEVROLET	340	32	9.6
DBA 52992	CHEVROLET	355	32	10.5
DBA 52994	CHEVROLET	325	32	9.25

DISC BRAKES AUSTRALIA ™

DISC BRAKES AUSTRALIA

A = Diameter
B = Original Height
C = Original Thickness
D = Min. Thickness
E = Centrel Hole Diameter
F = No. of Bolt Holes

Model	Years	F/R	DBA No.	S	X	4000 Series	5000 Series	Solid Vented	Dimensions (mm) A	B	C	D	E	F

DISC BRAKES AUSTRALIA

All rights reserved. © Copyright 1998-2011 Disc Brakes Australia Pty Ltd. TRADEMARKS: All DBA Part References listed in this catalogue are Trademarks of Disc Brakes Australia Pty Ltd.